



Nivelco

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Nivelco** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Nivelco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
Typ: Rdg-402-0	Artikelnr.: SS-RDG-403-0 Tuning fork limit switch NIVOSWITCH for liquids Connection: flange DN50 PN25 / 40, stainless steel PFA coated Housing aluminum, coated Sensor l = 300mm Microswitch SPDT relay, 250V AC, 8A Customs tariff number 9026 1029 00 Country of origin Hungary
Typ: Rvg-403-0	Artikelnr.: SS-RVG-403-0 Fork & extension ECTFE coated Connection: flange DN50 PN25 / 40, stainless steel PFA coated Housing aluminum, coated Sensor l = 300mm Microswitch SPDT relay, 250V AC, 8A
Typ: Mrc-205-03	Magnet float switch Article number: SS-NIVOPOINT Process connection: 2 "BSP 2 switching points L1 = 224mm L2 = 369mm Lges about 450mm
ArtikeInr.: Ss-Rcp-401-3	Ultrasonic compact transmitter for liquids RCM, probe L = 125mm Stainless steel housing Installation length L = 125mm Connection 1 "NPT 3-wire DIN connector Power supply 12 ... 55 V DC
2972	
4x085q0022ydo/10ppm	
9026102900	
DKD-471-F	
DRC2A22M	
DRH-3A2-2	

DTE6512M	
EASY TREK SCD-330-4	
EASY TREK SCD-34J-4	
EASY TREK SPB-380-4	
EasyTREK SCD-340-4	
F291765	
HBN5104S	
HPA4204S	
HPN4104S	
KLP2040M	
KSH303M	
KSK-201-0	
KSP2010M	
MAK-100-0	
MBL-515-2	
Mi-NWP 130-1	
Mi-SONAR-N SGV 342-2	
MKA-210-0	
MKA2108M	
MKA-211-1	
MKG-210-0	
MLB-112-0	
MultiCONT PRW-24A-1	
NAA1010M	
NAA1050M	
NAW 1040S	
NIVOMAG MKA-210-0 EXW	
NIVOMAG MKU-210-0	A013293 Magnetic coupling level switch, float switch, for underwater applications, (IP68) Ambient pressure: max. 25 bar, Ambient temperature: -20°C...+80°C, Medium density: min. 0.7...0.85 kg/dm ³ (depending on the swimmer, see table) Housing: aluminum Float cylinder Ø64mm, Float material: stainless steel 1.4571 Switch: 250V 2.5A / 220V DC 0.3A, Hysteresis cannot be changed, Fixed differential switch Installation length: L = 202 mm, Process connection: square flange;
NIVOMAG-MKA-210-0	
NIVOPRESS NAA-102-0	
Nivocap_CKK-140-1	
NLN1201M	

NLP1051M
NLP-110-1
NLP-120-0
NPK4310S
NPK4408S
NPK4690S
NWN-105-1
NWN1051M
NWN1101M
NWP-105-1
NWP-110-1
NWP1101M
NWP-120-1
NWP1201M
PKK 312-3
PKK-312-1
PKK-312-4
RCM 310-3
RCM 401-3X66
RCM4008S
RCM-402 L Ex
RCT-402-M
RCT-403-M
RFM-404-A
RHR-520-1,NIVOCONT (2M)
RHR-525-1,NIVOCONT (2.5M)
RKH-50-1
RLH-303-3
SAP-300-0
SEN-362-8EX
SGP- 390-2
SGP-390-6 Ex
SGV3804M
SPA370AS
SPA-380-4
SPA-380-4M

SPA-390-4	
SPA3904S	
SPA390M	
SPB-380-4	
SPB-390-4	
SPB-39N-8	
SSA-262	
STA-480-1	
WGM1404M	
WGP1404S	
MKA-220-0	
SS-NIVOCONT	Type KKH-222-5 2-channel conductive limit switch with 5 electrodes 24V ... 240V AC/DC Medium temperature max. 80°C Pmax 1 bar 2x SPDT 250V, 8A 24VDC, 8A Process connection 1-1/2" BSP polypropylene
SS-RCM-401-3	Housing stainless steel Installation length L=125mm Connection 1" BSP 3-wire DIN connector Power supply 12...55 V DC
PiloTREK WP-200 - İntegrated	
0120002	
Limit Switch MKA210-2LK100	Switching difference 10 mm Micro switch with 2 switching contacts Square flange connection with LK ø92 Mounting length 321 mm Protection class IP 65 Medium temperature -20 to +250 °C Ambient temperature -20 to +80 °C Body aluminum casting Internal parts stainless steel delivery including rod extension LK 100mm including flange gasket (max. 250 °C)
NIVOCONT RHR-504-1	Vibrating rod level Switches for powders and granular solids High-Temperature version (+160°C) Process Connection: 1 ½" BSP Housing: Aluminium (paint coated) Standard Probe Length: 0,4 m Output: SPDT, relay 250 V AC, 8A
Nivomag MKA-210-0	
A013294	NIVOMAG Cable for underwater version Cable per device Price per meter Minimum length 1m
MKA 230 -1 NO.H200641	IP 65 NO NC
TSP-211-0	Nivelco ThermoCONT Temperature sensor with neck tube Process connection: 1/2" BSP Measuring range: -50...600°C Process pressure: 25bar @ +20°C, 16bar @+400°C Material Medium of touched parts: 1.4571 Housing material: Aluminum, painted Installation length: 160mm Pt 100, Class A, 2-wire Electrical connection: Cable gland M20x1.5
CBR-204-2	Nivelco NivoCAP Capacitive rod electrode for continuous level measurement including display SAP-202-0 Housing: Painted aluminum Electrode: 1.4571, PFA insulated Rod length: 0.4m Electrical connection: Cable gland M20x1.5 Power supply: 12...36V DC Output: 4...20mA
KSH-202-0	NivoCONT multi-rod probe 2 electrodes + 1 reference electrode 2 switching points in conductive liquids, Aluminum housing Process connection: G 1 1/2" in 1.4571, for connection to limit switch KRK...
A000001-	NivoCont RKK 504-1 Vibrating rod level switch for powders and granular solids with PE-coated cable-extending probe Process Connection: 1 1/2" BSP Housing: Painted aluminum Probe Length: 4m (cable) Supply

	voltage: 20...255V AC/DC Output: SPDT relay
RKK 504-1 MAX BOY 4 MT	
RKR-505-1	ÇUBUK TİP BOY:50 CM
RKK 504-1 MAX BOY 4MT	/505-1
Mka-211-1 Nivomag Type Level Switch	
Mba-535-6m-400-00	
Drh-3a2-2 Drucksensornipress- Messbereich: 0...10 Barg- Genauigkeit: 0,5 %- Ausgang: 4...20 Ma	
Wgp1404s Pilotrek Pulse Radar Level Transmitter	
Krk5125m	
Wgm1404m Pilotrek Pulse Radar Level Transmitter	
Sep-38n-2	LEVEL TRANSMITTER ULTRASONIC 2WIRE
Npk4310s Nivopress Hydrostatic Level Transmitter	
Mbl-515-2 Nivotrack	
Mka-210-8	
A012768	NIVOSWITCH RCM 401-3 Swing fork for liquids, reliable detection of limit levels regardless of the installation position; Installation length: 125mm; Overload protection: max. 40 bar (4 MPa); Supply voltage: 15...29V DC; Output: PNP/NPN transistor; Electrical connection: 3-wire, Plug EN 175301-803A; Protection class: IP 65; Temperature range: -40...+70°C; Process connection: G 1" BSP; Housing material/processor connection: Stainless steel 1.4571
Rcm-301-3 Sensor	
Ac-22 Sound Siren	
Spa 390-4	
Rcm-400-3	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 69mm probe material: stainless steel 1.4571 Degree of protection in connection plug: IP65 process connection: 1 "BSP Process connection: 3-drach DC, DIN connector Supply voltage: DC 12 - 55V
Kkh-222-5	
Naa1050m Halter	
Krk-522-4	Bivocont Conductive electrode relay according to enclosed legend Assembly: U-rail assembly SUPPLY VOLTAGE: 24 V AC / DC Extent: 2 potential-free contact Protection class: IP20 Origin: Hungary customs tariff number: 90261029
Rcm3103m 9026102190	
Rcm4008s Nivoswitch Vibrating Fork Level Switch9026102900	
Nwp1051m	
Tbj-520-2	
Nwn-105-1 Float Level Sensor Ls1.1, Ls1.2	

Nln1201m Nivofloat Float Level Switch	
4x085g0022ydo/10ppm Sonde	
Rcm-401- 3	
Ksp2010m Nivocont Conductive Socket	
Npk-46-60	
Sat-304-0	
Npk4305m / 9026102190	
Rcm-301-3	
Rcm-400-3 Level Switch Nivoswitch	
Klp2040m Separator	
Easytrek Spa-370-4	
Rcm4158e	
Ksk-201 Electrode	
Separator Rkk-312-4m	
Krk-512-5	
Echotrek Stp-462-4	
Drucksensor Nivelco Nipress Drh-3a2-2	
Dtf6512m Nivopress Hydrostatic Level Transmitter	
Spb-370-8ex	
Easytrek Spa-380-4	
12440	
Nivofloat Nwn-105-1 Schwimmerschalter	
Ss-Sen-362-8	Integrated 2-wire ultrasonic compact transmitter for liquids EchoTREK - Type SEN-362-8 Measuring range: 0.4 ... 7m (60 kHz) Housing: stainless steel Process connection: flange DN80 / PN16, stainless steel Analog output 4-20mA + HART / Ex
Drc2a22m Drucksensor	
Mi-Switch-Nst Rkh 502-1	Vibrating bar Limit switch for powder and granules, operating temperature: -20 ° C ... 110 ° C, oscillating rod: stainless steel (1.4571), housing made of aluminum, process connection: G 1 1/2 "high power relay output, vertical installation, length: 207 mm, Supply voltage: 20-255 V AC / DC Output: SPDT, potential-free relay; 8A 250V AC
Nwp1051m Nivofloat Tilting Float Level Switch	
Spb-390-4 Easytrek	
Npk4408s Konverter	
Rhr-520-1,Nivocont (2m)	
Hbn5104s Microtek Tdr Level Transmitter	

Spa-380-4 Konverter Ebene Easytrek	
Naw1040s Adapter	
Spb-380-4 Ultrasonic Level Transmitter	
Easytrek	
Nivotrack Mta-500	
Drl-4a2-2	
Npk-43-10	
Rcp4013m	
Ctr-211-8 Nivocap 1.1m	
Rcm-400-3 (Art. Nr. 9701001850000000)	
Mlb-112-0 Magnetic Level Indicators	
Drucksensor Drh-3a2-2m	
Ksh303m Elektroden-Halter	
Easytrek Scd-310-4	
Rkh-502-1	
Sap- 200-0	
Npk4310m / 9026102190	
Rkr-503-5ex	
Spa370as Easytrek Ultrasonic Level Transmitter	
Nwp-110-1 Float Cable Level Sensor For	
Sewerage And Effluent	
Rcm4003	METER
Klp-201-0	
Krk-512-5 Level Control Relay	
Ss-Spb-370-8	Ultrasonic compact transmitter for liquids Housing PVDF, IP68 Measuring range 0.35 ... 8m (60 KHz) Connection 1 "or 2" BSP Power supply 12 ... 36 V DC Output 4-20 mA + HART / Ex ia
Naa1010m Leitungsverbinder	
Echotrek Stp-480-2	
Spa390m Easytrek	
Krk5125m Grenzschalter	
Npk-44-15	
Kln2100m	
Krk-512-5 Sensor	
Hpn4104s Microtrek Tdr Level	
Transmitter9026102190	
Mbl-515-2 Magnetostrictive Level Transmitters	
11705	

1262
Krk-512-5 Conductive Level Switch
Pew-215-6ex
Npk4690s Hydrostatic Level Transmitter
Kln-205-0
Rfm-404-A Nivoswitch
Sap-300-0 Display
Spt-39f-3 Ultraschallwandler-Level, 3-4m, 4-20ma, Easytrek
Ksh-203
Rcm4013m
Krk5125m Grenzschalter Nivocont
Npk-43-07
Kkh225m
Nivomag Mka-210-4
Pmm-312-1
Drh3a22s 9026102190nipress Pressure Transmitter
Schalter Endplatte Ebene Rcp-401-6m
Easytrek Spb-380-4
Nivofloat Nwn-110-1 Float Level Sensor Pear-Shaped For Wastewater, Neoprene.Kabel
???-220-0 R42573i Schwimmerschalter Niveau
Nivopress Npk-431-0
Npk-45-25
Sgv3804m Echotrek
Spt-390-4
Mlb-112-0 Nivoflip
Krk5125m Nivocont Conductive Level Control Relay
Spt-390-H
Kln-220
505-1
Tbc-521-2
4x085g0023ydo/20ppm
Obsolete - Easy Trek Sca-360-4 - Replaced By - Echotrek Stp-462-4
Nivoswitch Tuning fork limit switch according to the enclosed description

Rcm-400-M	probe length 69mm probe material: stainless steel 1.4571 Degree of protection in connection plug: IP65 process connection: 1 "BSP Process connection: 3-wire DC, M12 connector Supply voltage: DC 12 - 55V
Easytrek Spa-390-4	
Rcm-401-M	Nivoswitch Tuning fork limit switch according to the enclosed description probe length 125mm probe material: stainless steel 4.4571 Degree of protection in connection plug: IP65 process connection: G1 Process connection: 3-wire DC / M12 connection, plug Supply voltage: DC 12 - 55V