

## Nding Messtechnik

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Nding Messtechnik** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Nding Messtechnik Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">0-250m Bar Transmitter</a>	IP 67 DNV-GL
<a href="#">P115-400-G360</a>	Pressure transmitter P 115 0 ... 100mbar rel. Output: 4 ... 20 mA 2-wire Accuracy: <1% F.S. Process connection: G1 / 2A, and 11.6mm bore, 1.4404 Process seal: EPDM rubber 2m cable tail IP 68 Auxiliary voltage: 24V DC (9 ... 30V) No.
<a href="#">P121-400-G31R</a>	
<a href="#">P131-410-L11-316L</a>	
<a href="#">P133-111-P002-01R</a>	
<a href="#">P133-4W2-6020-01</a>	
<a href="#">P135K-450-1015-2</a>	
<a href="#">P20-HB1-1111</a>	
<a href="#">PDM 80</a>	
<a href="#">PDM80-2510-010 (230442105)</a>	Digital differential pressure gauge PDM 80-2 Measuring range: 0...10 bar Output: 0(4)...20 mA Three-wire Process connection: G1/4 internal, 1.4404 Process seal: FPM (Viton) Auxiliary voltage: 24V DC

(19...30V) No.	
<a href="#">P131-4B0-V17</a>	Pressure transmitter P131 0...50 mbar rel. Output: 4...20 mA 2-wire Process connection: G 1 internal, ISO 228-1, 1.4404 Process sealing: FPM (Viton) Cable length: 2 m, IP67 rated cable, potted electronics Accuracy: $\leq \pm 0.5\%$ FS @ 25°C Overload: -0.3/4 bar Auxiliary voltage: 9...30V DC No.
<a href="#">PTM82-3310-HD4G-0530</a>	Digital pressure gauge/thermometer 10bar/100°C Measuring range 1: 0...10.0 bar HD Overpressure resistance: 105 bar Burst pressure: 175 bar Analog output 4...20 mA, 3-wire 1 contact output: DC PNP, max. 200 mA Measuring range 2: 0...100°C Analog output: 4...20 mA, 3-wire Probe length: 50 mm, 1.4404 Process connection: G1/2", 1.4404 Process seal: EPDM rubber Auxiliary voltage: 24V DC (10...30V) No.