

Nord Drivesystem

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Nord Drivesystem Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Nord Drivesystem Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
BCSB 1-6L	Tag no :27P24 (P-234801)
772.1F AL-160MH/4	
SK1282AFBH-90SP/4 BRE20 TF	
SK1282AFBH F	Product name: Parallel shaft gear unit-F Translation 28.33 Level 2 n2 assuming n1 49,000 rpm Operating factor 1.00 Output torque M2 (Nm) 225.00 Gearbox design M1 Housing type hollow shaft flange B5 Selection of attachment cylinder F Attachment cylinder F Shaft size 30H7 Flange diameter (mm) 200 Venting Pressure venting Cover Cover Fastening element With fastening element Motor flange 160S Lubricant type Without lubricant Class Oil CLP 220 Lubricant quantity (l) 0.950 Specified lubricant: Mineral oil ISO VG 220 Color 7031 Blue-Gray Paint type: normal paint Painting instructions Basic (2) Loose part cover drive pinion Fastening element Engine gasket
	Version: as already delivered with the serial number 1003361609.00 Product designation Helical geared motor Engine speed 2,825 1 / min Translation 11,66 Output speed

Sk0f-71l/2	242,000 1 / min Service factor 2.30 Output torque M2 (Nm) 21.70 Power (kW) 0,550 Voltage (V) 230/400 Frequency (Hz) 50 Operating mode S1 Degree of protection motor IP55 Insulation class F Rated current 1 (AMP) 2.17 Rated current 2 (AMP) 1.25 Cosine 1 0.83 Type Gear M1 Housing type flange B5 Wave measure 16X28 Part number Special shaft 000000000050031130 Diameter flange (mm) 120 Vent open, with transport lock Circuit type star Terminal box position / cable insert 1 / I Lubricant mineral oil ISO VG 220 Class oil CLP 220 Lubricant quantity (l) 0.130 Color 7021 black gray Paint type solid color Painting instructions painting 2 CE Logo Yes CCC Logo No. Weight approx. 12 KG / ST
Sk 33f Al-132m/4 Tf - Obsolete, Replaced By - Sk 33f Al-132mp/4 Tf	
Sk 92372-90s/4 Tw - Obsolete, Replaced By - Sk 92372.1 V-90sp/4 Tw	
Sk 92372.1 V-90sp/4 Tw	
Sk01f-90l/4 Ear1	
Sk9022.1az-80s/4	Version: as already delivered with the serial number 202303822-100 - - - - - Product designion bevel helical geared motor Engine speed 1,375 1 / min Translation 219.25 Output speed 6,300 1 / min Service factor 1.00 Output torque M2 (Nm) 837,00 Max. Output torque. M2 max. (Nm) 860.00 Power (kW) 0,550 Voltage (V) 230/400 Frequency (Hz) 50 Operating mode S1 Degree of protection motor IP55 Insulation class F Rated current 1 (AMP) 2.63 Rated current 2 (AMP) 1.52 Cosine 1 0.73 Type Gearbox M4 Housing type hollow shaft flange B14 Wave measure 40H7 Venting pressure venting Circuit type star Terminal box position / cable insert 1 / I Lubricant mineral oil ISO VG 220 Class oil CLP 220 Lubricant quantity (l) 4,200 Color 7031 blue gray Paint type solid color Painting instructions painting 2 CE Logo Yes CCC Logo No. Attention: The service factor is less than or equal to 1.0. The transmission will be overloaded if the in
Sk 33f Al-132mp/4 Tf	