Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Nuova General Instruments



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Nuova General Instruments Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Nuova General Instruments Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Type: D7/C	Homologated: ASME VIII DIV.1 - UV Material: SS AISI 316L Conn. In: 3/8" NPT Conn. Out: 1/2" NPT Gasket: VITON (-20 / +200 °C) Set Pressure: 10,50 bar Relief Flow: 125,27 SCFM 15,6 °C Fluid: AIR
D10/C Replacement	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure: 12,00 bar Relief Flow: 843,17 Kg/h 0 °C
D10/Cs 0,86	4Bar
D10	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 42,00 bar Relief Flow: 2509,34 Kg/h 0 °C Fluid: AIR
D10/C 2012 G/S/L 0.77 0.5	-20/275 C DN 3/8”x3/4” PRESSURE SAFETY VALVE
D10 / 25bar / 1/2''	
D10/S	copy of s.n. 010242577

Ürün	Açıklama
	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 12,00 bar Relief Flow: 754,9
CW14N_D10/CS 4BAR	and 3BAR 2pcs.
D10/C	Homologated: TEST NGI Material: SS AISI 316L Conn. In: 3/8" NPT Conn. Out: G.3/4" ISO 228 Gasket: KALREZ (-20 / +275 °C) Set Pressure: 0,50 bar Relief Flow: 82,4 Kg/h 0 °C Fluid: AIR
G20/L 6,00bar	copy of s.n. 018069854 CE IV Brass CW614N In : G.1" ISO 228 Out : G.1"1/4 ISO 228 EPDM (-50 / +150 °C) 6,00bar 14048,7 Kg/h water
G20/L 5,00bar	copy of s.n. 018069851 CE IV Brass CW614N In : G.1" ISO 228 Out : G.1"1/4 ISO 228 5,00 bar 12824,65 Kg/h water
GAUGE,PRESSURE:	TYPE BOURDON TUBE,PRESSURE RANGE 0-4 BAR,DIAL SIZE 100 MM,CONNECTION SIZE 1/2 IN,CONNECTION TYPE MNPT,CONNECTION LOCATION BOTTOM,CASE STAINLESS STEEL GR.316,ENCLOSURE RATING IP68,STANDARD EN 837,SPECIAL FEATURES DRY CASE,SOLID FRONT DRAWING:3871-KK-VD-IV2715966400001 PAGE 6,10 POS: 39,93,TAG/EQUIP NO:2100-PI-21088,PON:7500063866
8.SMA 0-400 41M 1 FPM	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
G20/L 5,00 bar SS AISI 316L	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1" ISO 228 Conn. Out:G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 5,00 bar Relief Flow: 12824,65 Kg/h Fluid: WATER
G20/L 6,00 bar SS AISI 316L	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1" ISO 228 Conn. Out:G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 6,00 bar Relief Flow: 12824,65 Kg/h Fluid: WATER
D10/CS G1/2" G3/4" 4 Bar	Type: D10 / CS Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.00 bar Discharge Flow Rate: 192.3 Kg / h Fluid: STEAM
D10/CS G1/2" G3/4" 4.5 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.50 bar Discharge Flow Rate: 211.28 Kg / h Fluid: SATURATED STEAM
D10/CS G1/2" G3/4" 7 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.00 bar Discharge capacity: 305.89 Kg / h Fluid: SATURATED STEAM

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
D10/CS G1/2" G3/4" 7,5 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.50 bar Discharge capacity: 324.77 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 4 Bar	Type: G10 / S Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.00 bar Discharge capacity: 190.07 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 4.5 Bar	Type: G10 / S Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.50 bar Discharge capacity: 208.83 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 7,5 Bar	Type: G10 / S Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.50 bar Discharge capacity: 320.99 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 8 Bar	Type: G10 / S Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C)

Ürün	Açıklama
	Press. Calibration: 8.0 bar Discharge capacity: 399.61 Kg / h Fluid: SATURATED STEAM
Type: D10 ,Homologated : CE IV	material : Brass CW614N, Connection In : 1/2" NPT Connection Out: -- Gasket : Viton (-20/+200 C) Set Pressure : 4 BAr Relief flow : 287,09 Kg/H0 C Fluid : Air P/N# 810-CT-14V
D10/CS	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 45,00 bar Relief Flow: 2998,58 Kg/h 0 °C Fluid: AIR
Y001 D7 G.1/4" ISO 228	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: EPDM (-50 / +150 °C) Set Pressure: 2,50 bar Relief Flow: 102,86 Kg/h 0 °C Fluid: AIR
D7	Homologated: TEST NGI Material: Brass CW614N Conn. In: G.3/8" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 0,30 bar Relief Flow: 22,84 Kg/h Fluid: STEAM Copy of S/N 018077521
für 4 BAR	
CW614N	für 4 und 3 Bar
008183161	
008365627	
009234585	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
009274576	
009274734	
011376529	
012163181	
012312650	
013232305 / 013232306	
015466419	
017580806	
017580819	
019542172	
019542184	
019543432	
CW614N	
G10/S	
G14/L	
G20/L	
KR	
D10/CS 4 bar	copf of sn. 01813 brass CW614N1772
G20/S	Homologated: CE IV Material: Brass CW614N Conn. In: 1" NPT Conn. Out: G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 23,00 bar Relief Flow: 10415,46 Kg/h 0 °C Fluid: REFRIGERANT copy of s.n. 013359003
SFBSPG-V-10-S6-S-S-6-15-NTM	GAUGE,PRESSURE:0-10BAR,1/2IN,NPT, 100MM,-20-85DEG,SFBSPG,SFBSPG-V-10-S6- S-S-6-15-NTM-(0 to 10)-B-A-BB-X-SN-SY,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
manometer: 0-0.2 Kg/cm2 ,316L 1/2	
Manometer: 6" 1/2" NPT	Model 1.40.2.S.G MGS 40 6" DIAL 1/2" Bottom Coupling Monel 400
Model 1.40.2.A.G MGS 40	6DIAL 1/2 Bottom Monel400
MGS18 1.18.2.A.E/0-25/41M + M3D	
see List	
Model: D7 CE IV	Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure: 12,00 bar Relief Flow: 301,27 m3/h 0 °C Fluid: AIR
G14/L 1" T.C	Homologated: CE IV Material: Brass CW614N - SS AISI 316L Conn. In: 1" T.C. Conn. Out: G.1" ISO 228 Gasket: KALREZ (-20 / +250 °C) Set Pressure: 2,50 bar Relief Flow: 406,19 Kg/h 0 °C Fluid: AIR
G10/L G.3/4" ISO 228	Homologated: CE IV Material: Brass CW614N - SS AISI 316L Conn. In: G.3/4" ISO 228 Conn. Out:G.1" ISO 228 Gasket: KALREZ (-20 / +275 °C) Set Pressure:2,50 bar Relief Flow: 220,08 Kg/h 0 °C Fluid: AIR
Safety valve mixed type G14/L-MS in 1" triclamp	(DN50,4) out 1" gas ISO 228 set 2,5 bar (Kalrez seal, CE trademark)
Safety valve mixed type G10/L-MS in 3/4" gas	ISO 228 out 1" gas ISO 228 set 2,5 bar
Nr.020503610	Type: D10 D10 Quantity: 1 Homologated: CE IV Material: Brass CW614N

Ürün	Açıklama
	Conn. In: G.3/8" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 404,05 Kg/h 0 °C Fluid: AIR
Z7	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 8,00 bar Relief Flow: 272,12 Kg/h 0 °C Fluid: AIR
D10/S SAFETY VALVE 8.8 BAR	
Copy of S/N 021522519	Type: D10 D10 Quantity: 10 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 14,00 bar Relief Flow: 871,89 Kg/h 0 °C Fluid: AIR
COPY OF S.N. 021443294	Type: D10/C D10/C Quantity: 1 Homologated: CE IV Material: Brass CW614N (nickel plated) Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 3,70 bar Relief Flow: 180,86 Kg/h Fluid: STEAM
E5/LS600	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1/2" ISO 228 Conn. Out: G.1" ISO 228 Gasket: VESPEL (-196 / +250 °C) Set Pressure (bar gauge): 350,00 bar Relief Flow: 5509,73 Kg/h 0 °C Fluid: AIR

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
D10/CS	copy of s.n. 019563438 Homologated: CE IV Material: Brass CW614N Conn. In: 1/2" NPT Conn. Out: G.3/4" ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 30,00 bar Relief Flow: 487,89 Kg/h 0 °C Fluid: REFRIGERANT
D series relief and safety valve 11 bar	Relief valve: 1 timed automatic, 1 manual Safety valve ½ Drain valve manual ¾ and 1” Automatic drain valve ¾ and 1”
10G/S/L0.86	
D10/CS, G1/2" G3/4" PTFE	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-196 / +250 °C) Set Pressure (bar gauge):8,50 bar Relief Flow:614,56 Kg/h 0 °C Fluid:AIR
D10/CS, G1/2" G3/4" PTFE	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-196 / +250 °C) Set Pressure (bar gauge):8,00 bar Relief Flow:581,9 Kg/h 0 °C Fluid:AIR
D10/CS, G1/2" G3/4" VİTON	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-120 / +200 °C) Set Pressure (bar gauge):5,50 bar Relief Flow:418,61 Kg/h 0 °C Fluid:AIR
D10/CS, G1/2" G3/4" VİTON	Homologated:CE IV Material:Brass CW614N

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-20 / +200 °C) Set Pressure (bar gauge):5,0 bar Relief Flow:385,96 Kg/h 0 °C Fluid:AIR
G10/S, G1"-G1", VİTON	Homologated:CE IV Material:Brass CW614N Conn. In:G.1" ISO 228 Conn. Out:G.1" ISO 228 Gasket:PTFE (-20 / +200 °C) Set Pressure (bar gauge):4,00 bar Relief Flow:316,91 Kg/h 0 °C Fluid:AIR
G10/S, G1"-G1", VİTON	Homologated:CE IV Material:Brass CW614N Conn. In:G.1" ISO 228 Conn. Out:G.1" ISO 228 Gasket:PTFE (-20 / +200 °C) Set Pressure (bar gauge):4,50 bar Relief Flow:316,91 Kg/h 0 °C Fluid:AIR
D7 valve	Copy of S/N 023624002 Type: D7 Homologated: ASME VIII DIV.1 - UV Material: Brass CW614N Conn. In: 1/4" NPT Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 10,00 bar Relief Flow: 621,47 lb/h ~ 281,85 Kg/h 15,6 °C Fluid: AIR
¼ npt female female 90 elbow	
¼ npt male male	
023624002	D7 Homologated: ASME VIII DIV.1 - UV Material: Brass CW614N Conn. In: 1/4" NPT Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 10,00 bar Relief Flow: 621,47 lb/h ~ 281,85 Kg/h 15,6 °C Fluid: AIR

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
OEM ST18 0-16 BAR	
3/8"-3/4" 6bar	
G20	Homologated: CE IV Material: Brass CW614N Conn. In: G.1" ISO 228 Conn. Out: G.1"1/4 ISO 228 Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 12,00 bar Relief Flow: 3255,01 Kg/h 0 °C Fluid: AIR
023093899 G20	TEST NGI Brass CW614N G.1" ISO 228 G.1"1/4 ISO 228 KALREZ (-20 / +250 °C) 0,30 bar 472,58 Kg/h 0 °C ETHYL ACETATE
FFKM (-10 / +255 °C)	G20 TEST NGI Brass CW614N G.1" ISO 228 G.1"1/4 ISO 228 FFKM (-10 / +255 °C) 0,30 bar 472,58 Kg/h 0 °C ETHYL ACETATE
021146635 D10/CS	S/C LIBERA Brass CW614N G.1/2" ISO 228 G.3/4" ISO 228 KALREZ (-20 / +250 °C) 0,20 bar 100,54 Kg/h 0 °C ETHYL ACETATE
D10/CS - FFKM (-10 / +255 °C)	S/C LIBERA Brass CW614N G.1/2" ISO 228 G.3/4" ISO 228 0,20 bar 100,54 Kg/h 0 °C ETHYL ACETATE
020222429	Type: F25/P F25/P

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Quantity: 2 Homologated: CE IV Material: Brass CW614N Conn. In: 1"1/2 NPT Conn. Out: --- Gasket: EPDM (-50 / +150 °C) Set Pressure (bar gauge): 5,00 bar Relief Flow: 2412,1 Kg/h 0 °C Fluid: AIR
copy of s.n. 015451497	Type: D10/CS D10/CS Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 4,00 bar Relief Flow: 192,3 Kg/h Fluid: STEAM
011330281	Type: D10 D10 Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 11,00 bar Relief Flow: 696,45 Kg/h 0 °C Fluid: AIR
copy of s.n. 024174570	G20/L Homologated: CE IV Material: SS AISI 316L Conn. In: 1"1/2 T.C. Gasket: METALLICA (-196 / +450 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 1035,29 Kg/h
copy of s.n. 020133733	G20 Homologated: INAIL+CE IV Material: SS AISI 316L Conn. In: 1"1/2 T.C. Conn. Out: 1"1/2 T.C Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 1035,29 Kg/h

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
022046474	Homologated: CE IV+ATEX Material: SS AISI 316L Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 10,00 bar Relief Flow: 518,41 Kg/h 0 °C
0036 2020	Type: D7/S D7/S Quantity: 2 Homologated: CE IV Material: Brass CW614N Conn. In: 3/8" NPT Conn. Out: --- Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 55,00 bar Relief Flow: 2025,21 Kg/h 0 °C Fluid: CO2
020324147	D7/S Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: 3/8" NPT Conn. Out: --- Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 55,00 bar Relief Flow: 2025,21 Kg/h 0 °C Fluid: CO2
B12	Homologated:CE IVMaterial:Brass CW614NConn. In:G.1/2" ISO 228Conn. Out:---Gasket:NBR (-10 / +100 °C)Set Pressure (bar gauge):2,50 barRelief Flow:279,53 Kg/h 0 °CFluid:AIR
GI Model D7 Discharge Pressure Safety Valve	1/4" NPT male – Brass – 10 Bar
Fort Vale 88MM Super Maxi HighFlow Relief Valve	4” Flange - 316 S. Steel - 4.40 bar PRV Part Number 013/163008SL
1 inç	12.2 bar safety valve
Z21	
D14	
1½ - 8 Bar Sealed Safety Valve In Hydrophoric Tank	
005201338	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
016301867 - Safety Valve	
D10/S (copy of s.n. 013319176.)	Homologated: CE IV Material: Brass CW614N Conn. In: G.1 / 2 "ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 ° C) Set Pressure: 11.00 bar Relief flow: 696.45 kg / h 0 ° C Fluid: AIR
D10011087651	
D7 Cw614n G.1/4"	480 Kg/h 0 °C
Type B38/L	copy of s.n. 015253023 Type: B38/L Homologated: ASME VIII DIV.1 - UV+CE IV Material: SS AISI 316L Conn. In: 2" ANSI 150 Conn. Out: 2" ANSI 150 Gasket: METALLICA (-196 / +450 °C) Set Pressure: 12,00 bar Relief Flow: 19127,71 lb/h 15,6 °C Fluid: AIR
20g/S/L - 0,83 - 12bar	
½ - 10 Bar Sealed Safety Valve In Air Tank	
011087651	
B20/P	
½ - 4 Bar Sealed Safety Valve In Hot Water Tank	
D10/C 2014	
Z20	
10g/S/L - 0,86 - 12bar	
D10 Cw614n G.1/2"	930,37 Kg/h 0 °C
C 10 2009	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.