

Nuova General Instruments



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Nuova General Instruments** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Nuova General Instruments Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Type: D7/C	Homologated: ASME VIII DIV.1 - UV Material: SS AISI 316L Conn. In: 3/8" NPT Conn. Out: 1/2" NPT Gasket: VITON (-20 / +200 °C) Set Pressure: 10,50 bar Relief Flow: 125,27 SCFM 15,6 °C Fluid: AIR
D10/C Replacement	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure: 12,00 bar Relief Flow: 843,17 Kg/h 0 °C
D10/Cs 0,86	4Bar
D10	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 42,00 bar Relief Flow: 2509,34 Kg/h 0 °C Fluid: AIR
D10/C 2012 G/S/L 0.77 0.5	-20/275 C DN 3/8"x3/4" PRESSURE SAFETY VALVE
D10 / 25bar / 1/2"	
D10/S	copy of s.n. 010242577 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 12,00 bar Relief Flow: 754,9
CW14N_D10/CS 4BAR	and 3BAR 2pcs.
D10/C	Homologated: TEST NGI Material: SS AISI 316L Conn. In: 3/8" NPT Conn. Out: G.3/4" ISO 228 Gasket: KALREZ (-20 / +275 °C) Set Pressure: 0,50 bar Relief Flow: 82,4 Kg/h 0 °C Fluid: AIR

G20/L 6,00bar	copy of s.n. 018069854 CE IV Brass CW614N In : G.1" ISO 228 Out : G.1"1/4 ISO 228 EPDM (-50 / +150 °C) 6,00bar 14048,7 Kg/h water
G20/L 5,00bar	copy of s.n. 018069851 CE IV Brass CW614N In : G.1" ISO 228 Out : G.1"1/4 ISO 228 5,00 bar 12824,65 Kg/h water
GAUGE,PRESSURE:	TYPE BOURDON TUBE,PRESSURE RANGE 0-4 BAR,DIAL SIZE 100 MM,CONNECTION SIZE 1/2 IN,CONNECTION TYPE MNPT,CONNECTION LOCATION BOTTOM,CASE STAINLESS STEEL GR.316,ENCLOSURE RATING IP68,STANDARD EN 837,SPECIAL FEATURES DRY CASE,SOLID FRONT DRAWING:3871-KK-VD-IV2715966400001 PAGE 6,10 POS:39,93,TAG/EQUIP NO:2100-PI-21088,PON:7500063866
8.SMA 0-400 41M 1 FPM	
G20/L 5,00 bar SS AISI 316L	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1" ISO 228 Conn. Out:G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 5,00 bar Relief Flow: 12824,65 Kg/h Fluid: WATER
G20/L 6,00 bar SS AISI 316L	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1" ISO 228 Conn. Out:G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 6,00 bar Relief Flow: 12824,65 Kg/h Fluid: WATER
D10/CS G1/2" G3/4" 4 Bar	Type: D10 / CS Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.00 bar Discharge Flow Rate: 192.3 Kg / h Fluid: STEAM
D10/CS G1/2" G3/4" 4.5 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.50 bar Discharge Flow Rate: 211.28 Kg / h Fluid: SATURATED STEAM
D10/CS G1/2" G3/4" 7 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.00 bar Discharge capacity: 305.89 Kg / h Fluid: SATURATED STEAM
D10/CS G1/2" G3/4" 7,5 Bar	Type: D10 / CS Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 / 2 "ISO 228 Conn. Outlet: G.3 / 4 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.50 bar Discharge capacity: 324.77 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 4 Bar	Type: G10 / S Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.00 bar Discharge capacity: 190.07 Kg / h Fluid: SATURATED STEAM
	Type: G10 / S Quantity: 20 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO

G10/S G1" G1" 4.5 Bar	228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 4.50 bar Discharge capacity: 208.83 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 7,5 Bar	Type: G10 / S Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 7.50 bar Discharge capacity: 320.99 Kg / h Fluid: SATURATED STEAM
G10/S G1" G1" 8 Bar	Type: G10 / S Quantity: 10 Approval: CE IV Material: Brass CW614N Conn. Inlet: G.1 "ISO 228 Conn. Outlet: G.1 "ISO 228 Tightness: VITON (-20 / +200 ° C) Press. Calibration: 8.0 bar Discharge capacity: 399.61 Kg / h Fluid: SATURATED STEAM
Type: D10 ,Homologated : CE IV	material : Brass CW614N, Connection In : 1/2" NPT Connection Out: -- Gasket : Viton (-20/+200 C) Set Pressure : 4 BAr Relief flow : 287,09 Kg/H0 C Fluid : Air P/N# 810-CT-14V
D10/CS	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 45,00 bar Relief Flow: 2998,58 Kg/h 0 °C Fluid: AIR
Y001 D7 G.1/4" ISO 228	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: EPDM (-50 / +150 °C) Set Pressure: 2,50 bar Relief Flow: 102,86 Kg/h 0 °C Fluid: AIR
D7	Homologated: TEST NGI Material: Brass CW614N Conn. In: G.3/8" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure: 0,30 bar Relief Flow: 22,84 Kg/h Fluid: STEAM Copy of S/N 018077521
für 4 BAR	
CW614N	für 4 und 3 Bar
008183161	
008365627	
009234585	
009274576	
009274734	
011376529	
012163181	
012312650	
013232305 / 013232306	
015466419	
017580806	

017580819	
019542172	
019542184	
019543432	
CW614N	
G10/S	
G14/L	
G20/L	
KR	
D10/CS 4 bar	copf of sn. 01813 brass CW614N1772
G20/S	Homologated: CE IV Material: Brass CW614N Conn. In: 1" NPT Conn. Out: G.1"1/4 ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure: 23,00 bar Relief Flow: 10415,46 Kg/h 0 °C Fluid: REFRIGERANT copy of s.n. 013359003
SFBSPG-V-10-S6-S-S-6-15-NTM	GAUGE,PRESSURE:0-10BAR,1/2IN,NPT,100MM,-20-85DEG,SFBSPG,SFBSPG-V-10-S6- S-S-6-15-NTM-(0 to 10)-B-A-BB-X-SN-SY,
manometer: 0-0.2 Kg/cm2 ,316L 1/2	
Manometer: 6" 1/2" NPT	Model 1.40.2.S.G MGS 40 6" DIAL 1/2" Bottom Coupling Monel 400
Model 1.40.2.A.G MGS 40	6DIAL 1/2 Bottom Monel400
MGS18 1.18.2.A.E/0-25/41M + M3D	
see List	
Model: D7 CE IV	Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure: 12,00 bar Relief Flow: 301,27 m3/h 0 °C Fluid: AIR
G14/L 1" T.C	Homologated: CE IV Material: Brass CW614N - SS AISI 316L Conn. In: 1" T.C. Conn. Out: G.1" ISO 228 Gasket: KALREZ (-20 / +250 °C) Set Pressure: 2,50 bar Relief Flow: 406,19 Kg/h 0 °C Fluid: AIR
G10/L G.3/4" ISO 228	Homologated: CE IV Material: Brass CW614N - SS AISI 316L Conn. In: G.3/4" ISO 228 Conn. Out:G.1" ISO 228 Gasket: KALREZ (-20 / +275 °C) Set Pressure:2,50 bar Relief Flow: 220,08 Kg/h 0 °C Fluid: AIR
Safety valve mixed type G14/L-MS in 1" triclamp	(DN50,4) out 1" gas ISO 228 set 2,5 bar (Kalrez seal, CE trademark)
Safety valve mixed type G10/L-MS in 3/4" gas	ISO 228 out 1" gas ISO 228 set 2,5 bar

Nr.020503610	Type: D10 D10 Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: G.3/8" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 404,05 Kg/h 0 °C Fluid: AIR
Z7	Homologated: CE IV Material: Brass CW614N Conn. In: G.1/4" ISO 228 Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 8,00 bar Relief Flow: 272,12 Kg/h 0 °C Fluid: AIR
D10/S SAFETY VALVE 8.8 BAR	
Copy of S/N 021522519	Type: D10 D10 Quantity: 10 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 14,00 bar Relief Flow: 871,89 Kg/h 0 °C Fluid: AIR
COPY OF S.N. 021443294	Type: D10/C D10/C Quantity: 1 Homologated: CE IV Material: Brass CW614N (nickel plated) Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 3,70 bar Relief Flow: 180,86 Kg/h Fluid: STEAM
E5/LS600	Homologated: CE IV Material: SS AISI 316L Conn. In: G.1/2" ISO 228 Conn. Out: G.1" ISO 228 Gasket: VESPEL (-196 / +250 °C) Set Pressure (bar gauge): 350,00 bar Relief Flow: 5509,73 Kg/h 0 °C Fluid: AIR
D10/CS	copy of s.n. 019563438 Homologated: CE IV Material: Brass CW614N Conn. In: 1/2" NPT Conn. Out: G.3/4" ISO 228 Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 30,00 bar Relief Flow: 487,89 Kg/h 0 °C Fluid: REFRIGERANT
D series relief and safety valve 11 bar	Relief valve: 1 timed automatic, 1 manual Safety valve ½ Drain valve manual ¾ and 1" Automatic drain valve ¾ and 1"
10G/S/L0.86	
D10/CS, G1/2" G3/4" PTFE	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-196 / +250 °C) Set Pressure (bar gauge):8,50 bar Relief Flow:614,56 Kg/h 0 °C Fluid:AIR
D10/CS, G1/2" G3/4" PTFE	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-196 / +250 °C) Set Pressure (bar gauge):8,00 bar Relief Flow:581,9 Kg/h 0 °C Fluid:AIR
D10/CS, G1/2" G3/4" VİTON	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-120 / +200 °C) Set Pressure (bar gauge):5,50 bar Relief Flow:418,61 Kg/h 0 °C Fluid:AIR
D10/CS, G1/2" G3/4" VİTON	Homologated:CE IV Material:Brass CW614N Conn. In:G.1/2" ISO 228 Conn. Out:G.3/4" ISO 228 Gasket:PTFE (-20 / +200 °C) Set Pressure (bar gauge):5,0 bar Relief Flow:385,96 Kg/h 0 °C Fluid:AIR
	Homologated:CE IV Material:Brass CW614N Conn. In:G.1"

G10/S, G1"-G1", VİTON	ISO 228 Conn. Out:G.1" ISO 228 Gasket:PTFE (-20 / +200 °C) Set Pressure (bar gauge):4,00 bar Relief Flow:316,91 Kg/h 0 °C Fluid:AIR
G10/S, G1"-G1", VİTON	Homologated:CE IV Material:Brass CW614N Conn. In:G.1" ISO 228 Conn. Out:G.1" ISO 228 Gasket:PTFE (-20 / +200 °C) Set Pressure (bar gauge):4,50 bar Relief Flow:316,91 Kg/h 0 °C Fluid:AIR
D7 valve	Copy of S/N 023624002 Type: D7 Homologated: ASME VIII DIV.1 - UV Material: Brass CW614N Conn. In: 1/4" NPT Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 10,00 bar Relief Flow: 621,47 lb/h ~ 281,85 Kg/h 15,6 °C Fluid: AIR
¼ npt female female 90 elbow	
¼ npt male male	
023624002	D7 Homologated: ASME VIII DIV.1 - UV Material: Brass CW614N Conn. In: 1/4" NPT Conn. Out: --- Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 10,00 bar Relief Flow: 621,47 lb/h ~ 281,85 Kg/h 15,6 °C Fluid: AIR
OEM ST18 0-16 BAR	
3/8"-3/4" 6bar	
G20	Homologated: CE IV Material: Brass CW614N Conn. In: G.1" ISO 228 Conn. Out: G.1"1/4 ISO 228 Gasket: NBR (-10 / +100 °C) Set Pressure (bar gauge): 12,00 bar Relief Flow: 3255,01 Kg/h 0 °C Fluid: AIR
023093899 G20	TEST NGI Brass CW614N G.1" ISO 228 G.1"1/4 ISO 228 KALREZ (-20 / +250 °C) 0,30 bar 472,58 Kg/h 0 °C ETHYL ACETATE
FFKM (-10 / +255 °C)	G20 TEST NGI Brass CW614N G.1" ISO 228 G.1"1/4 ISO 228 FFKM (-10 / +255 °C) 0,30 bar 472,58 Kg/h 0 °C ETHYL ACETATE
021146635 D10/CS	S/C LIBERA Brass CW614N G.1/2" ISO 228 G.3/4" ISO 228 KALREZ (-20 / +250 °C) 0,20 bar 100,54 Kg/h 0 °C ETHYL ACETATE
D10/CS - FFKM (-10 / +255 °C)	S/C LIBERA Brass CW614N G.1/2" ISO 228 G.3/4" ISO 228 0,20 bar 100,54 Kg/h 0 °C ETHYL ACETATE
020222429	Type: F25/P F25/P Quantity: 2 Homologated: CE IV Material: Brass CW614N Conn. In: 1"1/2 NPT Conn. Out: --- Gasket: EPDM (-50 / +150 °C) Set Pressure (bar gauge): 5,00 bar Relief Flow: 2412,1 Kg/h 0 °C Fluid: AIR
copy of s.n. 015451497	Type: D10/CS D10/CS Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 4,00 bar Relief Flow: 192,3 Kg/h Fluid: STEAM
011330281	Type: D10 D10 Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: G.1/2" ISO 228 Conn. Out: ---

	Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 11,00 bar Relief Flow: 696,45 Kg/h 0 °C Fluid: AIR
copy of s.n. 024174570	G20/L Homologated: CE IV Material: SS AISI 316L Conn. In: 1"1/2 T.C. Gasket: METALLICA (-196 / +450 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 1035,29 Kg/h
copy of s.n. 020133733	G20 Homologated: INAIL+CE IV Material: SS AISI 316L Conn. In: 1"1/2 T.C. Conn. Out: 1"1/2 T.C Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 6,00 bar Relief Flow: 1035,29 Kg/h
022046474	Homologated: CE IV+ATEX Material: SS AISI 316L Conn. In: G.1/2" ISO 228 Conn. Out: G.3/4" ISO 228 Gasket: VITON (-20 / +200 °C) Set Pressure (bar gauge): 10,00 bar Relief Flow: 518,41 Kg/h 0 °C
0036 2020	Type: D7/S D7/S Quantity: 2 Homologated: CE IV Material: Brass CW614N Conn. In: 3/8" NPT Conn. Out: --- Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 55,00 bar Relief Flow: 2025,21 Kg/h 0 °C Fluid: CO2
020324147	D7/S Quantity: 1 Homologated: CE IV Material: Brass CW614N Conn. In: 3/8" NPT Conn. Out: --- Gasket: PTFE (-196 / +250 °C) Set Pressure (bar gauge): 55,00 bar Relief Flow: 2025,21 Kg/h 0 °C Fluid: CO2
B12	Homologated:CE IVMaterial:Brass CW614NConn. In:G.1/2" ISO 228Conn. Out:---Gasket:NBR (-10 / +100 °C)Set Pressure (bar gauge):2,50 barRelief Flow:279,53 Kg/h 0 °CFluid:AIR
GI Model D7 Discharge Pressure Safety Valve	1/4" NPT male - Brass - 10 Bar
Fort Vale 88MM Super Maxi HighFlow Relief Valve	4" Flange - 316 S. Steel - 4.40 bar PRV Part Number 013/163008SL
1 inç	12.2 bar safety valve
Z21	
D14	
1½ - 8 Bar Sealed Safety Valve In Hydrophoric Tank	
005201338	
016301867 - Safety Valve	
D10/S (copy of s.n. 013319176.)	Homologated: CE IV Material: Brass CW614N Conn. In: G.1 / 2 "ISO 228 Conn. Out: --- Gasket: VITON (-20 / +200 ° C) Set Pressure: 11.00 bar Relief flow: 696.45 kg / h 0 ° C Fluid: AIR
D10011087651	
D7 Cw614n G.1/4"	480 Kg/h 0 °C

Type B38/L	copy of s.n. 015253023 Type: B38/L Homologated: ASME VIII DIV.1 - UV+CE IV Material: SS AISI 316L Conn. In: 2" ANSI 150 Conn. Out: 2" ANSI 150 Gasket: METALLICA (-196 / +450 °C) Set Pressure: 12,00 bar Relief Flow: 19127,71 lb/h 15,6 °C Fluid: AIR
20g/S/L - 0,83 - 12bar	
½ - 10 Bar Sealed Safety Valve In Air Tank	
011087651	
B20/P	
½ - 4 Bar Sealed Safety Valve In Hot Water Tank	
D10/C 2014	
Z20	
10g/S/L - 0,86 - 12bar	
D10 Cw614n G.1/2"	930,37 Kg/h 0 °C
C 10 2009	