

Olympic Controls

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Olympic Controls Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Olympic Controls Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
T-80148c24	RELAY T-BAR 24VDC 94OHM
901-24c-12	POWER RELAY, 24PDT, 12VDC, 1A, PLUG IN, PRODUCT RANGE: 900 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
802-24c	SWITCH, TOGGLE, 24PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:24PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
T-8601-51	SNAP IN CONTACT HAND RATCHET CRIMPING TOOL, FOR USE WITH TBAR 88601 AND 88631 SERIES CONNECTORS
801-36c24	POWER RELAY, 36PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE: 800 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
902-36c	SWITCH, TOGGLE, 36PDT, 1A, PRODUCT RANGE:902 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:36PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
802-36c	SWITCH, TOGGLE, 36PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:36PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
902-24c	SWITCH, TOGGLE, 24PDT, 1A, PRODUCT RANGE:902 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:24PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
901-36c-24	POWER RELAY, 36PDT, 24VDC, 1A, PLUG IN, PRODUCT RANGE: 900 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-12c24	POWER RELAY, 12PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE:

Ürün	Açıklama
	800 SERIES, CONTACT CONFIGURATION:12PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-48c24	POWER RELAY, 48PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE: 800 SERIES, CONTACT CONFIGURATION:48PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-24c12	POWER RELAY, 24PDT, 12VDC, 5A, PLUG IN, PRODUCT RANGE: 800 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
901-12c-12	POWER RELAY, 12PDT, 12VDC, 1A, PLUG IN, PRODUCT RANGE: 900 SERIES, CONTACT CONFIGURATION:12PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-24c24	POWER RELAY, 24PDT, 24VDC, 5A, PLUG IN, PRODUCT RANGE: 800 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
902-48c	SWITCH, TOGGLE, 48PDT, 1A, PRODUCT RANGE:902 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:48PDT, SWITCH OPERATION:ON, SWITCH MOUNTING:-
802-48c	SWITCH, TOGGLE, 48PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:48PDT, SWITCH OPERATION:ON, SWITCH MOUNTING:-
901-24c-24	POWER RELAY, 24PDT, 24VDC, 1A, PLUG IN, PRODUCT RANGE: 900 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
802-12c	SWITCH, TOGGLE, 12PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:12PDT, SWITCH OPERATION:ON-(ON), SWITCH MOUNT
901-48c-24	RELAY, 48PDT, 24VDC, PANEL, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:48PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PANEL, COIL TYP
801-48c12	POWER RELAY, 48PDT, 12VDC, 5A, PLUG IN, RELAY TYPE:GENERAL PURPOSE, COIL VOLTAGE VDC NOM:12V, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NOM: 120V, CON
801-36c12	DUST TIGHT POWER RELAY, RELAY TYPE:GENERAL PURPOSE, COIL VOLTAGE VDC NOM:12V, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NOM:120V, CONTACT VOLTAGE DC

Ürün	Açıklama
801-36c-115	POWER RELAY, 36PDT, 115VAC, 5A, PLUG IN, PRODUCT RANGE:800 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:-, CONTACT CURRENT:-, RELAY MOUNTING:PANE
901-12c-24	POWER RELAY, 12PDT, 24VDC, 1A, PLUG IN, PRODUCT RANGE: 900 SERIES, CONTACT CONFIGURATION:12PDT, COIL VOLTAGE:24V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
801-48c115	POWER RELAY, 48PDT, 115VAC, 5A, PLUG IN, RELAY TYPE:GENERAL PURPOSE, COIL VOLTAGE VAC NOM:115V, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NOM: 120V, C
801-24c28	POWER RELAY, 24PDT, 28VDC, 5A, PLUG IN, PRODUCT RANGE: 800 SERIES, CONTACT CONFIGURATION:24PDT, COIL VOLTAGE:28V, CONTACT CURRENT:-, RELAY MOUNTING:PAN
802-72c	SWITCH, TOGGLE, 72PDT, 5A, PRODUCT RANGE:802 SERIES, ILLUMINATION:NON ILLUMINATED, CONTACT CONFIGURATION:72PDT, SWITCH OPERATION:ON, SWITCH MOUNTING:-
901-36c-12	RELAY, 36PDT, 12VDC, PANEL, PRODUCT RANGE:900 SERIES, CONTACT CONFIGURATION:36PDT, COIL VOLTAGE:12V, CONTACT CURRENT:-, RELAY MOUNTING:PANEL, COIL TYP