



Omega

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Omega Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Omega Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Sa1-T-120	9 Packet (45 piece)
Sa1xl-T-300	
Sa1xl-T-200	
Sa1-Rtd-200	
Tjc5-Cpss-Im050g-150	
Filterelement 51140-R	Fr Filter / For filter AF 2006
Filterelement 51140-S	Fr Filter / For filter AF 2006 S
E-10-M	OMEGA elastic element set E-10-M best. made of 2 steel / PU half-shells (short) including mounting screws
8JX24SPP	24S (7X32) MULTIPAIR CABLE
LC411-15k	Low profile Loadcell , Range 0-15000lbs for use with Connector / soldseparately
PT06F10-6S-R	Twist Lock Connector ROHS
WTKr-8-M3gs	
TJC-325CA.SS.040.u-4	
SA1XL-K-325	
SA1-RTD-325	
SA1-K-120	
OMEGA elastic element set E-10-M	best. made of 2 steel / PU half-shells (short) including mounting screws

OMEGA hub 10-M	
OMEGA elastic element set E-3-M	best. made of 2 steel / PU half-shells (short) including mounting screws
E-40-M	OMEGA elastic element set E-40-M best. made of 2 steel / PU half-shells (short) including mounting screws
OMEGA hub 40-M	OMEGA hub 40-M Hubs unbored / pre-bored
E-30-M	OMEGA elastic element set E-30-M best. made of 2 steel / PU half-shells (short) including mounting screws
OMEGA hub 30-M	OMEGA hub 30-M Hubs unbored / pre-bored
Filterelement 12075-S	For Filter / For filter AF 0186 S End cap / endcap: Kunststoff / plastic
Filterelement 12075-R	For Filter / For filter AF 0186 R End cap / endcap: Kunststoff / plastic
RPE700SP shortpass filter 25mm	
EMD 12	Electronic condensate drain 16 bar / Electronic Condensate Drain 16 bar 230 V / 50-60 Hz
HH-K-20-SLE-1000	INSULATED T/C WIRE, Type K, AWG20, Insul. high temp glass , max. 700C, ANSI-color L=1000 feet
SMPW-CC-KI-M	CABLE CLAMP CAP SMPW CONNECTOR, Type K, male, IEC-color green
SMPW-CC-KI-F	CABLE CLAMP CAP SMPW CONNECTOR, Type K,female IEC-coloeer green
OSTW-KI-M	THERMOCOUPLE CONNECTOR TYPE K MALE, IEC COLOUR, hollow pins
OSTW-KI-F	THERMOCOUPLE CONNECTOR TYPE K FEMALE, IEC COLOUR
OSTW-KI-M-S	THERMOCOUPLE CONNECTOR TYPE K MALE, IEC COLOUR, solid pins
PCLM-DTC	CABLE CLAMP for DTC-Connectors
RSACL	PANEL ADAPTOR CLIP
OSTW-J-M	STD T/C CONN W/WINDOW , MALE, TYPE J, ANSI/IEC BLACK, hollow pins
OSTW-J-M-S	STD SOLID PIN CONNECTOR, TYPE J, ANSI-IEC BLACK, solid pins
OSTW-J-F	STD T/C, CONN W/WINDOW , FEMALE, TYPE J, ANSI/IEC BLACK
RSJ-K-R	ROUNDFACE STF PANELJACK, TYPE K, ANSI YELLOW
	Eight Channels Programmable Portable Data Logger Accuracy

OM-CP-OCTPRO	<p>± 0.1 % Accuracy Detail Current Accuracy: ±0.024 mA Voltage Accuracy: ±0.1 mV, ±0.01 V Thermistor Accuracy: ±0.50% RTD Accuracy: ±0.1 °C Thermocouple Accuracy: J, K, T, E, N: ±0.5 °C R, S, B: ±2.0 °C Battery Size and Type 3.7V Li-ion Data Interface USB Dimensions Note 6.65 in x 4.40 in x 1.41 in (168.9 mm x 111.8 mm x 35.8 mm) Data logger only Display Note LCD Touchscreen: 5 inch LCD capacitive touchscreen. Display Type LCD Enclosure Ratings IP20 Frequency Input Range 0 to 25 kHz GrossWeightValue 3.6 Height 6.65 in pedance Input Current Input Impedance: 30Ω, Voltage Input Impedance: 1 GΩ,Frequency Input Impedance: 58 kΩ Input Control Signal Millivolt input: -100 to 2450 mV Volt input: -0.5 V to 12.0 V Input Current -5 to 50 mA Input Type Thermocouple, RTD, Thermistor, Current,Voltage, Digital Length 1.41 in Materials Polycarbonate Mounting Handheld, Tabletop or Wall Mounting Number of Channels 8 Pulse Input Note 0 to 4,000,000,000 Pulses Relative Humidity 0 to 95% RH non-condensing Resolution 0.1 °C Resolution Note Current Resolution: 0.0001 mA Voltage Resolution: 0.0001 mV, 0.0001 V RTD Resolution: 0.01 °C Thermisor Resolution: 0.01 °C Thermocouple Resolution: J, K, T, E, N: 0.1 °C R, S, B: 0.5 °C Sampling Rate 4 kHz Series ID OM-CP-OCTPRO- Logger Start Modes Delayed Start, Immediate Start Supply Power Note • Rechargeable 3.7 V Lithium Ion Battery, • Continuous on-screen sampling: 9 hours; Stand-by mode: 100 hours Supply Power Type USB Thermocouple Type J, K, T, E, R, S, B, N Wiring/Connector Table 2-, 4-Wire RTD</p>
E-20-M	OMEGA elastic element set E-20-M best. made of 2 steel / PU half-shells (short) including mounting screws
OMEGA hub 20-M	
E-30-M	OMEGA elastic element set E-30-M best. made of 2 steel / PU half-shells (short) including mounting screws
OMEGA-Hub 30-M	
E-50-M	OMEGA elastic element set E-50-M best. made of 2 steel / PU half-shells (short) including mounting screws
OMEGA-Hub 50-M	
E-60-M	OMEGA elastic element set E-60-M best. made of 2 steel / PU half-shells (short) including mounting screws
OMEGA-Hub 60-M	
MDS08440D040002-0000000001	
ML4C-143-30	FOUR TEMP RATINGS, 30/PK
ML4C-143-30	
8MB-100/38-30	
ML4C-121-30	
ML4C-166-30	

ML4C-210-30	
ML4C-188-30	
ML4C-241-30	
ML4C-241-30	
HMPW-KI-F	
4C-400-30	
TL-10-290-30	
TL-10-390-30	
Coupling E-20 :184 (Including the Apparatus)	
Coupling E-30 :210 (Including the Apparatus)	
Coupling E-40 (Including the Apparatus)	
Coupling E-50:279 (Including the Apparatus)	
HSTC-TT-K-24S-36	HERMETICALLY SEALED TIP T/C
OM-CP-RHTEMP101A	Relative Hum&Temp logger
OM-CP-IFC200	Usb interface cable
OMEGA elastic element set E-10-M	best. made of 2 steel/PU half shells (short) including mounting screws
OMEGA elastic element set E-4-M	best. made of 2 steel/PU half shells (short) including mounting screws
PX655-0.5DI	Low pressure Transmitter with range of 0-0,5" of water
PX359_015_VI	Pressure trans. range 0 to 15PSIV , OUT 4-20ma , M12-connector
PX359_100_GI	
PX359_030_GI	
OM-CP-IFC200	interface cable
Typ: E and ES	PN:10287730 OMEGA tm10
HH306 model	SMPW-CC-KI-M
Elastic element set E-3-M	best. made of 2 steel/PU half shells (short) including mounting screws
TD 16 M	3400395 Timer Controlled Condensate Drain Max. Betriebsdruck / Max. Operating Pressure: 16 barg

1PT100KN1510	CERAMIC PLATINUM RTD ELEMENT 0.9MM X 15MM LENGTH
HX93BDV0	T/HUM TX WALL MNT DISPLY0-1VDC
E70 HDY type, 2100 Nm torque,	motor diameter: 85 mm, fan side shaft diameter 90mm 2 sets of elastomer REX Omega couplings.
PX309-2KGI	2000 PSIG CURRENT PRES TRAN
QM-CP-RHTEMP101A	
43 Plus Price Blower	M-340BL03&04 DB 235 C BLOWER
OMEGA hub 30-M	
OMEGA elastic element set E-30-M	best. made of 2 steel/PU half shells (short) including mounting screws
SN.: 07491/22/16	
PRX102-18N Inductive RPM Sensor	
E-40 HDY	
E-50 HDY	
CHAIN LOCK 16 MM REF: OMEGA SR2235	
CHAIN LOCK 26 MM REF: OMEGA SR22521	
HAND WINCH STRAP WITH HOOK REF: OMEGA SR296060	
PX359-100GI	100 PSIG CURRENT PRES TRAN
PX359-015VI	PRESS TRANS.0 TO 15PSIV 4-20MA
BB703-230VAC-C2	Miniature blackbody calibration source, 230 Vac
DPG7000-5K	
VS 120	
VS 130	
VS 150	
VS 170	
PX1004L1-250AV	
SYS/FTB-202	
FLSC-34 signal conditioner	
QM-73	
E20	

Programmable Mass Flow Meter and Totalizer	FMA-4311 Model
NHX-J-F	HI TEMPERATURE CONNECTOR,BLACK
NHXH-J-M	HOLLOW PIN CONNECTORS,BLACK
XCIB-J-4-2-10	
PSW-191	10 to 150 psi, fixed deadband
1 CAP 42MM 2 CAP 24MM OMEGA E4-M 62NM	
FCH-FGC10262R	CIRRUS 40/1 60W 24V HEATER 24V
REX VİVA 290	
PSS-D12A-220V	
DP40-A3	ANALOG OUTPUT BOARD FOR DP41-U,S,T,E
RA-18-14-SS	SS REDUCING ADAPTOR, 1/8"NPT MALE TO 1/4"NPT FEMALE
DP24-E-DC -	
P19226 - Cable track	Chain assembly
P19228 - Bracket	Bracket (Inner, with hole)
P19227 - Bracke	Bracket (Outer, with hole)
P19230 - Bracket	Bracket (Inner)
P19229 - Bracket	
Spare Parts	
FS10.2.2.3.G10.9.3.0.1E15220	
REX viva VS 110	
REX viva VS 130	
REX viva VS 150	
REX viva VS 170	
DP7001	TEMPERATURE PANEL METER
THERMOCOUPLE TYPE K DİAM 8	LONG 2 MT
TJ36-CASS-18U-3-SB-SMPW-M	
TJ36-CASS-116U-2-SB-SMPW-M	
GG-J28-1000	INSULATED T/C WIRE High Quality Type "J" Thermocouple Grade Wire Choice of Insulation, Wire Gauge, & Length Available in Class 1 or Class 2 IEC Tolerance Solid or Stranded Conductors

SICSS-040G-6-SHX	SUB-MINI T/C ASSEMBLY W/SHX 150 and 300 mm length Shell diameter from 0.25 to 3.0 mm Coat made of 304 SS, 321 SS or Inconel Maximum measuring temperature (with 3 mm jacket diameter) with 304 SS jacket up to 898°C, with Inconel jacket up to 1148°C With SHX or NHX ceramic connectors for temperatures up to 650°C With pipe clamp for added stability
RDXL6SD-USB	
LC402-200K	
UWTC-2	Wireless Thermocouple/RTD Monitoring and Logging System Type: UWTC-2 Accuracy $\pm 0.5\%$ Accuracy Detail Thermocouple: Types J and K: $\pm 0.5\%$ rdg or $\pm 1.0^\circ\text{C}$ (1.8°F), whichever is greater Types T, E, and N: $\pm 0.5\%$ rdg or $\pm 2.0^\circ\text{C}$ (3.6°F), whichever is greater Types R, S, B and C: $\pm 0.5\%$ FS Approvals FCC/Industry Canada, SRRC Data Interface Wireless, USB Display Type N/A Electrical Connection Standard Male Thermocouple Connector Enclosure material ABS plastic Form factor: Handheld Gross Weight Value 0.55 Height 2 in Input Range -100 to 1260 °C Input Range Note J: -100 to 760°CK: -100 to 1260°CT: -200 to 400°CE: -200 to 1000°CR: 260 to 1760°CS: 260 to 1760°CB: 870 to 1820°CC: 0 to 2315°CN: -100 to 1260°C Input Type Thermocouple Types: J, K, T, E, R, S, B, C, N umbrella of Channel 1 Operating Temperature, Max 70°C Operating Temperature, Min -10°C Probe Diameter 0 in Probe Length 0 in Process Temperature, Max 1260°C Process Temperature, Min -100°C Relative humidity 0 to 95% RH Thermocouple resolution: 1°C Sensor Type Temperature Series ID UWTC Sheath Material N/A Software Compatible with Windows (2000, XP, Vista, and 7) operating system Supply Power Note One 3.6 V lithium, 2.4 Ah capacity (AA) (included) Power Supply Type: Battery Temperature Probe Style N/A Weight 70 g Width 4 in Wire Length 0 ft
Dp12	
Tqss14g12	
242pc05m	
R0000783-1	
70a-3	
Rscm-Ei-30-0-0	
115tfads	
Chal-001	
Omni-Cal-Iib8	
Nmp-J-M	
Dp25-Tc-Dc10/32	

98227k	
Cn77332a2	
Os65-Ma1-R4-2	
Hx92v	
Ezp-T6c-Fs	
Nk17v032	
Bt086a35b60j	
Px219-060g5v	
Nh1g200	
Lvv-111	
Fhs-2	
Cain-116u-12	
Omb-Dbk35	
Rmj-T-R-Rohs	
Coma-C4	VOICE SYNTHESIS AUTO-DIALER REMOTE MONITOR
5201103050	
Ogp-K-M	
Rd3751	
Lcmfl-10n (10n)	
Hx93v	
Px409-001cg5v	PRESSURE TRANSDUCER HI-ACCURACY 0-5VDC 0-1PSICG
Mtc-41-Mc	
Rsj-Gi-S	
Pt003g4l10	
Pheh-45-10	
Pr-11-2-100-1/4-24-E	
Mlim-5	
Nb2-Icss-18g-12	
Rhdp-Cal-Bot	
Rhs-78	

Trpt	
Tx62	
M-10783-2	
Rd8804cd	
Cx5301	
Px303-2kg5v	
Rtd-Npt-72-E-Dual-1/8	
Wtj-Hd-72-S	
Cn4116r1r2	
Cni8dv23	
Wb-Asc-Gp	
Jbcb-5-K-M	
5sc-Tt-K-30-72	
Tj120-Icss-18g-6-Smp-M	
Omb-Dbk19	
Rp43	
Drm-Acv-C	
2004za50601202	
1702	
Kmqin-062g-12	
Pr-11-2-100-1/8-12-E	
Psw-108	
Ncb001	
Tj36-Icss-18u-24	
Omg-Usb-Dio96	
Cn101j-1000f	TEMPERATURE MONITOR W/ALARM 6CHANNEL
On-970-44005	
5tcggj3072	
Om-Nomad-Rh-32	
Lvu-153	
Pclm-Gst	

Hst-N-M
Lvsw-701
Mmlz200xq2
Cn310-J-F
Fp5340gi
Lvc512
Xcib-K-4-2-3
Os-600
Os136-1-Mv-F
Px103u1-100g5v
Tx93-K3
115-K-F
Px302-015av
Co3-K
Smtc-Ch-S-Each
Rhsp-Frt
Os36-01-K-80f
Dp24-E
Mpj-K-F
Os551-Mv-1
E50
Psw127
Cn743
Rhcn-7006
Mh-Rsj-1
Hdc06225
Cn310-K-F
Cn9000a
Cn9151a
Kmqxl-125u-24

Px215-100gi	
Rscm-T-4-4-5	
Dpg8001-30	
Tj36-44004-3/36-6	
Rscm-T-4-4-4	
Os523e-1	
1-.385a-U8-304ss	
Hh-K-24-Sb/Ft	
Px613-2kg	
Mml400	
Nh3u560	
Dmd-465-220	
T/C-K3q-4smu-Mm-E	
Recj4-5	
Cn101j-250f	TEMPERATURE MONITOR TYPE-J 250F HIGH ALARM 6-CHAN.
Dp41-Rtd	RTD INDICATOR 115VAC 6DIGIT
Nk17v050	
Osj1	
Cn76050	
Tj240-Icss-316g-12-Sb	
Ftb-408a	LIQUID FLOW METER 1.5 4.59 INCHES
Lv-91a	
Ust-K-F	
Prtf112100146esb	
Reck1-13	
Lcfd-25	
524 For Pump 200 - 670 B Gb Pf S¼rie Nº: 9972197129 / 000300 Shaft Sleeve	
Os38-10-J	
650-R-X-120vac	
Ntcbj	

4055-E-1100	
Cn9122a	
650-J-A	
2002	
Hpc-Co-S-Each	
Us922	
Os100-Ap	
Lv-5900	
Rs-78	
Lcgb2k	
Cni3252	
Cn76050-Pv	
Gls138316	
Cn102e-500f	TEMPERATURE CONTROL LOW TEMP ALARM
Px154-005di	
Nh1g250	
Px141-015v5v	
457 For Pump 200 - 670 B Gb Pf S¼rie Nº: 9972197129 / 000300 Neck Ring	
Dpf76	
Phtx-22	
Hh611apl4	
2160a	
Dp82t	PROCESS CONTROL DIGITAL 90/132VAC 4/400HZ
Dp24-E-Dc	
81006	
Scass-062u-6-Dual	
Drn-Acc	
Fl-X3	
Hh81	
Nh1g160	

199-Sc-X-X	
Lvu-1501	
Pt01f10-6p	
Ns-Lge-420	
Psw-514	
8804pt00dg4	
Rsjkr	
Bb701-230vac	
680	
4001a-Kf	
R0000742-1	
Eis-2b	
Cdc-Cn	CONDUCTIVITY CONTROLLER
Rtpc-SI3	
Sv-358-24vdc	
Hhsl402sd	
98202k	
Dp25-S	
Px700200gi	
450-Ajt	
Os3601j80f	
Rsj-K-S-Rohs	
Reck1-14	
Hwc/Nb3-Cass-14g-6-Tbsl/3/4-260s-U41/2-316ss	
199-Tc-X-X	
88010k	
Wtj-6-48	
Ni80-032-50	
Jmqss-062u-6	
Nh3u500	

Hh-20-Sw
Teck10-9
Cn3001
Ost-K-M
Ltu-101
Drtb-T
Th-Lmp4
Seex-J-48-2-3
Fma1820
Dpf401
Nh2u355
Mpj-Cap-6
5sc-Gg-K-30-36
Hh-25tc
Oma-Guardit
Wtk-6-60
Dp41tcr
Lvn-91
Wtk-Hd-72-S
Ezio-Hscm1
Pt-0-100
Chal-005
Omb-Dbk15
Px303300g10v
873c
40823102
Ptc-1
Rec-100m-Lh
Hz13000
Tx4w-50
Cn3004-D3-F3-F3
TEMPERATURE CONTROLLER 120V-IN DC/4-20MA-OUT-4

Ithp-5	
Px293-006d5v	
Cn76133-4sp	
Rd1801-Ar6	
6103-J-0/300f	
4002akc	
Ct485-Cmf-Each	
Px439-010gi	
Cn77354-C2	
Px219-030gi	
Sicss-125u-6-Shx	
Cni833	
Lv752	
6102k-0-1200c	
7035-J-600	
Tjc36-Cass-062u-6	
Phe-6510	
Expp-Rs-16-100	
Lp802150	
Phcn370ph	
Al32.04	
Tx903	
Ct7312	CHART RECORDER CIRCULAR PROCESS 2PENS 2RELAYS
Cpp941	
Dp461-Xa	
Fl-500-R2	
Pr-11-2-100-1/4-6-E/120	
Rsc-J-2-4-3	
Cn8502tc-R1-R2	
Px760-600wcdi	

Ssr330dc10	
Dp282-P24	
Cn1211-A1	PROCESS CONTROLLER
4001ajff	
Lcda-25	
Rtd-2-F3105-36-T-Otp	
Dp205-E	
Fma-5709-I	FLOW METER 0-5SLM 4-20MA 12-15VDC 150PSIG
XI-5-Mb2-15-St	
Cn355-Kc6	
Hp1-4cddc	
Dtc-K-M	
Cn4601tr-F1	
CI523	
Mtp-U-M	
SI100	
Nb2-Caxl-18e-3.5	
Lvcn-51	
2160a-Kk-04	
FI-1004	
Prtf112100189e	
Cn138tc-F-A11	
Dp45jc	
Cass-18e-12	
Pr-13-2-100-1/4-6-E-Pfa	
Os137-Ap	
Px615-300qi	PRESSURE TRANSDUCER 0-300PSIG 10-30VDC
1/4-SIk	
Lvu-1504	
6155a-S,C0 Obsolete/Replacement Rd6 + Mdr-10-24	

[Mpj-U-F](#)

[Cn371-Jf4](#)

[M60/1290](#)

[Sp-Ra-J-6](#)

[Px613-30vac5v](#)

[Mml600](#)

[Psu-93](#)

[Lvu-701](#)

[Srfg4085](#)

[Rtpc-Sl2](#)

[Kfg-5-350-C1-1111m2r-Each](#)

[5tc-Tt-J-36-36](#)

[Wb-31](#)

[Cml00020](#)

[660-T](#)

[Reck1-1](#)

[Lccb-2k](#)

[Kqin-14-U-6](#)

[P-M-A-6-50-M10-Ts-12-IP68](#)

[Dpc10-Rt](#)

[Px02k5-005gi](#)

[Dp25-E-Ar](#)

[Hmpw-Ki-M](#)

[Tpj-U-F](#)

[Ssr12](#)

[Isk5163/88006k](#)

[Cn76122](#)

[Txdin70display](#)

[Pr-11-2-100-1/8-6-E](#)

[451t-250](#)

Px811-200av	
Tx82b	
Pr-14-2-100-1/4-18-E	
Sc-Gg-K-30-36	
Fma1814	
Tj36-J-116u-6-Acl	
Dp280r	
Os550mb	
Fma-905-V	
Hh1	
Smtc-Ir-P-Each	
Exppj20tcbp25	
Cl23a	
Ost-J-F	
Rd2020	
Kqss-116e-36	
Px906-5kgv	
6001	
Nk17v025	
12075 A	Filter Element
873f	
Cn310dc	
PI-085005	
Fma1728	
Cn76122-4sp	
Idrn-St	
Lcm703-75	
Cn882k-500f	
Cl-474	CALIBRATOR FOR RTD LCD DISPLAY HANDHELD
Hh-K-24-Sb-500	

Rscm-T-4-2-3	
Ezio-4thi	
Rscm-T-4-3-4	
Cn76050-485	
8803p00c04m	
Cni1653-Dc	
Hx93ac	
Icss-116u-12-Dual	
Dp25b-E-230-Ar	
Ld600100	
Mml4000	
Rd250cp0500	
Tx91a-J5	
Cn9221	
Fp5302	
Rhp-58	
Cn2001mv100-D6	
Ftb795-Nd	FLOW METER 2IN NPT TURBINE
Rsc-J-1-4-2	
Mtc-24-Ff	
Rhcm-40-AI-W	
Php-311-K	PUMP CHEMICAL METERING 40GPD 250PSI 17BAR 115VAC
6102-K-0-1000f	
Acc787a	
6132h-J-0/300f	
Inet-100hc	
57-J-0-300f	
Cn101k1000f	
Tj36-Cain-316g-3-Bx-Ost-M	
2wtxi-0-K-200	
Adrtu3363	

Smtc-Co-P
88107
Ct485bwhite
Srted-2-180
50
Ssr240ac25
Pr-13-2-100-1/16-12-E
156
Om-Cp-Quadtemp-A
Upj-1-18-J
6000-Jr
Dp25b-E
Lcmfl-20n (20n)
Cn1602-R1
A-25-125f-3-3/4
88006/88016/88026
166-718
Pr-14-2-100-1/4-6-E
Fma-5dv
450201000
Flsc-18b
Rhs-43
Fl-1408
Px302-300gv
Psw365
Os137-2-Ma
Co2-K
922
Tt-K-20-Sle
Drfvac24vdc65

Px540-150gi
Lvk-171
R0000663-1
Cn2081jf
88006k
FI-500-R1
Smp-J-M
Cn8201-R1-AI1
Ewse-Pt100-Tx
Mlim-1
Ct485-Cmf
Px429-015-L050
Otp-U-M
Cn882j-1200f
461 For Pump 200 - 670 B Gb Pf S¼rie Nº: 9972197129 / 000300 Packing
Rtd-Npt-72-E-1/4
Cn351-Jc2
Rmj-T-S
Rmj-K-R
Dpi16dc
76130
6102k0
88000krscsmpwm
Smpw-R/S-M
50-39067-1187
Ostkmf
5831a
400a407
Cn76020-4sp
Rdxl6sd

Px309-200g5v	
Irco-010	
Nox-T-F	
Rtbc-Ep	
Os550a-Pcab-33	
Px725-300gi	
Tj36-Cass-316g-6	
Rhcl-2-Sr	
Cni8a33	
Psw-198	
Fma-A2405	
Dp41-E-S2	
Wtk-8-60-Tt	
502 For Pump 200 - 670 B Gb Pf Srie N: 9972197129 / 000300 Casing Wear Ring	
Cn8631tc	
Tl10105	
3af	
A-0-100f-15-1/4	
Cn76133-485a	TEMPERATURE CONTROLLER
Kmtss-125u-6	
Px300-3kgv	
Otp-U-F	
Omb-Pdq2	
Ic-11-F	
Acfhbb02 Obsolete Board, Printed Circuit	
Dm-Ps-750	
404-875	
Cn310-T-C	
Pgc-20l-30v	

Rtcb-3070-240v	
12075 S	Filter Element
Drtb-K	
Tj36cass316g18	
5lsc-Gg-K-24-36	
Fma-902-V-S	AIR VELOCITY TRANSDUCER 15-18VDC
Cn63200-Dc1-Al-Lv	
Rhx13sd	
Om-40-C-V	
Tc-T-Npt-G-72	
Rtd-Npt-72-E-Cla-1/4	
Flsc-720-I	
Rmj-Ki-R	
Wtj-8-120	
Fma1714	
Hh11	
Wtj-10-36	
Pftfs-8t	
Pgt-60l-150	
Rm12r-B	
Cdtx-45	
Drf-Tcs-115vac-0/1600c-0/10	
0100-0026	
Cn7001r1a	
Cct-01-0/10v	
10287355	
Omcquadproces	
4002-Jc	
Osw3-5	
Ct585b	
Bb-4a	

Ct485pr
D922t06-A20/L13/E607
N0-0481
Psw-543
871
Omp-MI-Disp-Mnl
Cn7101r1-F-Pv-Rsp
E20508
2034e9531a
Sh-1-8-100
Os550-Ls
Cn77533-Pv
Cn7101r2
Px481ad-006g5v
Rscm-Ji-120-1-1
Cn76022
Flmh1040al
Tcjnptg72
Cp1020
Fmg-3002-Pp-D
Ld500-2.5
Dp119kf1
E67039
Rtpc-Sla
Rd100a-02
Cn8121r1
Cn811r1
Otp-K-M
Cn77553
Cn77r353-A2

Fv103	
Lv401	
Tt-K-24-Twsh-Sle-50ft	
Stc-Gg-J-24-72	
Ld500-5	
20100039211200	
Rtd-2-1pt100kn2528-36-T	
Omees10rm	
236pc100gw Sensor Vacuum Gauge +/- 100 Psi Honeywell Sensing And Control	
Nk24v006	
Dpf701	
Lcm501-50	
88106k-Iec-Oem	
Mh-Rmj-10	
Dra-Act-Sv	
Rd110-Zfp	
Cn4821-F1	
Brk-116-18	
410a-T-F	
1000107	
Omb-Dbk16	PC BOARD STRAIN GAUGE 2CHANNEL
Smtc-AI-P	
Dp-F65	
Cl307a	
Cdcl35	
Dp205-Tc	
Fl7105a	
Slir-20	
Hdc00393	
175	

Reck1-6	
E80036	
199-P2-X-D	
Pgc-25I-30v	
Lvk-50	
7055-K-1500	TEMPERATURE ANALOG PYROMETER 0-800C 0-1500F TYPE-K
Px309-200gi	
Px215-30vaci	
Mma-100vp4a0t4a6	
Px360-3kgv	
Ustw-J-F	
Dps3200-P	
Sa1-J	
Ld500a	
Ri-100/120v	
Cdtx-824	
6002	
Px277-01d5v	
Px305-050ai	
Rih-1000/240v	
5021cy	
Os36-01-J-180f	
Bt-000-J-21/4-60-1	
Cn2110-R20	
Hhf81	
SI105	
Os210abs	
Dp119-Jf1	
40a-T-F1	
Dp41-Tc	

Recj4-12	
Rsc-K-2-4-3	
Filterelement 0310-A	for housing / for housing CHP 005 End cap / endcap: aluminum Operating pressure: 0 - 400 bar
Ssr1240dc10	
Ip610x15	
2010d050001201	
Cn1a-Rtd	
Nk17v016	
Jmqss-020g-6	
Hmpw-K-Mf	
Px4200-010gi	
Kmqss-125g-6	
Rhp-78	
Hx303c	
Ssrin660dc25	
Px180-200gv	
Psw-321	
Nh3u450	
Px41t0-030gi	
88225k	
Mc2-2-40-120	
Slir-20-Each	
Co2-E	
Fmq3002-Pvdf-D	
D921	
Ct485-Cdf-Each	
Px621	
Sv2001316ss	
Cn616tc1	
Tx41-Tc-A-R4	PROGRAMMABLE TRANSMITTER W/ANALOG RELAY

Scpss-062u-24
Reck4-10
9000cn9121
D1411
Px615-30vaci
Cn2001tc
Upj-J-F
Dp2000-D7
Om-Cp-Ifc200
Psw-141-Hr
Rsj-J-R
Lcmfl-10n
Ip411-020
Cn2011jfi02
Rd4031
Psw-374
Os36-J-440f
Rhs-58
Sl-2n
Ann-60
100-310 A
Drm-Ps-1000
402b-J-F
19211922
458 For Pump 200 - 670 B Gb Pf Srie N: 9972197129 / 000300 Lantern Ring
Rsj-R/S-S
Nd2t016
16513430
Px205-300gi
Cn3251-Rr

CI342	
Pst-B15	
Minimsd	
Tac80b-K	
Reck1-3	
Tlcp-20	
Dp18-M2	
Srfg-206/10-P	
Rhb-Tp	
8803p00c04f	
Rtdcap-100a-2-P098-050-T-40	
70a-2	
Om5-Bp-16-C	
Lcae-1kg	
Ann-150	
Nb1-Icss-14u-15	
Lcgb-15k	LOAD CELL 0-15KLBS
Dp116jf19	
Brk-18-14	
Lc1011-10k	
Px605-150gi	
2nb2-Icss-116-U-18	
Cn9000acn9111a	
Cn76030	
Px43e0-100gi	
12075 P	Filter Element
Px700-200g10v	
Rd-822	
6102-K-0-500f	
Osmini212dma	

E10-7300025
Cn76033-4sp
Cn4811-Dc1-AI1-Di
2003ea30000001
Fsw-30a
Cdcn-202
Rih-750/120v
Cn8592r1dc2
Px3025kgv
88006k-Iec-Oem
Cn8502rtd-R1-R2
Reck1-12
Dp25-E-R
Wtt-Hd-72-Ostw-M
Lvcn-71-36
Cdcn
Xcib-J-1-1-10
Px 410-015gi
Ct485b
Pr14210014512
Tx-81
Ct485
Psw-191
Px-673
Hacl
Px605-200gi
Rd1600-Rh
Sacl
Tx86
Tc.Gg.K.24.36.Smp.M

Hwa/Nepb-Icdualss-144-3/4-26-Dh-U-4-1/2-316-Ss
Cn2011k
Mtc-AI-S
Os65-V-R4-3-C50-Os-Nist
Wtj-10-24
Gst-J-F
Px102-050gv
Hh603a
Lvr313
Ps-4g
Reck1-5
Recj4-13
Cl-304
Hhf42
Px309-2kgi
SRTD-1 Accuracy ± 0.5 % Bend Radius, Min 9.5 mm Cable Diameter 0.06 in Cable Length 36 in ECCN EAR99 Electrical Connection Stripped Leads Insulation PFA Insulation Resistance 50 MΩ Insulation Resistance Note 50 M Ω minimum at 50 Vdc ribbon cable. 100G Ohm minimum at 500 Vdc, round twisted cable (dry conditions at room temperature). Mounting DIN Platinum Nominal Resistance 100 Ω Number of Wires 2 OkForExport true Process Temperature, Max 260 °C Process Temperature, Min -200 °C RRS Code 2 Response Time <200 ms Response Time Note <200 milliseconds lag on metal surfaces Self Heating Effect 0.33 °C / mW Sensor Height 0.64 mm Sensor Length 25 mm Sensor Width 15.7 mm Stability <0.2°C Stability Note <0.2°C drift per year at rated service and proper mounting Temperature Coefficient 0.00385Ω/Ω/°C Temperature Coefficient Note α=0.00385Ω/Ω/°C Temperature Sensor Type RTD
Px180-300gv
Idrnacv
C-555-D
200-Pc-2cy
Reck4-1
Cn76130-485
5tc-Gg-Ji-24-2m

Tw-2
Al32.01
4202a-Pf2
4001a-Jc-300
Reck1-8
Reck1-9
Cn9211a
NhXH-J-F
Tx4-100
Nb1-Cxss-14u-36-Tbsl
Dp41z-S-Ar-Gn
Cnith-I8dh33-5-2.4
Cn101k-1000c
Tj240-Icss-14u-6
Slco-20
Dr-Io-Oac-Ra-280
Dpg1100b-100g
Ip311d030
321 For Pump 200 - 670 B Gb Pf S¼rie Nº: 9972197129 / 000300 Deep Groove Ball Bearing
Px430-Clamp
1606-0-J-0-999f
TEMPERATURE CONTROLLER 120-240VAC 5/10AMP
6001-J
Svp-1
Px181-200g5v
Dp461
Fsw-42a
Cn77323-C4
Rect1-14
602006507

Rsp-1-10pk
Dp30j2
Dp371-Jf4
Nh00g100
Sv6001
Cni3253-C24-Dc
Cn612tc1
Cct-08-0/650v-220vac
4202a-Pf1
Ip211-X30
Slal-20-Pk
Lcgd-50
Dp116ef1
Cn63100-R1-R2-F3-C4-Lv
Ann-10
Cn4431tr-F1
Rmj-T-R
Px219-015g10v
650jxd120vac
Smtc-Al-S
Upj-1-20-J
Osw3-3-Pg
6102j-0-500f
Cx5300
Os-1200-Las-Wc
2003ea30000000
Cn77352-A2
Nk17v010
Rlc-70-10/40-30
Cn2081kf

Os65-J-R5-3	
Fma-1702	
Nk17v020	
Drf-Tcj-24vdc-0/400c-0/10	
Phcn-37	
Px4200-100gi	
Hhp701200	
405b	
Cn76063-Pv	
Prs3100ah0300d1c	
Cn76050-4sp	
Pm1001	
Ftb-978a	
Dpg8001200	
Prtf-19-2-100-1/8-6-E	
Fma1002b-Ma	General Purpose Industrial Air Velocity/Temperature Transmitter/Indicator
Ost-K-F	
Dfg51-2	
Hh-20-Sw-J	
Sr2	
A204 Obsolete Power Supply Unit	
88013k-Iec-Oem	
4002a-Jc	
He359thm200	
Gkmaqss-062u-6	
Os1552-A-816a	
88309k	
Fp1020	
Rmj-G-S	
E922t20	

TI-E-250/Each	
Fsw-119	
Ssr330ac10	
Rhsp-W	
Icss-18u-12	
Ov512wh	
Sfcl-1	
Smtc-Co-S	
Lcgd-5k	
Reck1-7	
Cn5001k3	
Mpj-Cap	
Px409-10wvi	PRESSURE TRANSDUCER 1/4INNPT 0-10 PSI
Reck1-2	
Cn76153-485	
Cct-05-40/70-24vdc	
Px305050gi	
Rdxl8cd	Input Portable Thermometer/Data Logger with SD card Omega rdxl8cd
Lvcn414	
Psw-542	
Smcl-Each	
Hh82	
Px439-010g1	
Mss-10	
Rsj-C-R-Rohs	
Ezio-8aniv	
Tx-41-Rm	
Cn1166-R1-R2-R3	
Cn4801-Dc1	
Tx83	

Cn76022-Pv
Px305-300gi
Xc1bj1210
4202-Pf2
Cn4316r1r2
Dp25bsa12
Dp900
Xbtkj25
Tt-E-20-Twsh-500
821322d
98202k-Iec Surface Probe Type K Iec Colours
Lcmfl-20n
Dp2000p8
Dp460-T-115
Pr-11-2-100-1/4-6-E-84
Tyef-02
88108
Tx91a-J2
Cf-090-J-5-72-1
4001-Kc
Mlad-1
Rsc-K-1-4-2
88007
Wtj-8-L-120
Hub 10-M Cb
Nmptf
7055-J-500
Uwtc-1
Os550-Mb
Cni1653

Gp9111s
Kmtss-062g-6
Scass-040u-6-Shx
88202k-Re
6002-P2
Prtf-10-2-100-1/8-6-E
Os423-Ls
Hh12b
Dp41-E-A
Pguf-25l160psi/11bar
Lcgd-10k
Dp25-Tc-A
Rtd-830
Irco-015
Hx13c
4202a
Um20b18
4201-P-F1-T
SI301
Otp-T-M
Cn77353-A2
Fsw-C1
Ews-Tx
Rtd-2-F3105-36-G-Mtp+sprtx-M1
Lcm703-150
Lv-110
Cx340-10j
5tc-Gg-Ni-30-2m
Tac-81k
Ann-80
Lc501-200

Dpi8a-Dc
Px102-100sv
6303v
Mbs-02
Reck1-4
Ustw-K-F
Cn371-Jf3-24vdc
Rtcb-3060-240v
Px278-30d5v
Px309-002gi
Cn76063
Tx93ak4
Os550-Mn
Lv622-P
Tj120-Cpss-18u-2
M-2929-2
Sjp2-12-J
Bd9011a
Nb1-Cass-14u-36
Wtk-14-24
Fma-773a-V-N2
Flsc-Amp
Lc8313-200-3k
Xs-E-14-1000
Nhxx-U-M
Qs36
Rd292-Hiv8
Smphtk6
Drg-Sc-Dc-B
Cn330

H-0-200f-21/2-1/2
E11113106cf090j5
Ostw-Cc-E-M
6155a-S,C1 Obsolete/Replacement Rd6 + Mdr-10-24
Jhss-Im45u-Rsc-600
Os37-10-K
Rtd-2-F3105-36-G