

Optron

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Optron Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Optron T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
9900020.1	Humidity sensor for insertion, single electrodes with short-circuit suppression 4-fold LED display and beep, Battery operation, power supply including USB connection cable, mounting bracket and 20 x single insertion electrodes of your choice (please specify item number) Dimensions: Ø 42 mm Length: 185 mm (without electrodes) Weight: 1060 g Customs tariff number: 9031.8
9900100	Power supply including USB connection cable (1.8m) for humidity sensors
Single insertion electrode 32-100 mm usable length	Single-point insertion electrode, 32 mm usable length (Needle Ø= 2.0 mm) Single insertion electrode, 36 mm usable length (Needle Ø= 2.5 mm) Single insertion electrode, 40 mm working length (Needle Ø= 2.0 mm) Single insertion electrode, 55 mm usable length (Needle Ø= 2.5 mm) Single insertion electrode, 80 mm working length (Needle Ø= 2.5 mm) Single insertion electrode, 100 mm working length (Needle Ø= 2.5 mm)
9900071	Single insertion electrode, 100 mm working length (Needle Ø= 2.5 mm), shaft insulated by powder coating.

Single insertion electrode 25-80 mm usable length	Einstech-Doppelelektroden 25 mm lang in Kunststoffhalterung m. Anschlusssteckern (Nadel Ø= 2,5 mm) Einstech-Doppelelektroden 32 mm lang in Kunststoffhalterung m. Anschlusssteckern (Nadel Ø= 2,0 mm) Einstech-Doppelelektroden 40 mm lang in Kunststoffhalterung m. Anschlusssteckern (Nadel Ø= 2,0 mm) Einstech-Doppelelektroden 55 mm lang in Kunststoffhalterung m. Anschlusssteckern (Nadel Ø= 2,5 mm) Einstech-Doppelelektroden 80 mm lang in Kunststoffhalterung m. Anschlusssteckern (Nadel Ø= 2,5 mm)
9900061	Surface sensors - extremely multifaceted Version, length 300 mm for measurements under floor coverings such as carpets, etc. Sensor with multi-section, flexible test probe (adaptable to humidity sensor item no. 9900015) Carrier material: Glass fiber reinforced epoxy resin Conductor tracks: copper, nickel-plated Active test zone: 50x10 mm on both sides Length: 300 mm Width: 10 mm Diameter: 1.5 mm Further information: see datasheet.
9900060	Screw connection for electrodes (Knurled screw)
9900028	Protective cap (screw-on)
9900052	Penetrating double electrodes 80 mm long in Plastic bracket with connector plugs (Needle Ø= 2.5 mm)
325.121.34	LIGHT BARRIER G35EF2V2
9900048	
9900010	
735.223.01	D200/D300 POWER SUPPLY
3834370	
729.359.101	MICROCOMPUTER OMC101
735.233.01	D300 POWER SUPPLY 24 VDC
3821010	
118.306.224	MONITOR UNIT FSU201, D1XX / E1XX CONFIGURATION, REPLACEMENT FOR CRT SCREENS
353.101.2001	SENSING COIL IRT200A
730a	RADIOMETER/PHOTOMETER
329.121.11	LIGHT SCREEN LV200M, SENSING AREA 200MMX100MM
3740300 Mp 2000	
353.101.2501	SENSING COIL IRT250A
Mp 2000 3740300 Digital-Thermometer	
329.113.11	LIGHT SCREEN LV150/150M, SENSING AREA 150MMX150MM

9900015.1	Humidity sensor for insertion double electrodes with short-circuit suppression 4-LED display and signal tone, battery operated, Power supply including USB connection cable, mounting bracket and 1 piece double insertion electrode L=32mm (Art.9900064) Dimensions: Ø 42 mm Length: 180 mm (excluding electrodes) Weight: 940 g
325.121.24	LIGHT BARRIER G35EF1V2
3874460	
9900051	
729.341.140	INTERFACE BOARD, 8 INPUTS, 8 OUTPUTS, 4DAC
729.333.644	INTERFACE BOARD, 8 INPUTS, 8 OUTPUTS, 4 DAC, 4 ADC
729.314.64	DATA INTERFACE BOARD (1 RS232 PORT)
9900064	
Sas-2140a	
329.111.11	LIGHT SCREEN LV150M, SENSING AREA 150MMX100MM
In5pd	
729.326.53	INTERFACE BOARD, 16 OUTPUTS, 1 DAC (16 BIT)
9900020	
729.100.842	OPERATOR TERMINAL F1000
3874460 In510	