

Packo



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Packo Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Packo T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
NP /66-32 /062 (O -85) B07S18KEW Y55P9006-- W3	
138103	
34-19-74	
33-53-57	
PAX202956	PH NP66-32 BSP 1"1/4 -1" 304 PUMP HOUSING NP66-32 BSP IN 1"1/4 OUT 1" Pump housing only.
PAP003915	NP /66-32 /062 (O-85) B07S18KEW Y55P5019-- W3 Packo centrifugal pump NP Complete pump. Our product specifications: Set details Outlet pressure 8 m Flow rate 5 m ³ /hr Pump details Position of pressure port 12
PAP005750	ICP+/32-160 /402 (X -155) D11S33KEB Y55P5019-- W3 Packo centrifugal pump ICP+ X special impeller As pump number 134050
PAP005751	ICP+/32-160 /402 (O -145) D11Q33SEB Y55P5019-- W3 Packo centrifugal pump ICP+ Same as pump number 137174

	TRAP0010
ZL /110-130/044 (BW-120) D17STEP	Bi-Wing rotors DIN11851 DN25 Single mechanical seal WC/WC/EPDM Secondary seals: EPDM Free shaft ends without motor, base plate, coupling, coupling guard Drive shaft
Mechanical seal complete ZL100	Material pairing: tungsten carbide/tungsten carbide/EPDM (Two seals are installed in the pump)
PAP009110	ICP3/80-200 /404 (C-180) x11S43JEW Y55P5019-- M3 Packo centrifugal pump ICP3 x = Pump housing with loose Flanges (EN1092) and Drain BSP 3/8" external thread.
ICP2/32-125/152 (O-105) E09D33SVW Y65P5024XY A3	PAP007863 Packo centrifugal pump ICP2 Medium conveyed: Water with aluminum dust Flow rate: 12 m ³ /h Delivery head: 14 m or 1.4 bar Minimum flow rate: 1.5 m ³ /h Density: 1 kg/dm ³ Viscosity: 1 cP Temperature: 20°C Connections: Connections according to DIN EN1092- 1/02 Loose flange Suction side: DN 50 Pressure side: DN 32 Wheel: open wheel, diameter 105 mm Double mechanical seal, pressureless Material pairing: Medium page: Silicon carbide/Silicon carbide/Viton Atmosphere page: Coal/Silicon carbide/Viton Secondary seals: Viton (FKM) Motor: 1.5 KW 2-pole 3x400V 50 Hz, IP65-F EX protection: ATEX & IECEx, Ex db IIC T4 Gb / Ex tb IIIC T125C Db, LCIE 19 ATEX 3028 IECEx LCIE 19.0038X
44138	
44142	
4532-839 +4531-031 +4532-930	
44139	
Iff2/80-200/404 (O-210)	