Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Pauly

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Pauly Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Pauly Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
1661Ex02	
4314qE	
ET103/2000 /e2/i/stH4/24VDC	
PP83201/2/ R/e1/1M16/1M20/z3s/1stLU5/115VAC (Ord.nr.2420x22)	
PS20G19 /y/ir/stH4	
PV2092/2E /e2/y/i/stH7/24VDC	
PV2092/2E/e2/i/stH7/24VDC	
PP2441q/220/R28E	/e2 /1stLU5 Receiver | hole detector | Monitoring width: 220mm | Response time- Characteristic q=1.5ms | PNP, 60mA, short-circuit proof | 4+1-pin device connector | Power supply from the transmitter Country of origin: Germany Customs tariff number: 85369095
PP2441q/220/R28S	/2stLU5 /24VDC Sender | hole detector | Monitoring width: 220mm | Response time characteristic q=1.5ms | 4 +1-pin device connector | 24Vdc Country of origin: Germany Customs tariff number: 85369095
PP83201	/e2 /1M16 /1M20 /z3s /1stLU5 /24VDC power supply | 10VA | for 1 hole finder system/pair of light barriers | PNP, 60mA, short-circuit proof | metric fitting | On/off delay 3 sec | 4+1-pin device connector | light/dark switchable | 24Vdc Country of origin: Germany Customs tariff number: 85369095
PP2445CC2	/5m /2stLU5 Connection cable | connectors assembled on both sides (socket & pins) | 4+1-pin device connector | Length: 5m
SENSOR DETECTION 24VDC/e2/i/stH4	
PP2441q/220/R28S/2stLU5 /24VDC	Transmitter | Hole detector | Monitoring width: 220mm | Response time characteristic q=1.5ms | 4 +1-pin device connector | 24VDC

PP83201/2/e2/1M16/1M20 /z3s/1stLU5/24VDC	Power supply | 10VA | for 1 Hole finder system/pair of light barriers | PNP, 60mA, short-circuit proof | metric Screw connection | On/off delay 3 sec | 4+1-pin appliance plug | light/dark switchable | 24VDC
PP2441q/220/R28E/e2 /1stLU5	Receiver | Hole detector | Monitoring width: 220mm | Response time- Characteristic q=1.5ms | PNP, 60mA, short-circuit proof | 4+1-pin device connector | Power supply from the transmitter
ET103/2000	/e2 /i /p1 /fx /stLU5 /24VDC Reflex switch | adjustable | active Background suppression | PNP, 60mA, Short-circuit proof | Level indicator "DIANA" | Converter increases resistance to radiant heat Protected | Increased vibration resistance | 4+1 pole Device plug | switchable between light and dark | constant light resistance 80kLux | 24VDC
PP2445CC1	/5m /1stLU5 Connection cable | single-ended termination Plug (socket) | 4+1-pin device plug | Length: 5m Weight: Net ~0.20 kg
Cve /9mkop	
Pp2441q/220/R28s/ 24vdc	
Pp2445/220 Qq	
Pp20110-2	
3153 E	
Et103/2000v /E2/Y/Sta5/24vdc Tester	
Pp2445cc2/5m/2stlu5	Connecting cable | pre-assembled on both sides Connector (socket & pins) | 4+1-pin Device plug | Length: 5m
Pp2441q/220/R28e /E2/1stlu5 (Ord.Nr. 4313qex03)	
Sk-3118-E-2db27	
Pv2092/2e /E2/Y/I/Sth7/24vdc	
Jf19h	
1885x10	
1661ex02 , Type Pp2092/2e /E2/I/Sth7/24vdc	
Pp2445/88 Qq	
Sth7w	
Sk-3118-E-2db26	
Pp2441qe	
Ps20g19 /Ir/Sth4	

(4314qe) Pp2441q/308/R153e /E2	
5841m14st	
Pv2092/2e/E2/I/Sth7/24vdc	
Pp2441q/308/R153/E	
Cable (Ste4) /4mkop/2ste4	
Pp84201/2	
Pp2441q/308/R153s /R2/Z3s/115+230vac	
Pp2445/308	
Pp2445/154 Qq	
Pp 2441	
1300039967	
Pp85301	
Pp83201-3	
Et103/2000 /E2/I/Sth4/24vdc	
Pp20110-2 /E2/2pg7/2pg11/Q/24vdc	
Pp2445/308 Qq	
Pp2441q/308	
Pp2445cc2 /5m/2stlu5 (Ord.Nr. 4350cc2x01)	
Pp2445/88	
Pp2441q/308/R153e/E2	HOLE DETECTOR RECEIVER
Pp2441/308/R153e/E2 (Ex Pp2441e/308/R153/24vdc)	
Cs/4mkop	
Pp2441-154/R27s/24vdc	
Pp2441s/308/R153s/R2z3s/115+230vac	
Pp2441qs/220/R2824vdc - Obsolete, Alterantive - Pp83201/2 /R/E1/1m16/1m20/Z3s/1stlu5/24vdc (Ord.Nr. 2420x19)	
Ps20g19	
Pp2441q/220/R28s /2stlu5/24vdc (Ord.Nr. 4313qsx03)	

Ce/4mkop
Et103
Kabel (Ste4) /4mkop/2ste4
Pp2445/220
1884x05, Type Ps20g19 /Ir/Sth4
Pp86301
Ps20r26ii
Ste4
Pp83201/2
Pp2441q
Pp2445/154
Pp83201/2 /R/E1/1m16/1m20/Z3s/1stlu5/24vdc (Ord.Nr. 2420x19)
3153s
Pp2441qe/220/R28e2 - Obsolete, Alterantive - Pp2441q/220/R28e /E2/1stlu5 (Ord.Nr. 4313qex03)
3153 (3153e + 3153s)
Ad26ss2
1665ex13
Cvs /4mkop
Pp83201/224vdc/R/Z3 - Obsolete, Alterantive - Pp2441q/220/R28s /2stlu5/24vdc (Ord.Nr. 4313qsx03)
Pp2445/220 Q
Pp2441q/308/R153e /E2
Pp2445/154 Q
Jp195 /R/D/Rl/Sth7/20...230vuc
(4314qs) Pp2441q/308/R153s /R2/Z3s/115+230vac
Et103/2000v /E2/Y/Sta5/24vdc
Pp2445q/308e
Ad26ss1

Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Pp2841qe/308/R125
P/N: 1721ex01 Type: Pv2092/2e /E2/Y/I/Sth7/24vdc
Sta5w
Pp2441q/308/R153e /E2, 4314qe (Empf.Lochsuchger.,Messweite;308mm Gleichlichtfest Bis 80 Klux , 3+1-Pol.Ger. Metallstecker)
Pp2445/88 Q
Pp2445/308 Q
Ps20g19/Y/Ir/Sth4
Pp2441-154/R27e/E2
Pp2441q/220/R28e/E2
Wr60
Pp2441q/308/R153