Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Pekos



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Pekos Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Pekos Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
K040ss	Ball DN40 Material 1.4408/CF8M
W040ss	Stem DN40/65 Material 1.4401
K050ss	Ball DN50 Material 1.4408/CF8M
W080ss	Stem DN80/100 Material 1.4401
Ball Dn50 1.4408/Cf8m	
Ball Dn40 1.4408/Cf8m	
Stem Dn80/100 1.4401	
Stem Dn40/65 1.4401	
Complete Assy	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)
Ball	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)
seat	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)
gasket	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)
Stem bearing	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Thrust bearing	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)
Gland packing	3-WAY BALL VALVES CLASS: 150 150˜250 A (6”˜10”)
QWCC 8925 or 892S.	The flange inner diameter of this valve is 110 mm. We could not read the material code completely. However, as far as we have read, they are PEKOS QWCC 8925 or 892S. . If there is no repair kit for this valve, you can send us an offer for a new one.
000 070 961	Coupling made of stainless steel 1.4305 for bracket height 60 mm, VKT 14 (diagonal) -> VKT 14 including red position indicator Connection fitting: Pekos KURB806SGSGV, 1/2"BSP ZFL. 5.5mm Drive connection: square 14 mm (45° offset) (Mecafrance deadman attachment) ---------- 01.2 220 822 998 1st CONSOLE F03/F05 HEIGHT 60 MM GALVANIZED STEEL EN 15081 02 804 220 007 1 ASSEMBLY dead man's attachment complete with: - ball valve - clutch - Console Functional test and setting of the end stops 02.1 807 047 825 1 Deadman system: handlever, spring return (NC) 25-32v DN 25/32 (venturi) Body out of steel (System Mecafrance) ISO bottle F05 / VKT 14 (45°) torque 15 Nm
PEKOS F.K806 SGSGV 800 NPT 1"	CL800, NPT, body and ball 316 SS, Ball valve
000 072 374 1/2"NPT	3-part ball valve type K806SGSGV, cl. 800 Size DN 1/2"NPT Housing stainless steel A182F316 Ball stainless steel A182F316 Seat PTFE+CG (Carbon-Graphite) Packing Graphite + PTFE+CG (Carbon-Graphite) Housing seal Graphite + PTFE+CG (Carbon-Graphte) FIRE SAFE Approval, ATEX 94-9EC, PED 97/23/CE Design API 6D, B16.34, Materials acc. NACE MR0175 m. hand lever

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
000 072 374 1"NPT	3-part ball valve type KRB806SGSGV, cl. 800 1"NPT Housing stainless steel A182F316 Ball stainless steel A182F316 - RB (reduced bore) Seat PTFE+CG (Carbon-Graphite) Packing Graphite + PTFE+CG (Carbon-Graphite) Housing seal Graphite + PTFE+CG (Carbon-Graphte) FIRE SAFE Approval, ATEX 94-9EC, PED 97/23/CE Design API 6D, B16.34, Materials acc. NACE MR0175 m. hand lever
PK-10	
2 Way Valve: FIG.Z 06 TTTG	
3 Way Valve: FIG.Z 86 TTT	
see list	
THREE-WAY VALVE DN25 PN40 (NG)	DN25 PN40 Flange sealing surface form E, material body: G-SC 25 With lifting gear H4 gastight, work pressure: 10 bar Medium: natural gas max. flow rate:220 Nm3/h t=20 C
THREE-WAY VALVE DN25 PN40 (HYDROCARBON)	DN25 PN40 material body: G-SC 25 With lifting gear H4 gastight, work pressure: 4 bar Medium: hydrocarbon gas
THREE-WAY VALVE DN25 PN40 (NG + H2)	DN25 PN40 Flange sealing surface form E, material body: G-SC 25 With lifting gear H4 gastight, work pressure: 24 bar Medium: natural gas+hydrogen max. flow rate:220 Nm3/h t=80 C
THREE-WAY VALVE DN25 PN40 (H2)	DN25 PN40 material body: G-SC 25 With lifting gear H4 gastight, work pressure: 21 bar Medium: hydrogen
DN200 CL150 3 Way T Port AKT 316 Ball Valve	
DWG - 71517	LOATING BALL VALVE 3 WAY 120° "Y" TYPE ANSI 1" CLASS 600 RF
DS-6499	FIG.Z 84 TTT PN 40 DN 25/100 Y Type 120°
FIG.Z 94 TTTGV CL150 2"	MANUAL BALL VALVE
REPAIR KIT Z 94 TTTGV CL150 2"	
SPARE BALL 2"	
Fig Gks04 Sgsgv	DN200 PN40 Spherical valve flanged, trunnion design, 2 pieces, fullbore C.S.1.0460 forged carbon steel body 316 ss sphere PTFE gasket

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	bareshaft
Dn200 Pn40	PEKOS-Kugelhahn mit vollem Durchgang DN200 PN40 Körper: 1.4408 Edelstahl Kugel und Innenteile: 1.4408 Edelstahl Ventillänge L: 400 F5 Dichtung PTFE Verpackung: Graphit Anschluss: angeflanscht Faire sicher Steuerung: mit pneumatischem Antrieb Stellantrieb (Stellantrieb) sc300034,5 / f16-n-d (46 a Einfachwirkende Federrückstellung (mit Schnuraktion: streuen, um zu schließen) Drehmomentwert: 4,5 bar max. 1.352 nm, min.982 nm Aksesur aa4 Luftanschluss b4 max. 8 bar Pilotventil: mv3dc24 Schaltkasten: führte mit cr3mvazm12 / mv3dc24 PN40 dn 200 Flüssigkeit: Sauerstoff Die Ventile müssen entfettet sein. Und durch Zertifikate verifiziert werden. ATEX-Zertifikat ex 2gd technische Datei
Z 96 TTTG PN40 DN50	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.