

Peristaltic Pump

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Peristaltic Pump Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Peristaltic Pump Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
SR25.6 0,8 NI/h, 115/230 V	01P1350 Peristaltic pump type SR25.6 for front panel mounting, sheet thickness: min. 3.5 mm, speed: 10 rpm, delivery rate: 0.80 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., Material: Novoprene, PVDF, connections: PVDF hose connection DN 4/6, mains: 115/230 V, 50/60 Hz, cable length: 700 mm Stat. Item no. 84136080 Origin of goods: DE Pref.: EU
SR25.2.W, 115/230 V	Peristaltic pump type SR25.2. W for wall or surface mounting, rotational speed: 5 rpm, capacity: 0.3 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., material: Novoprene, PVDF, PVDF hose connection DN 4/6, power: 115/230 V, 50/60 Hz with connection terminal Attention: Successor to 01P1000 - SR25.1 ** Harmonized code: 84136080 CoO comm.: DE pref.: EU
THOMAS 29012726	
Sr25.2 0,3 NI/H, 115/230 V, Ecm	Peristaltic pump type SR25.2 for front panel mounting, sheet thickness: min. 3.5 mm, speed: 5 rpm, flow rate: 0.30 NI / h liquid, pressure range: 200 mbar up to 2.2 bar abs., material: Novoprene, PVDF, PVDF hose connection DN 4/6, mains: 115/230 V, 50/60 Hz, cable length: 700 mm Stat. Lot no. 84136080 Origin of goods: DE Pref.: EU
Sr25.2-G In Housing, 0.3 NI / H, 115/230 V	Peristaltic pump SR25.2-G in the housing, speed: 5 rpm, delivery rate: 0.3 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., Material: Novoprene, PVDF, connections: PVDF hose connection DN 4/6, housing made of Polycarbonate, dimensions (H x W x D): 105 x 105 x 107 mm, Cable entry M20, mains: 230/115 V, 50/60 Hz Stat. Lot no. 84136080 Origin of goods: DE Pref.: EU

Ürün	Açıklama
Sr25.2.W 0,3 NI/H, 115/230 V	Peristaltic pump type SR25.2.W for wall or surface mounting, speed: 5 rpm, delivery rate: 0.3 NI / h liquid, pressure range: 200 mbar to 2.2 bar abs., material: Novoprene, PVDF, connections: PVDF hose connection DN 4/6, mains: 115/230 V, 50/60 Hz with connection terminal ** Attention: successor to 01P1000 - SR25.1 **