

## Petz

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Petz** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Petz T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">TR.Ex-RTH</a>	<p>pi Ex room temperature / humidity / dew point measuring unit, Zone 1, 2, 21, 22 Integrated display for measured value display and on-site parameterization Cable length from the transmitter to the sensor up to 100 m no additional barrier required in the control cabinet Power supply: 20 ... 28.8 VAC / DC 50-60 Hz Power consumption: 3 W / 5 VA Outputs: 2 x 0...10V DC / 0...20mA (scalable and calibrated) Housing material: High-tech polymer halogen- and silicone-free Housing protection: IP66 Humidity range: 0...100% RH without condensation Temperature range: -40...+70°C Dimensions: approx. 175 x 110 x 56 mm Specification: II2(1)G Ex eb mb ib [ia Ga] IIC T4 Gb II2(1) D Ex tb ib [ia Da] IIIC T130°C Db incl. sensor Measuring range: -40...+125°C , 0...100%rH Length: 50 mm Case material: stainless steel Housing protection: IP66 Humidity range: 0...100% RH without condensation Temperature range: -40...+125°C Dimensions: approx. 80 x 45 x 66 mm Specification: II2G Ex ia IIC T6/T5/T4 Gb II2D Ex ia IIIC T130/95/80 °C Db</p> <p>(Old.) pi Ex-Temp./Humidity/Dewpoint measuring unit, Zone 1, 2, 21, 22 Integrated display for measured value display</p>

[TR.Ex-DTH-200](#)

and on-site parameterization Cable length from the transmitter to the sensor up to 100 m no additional barrier required in the control cabinet Power supply: 20 ... 28.8 VAC / DC 50-60 Hz Power consumption: 3 W / 5 VA Outputs: 2 x 0...10V DC / 0...20mA (scalable and calibrated) Housing material: High-tech polymer halogen- and silicone-free Housing protection: IP66 Humidity range: 0...100% RH without condensation Temperature range: -40...+70°C Dimensions: approx. 175 x 110 x 56 mm Specification: II2(1)G Ex eb mb ib [ia Ga] IIC T4 Gb II2(1) D Ex tb ib [ia Da] IIIC T130°C Db incl. sensor Measuring range: -40...+125°C , 0...100%RH Immersion depth: 200 mm Case material: stainless steel Housing protection: IP66 Humidity range: 0...100% RH without condensation Temperature range: -40...+125°C Dimensions: approx. 80 x 45 x 66 mm Specification: II2G Ex ia IIC T6/T5/T4 Gb II2D Ex ia IIIC T130/95/80 °C Db