

## Pewag

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Pewag** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Pewag T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	Aıklama
<a href="#">Ple/N 22</a>	pewag PLE/N Eta Load capacity: 15,000 kg weldable anchor point Item: # 92463
<a href="#">22mm Grade100 Winner chain</a>	Quantity: 4 pieces will be in the form of 5 meters. Used in log carrying cranes
<a href="#">Link for 22 mm Grade 100 Winner chain</a>	Code: CW 22. It is used in cranes carrying logs.
<a href="#">Main Link-Type A for 22mm Grade100 Winner chain</a>	Code:A 36. It is used in cranes carrying logs.
<a href="#">04757</a>	
<a href="#">09761</a>	
<a href="#">11390</a>	
<a href="#">13G120RLB</a>	
<a href="#">16543</a>	
<a href="#">49696</a>	
<a href="#">49697</a>	
<a href="#">50206</a>	
<a href="#">58493</a>	

<a href="#">63646</a>	
<a href="#">87664</a>	
<a href="#">BW40 (70798)</a>	
<a href="#">CW26 (89021)</a>	
<a href="#">MW56 (70801)</a>	
<a href="#">WIN 22 400 EN 818-2</a>	
<a href="#">3002473(A11516)</a>	CHAIN LINK 56 DIN 745 C45 VI INCLUDES 2 HEXAGONAL NUTS M12 / BRACKET
<a href="#">3002802(A86335)</a>	DISTANCE LATCH L56 DIN 745 Dimensions: 95 x 40 x 6mm
<a href="#">Lifting point</a>	
<a href="#">4026520(A16544)</a>	SCREW BOLT FASTENING BDS 19X75 Bucket attachment for round steel chains suitable for toothed sprockets and chain rollers, for cups with rear wall mounting, easy assembly on the chain, reusable, no wearing part consisting of: 2 drop-forged and tempered clamping halves, Socket head cap screw with Stover security nut and 4 hexagon nuts M20
<a href="#">4027850(A49697)</a>	REPLACEMENT SEGMENTS FOR SEG-E 16/ 500 highly wear-resistant case-hardened, 8 segments per chain roller
<a href="#">ZG.NR. 11292A</a>	49697
<a href="#">BUCKET ATTACHMENTS BDS 14X50</a>	
<a href="#">CONNECTİNG LİNKS VHV 14X50</a>	
<a href="#">4027808(A47614)</a>	VERB.GLD VHV 14X 50 high-strength, highly wear-resistant connecting links type VHV Material: Cr-Ni alloyed special steel, case-hardened consisting of: 1 open connecting link, 1 pc. closing flap, 2 pc. dowel pins
<a href="#">4026518(A16542)</a>	SCREW BOLT FASTENING BDS 14X50 Bucket attachment for round steel chains suitable for toothed sprockets and chain rollers, for cups with rear wall mounting, easy assembly on the chain, reusable, no wearing part consisting of: 2 drop-forged and tempered clamping halves, Socket head cap screw with Stover security nut and 4 hexagon nuts M14
<a href="#">BDS 14X50</a>	
<a href="#">VHV 14X50</a>	
<a href="#">VHV 19x75 U31</a>	
<a href="#">Wie Zeichnung</a>	Je 1000stk.
<a href="#">29.5x25 L3</a>	
<a href="#">29.5x25 L4</a>	
<a href="#">WINNER 400 G8W 19X57 LFM LAC/DB</a>	4002695(A04397)
<a href="#">WMK19</a>	GK8 load chain 19x57, Tf. 11500 kg, EN 812-2, descaled, black painted
<a href="#">WPK20</a>	G10 load chain 16.0t 20x60x29mm, powder coated surface
<a href="#">Edging MACHINE WITH HOOK AND BELT.</a>	50 MM X 10 MT, 2,5 TON CAPACITY (WITH EVENING MACHINE AND TENSIONING BELT), TS EN 12195-2
<a href="#">Edging MACHINE WITH HOOK AND BELT, 50 MM X 12 MT.</a>	, 2,5 TON CAPACITY (WITH EVENING MACHINE AND TENSIONING BELT) TS EN 12195-2
<a href="#">Edging MACHINE WITH HOOK AND BELT, 75 MM X 10 MT.</a>	5 TON CAPACITY (WITH EVENING MACHINE AND TENSIONING BELT) TS EN 12195-2

<a href="#">Edging MACHINE WITH HOOK AND BELT, 75 MM X 12 MT,</a>	5 TON CAPACITY (WITH EVENING MACHINE AND TENSIONING BELT) TS EN 12195-2
<a href="#">CHAIN TENSION, RATCHET, HOOK/HOOK, FOR 10 MM CHAIN</a>	GRADE 80 TS EN 12195-3
<a href="#">CHAIN TENSION, RATCHET, HOOK/HOOK, FOR 13 MM CHAIN</a>	GRADE 80 TS EN 12195-3
<a href="#">HE WN- G80 RAS-7X21</a>	
<a href="#">WRSL13</a>	GK10 safety eye load hook, f. chain 13mm, length 205mm, Load capacity 6700kg
<a href="#">Universal ED 3690 Anti-Slip Chain</a>	(Repair ring 12 mm, Skoba 34940, Stitch lock VBS 14). Tire size 18. 00-25
<a href="#">SAP: 4019318 AWHW 10 WELDING HOOK PC/O</a>	
<a href="#">4013891(A57643)</a>	PLEW 2,5T -20°C PC/O Typ: PLEW 2,5t** Load capacity 90°: 2,500 kg Load capacity 0°: 4,000 kg **Purpose: The pewag PLEW serves as an anchor point for welding to loads in which elements of Chain slings (hooks, shackles, straps...) for lifting the Load can be attached.
<a href="#">PLEW weldable eye bolt WLL: 10 mT</a>	
<a href="#">PLE/N 6</a>	Profilift Lifting Point WLL = 1.12 t
<a href="#">PLBW 2,5 t</a>	Profilift Lifting Point PLBW = 2.5 t
<a href="#">DELTA PLDW 6,7 t M30</a>	
<a href="#">25351000038534</a>	Connecting link 89340 Matching type designation Connex 0.25 Net weight KG CW10/09 CONNEX CONNECTOR G10 PC/O
<a href="#">25250000042443</a>	Swivel stand 1,000kg PLDW Delta M14x22mm Product description Swivel bracket with oval ring Permissible payload 1,000.00 kg Type designation PLDW Delta Type of attachment: Screw-on Thread type M14 Usable screw length 22.00 mm Screw present: Yes Permissible payload 90° 1,000.00 kg Rotatable under load: Yes
<a href="#">25250000035676</a>	Swivel block 4,000kg PLDW Delta M24x40mm Product description Swivel bracket with oval ring Permissible payload 7,000.00 kg Type designation PLDW Delta Type of attachment: Screw-on Thread type M24 Usable screw length 40.00 mm Screw present: Yes Permissible payload 90° 4,000.00 kg Rotatable under load: Yes
<a href="#">UNILOCK CONNECTING LINK U26</a>	
<a href="#">CHAIN DIN 5688-8 B22</a>	
<a href="#">CHAIN DIN 5688-8 Ni19</a>	
<a href="#">MASTER LINK M36</a>	
<a href="#">CHAIN DIN 5688-8 Ni32</a>	
<a href="#">CHAIN DIN 5688-8 A72</a>	
<a href="#">CHAIN DIN 5688-8 B40</a>	
<a href="#">CHAIN DIN 5688-8 Ni32</a>	
<a href="#">25201500037100</a>	Pipe hook 3,000kg PHW Product description Container hooks Permissible payload 3,000.00 kg Hook opening 40.00 mm PIPE HOOK PHW 3 T
<a href="#">25250000035000</a>	Pewag anchor point Delta PLDW Pewag Delta PLDW anchor point M30 thread Load capacity 6.7 t.
<a href="#">27805-1</a>	

<a href="#">SDS 14 x 50</a>
<a href="#">G80 E10 14x50 SI BK</a>
<a href="#">27806-1</a>
<a href="#">27807-1</a>
<a href="#">27815-1</a>
<a href="#">Hv 34x136 G80e10</a>
<a href="#">57999</a>
<a href="#">Hksb 10.8 Sicherheitshaken M.Gab.Pc/R</a>
<a href="#">Vhv 16x64 Mm Verbindungsglied</a>
<a href="#">Bds 16x64 Mm</a>
<a href="#">Hv-Kette 34x126 Wn G80 E10</a>
<a href="#">Typ: Ple 6/N (Artikelnummer 92458)</a>
<a href="#">Profilift Beta Plbw 15t M48</a>
<a href="#">Seg-E 16/500</a>
<a href="#">Plaw Mit Hå220;Lse 0,3t M8</a>
<a href="#">Awhw 6,3</a>
<a href="#">Klhw 8</a>
<a href="#">Part No. 13g120td/20</a>
<a href="#">Seg-A 16/500</a>
<a href="#">Khv 34 X 126</a>
<a href="#">Pldw 24t</a>
<a href="#">Ehv 34x136</a>
<a href="#">Vhv 34x136 N31</a>
<a href="#">11135</a>
<a href="#">84432</a>
<a href="#">Dsu 16x64 Mm</a>
<a href="#">78633</a>
<a href="#">58493 Pewag Winner Profilifttyp: Plaw 0.63 T</a>
<a href="#">Aw 36 G10</a>
<a href="#">Kfb 34x136</a>
<a href="#">Lat Dss M48 - Obsolete</a>
<a href="#">Part No. 13g120rb</a>
<a href="#">49999</a>
<a href="#">G10 Lhw10</a>
<a href="#">Veuw 1 T</a>
<a href="#">C (200/160)</a>



Yursat DıŐ Tic. M¼nendislik  
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505  
Osmangazi/BURSA  
+90 224 2400304  
[info@yursat.com.tr](mailto:info@yursat.com.tr)  
[www.yursat.com.tr](http://www.yursat.com.tr)

---