

Piab



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Piab Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Piab Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Suction Cup U30.20	-Silicone red -Rubber part
Suction Cup U15.20	-Silicone -Rubber part
P6040.V.CZ.00.AA.04	Vacuum pump - 10 pieces COAX® Cartridge Xi40-3 - T-slot fastening - Compressed air - connection thread G½ " - Vacuum connection thread G 2 " - silencer 2½ "
P6040.V.DB.00.AA.03	P6040 vacuum ejector - COAX® cartridge Xi40-3X12 - Mounting T-slot - Compressed air connection G1 / 2 " - vacuum connection G 1 1/2 " - silencer
P3010.00.AL.28.AA.00	-Vacuum pump -Housing, compressed air connection ø = 6 mm COAX® cartridge module Xi10-3FSx2 with RSV Function AVM2 NC G thread Nomenclature number: 84141089 Country of origin: Sweden
COAX Cartridge Mini Pi 12-3 FS	-Max. Ultimate vacuum 90 kPa - max.air consumption 0.44 NI / s at 0.314 MPa - with retaining cap - with silencer - with vacuum filter
0101115	
0101117	
0101122	
0101131	
0106352	
0106639	
0106722	
0107124	
0107149	
0107561	

0108981	
0109398	
0116993	
0120181	
0124880	
0125173	
0125174	
0125685	
0126331	
0126434	
0128421	
0128423	
0128426	
0200405	
0200417	
0202850	
0208975	
0212040	
124344	
204991	
2901 1/8 30-7901-3056	
3107030	
3116057	
3116061	Vacuum switch, electromechanical adjustable with screw - Overpressure max. 0.6 MPa Signal range: 15-95 kPa, Function: NO/NC Material: PBTP, PVC, CuZn, PA, VA, NBR, POM, Al Temperature range: -20-85 °C Vacuum connection: M5 Safety classification: IP67 Net weight: 0.0855 (kg)
3116063	Vacuum switch, pneumatic adjustable with screw (NC) - Overpressure max. 0.6 MPa Signal range: 15-95 kPa, Function: NC Material: CuZn, PA, VA, NBR, POM, Al Temperature range: -10-60 °C Vacuum connection: M5, weight: 39 g
3116651	

3116652
3116674
3150006S
3150061
3150101
3150109P
3150118S
3150125S
3150125S S.F15S50.XXX.00
3150230
3150230S
3216009
3222189
3250083S
3350066
348-015-02 / 20-3348-6200
50-6540-0800
6-1/8 50-6463-0656
6-M5 50-6522-0652
7320485
926-M1NS2000-P
9900668
9901173
9901568 VGS3010.AF.01.BA
9902095
9902633 P3010
9902973
9904053
9904217 SI32-3-PCL.S3BN.S.AD.SV
9904337
9904528 2901

9904557
9909608
9914109 2901
9914288 2901
9914853
A331-3C2 /20-0331-1800
AQR 0210, G1/4"
B110.20.11UA
B-20
B35XP
B50 MF
B50X20
B52XP
B75.20
BF80P.4H.08UA (ART.NR.0102370)
BFF60 0118994
BL20-2
BL30-2.20; 0101118
BL40G38
BX35.G14
BX52.G14
BX52P 0104727
BX52P30/60 W000201824
BX75P.4K.07UF.F(ART.NR. 0106606)
COAX
D=250
F110 0100561
F15
F40-2.20
F-OB

FX77	
I.V4E3.P4.38.6A.C.EC.AAL.0.RU	
L28A6-BN	
LC16-F1820	
LC20	
LKVE16	
LKVE8	
LOAD CELL	
M100 M5A 0102137	
M25 B6-DV	
M25B5ADNA -ARTIK URETILMIYOR . SUNULAN PCL.X1AN.S.AD.SV	
M5-1/8 50-2511-5256	
Nylon 3 Piab	
P3010 C3X1/8	
P3010.00.AG.01.AA.00	
P5010	
P6010	
PCL.X3BV.S.AD.S	
PCLX1BNS08DSV	
3222038	Vacuum pump MINI M10A6-BN MINI M10 - optimal feed pressure 0.60 MPa - max. final vacuum 84 kPa - Connection plate B - Compressed air connection 1/8" NPSF - Vacuum connection 3/8" NPSF - Nitrile seal
Piab20	
PNP	
PNP NO LM8	
PW.P80L.PR6.76T.33.CBA.1A.ASS.0.RU	
S.BX25P3060.XXX.00 W000201818	
S.F30-2S50.XXX.00	
UBERLASTSCHUTZ LKVE SEILDURCHMESSER 12-16 MM	
VG S 5010.AG.02.BA 9900760	

VGS5010.AG.02.BA	
VS40	
X10A6-AN	
9904034	PCL.X2BN.S.08D.SV piCLASSIC - COAX® cartridge module Xi40-3x2 - Standard, nitrile Connections: - Compressed air: Push In 8 mm - G1/4" IT - Vacuum G3/4" F - Muffler G1" M - Vacuum gauge Customs tariff number: 84141089 SE
3116672	Vacuum filter G1, 10µm - Pressure range: -0.1-0MPa - Material: PE, PP, PA - Operating temperature range: -20-80 °C - Filter fineness: 10 µm - Weight: 424g - Flow rate, max. 42 NI/s - Own volume: 495 cm³ - Filter area: 0.019 m²
0117719	Control unit for P6010 CU NC - On/Off function - blow-off function (adjustable) - Including connection plate for P6010
Vakuumpumpe MINI M10A6-BN MINI M10	optimum feed pressure 0.60 MPa - max ultimate vacuum 84 - kPa - connection plate B - Compressed air connection 1/8" NPSF - Vac. Connection 3/8" NPSF - Nitrile seal
MR5M (E18601267)	0214545 Sprue Cutter
F1 (E18601447)	0214223 Cutting Blade
DS 23 0104640	Solenoid valve DS 23 for ON/OFF control without connecting parts, plugs - Feed pressure max. 0.7 MPa - feed pressure 0.2-0.6 MPa - Mat.: Ni,AL,VA,POM,CuZn,NBR - Temp. range: - 18-50 °C - Weight: 100g - 24V, 2.5W, NC - Degree of protection, with DIN (c) connector: IP65 - Nominal flow rate 1.3 NI/s - Connection 3xM5 - Commodity number 84818079 - Country of origin USA
COAX MICRO Tİ 05-2	
P6040.V.DB.00.AA.03	P6040 vacuum ejector - COAX® cartridge Xi40-3X12 - Mounting T slot - Compressed air connection G1/2" - Vacuum connection G 1 1/2" - silencer
Suction cup B50.30	0101107 -Nitrile PVC -rubber part
S.B35XP3060.G14M.01	0205105 Suction cup B35XP - 1.5 folds - Polyurethane 30/60° Shore - G1/4" external thread - with filter screen
Filter holder kit FM23-50	0205572 piCOMPACT 23 vacuum ejector Kit consisting of: - Sight glass - Filter element - Fixing screw - seals
Filter holder kit FM23L-50	0205573 piCOMPACT
Spare parts kit piCOMPACT 23	0205484 for single compressed air connection Includes, among other things: - piCHIP housing seal with check valve - piCHIP housing seal without check valve - Gasket set for the SX ejectors - additional seals, screws & nuts for a piCOMPACT 23 module
10MM RBKT10 PICOMPACT23	
	Pressure range: -0.1-0 MPa - Material: PE, PP, PA -

3116652 Vakuumfilter G3/4, 10µm	Temperature range: -20-80 °C - Filter fineness: 10 µm - Weight: 170g - Flow, max. 15 NI/s - Own volume: 205 cm³ - Filter area: 0.010 m²
Suction cup F30-2.10	Chloroprene -Rubber part
piINLINE Micro Ti, 6-6 mm	0122022 -Max. Final vacuum 84 -kPa -Max. Air consumption 16.2 NI/min at 0.40 MPa -Max. Vacuum flow 19.2 NI/min at optimal feed pressure of 0.40 MPa
3101058U	MLL800 Vacuum Pump
P6040XI	95KPA,PA POM SS AL NBR HDPE,229X195,BASE,CBL LEADER COIL
9901391	P6040.V.DB.00.AA.03 P6040 vacuum ejector - COAX® cartridge Xi40-3X12 - Mounting T slot - Compressed air connection G1/2" - Vacuum connection G 1 1/2" - Silencer
Suction cup BL50-2.10.05AB	0101696 -Chloroprene -G 1/4" external thread with filter sieve
0101875 F75.30.07NE Nitrile PVC complete with	G 3/8" internal thread
0124960 Level compensation LC25-M3840	- Stroke length 40mm
0101874 Suction cup F75.30.07ND	Flat suction cup 75mm - Nitrile PVC - Fitting with G 3/8" internal thread and filter sieve
PICOMPACT23 FM23-50	
PICOMP23 FM23L-50	
SPARE PART KIT PIAB PICOMPACT23 0205484	
10MM RBKT10 PIAB PICOMPACT23	
P6010.AE.01.LA.52	9900012 vacuum pump - Housing - COAX® cartridge module Si32-3x4 - T-slot assembly - Connection plate with G thread - Connection thread 2x G1" incl. silencer 1" Not a dual use item Net weight: 2.3402 (kg)
0101137	Saugnapf F50-2.30 -Nitrile PVC -Rubber part
3116652	Vakuumfilter G3/4, 10µm - Pressure range: -0.1-0 MPa - Material: PE, PP, PA - Temperature range: -20-80 °C - Filter fineness: 10 µm - Weight: 170g - Flow, max. 15 NI/s - Own volume: 205 cm³ - Filter area: 0.010 m²
9904044	PCL.X1BN.S.DD.SV Vacuum pump - COAX® cartridge module Xi40-3x1 - Standard, nitrile Connections: - Compressed air 1/8" NPSF - Vacuum G3/4" IG - Silencer G1" AG - Vacuum gauge
9904217	PCL.S3BN.S.AD.SV Vacuum pump piCLASSIC - 3 pieces COAX® Cartridge Si32-3 - Nitrile seals Connections: - Compressed air G1/4" - Vacuum G3/4" IG - incl. silencer G1"

	AG - incl. vacuum gauge
0120294	COAX Cartridge Mini Xi 10-2 C - max. final vacuum 94 kPa - max. air consumption 0.46 NI/s at 0.50 MPa - with retaining cap
9904044	PCL.X1BN.S.DD.SV Vacuum pump - COAX® cartridge module Xi40-3x1 - Standard, nitrile Connections: - Compressed air 1/8" NPSF - Vacuum G3/4" IG - Silencer G1" AG - Vacuum gauge
P3010.00.AE.00.AA.00 Pi12-3x1	
P3010.00.AE.00.AA.00	- Vacuum ejector P3010 - Housing, compressed air connection ø=6 mm - COAX® Cartridge Pi12-3FSx1 - without connection module
P3010.00.AE.00.AA.00 Pi12-3x1 Batch 753245	
D1-X531-3 KT 24VDC 2,5KW	
0104274	Solenoid valve DS 23 for ON/OFF control of the pump modules - Feed pressure 0.2-0.6 MPa - Material: Ni,AL,VA,POM,CuZn,NBR - Temperature range: -18-50 °C - Weight: 100 g - Voltage 24 V - Protection class, with DIN (c) plug IP65 - Nominal flow 1.3 NI/s
PIAB LKVE – 8	Working range 0 – 8000 Kg - Rope diameter: 16-20mm - Signal output 4 – 20 mA - Supply voltage 24 VDC
MFE.200H.AS1	- Nozzle size ø2 mm - NC vacuum + NC blow off - High vacuum - M12, 8-pin - With silencer multi-function ejector
PCL.S3BN.S.AD.SV	vacuum pump piCLASSIC - 3 pieces COAX® Cartridge Si32-3 - Nitrile seals Connections: - compressed air G1/4" - Vacuum G3/4" IG - incl. silencer G1" AG - incl. vacuum gauge
FC75.30.07UF	suction cup FC75 - Nitrile PVC - G 3/8" external thread with NPSF 1/8" internal thread Country of origin: Malaysia Statistical commodity number: 40169997
0206532	Suction cup BFFT90P.5S.G70MR - Ø 93 mm - Design: bellows - Material: Polyurethan - Shore hardness: 60 A° - Temperature range: 10-50°C - Mounting: 3/8" G internal thread - filter sieve
0124959	Leveling device LC25-F3840 Leveling - Material: Al, SS - Temperature range: 0 - 60 °C - Connection size: 2x G3/8" IG - Stroke length: 40 mm
0121170	Cross connector 25-25 PMAT - Two clamps (diameter 25mm) - 65 mm axle distance
Saugnapf F50-2.30	-Nitrile-PVC -Rubber part
0118200	piSAVE® onoff with large hysteresis Energy saving system NO - Feed pressure, range 0.17-0.7 MPa - Material: Al, NBR, PA, SS, CuZn - Temperature range: 0-60 °C - Weight: 89 g - Connection, compressed air 2x Ø8 mm / 2x 1/8"NPSF -

	Connection, vacuum 2 x M5 - Working range: 15-99 kPa - Hysteresis: 5-10kPa
PICLASSIC PIAB PCL.X1BN.S.DD.SW 9904044	
FOAM.KVG.400.120.N412	Kenos replacement foam - Length 400mm - Width 120mm - Foam thickness 40mm EPDM IT - With filter mat - Medium round grid
PCL.X2BN.S.AD.X	piCLASSIC vacuum pump - COAX® cartridge module Xi40-3x2 - Standard, Nitrile Connections: - Compressed air G1/4" IG - Vacuum G3/4" IG - without accessories Net weight: 0.8158 kg/piece
0200328	S.F33SF50.XXX.00 Suction cup F33 FDA - Rubber part - Ø 33mm - Silicone. 50° Shore A, blue - detectable - FDA compliant Weight 0.0054 (kg)
0210488	FOAM.KVGL.1200.400.N405 Kenos replacement foam - Length 1200mm - Width 400mm - Foam thickness 40mm - Without F filter - grid spacing 5.30 mm
0209942	G.BV.FIL.KVGL.1200.300.N405
VSAB 53.0mm G¼ Diameter:50mm Suction Cup	
0106965	
0106352 Saugnapf F75p 30/60,G1/2"	
0118991	
0104640	
20-301/8\"ms	
20-0333-1000	
Coax-6xsi32-3	
3150101s	
0103088	
Dynamometer 1000 Kg Typ B	
0209137 Kabel Control 10 M	
Saugnapf S. B30-2hn75,G38m.01	
0115285	
Suction Cup B30-2 Silicone	
9914109 2901 G.Bgi48s50.B1.S1.G14m.00	
31 16 674 Interchangeable Filter Element	

25tn 8/2	
0110245	
0106374	
Pfg 25 Si-55	
0103293	
0125685 Vacuum Switch Vs4016 65 -Kpa	
D20two50	
9904528 2901 Injektor Plc.P1bn.S.Dd.Sv	
0101122 S.BI50-2s50.Xxx.00, Suction Cup BI50-2.20	
0101137 Saugnapf Suction Cup F50-2.30	
0101884	
0118994	
0202850 Saugnapf B-BI40-2, Detektierbar, Detectableblue	
0126065	
3222097	Vacuum pump MINI X10A6-ANMINI X10 - opt. feed pressure 0.50 MPa - max. final vacuum 95 kPa - Connection plate A - Nitrile seal
0101129 Suction Cupf20s.F20cr50.Xxx.00	
0204991	
X10a6-An Ejektor	
0118671	
Vakuum-Injektor Mini Coax Xi-2 1/8"	
0101884 Sauggreifer Vakuumsuction Cup B110.20.11na,	
Lc12-F0510	
0104658	
3150109? Suction Cup B150.30, Nbr/Pvcca. 0,1kg/Stk.	
012833	
9914288 2901 Vacuum	

Cupg.Bgi48s50.B3.S1.G38m.01 0106346 B75p
0116993 Saugnapf Bl40-4 Silikon G 3/8"
3150101 Suction Cupb10-2s.B10-2cr60.Xxx.00
20-0072-0071
0124879
0107124 Coax Cartridge Midi Si 32-2
0103296
Pcl.X3an.F.08d.Sv
B 300257
3116652 Vacuum Filter 3/4" Cpl., Nylon
204991 Saugnapf B15xp
Dynamometer 1000 Kg, Type B, Art N: 300025
MII400
3101057
0200405 Saugnapf Silikon-Piab B20 Fcm
0124955 Kompensator Ebene Lg20-F1425
Aqr 02
3222219-X20a6-Cn
S.B50np50.Xxx.00
M25b6-Dn
Saugnapf S. F40-2np50.Xxx.00
Wk 2000
0101137
M25-Classic
0209090
0125967
Lc16-M
31 16 652

[3150125s S.F15s50.Xxx.00 Sauggreifer](#)

[Vakuum Silikon F15](#)
[0118429](#)

[0101131 Suction](#)
[Cupf25s.F25cr50.Xxx.00](#)

[0209137](#)

[12,5tn 4/1](#)

[103293](#)

[103289](#)

[Xi40-3 Pcl.X2bn.S.08d.Sv](#)

[Fc50](#)

[0129641](#)

[3116064](#)

[0101101](#)

[B15-2](#)

[0107129](#)

[Fcf75p.5r.G45w](#)

[0104729, Sbx52p3060.Xxx.02](#)

[S.BI20-2s50.Xxx.00 Red Suction Cup](#)
[Without Holder No. 0101116](#)

[Saugnapf B40.10 S. B40cr60.Xxx.00](#)

[Vgs3010.Af.01.Ba](#)

[9902095 P6010.Ad.01.Me.52, Vacuum](#)
[Pumpzolltarif-Nr.](#)
[84141089ursprungsland Singapur](#)

[3222219](#)

[107303](#)

[3216009 Silencer 3/8"](#)

[Wk](#)

[0128421 Filter Insert 1/8", 1/4", 3/8",](#)
[Ppx10re Im 3er-Pack](#)

[3150101s Saugnapf B-10](#)

[0110290 Suction Cup Bf110p.5k.G40m](#)

[0106606](#)

0118695	
3216002	
9909608 Saugnapf Silikon Piab B20 Silicone Fcm, G1 / 8 ", Mit Filtergewebe	
01 04 396	
0104283á;	
0101133 (F30-2.10)	
Lkve-4	
0101115 Suction Cuppl 20-2s.BI20- 2cr60.Xxx.00	
20-0072-0072	
9904039	
0104272	
M32-4-Wire Dc Pnp	
Vakuum-Sauggreifer Piab Nr. 0101109(B50-2.30)	
B10-2	
3222099	
M25b6adn0102184-M25-Clasic(Ex32-01- 070)	
0106066	
20tn 4/1	
3107031	
0209137 Cabel	
- U15 Piab	
M25b6adn0102184-M25-Clasic(Exmld25)	
0107145	BX75P Rubber part with filter screen - Polyurethane 30/60° Shore
0118992	
0118997	
Xlf150	
0107477	

0101129
Vgs5010
3350066 Schwenker BI-40 G1/2"
1/4-1/8 50-2531-5756
3150286 S
1/8-1/4 50-2511-5657
B52ns18
9902973 Saugnapf G. S35.T60.B1.S1.G18m.01
103296
Pcl.S2bv.S.08d.Sv
F75.30.W
3250085
P3010pi12/3
0101769 S.F50-2np50.G38m.01
0119121
0110290
107379
M20a5-B1n
0128423 Filter Insert 1/2", 3/4", Rv25/P/B/035 3er-Pack
0101137 F50-2.30
Vs 4118
3150230 Suction Cupb15-2s.B15- 2cr60.Xxx.00
P6010.Ad.01.Me.52
0101117 S.BI30-2cr60.Xxx.00, Suction Cup BI30-2.10
0115345
0109006 S.Bx25p3060.Xxx.00
I.V4e3.P4.38.6a.C.Ec.Aal.0.Ru
124344 S.Bx15p3060.Mm5m.00, Suction Cupbx15p.4k.01ac

Suction Cup Silicone B20
103294
0101118 (BI30-2.20)
Vakuum-Sauggreifer Piab Nr. 0101104(In30-2.20)
B 20 Saugnapf Suction Cup Chloroprene (Black)
0203030
0104283
0106957
Pcl.S1bn.S.Ad.S
Cu-1/2
0108981 Cartridge Holder Midi-2 3/8", Midi Coax
BI20-2.20
Bf-80y Fc75
0106798
0101172
Mj10a6-Bn(Ex.M100b6dn)
3150125s S.F15s50.Xxx.00, Suction Cup F15.20
3150006s Saugnapf U-15
S.F30-2s50.Xxx.00 Suction Cup F30-2.20
0101411
0101116
0104271
9900668 Vacuum Grippervgs5010.Aa.00.Ba
3116653
115314
0120181 Zakaz-Mvtu@Yandex.Ru
0200417 S.F20sf50.Xxx.00, Suction Cup F20.21

3150107p
0101944 Complete Kit B110-2 Vacuum Tire
0101134 (F30-2.20)
F110.30.W
Bx75p.5k.G40w.F
0101134
0101166
0100212
45tn 8/1
0101161
Ap33.50.071
0107151
L63
0101411 U30.30.02af
X40f6kn
U15
0100194 H40b6-Dv