**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

# Plymovent

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

**Plymovent** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

*Firmamız Plymovent Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.*

| Ürün | Açıklama |
|---|---|
| Mobilegoplus/3m (215) | 0000111473 |
| Dualgoplus/3+4m (435) | 0000111515 |
| Monogoplus/4m (215) | 0000111491 |
| Kua-4 | Metal tube arm |
| Monogo Plus | Stationary filter unit with METAL tube arm |
| MFD 435 | 7025100000 |
| UltraFlex-3 / extraction arm | 7925170090 |
| UltraFlex-4 / extraction arm (alternative) | 7925220090 |
| MAGNETIC SAFETY KIT | (DISCONNECT THE CAR EXHAUST SYSTEM HOSE WHEN INSTALLING THE METER AWAY TO MOVE FREE AND EMPLOYEES, AT THE SAME TIME CERTAIN THICKNESS IN THE EXHAUST SYSTEM FROM THE INLET, WHERE THE HOUSING HOSE AND SYSTEM DAMAGE TO THE MAGNETIC DAMAGE TO THE REPLACEMENT) |
| MAGNETIC EXHAUST | VEHICLE HOSE CONNECTION KIT (MAGNETIC CONNECTION ON THE FIRE VEHICLE EXHAUST PIPE-TO THE SUCTION HOSE AGAINST MAGNETIC HOSE AGAINST MAGNETIC HOSE CONNECTION APPLICATION TO THE LEAKAGE EMPLOYMENT WHEN THE VEHICLE CONNECTION IS CONNECTED TO THE LEAKAGE SYSTEM. |
| VEHICLE RADIO FREQUENCY TRANSMITTER | (CONNECTED TO THE VEHICLE IGNITION, IT ENABLES THE FAN TO AUTOMATICALLY WHEN THE VEHICLE IGNITION IS TURNED ON. THE TRANSMITTER SENDS A WIRELESS SIGNAL TO THE NRC-24V/230V RECEIVER AND RUNS THE FAN TO RUNNING THE PRODUCT DEVICE -300 DEVICE DEVICE. |
| RADIO FREQUENCY RECEIVER | (RECEIVE THE OPERATION OF THE SYSTEM BY DETECTING |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | THE SIGNAL FROM THE SIGNAL TRANSMITTER ON THE VEHIC BY OPERATION OF THE VEHICLE, THE RECEIVER SENSOR STOPPING THE SYSTEM AFTER THE VEHICLE LEADS FROM THE PARTICULAR DISTANCE STATION - WORKING RANGE 100-300 MT) |
| MANAGEMENT BOARD | (A SYSTEM PANEL WITH AUTOMATIC AND MANUAL OPERATION FEATURE AND WITH ITS INSIDE PROTECTION FUSE, WHEN THE SYSTEM IS ACTIVE, THE SYSTEM STARTS AND STOPS THE SYSTEM WITH THE INFORMATION RECEIVED FROM THE SIGNAL RECEIVERS AND THE SYSTEM FAN FREQUENCY CONTROL) |
| 09820310110 | |
| 09850060050 | |
| 37756 | |
| 37993 | |
| 6387 | |
| 7274 | |
| FCC-50/HE | |
| H10-610x610x292 | |
| 110877 | SER-850 Spring operated hose reel for 125 mm-150 mm hose Hose capacity up to 10 m, 850 mm drum width Excl. hose connection- |
| 111919 | MAS-150 Hose connection kit Ø 150 mm, for SER reels-Hose Connection Kit Stoppers and Reductions |
| 110200 | ET 150 Exhaust hose Ø 150 mm, L = 10 m-Exhaust Suction Hose L:10m D:100 mm-650 C temperature |
| 109627 | HTA 150-200 Hose connection Ø 150 mm, nozzle Ø 150 mm-Alu. Exhaust Nozzle |
| 100306 | FUA-3000 (435) Extraction Fan-1,5 HP-380 V-50 Hz-3 ph |
| 80FMS055 | Fan Manual Starter 2,5-4 Fan Thermal Switch |
| DUCTS | Ventilation Channels/Suspension Consoles/Fittings/Jet Cap-Fan post front shot |
| 7445000000 | SFS (incl. NCW 11)<br>The SFS is a self-cleaning filter unit for 1 extraction arm. |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | The unit is equipped with a filter, type FCC30. The FCC30 is a cellulose DuraFilter©. The filter has a surface area of 30 m² and an efficiency of 99.8% (EU9). Since the filter is made of cellulose, It is not suitable for heavily oil-treated steel. The filter is designed for the following applications economically:<br>- MIG/MAG solid wire > 700 kg/year<br>- MIG/MAG flux-cored wire > 500 kg/year<br>- TIG<br>- Rutile electrodes > 500 kg/year<br>- Basic electrodes > 500 kg/year<br>The filter is automatically cleaned with the help of a compressed air shower (the RoboClean© system). The unit contains a Differential pressure switch that activates the cleaning mechanism when the resistance of the filter becomes too high. The captured particles are blown off the filter by the compressed air shower and then fall into a removable container.<br>A control box CB(-WCS) is required to control the unit.<br>A mounting bracket is included for installation.<br>Weight of the unit is 85 kg. The unit is on both sides with an inlet and outlet Ø160 mm. The device requires a Compressed air connection of 4-5 bar (60 NL/min.). The compressed air must be dry and oil-free. |
| Oc-1 Me-41/42 | |
| 6475-1011 | |
| 6900-1011 | FILTER CARTRIDGE |
| Oc-2 Me-41/42 | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*