Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Pneumatic valve

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Pneumatic valve Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Pneumatic valve Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Typ 3351 DN 25 PN 16	Standard: DIN; Nominal size: DN 25; Nominal pressure: PN 16; Housing material: EN-GJL-250; Housing connection: flanges; Housing connection type: B DIN EN 1092; Direction of flow: Direction of flow on both sides (FTO calculation); Flow coefficient Cv: 16; Flow coefficient Kvs: 14; Leakage class: VI; Sealing edge cone: soft sealing glass ball reinforced PTFE; Cone material: 1.4404; Seat material: 1.4006 + QT; Seat sealing edge: metallic; Stroke: 8 mm; Upper valve part: Standard (STD); Housing seal material: graphite sealing ring with metallic carrier 304; Pack: PTFE graphite; Pack Design: Standard; Packing spring material: 1.4310; Safety position: closing; Drive area: 60 cm^2; Spring Package: For Standard Differential Pressure; Membrane material: NBR; Pneumatic drive Connection: G1 / 4; Upper part material: GJL-250; Safety position for drive: closing; Characteristic curve: open / close; Seat bore: 24; Plug stem material: 1.4401 / 1.4404; Material no .: 1776439 84818059 FR
Typ 3351 DN 15 PN 16	On / off valve Standard: DIN; Nominal size: DN 15; Nominal pressure: PN 16; Housing material: EN-GJL-250; Housing connection: flanges; Housing connection type: B DIN EN 1092; Direction of flow: Direction of flow on both sides (FTO calculation); Flow coefficient Cv: 7.5; Flow coefficient Kvs: 6.3; Leakage class: VI; Sealing edge cone: soft sealing glass ball reinforced PTFE; Cone material: 1.4404; Seat material: 1.4006 + QT; Seat sealing edge: metallic; Stroke: 8 mm; Upper valve part: Standard (STD); Housing seal material: graphite sealing ring with metallic carrier 304; Pack: PTFE graphite; Pack Design: Standard; Packing spring material: 1.4310; Safety position: closing; Drive area: 60 cm^2; Spring Package: For Standard Differential Pressure; Membrane material: NBR; Pneumatic drive Connection: G1 / 4; Upper part material: GJL-250; Safety position for drive: closing; Characteristic curve: open / close;

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Seat bore: 24; Plug stem material: 1.4401 / 1.4404; Material no .: 1779017

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.