

## Pomtava

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Pomtava** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Pomtava T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



| ¼r¼n                                       | A¼ıklama  |
|--|---|
| <a href="#">1610-1-1/A/0.6/S/KA/12/14</a>  | Stainless steel body pump 0.6 cc / rev Standard play, direction of rotation clockwise Combined shaft seal KA Drive shaft 12 mm, connection G1 / 4 "       |
| <a href="#">3610-3-1/A/10/J/T2</a>         |   |
| <a href="#">BL20-1895</a>                  |   |
| <a href="#">91664-15</a>                   |   |
| <a href="#">Pump 11091</a>                 |   |
| <a href="#">11091/A/0.3/S/Var.B/12/14</a>  | Stainless steel body pump 0.3cc/rev Direction of rotation right, shaft 12mm Standard clearance with PTFE stuffing boxes Shaft seal, inlet/outlet top      |
| <a href="#">11091/AZ/0.6/S/Var.B/12/14</a> | Stainless steel body pump 0.6cc/rev Direction of rotation right/left, shaft 12mm Standard clearance with PTFE stuffing boxes Shaft seal, inlet/outlet top |
| <a href="#">11091/AZ/4.5/S/Var.B/12/14</a> | Stainless steel body pump 4.5cc/U Direction of rotation left/right, shaft 12mm Standard clearance with PTFE stuffing boxes Shaft seal, inlet/outlet top   |

|  |  |
|--|--|
| <a href="#">BL-25-1685</a>                             |  |
| <a href="#">2610-1-1/A/3.0/S/KA/12</a>                 |  |
| <a href="#">P4003-A-S-2-N-I108-O86-120-14-R-5</a>      |  |
| <a href="#">3301354</a>                                |  |
| <a href="#">Bn 806</a>                                 |  |
| <a href="#">3301154-30-F-4</a>                         |  |
| <a href="#">116580-30-2</a>                            |  |
| <a href="#">16811-30-2</a>                             |  |
| <a href="#">BI-17-0922</a>                             |  |
| <a href="#">Ptmix-1</a>                                |  |
| <a href="#">1610-1-1/A/0.3/F/T2/Ka/12/14</a>           | viscosity:0-2 cp, working speed:20-100 rpm, process temperature:70-85°C  |
| <a href="#">18140081</a>                               |  |
| <a href="#">44889</a>                                  |  |
| <a href="#">12-00-44-0410-C-4</a>                      |  |
| <a href="#">11183/A/1.2/Var.A/12/14/Hzl, 98-116-16</a> | viscosity:60.000-130.000 cp, process temperature:70-85 °C, working speed:20-100 rpm  |
| <a href="#">11091/A/1.2/S/Var.B/10/14</a>              | Stainless Steel Body Pump 1.2cc / U Turning right, shaft 10mm Standard clearance with PTFE stuffing box Shaft seal, inlet / outlet above |
| <a href="#">A2135</a>                                  |  |
| <a href="#">P4003-A-S-4-R-I108-O86-120-14-L-5</a>      |  |