

Prosoft Technology

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Prosoft Technology Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Prosoft Technology Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
MVI56E-MNETC	
PLX31-EIP-PND	EtherNet/IP to PROFINET Device Gateway
5102-DFS3-DFM	
MVI56E-MCM	
MVI56-PDPMV1	
MVI69-ADM	
MVI69E-MBS	
MVI69-MCM	
A-J1939R	SAE J1939 Router Module
5105-MCM-PDP	MODBUS MASTER/SLAVE TO PROFIBUS DP SLAVE GATEWAY
PLX32-MBTCP-PND	Modbus TCP/IP Client/Server to PROFINET Device Gateway for dual subnets
plx32-eip-pnd	
PLX32-EIP-PND-	Ethernet/IP to PROFINET Device Gateway for Dual Subnets

PLX31-EIP-MBS	Ethernet/IP to Serial Modbus Gateway
RLX2-IHNF-A	802.11abgn Fast Industrial Hotspot , FCC model
A2504S3-O	4 dBi Omni RP-SMA MIMO antenna with 15 foot pigtail 2.4/5GHz
PLX31-EIP-MBS	Ethernet/IP to Serial Modbus Gateway
RLX2-IHNF-E	802.11abgn Fast Industrial Hotspot , Version for countries following CE type approval rules
A2506N3-O	6dBi Omni N-Jack Single MIMO antenna with 3 foot pigtail 2.4/5GHz
C19M10-80-002	2' LMR® 195 RA RP-SMA --> N BH jack cable
NSY-1000	C60M40-40-100 100' LMR® 600 N Plug --> N plug cable
C19M10-40-010	10' LMR 195 RA RP-SMA --> N plug cable
RLX-WPK001	RF Connector Weather proofing kit
SAE J1939 Router Module	
PLX32-EIP-PND	EtherNet/IP to PROFINET Device Gateway for Dual Subnets
MVI56-104S	Modbus Master/Slave Communication Module
MVI56E-MNET	Modbus TCP/IP Enhanced Communication Module
Ethernet switch	32 ports Ethernet Switch (Layer 2 Managed, 30 ports for Cat 6+ 2 ports fro FO) (Note-3)with SFP module
TCO/IP to IEC 60870-5-104 Gateway	Model no. PLX32-MBTCP-104
RLX2-IHNF-E	802.11abgn Fast Industrial Hotspot , Version for countries following CE type approval rules
MVI 94-MCM	It will be Modbus master/slave, will work with 12-24 VDC supply, will work at 0-55 C° temperature, will work between 5-95% humidity, will have a LED indicator showing the operating status, configuration serial port (PRT1); Mini-DIN, RS-232, will support hardware handshaking features, application serial port (PRT2); Mini-DIN, RS-232/422/485 jumper selectable, will support 500V optical isolation from backplane features, dimensions H x W x D: 9.4 cm x 9.4cm x 6.9 cm
MV194	MCMREVB01REVB02 INRAX-MVI94MCM INRAX-MVI94-REV-B03 12-24VDC
PLX51-HART-4I	Prosoft, 4 Channel HART Analogue Input to Ethernet Gateway
PLX82-MNET-61850	Modbus TCP/IP to IEC 61850 (Client) - 2 Port
RLX2-IHNF	For our mobile robot project, which will operate within a 40-meter by 15-meter area, we need Profisafe Wi-Fi AP and client products to transmit communication wirelessly.
ILX56-PND	PROFINET Device for ControlLogix
MVI56E-MNET	Modbus TCP/IP Master/Slave Enhanced Communication Module