Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Pyropress

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Pyropress Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Pyropress Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
HVAC LP Switch – 50 Ba	
HVAC HP Switch – 700 Bar	
HVAC HPC units – 700 Ba	
HVAC Temperature Sensor	
HVAC Safety Relief Valve (28 Bar)	
HVAC Solenoid Valve	
Dual Manometer(Pressure-0 to 200pa)	and Temperature Sensors(0-100deg C)
DF62SA/2G01SB1/MB	Ordering code : DF62SA/2G01SB1/MB Construction materials : Switchcase - 316 st steel : Wetted parts - 316 st. steel with Viton diaphragm. Mounting : Via fully interchangeable Guardian mounting bracket Adjustment range : 0.15 – 1.15 bar Setting A & B : 0.4 Bar Falling Deadband : < 0.25 Bar Max. working pressure : 28 bar equalised / 14 bar one sided Process connection : 2 x ¼" BSP female Electrical connection : M20 x 1.5 ISO Microswitch : 2 x SPDT, rating 5A @ 30 Vdc / 5A @ 240 Vac ind. Ingress protection : IP66/IP67
Test/Calibration Certificate	
Certificate of Conformity	
PF61AB/2W101/S1XB	Construction : Switchcase - Black anodised aluminium alloy. : Pressure housing - 316 stainless steel. : Element - Viton diaphragm Mounting : Surface via two through case fixing holes. Range : 6 - 18 Bar Setting : Mid-Range Rising unless otherwise advised Max. working pressure : 50 Bar

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Process connection : ¼" BSP female Electrical connection : M20 X 1.5 ISO Microswitch : 1 x SPDT, rated 5A @ 250 Vac / 5A @ 30 Vdc Inductive ATEX/IECEx certification : II 2G Ex db IIC T6....T5 Gb (Tamb -50 to +75°C T6 / -50°C to +90°C T5)
P1201/A210n15/Ss1x	GUARDIAN PRESSURE SWITCH 24BAR 20-180PSI -50-90C
P2101/A210n21/Ss1x	PRESSURE SWITCH 10-90PSI 1A 24VDC IP66 GUARDIAN
Pf263s7b/B_31f22c/67s_Aa	
S618/32fmo/24d	
P210m/A210n21/Ss1x	PRESSURE SWITCH 40BAR 10-90PSI -50-90C
S610 Replaced By S610/25fmo/24dc-00088	
Te172a3u/075mt/Sb1dc	PRESSURE SWITCH
S 60 Obsolete Replacement S610	
P2303/Bg31n22/Ss3x	PRESSURE SWITCH 700BAR 1200-1800PSI -20-150C
S610/25fmo/24dc-00088	
P230m/B131n22/Ss4x	PRESSURE SWITCH 700BAR 70-370PSI -20-150C
P210m/B210n15/Ss1x	PRESSURE SWITCH 50BAR 20-180PSI -20-150C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.