

Rader Vogel

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Rader Vogel Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rader Vogel Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
178 A/250/080/2/45 H7	A:-267960-283359-285566
5720011500	174/80/035/035/20 VULKOLLAN roller Outer Ø 80.0 mm Width 35.0mm Hub length 35.0 mm Clamping length 35.0 mm Bearing type deep groove ball bearing 6204-2RS Bearing inner Ø 20.0 mm Shore hardness A 93 Material group rim steel Load capacity 250 kg
5720011500	174/80/035/035/20 VULKOLLAN Laufrolle Outer Ø 80.0 mm Width 35.0mm Hub length 35.0 mm Clamping length 35.0 mm Bearing type deep groove ball bearing 6204-2RS Bearing inner Ø 20.0 mm Shore hardness A 93 Material group rim steel Load capacity 250 kg
5750370031	178/160/050/5/30 VULKOLLAN Rad Outer Ø 160.0 mm Width 50.0mm Hub length 50.0 mm Clamping length 50.0 mm Bearing type deep groove ball bearing 6006-2RS Bearing inner Ø 30.0 mm Shore hardness A 93 Silicone treatment silicone-free Material group rim cast Load capacity 730 kg
	178/180/050/5/25 VULKOLLAN Rad Technical characteristics Outer Ø 180.0 mm Width 50.0mm Hub length 60.0 mm

5750405005	Clamping length 60.0 mm Bearing type deep groove ball bearing 6205-2RS Bearing inner Ø 25.0 mm Shore hardness A 93 Material group rim cast Surface treatment painted (light gray RAL 7035) Load capacity 790 kg
5715171363	173/200/070/5/35 VULKOLLAN Rad Technical characteristics Outer Ø 200.0 mm Width 70.0mm Hub length 70.0 mm Clamping length 70.0 mm Bearing type deep groove ball bearing 6307-2RS Bearing inner Ø 35.0 mm Shore hardness A 95 Silicone treatment silicone-free Material group rim steel Load capacity 1340 kg
178/100/040/5/25	255331 / (2D) COUNTER WEIGHT WHEEL / VULKOLLAN, 5750.0650.43, EXTERNAL CAP:100MM, EN:40MM, IC CAP:25MM, VULKOLLAN-WHEEL LOAD CAPACITY:360KG, 93 SHORE
5752630501	78 A/300/080/2/50 H7 VULKOLLAN wheel Outer diameter 300.0 mm Width 80.0 mm Hub length 80.0 mm Bore type through hole with groove Bore diameter 50.0 mm Fit through hole H7 Groove width 14.0 mm (groove according to DIN 6885) Shore hardness A 93 Silicone treatment silicone-free Material group rim cast iron Load capacity 2200 kg
5710539100	172/406/170/342/290 H7 VULKOLLAN Rad Technical characteristics Outer diameter 406.0 mm Width 170.0 mm Hole type center hole with connection holes Hole diameter 250.0 mm Fit through hole + 0.2 Number of connection holes 15 Connection hole diameter 13.0 mm Pitch circle diameter 270.0 mm Shore hardness A 93 Material group rim cast iron Load capacity 6330 kg
173 A/200/050/2/35 H7	TURN TABLE DRIVE WHEEL / VULKOLLAN, ARTICLE NO:5715.1629.51, INNER CAP:35MM, OUTER CAP:200MM, WIDTH:50MM, KEYWAY, 2000 KG CARRYING CAPACITY, FOR TT1 AND TT2 EQUIPMENT
5715040200	173/060/020/5/20 VULKOLLAN bike outer diameter 60.0 mm width 20.0 mm hub length 20.0 mm clamping length 12.0 mm Bearing type deep groove ball bearing 6004-2RS bearing inner diameter 20.0 mm Shore hardness A 93 material group rim steel load capacity 110 kg
5715010500	173/040/020/5/10 VULKOLLAN bike outer diameter 40.0 mm width 20.0 mm hub length 20.0 mm clamping length 8.0 mm Bearing type deep groove ball bearing 6000-ZZ bearing inner diameter 10.0 mm Shore hardness A 93 material group rim steel load capacity 70 kg
178/180/050/5/25 / 1	
178/200/076/5/35	
173/050/018/5/15	
0029902329	
52041025	
9815054219	

[Tmp5751731000](#)