

Raoul Lenoir

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Raoul Lenoir Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Raoul Lenoir Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
CIRCULAR LIFTING MAGNET	ITEM 1 CIRCULAR LIFTING MAGNET Diameter : 1 500 mm Weight : 2 500 mm Protection : IP 55 Power : 10 000 Watts at 15 C Voltage : 220 VDC Duty cycle 60 % (10 Mn Cycle) Ribbed foundry frame made of high magnetic permeability cast steel Wear plate non magnetic manganese steel Winding out of aluminium wire conducting material A fill in resin blocking and insulating the coil in the frame with dielectric property External reinforced connecting box Chain with three common suspension ring Lifting capacity kg Slab : 19000 Turning Density 0.2 1T/M3 : 330 Light scrap : Density 1 3 T/M3 :630 Cast iron Density 3 4.5 T/M3 : 1100 Ball : 6500
ALSCH/CC1000	1 FEEDING, COMMAND & CONTROL DEVICES FROM OUR MODEL General features : Cabinet dimension : L1200 x H1200 x D400 mm Painting : RAL 7035 Tension 3 x 400 VAC , 50 Hz Working rate 100 % One main fuse switch Transformer with separate winding (supplied with box) with primary tension variation + 5% Recifier with diode bridge, inverted voltage 1200 V with RC circuit One socle with fuses HPC type protector ☐ Inverted supply unit magnetization and unmagnetization

Ürün	Açıklama
	including : One magnetizat ion relay Discharging resistance box (provide for external use with roof and lateral side) Protection devices : fuses, diode...protection are used to avoid short cut, overload, fuses in the DC output Relays supplied are wired on terminal blocks and with ide ntified cores.
1 BACKUP SECURITY SYSTEM BB/CC1000	Included : - 1 Electronic charger included in our control box TRL 12 - Automatic released when the charging cycle is completed - Protection class IP65 - Casing acidproof - Lighting and audio alarm when the batteries power is required Please note that the battery box has to be ventilated or air cooled Nota : These equipments will be supplied by us : 1) Industrical and Maintenance free battery elements for 20 mintues autonomy for 220 VDC operation voltage 2) Battery box Mounting, adapting, setting up and other accessories at your expenses or supplied with extra cost.
1 SET HEAVY DUTY CONNECTORS	- Spring mark LEGRAND - Femelle and male - Capacity : 16 000 W - Voltage : 220 VDC
CABLE REELS	- Spring mark LEGRAND (Mechanical motorisation) - Trade mark DELACHAUX - Active cable length 25 m
Belt For Ov 630/100p	
Ovap 1000/35	
Adi/90m	
10903001	
05163f 17736	We need the Magnetic Sticks (1100mm length 250mm diameter) PLEASE SEE ATTACHED PHOTO
A0903099	
Belt For Ov h790/80p	