

Raziol

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Raziol Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Raziol Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
1012100150	RB F 0150 Roller lubricator standard felt ø 60 mm Low-wear felt rollers ø60 mm. The felt rollers are supplied with oil from the inside out through fixed hollow axles, Roll adjustment by tension springs, Min.recommended belt width: approx. 80 mm max.greasing width: 150 mm, Permissible oil viscosity (40 ° C): approx. 150 mm ² / s With oil connection hoses and optical Feed control (dropper chambers), Model TK 2.
1080040004	
1040143222	D 040 ST SSO 2.5 bar upright "NC contact" 40 l container upright completely assembled with: ----- - "NC" float switch with device socket - Compressed air fitting up to 2.5 bar
1044111300	Oil distributor block VBMV-2 with two magnetic valves (but without throttles) on mounting plate for separate pressure reservoir. Complete with 2 solenoid coils 24V DC, oil connection for hose 10x3.5 and screw connections for hose PU-8/6, incl. hose NBR / PVC 10x3.5 (Aø17 / lø10), assembled to 5 m
3009532111	THROTTLE COMPLETE FOR OIL DISTRIBUTION BLOCKS VBMV AND VBMV-02 Thread 1/8 "
1042110012	Dos MST 010D-SS VBMV-2 opener Dosing system for customer-side control Consisting of: 1 x pressure reservoir with 10 L capacity

Ürün	Açıklama
	and compressed air fitting up to 2.5 bar 1 x float switch, switching type "opener" 1 x filter 1/4" with ball valve 1 x oil distribution block VBMV-2, NW 1.0 mm with two Solenoid (24V DC) and two throttle valves. FOR WALL MOUNTING
4043000047	Cable 05.0 m float switch for EBAD 4000 KL with appliance socket incl. LED and quenching diode
4043000050	Cable 05.0 m for valve 5/2-1/4 to EBAD4000 KL appliance socket incl. LED quenching diode
1012180300	RB 300 FK-P SW Roller oiler Kipp Pneumatic felt ø 60 with the following properties: - Oil mist-free lubricant application through low-wear felt rollers - The oil supply to the felt rollers is done from the inside by fixed hollow axles. - The adjustment of the upper roller to the material is done by Pneumatic cylinder, stroke height approx. 10 mm, with swivel device - Roller set change without tools - Oil connection on both sides of the upper and lower roller Technical data: - greasing rollers Ø 60 mm - Maximum recommended material thickness: approx. 5.0 mm - Maximum recommended oil viscosity (40°C): approx. 150 mm ² /s - The oil must not be resinous and must not contain any solids. Dimensions: - Length in DLR: approx. 100 mm - Width across the DLR: approx. 555 mm (incl. space for oil connection) - Passline: 80 mm The scope of delivery of the roller oiler includes oil connection hoses with optical inflow control (dropper chambers TK4) including four quick-connector sockets. With built-in roller change kit: RB 300 FK-P SW. Roller oiler Kipp Pneumatic felt Ø 60 with the following properties: Oil mist-free lubricant application through low-wear felt rollers. The oil supply to the felt rollers is done from the inside by fixed hollow axles. The adjustment of the upper roller to the material is done by Pneumatic cylinder, stroke height approx. 10 mm, with swivel device. Roller set change without tools. Oil connection on both sides of the upper and lower roller. Technical data: greasing rollers Ø 60 mm, Maximum recommended material thickness: approx. 5.0 mm, Maximum recommended oil viscosity (40°C): approx. 150 mm ² /s. The oil must not be resinous and must not contain any solids. Dimensions: Length in DLR: approx. 100 mm, Width across the DLR: approx. 555 mm (incl. space for oil

Ürün	Açıklama
	connection). Passline: 80 mm. The scope of delivery of the roller oiler includes oil connection hoses with optical inflow control (dropper chambers TK4) including four quick-connector sockets. With built-in roller change kit:
1018482307	CHANGE KIT 0300 / 0300 SW Low-wear felt rollers, ø 60 mm for roller belt oilers of type RB FK SW 0300/ RB FK P SW 0300/ RB PF SW 0300 consisting of: Axles, rollers, bearings, felt rollers, end plates, screw connections and quick-release connectors Technical data: Felt rollers Ø 60 mm Maximum greasing width: 300 mm Minimum recommended greasing width: approx. 200 mm Maximum recommended oil viscosity (40°C): approx. 150 mm ² /s The oil must not gum up and must not contain any solids.
1080040004-	TK 4 2 dripper chambers with PVC-8/5 tubing Optical feed control for connection to roller belt oilers with a Grease application width >300 mm consisting of: - 2 drip chambers - 2 x 1.5 m PVC-8/5 hoses and 4 x 1.5 m PVC-8/5 hoses - 2 Y-connectors
1040940219	Funnel with check valve for manual filling of pressure storage tanks Consisting of: 1 x check valve 1" with connection fittings 1 x funnel Ø 160 mm, capacity 1.2 L For mounting on pressure tanks Funnel with check valve for manual filling of pressure storage tanks. Consisting of: 1 x check valve 1" with connection fittings, 1 x funnel Ø 160 mm, capacity 1.2 L. For mounting on pressure tanks
3100016743	Lid for funnel ø160mm with chain Powder coated RAL 1007 Lid for funnel ø160mm with chain. Powder coated RAL 1007
1042110018	Dos MST 010D-SS VBMV-2 opener in stand Dosing system for customer-side control Consisting of: 1 x pressure reservoir with 10 L capacity and compressed air fitting up to 2.5 bar 1 x float switch, switching type "opener" 1 x filter 1/4" with ball valve 1 x oil distribution block VBMV-2, NW 1.0 mm with two Solenoid (24V DC) and two throttle valves. The unit is in a stand (H 705 mm x W 550 mm x D 255 mm)

Ürün	Açıklama
	assembled and ready for connection. Oiling System
3009510422	Pressure regulator G1/4 0.1-3 bar lockable lockable with handwheel Pressure regulator G1/4 0.1-3 bar lockable with handwheel
CRF 14 TEO	
1045911111	HST hand lever up to 2.5 bar HIFT CONTROL HAND-OPERATED For starting and stopping the upper grease roller (e.g. when threading the tape) With pressure reducer and manometer up to 2.5 bar and connections for PU-AIR hose 4/2.3
3073141320	
3073141326	
3073141321	
09539254	
80720005	
3073141324	
1080720017	
3073141317	
3073141325	
Ebad3000	
Rb Pf-Sw 1200	981133 Rollendurchmesser: 40 mm Wellenlänge: 1200 mm
3009165500	
Kit-2-11/13-16	
1080720005	
3073141318	
3073141327	

Ürün	Açıklama
Lubricate Machine	800mm long 6mm thick
3001080400	
3073141323	
1080720017(Ex, 80720005)	