

Re S.P.A.

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Re S.P.A. Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Re S.P.A. T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
01A02008	Brake pad for Combiflex brake Type CX.01A67016-R15.AR3 with patented noise filter Coefficient of friction : 0.35 (standard)
CF.085.0100.40.2RS mA EVO	07.06A08011.00 Load cell as flange version Output : 4-20mV Control range : 0 - 100 kg Protection class: IP 53 !!!!! WITHOUT plug !!!! CODE: 6A08036
07.04B03009.00	Web edge control with ultrasonic sensor Type WG.0255.0160.0200.050.W-LIGO microprocessor controlled Complete with 1* Control Rack 2* pulleys 1* control unit type W-LIGO 1* ultrasonic sensor type SU.m-25 V2 1* sensor holder 1* cable set Technical specifications : Temperature : 0 - 50.00 °C Voltage : 24 Vdc Web tension max. : 150.00 N Adjustment range : +/- 10.0 mm Accuracy : +/- 0.10mm Roller length : 160 mm Working width max. : 100 mm Roller distance : 200 mm Roller diameter : ø50 mm Control roller: aluminum (optionally available with cork or rubber coating)
	Web edge control with ultrasonic sensor Type WG.0255.0200.0200.050.W-LIGO microprocessor controlled Complete with 1* Control Rack 2* pulleys 1* control unit

07.04B03009.00	type W-LIGO 1* ultrasonic sensor type SU.m-25 V2 1* sensor holder 1* cable set Technical specifications : Temperature : 0 - 50.00 °C Voltage : 24 Vdc Web tension max. : 150.00 N Adjustment range : +/- 10.0 mm Accuracy : +/- 0.10mm Roller length : 200 mm Working width max. : 140 mm Roller distance : 200 mm Roller diameter : ø50 mm Control roller: aluminum (optionally available with cork or rubber coating)
07.04B03009.00	Web edge control with ultrasonic sensor Type WG.0255.0400.0300.050.W-LIGO microprocessor controlled Complete with 1* Control Rack 2* pulleys 1* control unit type W-LIGO 1* ultrasonic sensor type SU.m-25 V2 1* sensor holder 1* cable set Technical specifications : Temperature : 0 - 50.00 °C Voltage : 24 Vdc Web tension max. : 150.00 N Adjustment range : +/- 10.0 mm Accuracy : +/- 0.10mm Roller length : 400 mm Working width max. : 340 mm Roller distance : 300 mm Roller diameter : ø50 mm Control roller: aluminum (optionally available with cork or rubber coating)
06.04253004.00	Brake caliper with brake pads Type CX.4253004 without flow brake valve and compressed air distributor Braking power: 100% Identification color: black
01D38011	
06.01A14023.00	Fan housing HP3 with fan for CX.250 Type RE.CX.01A14077-HP3 (V2) Voltage: 24 VDC Power: 50W Current consumption: 2.5 A Complete with fan housing HP3
06.01A67016.15	Brake pad for Combiflex brake Type CX.01A67016-R15.AR3 with patented noise filter Friction coefficient: 0.35 (standard)
06.42530118.00	Brake caliper with brake pad and mounting flange Type CX.42530118 Version as standard brake caliper Identification color: black
06.01D38011.00	Brake caliper, pneumatic Type CX NANO (12.7 mm thick) including mounting bracket, without through-valve or plug connection, max. torque 40 Nm (at 6 bar and ø 200 mm brake disc) max. air pressure = 6 bar
01A67016 PAD R15	BRAKE PAD
RE 4030024 Brake CX 300.8 220V	
Cx 250	
Ck.125.150.25 Acc	
11456. 1209 999-802-0206	
R15 999-800-0322	
Re Druckmessdose Cf.85.200.40.2rs	
Mega N090.01a	
Cf.85.15.40.2rs Ma Evo	
999-801-5105	

999-802-0208
TI.01/SI.3
B.651
Cf.120.25.52.2rs
999-800-0136
999-802-0031
SI3-Replaced By TI.01
999-800-0134
Mod. T-One Sn 00166.0906
999-802-1204
999-800-0106
Re Druckmessdose Ck.175.300.35
999-802-0212
999-802-0226
Re Druckmessdose Ck.175.300.35 All
Re-S-P-A-C650ralte-Ausf3;Hrungneue-Ausf3;Hrung-C651r-Istanbul-Turkiye
999-800-0113
10073065
999-802-0056
999-800-0307
TI.01
C.651.R
Cf.85.100.40.2rs
999-800-0135
999-802-1005
Cf.85.50.40.2rs
999-802-0247
999-800-0114
999-802-1021