Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Redlion

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Redlion Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Redlion Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
PAXI0030	Industrial tachometer / preset counter Measurement input: NPN, PNP sensors, CMOS, TTL, HTL, Namur Number of digits: 6 digits Digits: LED 7-segment red Digit height: 14 mm Case size: 92 x 45 mm Supply voltage: 11-36 VDC Protection class: IP65 on the front Housing dimensions: W 97 x H 50 x D 105 mm Operation: push button Connection: fixed terminal strip
PAXCDS20	Pluggable relay output card 4x changeover for Digital display PAX and digital large display LPAX
PAXCDL10	Pluggable analog output card for PAX digital display and large digital display LPAX 0 to 20 mA, 4 to 20 mA or 0 to 10 VDC Country of manufacture: USA Weight: approx 10g Customs tariff number: 9032.90.6080
RAM-6021	70404280 Industrial router Specifications: - WAN-to-LAN or LAN-to-WAN connectivity - built-in security and routing functions protect against unwanted intrusion - IPsec and SSL VPN tunnels - Stateful firewall - Port forwarding - packet filtering - Access Control List (ACL) - flexible all-in-one platform reduces the System complexity

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- NAT support for one-to-one or one-to-one Many translations - DHCP server and DHCP relay - Event engine for triggering I / O or email Notifications - SNMP v1, v2, v3, v2, v3 - Dynamic DNS - Modbus TCP / IP / ASCII / RTU - DNP3 slave - Syslog - Integrated traffic recording for an improved Troubleshooting - RAMQTT client for IIoT cloud connectivity Ethernet interface (10/100 auto-sensing): - 5x RJ-45 plugs Mechanics: - Dimensions: 120 x 96 x 51 mm - Weight: 544 g Redundant power consumption: - 4-pole screw terminal - Laterally mounted 2.5 mm barrel connector - Supply voltage 8-30 VDC (12 VDC nominal) Environmental conditions: - Operating temperature: -40 ° to + 70 ° C - Humidity: 5 to 95% non-condensing - Shock: IEC60068-2-2-27 - Vibration: IEC60068-2-6 Certifications: FCC, UL, CE, CE Product safety: Ex areas: Class I, Section 2, Groups A, B, C, D, ISA 12.12.01.01
IAMS0010	Universal input, process, mA DC, VDC, TC, 100 (RTD, potentiometer and linear Resistance) - Universal power supply, 21.6 to 253 VAC / 19.2 to 300 VDC - 3-way isolation (power / signal / output) - Select switching point values and / or Analog output models - Programming / display module (PGMMOD) - Programming in seven different Languages available
PAXCDS20	Pluggable relay output card 4x changeover for PAX digital display and large digital display LPAX Weight: 100g Customs tariff number: 9032.90.6080 USA
PAXP0010	Industrial digital display / process signal display

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Measuring input: standard signals 0/4 ... 20 mA, 0 ... 10 VDC Measuring rate: 20 measurements / sec., A / D converter with 16 bit resolution User inputs: 3, programmable Number of digits: 5 digits Digits: LED 7-segment red Digit height: 14 mm Case size: 96 x 48 mm Supply voltage: 11 ... 36 VDC Degree of protection: IP65 on the front Housing dimensions: 96 x 48 x 104 mm Operation: push button Connection: fixed terminal strip Country of manufacture: US Weight: 295g Customs tariff number: 9030.3300.80
DA30D-0F-000000-000	111530-336 Data Station DA30D - data management system for high-end applications, Multi-protocol converter with data logger, Advertising server, virtual HMI, for remote monitoring and control - HMI resolution 480x272, 800x480, 1280x720 px. - FTP server and synchronization for File transfer - OPC server for easy SCADA connectivity using OPCWorx - Synchronizes data logs with FTP and Microsoft SQL server - Alerting via SMS and email - MQTT connectors accelerate IIoT projects with simple point-and-click function - Embedded OPC UA server functionality - Interfaces: 2x RS232, 1x RS485, 1x 10/100 Base-T Ethernet port, 1x expansion slot for further interfaces, 1x USB 1.1 (type B), 1x USB host port - Internal memory: SD card slot, 4 MB flash memory, 8 MB SDRAM - Supply voltage: 10-30 VDC - Configuration via free Windows compatible Crimson software - Housing: plastic - Mounting: DIN rail - Dimensions: 31.8 x 127.7 x 101.4 mm - Degree of protection: IP40 - Weight: approx. 193 g - Operating temperature: -10 ° C ... + 50 ° C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Certifications: CE, UL - Customs tariff number: 8537.10.9090 - Country of origin: USA
708FXE2-ST-15	
NT328G-20SFP-AC1	
IFMR0036	Speed monitor 1 input / 1 output, Inputs: PNP / NPN, 2- or 3-wire, Relay contact, max. ± 90V, max. 25 kHz Output: changeover relay 5A at 240 VAC or 28 VDC Supply voltage: 9-32 VDC Setting via DIP switch Working temperature: 0 to + 50 ° C Dimensions: 28 x 107 x 79 mm Approvals: UL, IECEE CB, IEC 61010-1, EN 61010-1
ILS23000	230 VAC Inductive Load Suppressor (model no: ILS2 part number: ILS23000)
SNUB part number: SNUB0000	R-C SNUBBER inductüve load suppressor (model no: SNUB part number: SNUB0000)
Model: PAXICDL10	LINER OUTPUT CARD
Model: PAXP0010	PROCESS INPUT METER, RED DISPLAY, DC POWERED, 4-20 MA , 11-36 V DC INPUT
Redlion	
LMPC0000	
RDL-3000 RadyoLink	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.