

## Rema Tip Top



Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Rema Tip Top** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Rema Tip Top T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">5952373</a>	
<a href="#">5952139</a>	
<a href="#">5954553</a>	
<a href="#">5952548</a>	115X6X22
<a href="#">FROG CLAMP, TRACTION POWER 1000 KG, FOR RUBBER BELT</a>	
<a href="#">STITCHER 4MM W/BALL BEARING PN - 595 1044</a>	
<a href="#">STITCHER 12MM W/BALL BEARING PN - 595 1123</a>	
<a href="#">STITCHER 45MM W/BALL BEARING PN - 595 1130</a>	
<a href="#">NEEDLE STITCHER 46MM PN -595 1154</a>	
<a href="#">STITCHER 45MM CORRUGATED PN -595 1051</a>	

<a href="#">Rema Tip Top</a>	
<a href="#">Rema Tip Top</a>	
<a href="#">Rema Tip Top</a>	
<a href="#">Rema Tip Top</a>	
<a href="#">Rema Tip Top</a>	
<a href="#">5126051</a>	PN DIAGONAL PLASTER BLUE 05 PU/10 pcs Alternative for 5126116
<a href="#">5126037</a>	PN DIAGONAL PLASTER BLUE 03 PU/10 pcs
<a href="#">5021159</a>	WHEEL 115 TL PREMIUM / 20pc.
<a href="#">4. DUBLEX TIRE VALVE 5 CM - LONG NUT TYPE</a>	
<a href="#">TIRE RIM ORIGINAL 10 MM (29.5 R25 - 26.5 R25)</a>	
<a href="#">65/CN</a>	10mm
<a href="#">5380031</a>	RUBBER COVER PLATE, unvulcanized 5x500x3300mm =10 pieces a 10kg
<a href="#">5380062</a>	GUMIDECKPLATTE, unvulkanisiert 1x500x17800mm =5 Stk a 10kg
<a href="#">5440283</a>	Intermediate rubber strips Stz NL, unvulcanized 2.5x8x7200mm 12 pieces a approx. 7200 mm long, ZWG strips
<a href="#">5722200</a>	Intermediate rubber strips STZ NL, unvulcanized
<a href="#">5021551</a>	RAD 155 TL PREMIUM / 5pc. Net Weight: 9,000KG The reference product from passenger cars to OTR/EM • Bimodal connection layer (manufactured in one piece) • Reinforcement Rayon Cord • Padding at cord end • universally applicable • indispensable when repairing forklift and OTR/EM tires • 5 years shelf life
<a href="#">5021654</a>	RAD 165 TL PREMIUM / 3pc Net Weight: 13.356KG PU 3 pcs The reference product from passenger cars to OTR/EM • Bimodal connection layer (manufactured in one piece) • Reinforcement Rayon Cord • Padding at cord end • universally applicable • indispensable when repairing forklift and OTR/EM tires • Can be stored for 5 years
<a href="#">5021506</a>	RAD 150 TL PREMIUM / 5pc The reference product from passenger cars to OTR/EM • Bimodal connection layer (manufactured in one piece) • Reinforcement Rayon Cord • Padding at cord end • universally applicable • indispensable when repairing forklift and OTR/EM tires • 5 years shelf life
<a href="#">5642896</a>	Protractor W FIX 5, cutting width 10-14 mm, PU/20 pcs.
<a href="#">5959560</a>	

<a href="#">5177402</a>	T2-CL cleaning rubber, 5 rolls of 3x18x3000mm, approx. 1kg
<a href="#">549 1630</a>	Remaline MP40.6(4) x 2000 x 10000mm The wear protection with built-in signal layer Execution Dimensions: 6(4) x 2000 x 10 000 mm Signal layer: 1 mm Weight: 6.80 kg/m <sup>2</sup> Net weight: 154 kilograms High-quality rubber lining material The wear protection with built-in signal layer Reliable protection against wear and build-up with integrated replacement indicator Black wear layer Orange signal layer Very wear-resistant, especially in wet applications Very elastic High self-cleaning effect Reduces noise and dust Easy and good bonding thanks to CN bonding layer Particularly suitable for hard-to-reach components, where checking the lining thickness using conventional methods is difficult – Lining of gutters, pipes, hydrocyclones, Flotation cells, tanks, e.g. in the sand and gravel industry – Sludge extraction – Flexilo and bunker linings – Linings for sticky materials Polymer base: NR Specific gravity: 1.05 g/cm <sup>3</sup> (DIN ISO 1629 / EN ISO 1183-1) Hardness: 44 Shore A (DIN ISO 7619-1) Color: Orange/Black*
<a href="#">EXPEL-30</a>	WATER RETAINING FILTER
<a href="#">5285497</a>	3X500X10000mm Double-Sided CN Layered Tape Joint Filler Rubber
<a href="#">5496517</a>	
<a href="#">Sc 4000</a>	
<a href="#">5629644</a>	
<a href="#">5253112</a>	
<a href="#">Remaclean 60/ 7022054</a>	
<a href="#">5302507 (1 Pack = 25 Pcs)</a>	
<a href="#">5959307</a>	
<a href="#">5620045</a>	
<a href="#">5251043</a>	
<a href="#">Remaclean Kwa</a>	
<a href="#">5253105</a>	
<a href="#">5492998</a>	
<a href="#">5494972</a>	
<a href="#">5496555</a>	
<a href="#">5380316</a>	
<a href="#">5159389</a>	
<a href="#">5709270</a>	

<a href="#">5620083</a>	
<a href="#">5381316</a>	
<a href="#">5302545 (1 Pack = 25 Pcs)</a>	
<a href="#">5496523</a>	
<a href="#">5253121</a>	
<a href="#">5380017</a>	
<a href="#">Pr304 Art No:5254112</a>	
<a href="#">5954656</a>	
<a href="#">5496530</a>	
<a href="#">5380000</a>	
<a href="#">5930515</a>	
<a href="#">Pr200 Art No:525 2406</a>	
<a href="#">5507630</a>	
<a href="#">5253160</a>	
<a href="#">Remaline 60</a>	
<a href="#">525 2029 , 5253160</a>	
<a href="#">5930649</a>	
<a href="#">Type:Remaline 65/Cn Ref.No:549 0062</a>	
<a href="#">Remaline 60/Cn</a>	10x2000x10000mm TARIFF : 40082190
<a href="#">5954508</a>	