Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Rembe

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Rembe Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rembe Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
0801158	
120-0000000534	
125-0000000090	
1304321	
1310232	
141-0000000021	
14800188	
15200535	
15202928	
15203851	
15205234	
15205235	
15205806	
15206108	
153-0000000167	
154-0000000979	
1605100	
161-0000000144	
16301985	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
16302395	
16302505	
164-0000000029	
164-1000000002	
164-1000000027	
164-1000000028	
16702376	
16702377	
16702496	
16703192	
16703563	
16704285	
18900374	
18900882	
18901067	
22100105	
229-0000000508	
229-0000000521	
33900253	
44100572	
44100724	
44101117	
44101342	
44101714	
BT-KUB-6	
BT-ODV-F-1,5	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
BT-SKODIPV-F-28	
C-LEVER® direct 50 SS	
EVA HE SS + PB	
EVA-CLD-SS-230-PB (224-0000000520)	
K3-100007125	
Q-Rohr-3 DN 400	
QVII-5 quench valve	Article no.: 23900178 Explosion decoupling device with patented compressed air storage and integrated Quick-closing solenoid valve, "fail-safe function" in the event of voltage or Compressed air interruption, power supply and activation by EXKOP control. Nominal width (DN): 125 mm Cuff: food grade Flange standard: DIN EN 1092-1:2013-04, type 11 Pressure stage: PN 10 (EN 1092-1) Flange: aluminum with stainless steel bushing Housing: aluminum Colour: RAL 1015 Max. flow rate: 30 m/s Max. process temperature: 80 °C Heating: no Minimum ambient temperature: 0 °C Max. ambient temperature: 60 °C Installation position: any Protection class: IP 65 Voltage supply: 24 V DC from EXKOP® II control Compressed air supply: 6 bar g Compressed air connection: 8 mm (Festo) Vacuum bypass: no Certification: ATEX 2014/34/EU Test standard: DIN EN 15089:2009 EU Type Examination Certificate: FSA 04 ATEX 1537 X
QVII-8 quench valve	Explosion decoupling device with patented compressed air storage and integrated Quick-closing solenoid valve, "fail-safe function" in the event of voltage or Compressed air interruption, power supply and activation by EXKOP control.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal width (DN): 200 mm Cuff: food grade Flange standard: DIN EN 1092-1:2013-04, type 11 Pressure stage: PN 10 (EN 1092-1) Flange: aluminum with stainless steel bushing Housing: aluminum Colour: RAL 1015 Max. flow rate: 30 m/s Max. process temperature: 80 °C Heating: no Minimum ambient temperature: 0 °C Max. ambient temperature: 60 °C Installation position: any Protection class: IP 65 Voltage supply: 24 V DC from EXKOP® II control Compressed air supply: 6 bar g Compressed air connection: 8 mm (Festo) Vacuum bypass: no Certification: ATEX 2014/34/EU Test standard: DIN EN 15089:2009 EU Type Examination Certificate: FSA 04 ATEX 1537 X
QVII-10 quench valve	Article no.: 23900245 Explosion decoupling device with patented compressed air storage and integrated Quick-closing solenoid valve, "fail-safe function" in the event of voltage or Compressed air interruption, power supply and activation by EXKOP control. Nominal width (DN): 250 mm Cuff: food grade Flange standard: DIN EN 1092-1:2013-04, type 11 Pressure stage: PN 10 (EN 1092-1) Flange: stainless steel Housing: S235JR Colour: RAL 1015 Max. flow rate: 30 m/s Max. process temperature: 80 °C Heating: no Minimum ambient temperature: 0 °C Max. ambient temperature: 60 °C Installation position: any Protection class: IP 65 Voltage supply: 24 V DC from EXKOP® II control Compressed air supply: 6 bar g Compressed air connection: 8 mm (Festo) Vacuum bypass: no Certification: ATEX 2014/34/EU Test standard: DIN EN 15089:2009 EU Type Examination Certificate: FSA 04 ATEX 1537 X

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
QVIII-16 Quench Valve	Article no.: 23900274 Explosion decoupling device with patented compressed air storage and integrated Quick-closing solenoid valve, "fail-safe function" in the event of voltage or Compressed air interruption, power supply and activation by EXKOP control. Nominal width (DN): 400 mm Cuff: food grade Flange standard: DIN EN 1092-1:2013-04, type 11 Pressure stage: PN 10 (EN 1092-1) Flange: S235JR with internal stainless steel angle ring Housing: S235JR Colour: RAL 1015 Max. flow rate: 30 m/s Max. process temperature: 120 °C Heating: no Minimum ambient temperature: 0 °C Max. ambient temperature: 60 °C Installation position: any Protection class: IP 65 Voltage supply: 24 V DC from EXKOP® II control Compressed air supply: 6 bar g Compressed air connection: 8 mm (Festo) Vacuum bypass: yes Customer connection: NW3/4" Certification: ATEX 2014/34/EU Test standard: DIN EN 15089:2009 EU Type Examination Certificate: FSA 15 ATEX 1659 X
IR Set FMX-R-13 L 2000	Article no.: 157-0000000562 consisting of: - 1x FMX-R-13 L flame detector - 1x terminal box CB-FMX-R - 1x connection cable for FMX-R (25 m) - 1x light guide FX 2000 with 3x 2000 mm - 3x mounting material for light guide FX
Welding flange FMX-R	Article no.: 157-0000000488 for flame detector FMX-R 13 Material: 1.4404 Dimensions: W30 x H40 x D31 mm Weight: 0.15kg
PBX-R Hygienic	Article no.: 153-0000000390 The pneumatic box consists of a compressed air maintenance unit and a 3/2 way Solenoid valve for providing the flushing air of the flame detector. Technical specifications:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Design: Hygienic design housing 1.4301 stainless steel Gasket: Silicone, FDA Guideline 21 compliant CFR 177.2600 Installation: Wall spacer, hygienic design Pneumatic connection: Festo type IQS for 8 mm hose Pneumatic air supply: compressed air min. 5 bar g, max. 10 bar g, filtered, oil-free and dust-free according to ISO 8573-1:2010 [2:2:2] Medium temperature: -5 to +50 °C Ambient temperature: -5 to +50 °C Degree of protection: IP 66 Type of protection for solenoid valve: Ex tc IIIC T115°C X Dc supply voltage Solenoid valve: 24V / DC Dimensions: 227x227x120mm Weight: 6kg
Line Shutdown	Article no.: 153-0000000409 with key switch (1x) for EXKOP® Express to extend an EXKOP® Express control, to switch off a single line independently and manually using a key switch Dimensions: 100x200mm Weight: 0.003kg Material: metal key
EXKOP® Express Multizone-8	Article no.: 157-0000000568 explosion protection center EXKOP® Express Multizone-8 consisting of: 8 tripping circuits for controlling protective devices 8 detector inputs 8 control inputs (revision, shutdown, etc.) 20 relay outputs (alarm, warning, fault, revision) Display: touch panel Degree of protection: IP 54 Dimensions: W600 x H800 x D300 mm Weight: 45kg Housing: Powder-coated steel housing wall mounting Colour: light grey, RAL 7035 Ambient temperature: +5 °C to +40 °C Input voltage: 195 - 253 VAC, 47/63 Hz Power: 380VA Emergency power supply: 2x 12V, 12 Ah Mains bridging time: 4 hours
safety valve	SK-EX-GO-VENT-SI, 610 x 1118, art.1503259
KLISKEGV-920x920	One-piece, flat rupture disc for dust and/or gas explosion relief; suitable for processes with little or no overpressure and vacuum

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Artikel-Nr.: 20900559 Nominal width: 920 mm Nominal length: 920 mm Relief area: 8,500 cm² Type of protection: overpressure Bursting pressure: 0.1 bar g Burst temperature: 22 °C Lower Burst Tolerance: 20% Upper Burst Tolerance: 20% Vacuum resistance: 500 mmWS Bursting part: 1.4016 Gasket process side: silicone Gasket FDA Approved: Yes Max. permitted operating temperature: 150 °C Operating Conditions: Non-pulsating process Outer dimension width: 1,000 mm Outer dimension length: 1,000 mm Signal generator: SK Cable material: PTFE Cable Length: 2m External insulation: insulation cassette Outer Insulation Thickness: 40mm Certification: ATEX 2014/34/EU Test standard: DIN EN 14797:2006 Testing organization: REMBE EU Type Examination Certificate: FSA 04 ATEX 1538 X
IKLIEGV-SASL-340x385	Ex-Go-Vent Artikel-Nr.: 20900574 One-piece, flat rupture disc for dust and/or gas explosion relief; suitable for processes with little or no overpressure and vacuum Nominal width: 340 mm Nominal length: 385 mm Relief area: 1,300 cm² Type of protection: overpressure Bursting pressure: 0.3 bar g Burst temperature: 80 °C Lower Burst Tolerance: 20% Upper Burst Tolerance: 20% Vacuum resistance: 1,500 mmWS Bursting part: 1.4301 or similar Gasket process side: silicone Gasket FDA Approved: Yes Max. permitted operating temperature: 150 °C Operating Conditions: Non-pulsating process diameter d. Holes: 13mm Number of holes: 16 Outer dimension width: 400 mm Outer dimension length: 445 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	External insulation: insulation cassette Outer Insulation Thickness: 40mm Certification: ATEX 2014/34/EU Test standard: DIN EN 14797:2006 Testing organization: REMBE EU Type Examination Certificate: FSA 04 ATEX 1538 X Customs tariff number: 73269098
BURSTING DISC DN300 0.5 BAR 230 C ATEX	
BURSTING DISC DN500 1.5 BAR 65 C ATEX	
BURSTING DISC DN600 1.5 BAR 65 C ATEX	
PRESSURE SAFETY VALVE DN300 280MBAR ATEX	
0901188_0045	1/2_20 UNF x 6 SPS, 400BAR AT 400°C, TORO_55 Nm, 303/ING, 802621
Bt-Kub-10 Protective Membrane Rembe Bt-Kub-10 Du250 Rsr 2,65 Mpa 78 G.C Ss316l	
Article No.: 15202428	
1210010 Membran (Bt-Odv-Hl-24)	
164-1000000002 Materialzeugnis	
Skedp-586x920 Artikel-Nr.: 18900374 Alternative	
15200533 Kubbt-Kub-1,5knickstab-Umkehr Berstscheibe	
Sb-S-1	
Bt – Sk 0 Dipv – 20	
Bt-Skkub-V-2	
K3-100007125 Dreiteil-Berstscheibebt-Iafskodv-Fl-20	
15205053	
224-0000000519 Eva-Cld-Ss-230	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Controller	
Type: Bt-Kub-6	
Bt-Skrodv-F-6	
164-0000000029 Materialzeugnis	
120-0000000015	
Skex-Go-Vent 600x600 Explosionsschutzplatte	
Ev-00-000050	
15203331	
164-0000000035 Materialzeugnis	
120-0000000008	
Eva-Cld-Ss-230	
164-0000000128	
Bt-Odv-F-8	
Bt-Star-Hl-1 Rembe Safety Membrane Bt-Star-Hl-1 Du25 Rsr 6.3 Mpa 30 G.C Ss316l	
44100416	
Tx/01-219-Bd-P Rupture Disc For Overpressure	
44100422	
164-0000000132 Technischer Pass	
15202631	
15202619	
22000128	
Bt-Odv-Fl24	
229-0000000521 Standard Roto-Bin-Dicator Rb-H-A-X1-4-A-A-0-A	
Bw-Dms-Konverter	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
164-1000000028 Zertifikatmaterialzeugnis	
16702376 Igig-Hl-Hp-Sh-28 Berstscheiben-Halter	
141-0000000021 Einteilige Explosionsscheibebt-Iafskegv-Fl 48	
Skodv30 Flache Sicherheitsmembran	
164-0000000126	
Bt-Kub-1,5 Rembe Safety Membrane Bt-Kub-1,5 Du40 Rsr 1,6 Mpa 96 G.C Ss316l	
44100423	
162-0000000055 Signalling Unit Bird	
15202622	
22100090	
Kub Clean	
169-0000000367	
??-Kub-1 Dn 25 Pn 40 Sprengmembran	
15205289	
Bt-Star-Hl-14 Protective Membrane Rembe Bt-Star-Hl-14 Du350 Rsr 1,4 Mpa 80,2 G.C Ss316l	
15205983	
15202629	
Sk-Ero-Dn750	
Signal-Sensor	
Rembe Bt-Star-Hl-1 Rembe Safety Membrane Bt-Star-Hl-1 Du25 Rsr 6.9 Mpa 25 G.C Ss316l	
15205155	
Membrane	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
22100028	
Rembe Bt-Kub-2 Protective Membrane Rembe Bt-Kub-2 Du50 Rsr 0,315 Mpa 10 G.C Ss316l	
Pse-Bve113l03	
Bt-Skodipv-F-28 Membran	
20900422	
44100418	
Sb-S-1 (113-0000000014)	
Bt-Kub-1 (20800109)	
164-0000000128 Dokumentation Gost	
1304268 Tearing Membrane	
15205226	
Rembe Bt-Kub-2 Protective Membrane Rembe Bt-Kub-2 Du50 Rsr 0.9 Mpa 268 G.C Ss316l	
Odv/Bt-Odv-8	
4 Verschidene Membrane Nach Dem Fragebogen	
164-0000000035	
227 0000000152	
41700008	
22303217	
227 0000000036	
164-0000000044 Materialzeugnis	
164-0000000133	
24000134	
Bt-Kub-1,5 Protective Membrane Rembe Bt-Kub-1,5 Du40 Rsr 0,45 Mpa 230 G.C	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Ss316l	
Bursting Disc	
16702377 Igig-Hl-Hp-Sh-32 Berstscheiben-Halter	
Bt-Kub-1	Artikel-Nr.: 15205053 Buckle reversal rupture disc Medium in front of the rupture disc: gas Nominal size (DN): 25 mm Relief area: 5.5 cm² Type of protection: overpressure Holder system: IG-KUB Bursting pressure: 16 bar g Bursting temperature: 65 ° C Lower burst tolerance: 0% Upper burst tolerance: 10% Vacuum resistance: absolute Buckling bar: stainless steel Sealing part: Monel Certification: PED (2014/68 / EU) Test standard: AD 2000-Merkblatt A1 Customs tariff number: 73269098 old batch: 1112023
Eva-Cld-Ss-24	
00014581 Assembly Explosion Vent 305 X 610	
Bt-Kub-8	
44100421	
Bt-Odvsnr-F-3	
Ex-Go-Ventskegv-600x600	
16701474	
Rembe Bt-Kub-3	
22100029	
14800097	
15204114	
140-0000000065 Ex-Go-Vent	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
224-0000000519	
Bt-Star-Hl-3 Rembe Safety Membrane Bt-Star-Hl-3 Du80 Rsr 7.2 Mpa 211 G.C Ss316l	
16302598	
15202167	
15204706	
140-0000000048 Ex-Go-Vent	
15202621	
160-0000000272	
227-0000000036	
Bt-Kub-2 Rembe Safety Membrane Bt-Kub-2 Du50 Rsr 5.2 Mpa 181 G.C Ss316l	
Rembe Bt-Kub-2 Protective Membrane Rembe Bt-Kub-2 Du50 Rsr 0,315 Mpa 38 G.C Ss316l	
18900580	
15200535 Kubbt-Kub-1knickstab-Umkehr Berstscheibe	
Fvr3.7as1s4e	
Artikel-Nr.: 164-0000000028 Optional	
Bt-Kub-12 Protective Membrane Rembe Bt-Kub-12 Du300 Rsr 1,2 Mpa 83,8 G.C Ss316l	
15200533	
164-0000000133 Technischer Pass	
Agf 1012 Modul	
Rembe Bt-Kub-2 Protective Membrane Rembe Bt-Kub-2 Du50 Rsr 0.35 Mpa 230 G.C Ss316l	
121-0000000062	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
TC-KUB	TC-KUB-1,5 21600164 Buckling rod reverse rupture disc for direct installation between Tri-Clamp flanges Medium in front of the rupture disc: gas Nominal diameter (DN): 40 mm Relief area: 8 cm² Type of protection: overpressure Clamp standard: DIN 32676 NA Connect Pipe standard: DIN 11866 Series A (DIN) Nominal diameter according to pipe standard: DN 40 Burst pressure: 3 bar g Burst temperature: 130 °C Lower burst tolerance: 10% Upper burst tolerance: 10% Working pressure: 2.4 bar g Vacuum resistance: absolute Buckling rod: 1.4404/1.4435 Sealing part: 1.4404/1.4435 Clamp seal: EPDM dark Clamp seal USP Class VI certified: yes Clamp seal FDA-certified: yes Certification: DGRL (2014/68/EU) Test standard: AD 2000-Merkblatt A1
Bt-Ikb-2. Ig Kub Membran Vorbeugende	
162-0000000055	
227-0000000496	
15205227	
Skedp-586x920	
Bt-Kub-10 Protective Membrane Rembe Bt-Kub-10 Du250 Rsr 0,35 Mpa 80 G.C Ss316l	
164-0000000028	
Rembe Bt-Kub-6 Rembe Safety Membrane Bt-Kub-6 Du150 Rsr 0.45 Mpa 230 G.C Ss316l	
33900142	
Rsk 3489-72gk-Q12/Y01 Anti-Tamper-Membran	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
44100425	
Trichter C-Leverã174; Direct 50 Va	
Rembe Bt-Kub-4 Protective Membrane Rembe Bt-Kub-4 Du100 Rsr 0.45 Mpa 230 G.C Ss316l	
Bt-Snrodv-F-4	
Bt-Star-Hl-3 Rembe Safety Membrane Bt-Star-Hl-3 Du80 Rsr 7.2 Mpa 217 G.C Ss316l	
- Berstmembran Du150 Ru0.22	
162 0000000055	
44100846	
0910908	
44100066	
Bt-Snrrodv-F 6	
164-0000000027 Materialzeugnis	
169-0000000255	
Bt-Ikb-2. Ig Kub	
140-0000000028 Ex-Go-Vent	
24500172	
152000119	
15203181	
Iafskegv-920x920	
164-0000000044	
@423kce 0045torq 55nmrembe1601347700 Bar	
164-0000000132	
Tx/01-219-Bd-V Rupture Disc For Vacuum	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
44100847	
Rembe Bt-Kub-2 Protective Membrane Rembe Bt-Kub-2 Du50 Rsr 0.99 Mpa 75 G.C Ss316l	
0801091 Membran	
Rembe Bt-Kub-14	
Egv-305x610	
Yb9005,Type:Tc-Kub 1	
Bt-Kub-14 Protective Membrane Rembe Bt-Kub-14 Du350 Rsr 0.27 Mpa 107 G.C Ss316l	
44100424	
C-Leverã174; Direct 50 Ss	
Rembe Bt-Kub-6 Rembe Safety Membrane Bt-Kub-6 Du150 Rsr 1.11 Mpa 195 G.C Ss316l	
15202620	
Odv/Bt-Odv-16	
140-0000000004 Ex-Go-Vent	
227-0000000489	
15202623	
Qvii-8 Ventil	
Odv/Bt-Odv-12	
16301740	
Rembe Bt-Kub-3 Protective Membrane Rembe Bt-Kub-3 Du80 Rsr 1 Mpa 230 G.C Ss316	
44100417	
Skex-Go-Vent 600x600 Explosion Panel	
164-0000000027	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
Bt-Kub-6 Rembe Safety Membrane Bt-Kub-6 Du150 Rsr 0.45 Mpa 93 G.C Ss316l	
227-0000000152	
BT-KUB-3	Article No.: 41005216 Reverse Burst Disc Medium in front of the rupture disc: Liquid with gas cushion Nominal diameter (DN): 80 mm Relief area: 50 cm^2 Type of protection: Overpressure Mounting system: IG-KUB Burst pressure @ burst temperature: 5 bar g @ 150 °C Burst tolerance (-/+): 0 % / 10 % Operating pressure: 4 bar g Vacuum resistance: Absolute Burst bar: ss316(L) Sealing element: ss316(L) Certification: PED (2014/68/EU) Test standard: EN ISO 4126-

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.