Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Rense

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Rense Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rense Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
WM52-2-XX-H-T0	
WM52-2-XX-HT0	
WM52-2XX-H-TO	4.20mA
HF532-DB1XX5XX	Transmitter for humidity and temperature, duct design, 3/4-wire, 15...40 VDC / 12...28 VAC, vertical mounting, RS485 on terminals, 1 M16x1.5 cable gland, output signals: OUT1: 4...20 mA = 0...100 %RH, OUT2: 4...20 mA = 0...50 °C.
HC2A-S	Sensor module for humidity and temperature Standard design: anthracite. Sensor dimensions: 15x108mm, application range: 0...100%RH/ -50...100°C, humidity sensor: HygroMer HT-1, temperature sensor: Pt100 1/3 class B, accuracy@20°C±10K: ±0.8% rF/±0.1 K, including polyethylene filter and works certificate.
HF432-DB1XX2XX	Humidity and temperature transmitter with integrated sensor and polyethylene filter. Duct design, vertical assembly, supply voltage: 15...40 VDC / 12...28 VAC, sensor dimensions: 208 x 15 mm, connection: 1 M16x1.5 cable gland, output signals: OUT1: 4...20 mA = 0.. .100 %RH, OUT2: 4...20 mA = 0...50 °C.
HF732A-QBD6XSFXX	Humidity and temperature transmitter Advanced version; Accuracy at 23 °C: ± 1.0%RH / 0.2K duct version with 280 mm probe length, PPS snout 25/15 mm, 3/4-wire version, IP65 die-cast aluminum housing, supply: 15...40 VDC/ 12...28 VAC, connection: 7-pin Tuchel plug, (signals + supply, output signals: OUT1: 4...20 mA = 0...100 %RH, OUT2: 4...20 mA = 0...150 °C.
SPA-WM	Wire filter element HC2A industrial probe
HT-734-M-06	Sensor
Wm52	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Wm-52-2-Xx-H-X-F01	
Wm52-2- Xx-H-T1- F01	
Wm52-2-Xx-H-T1-F01 (Wm52-2)	
Wm52-2- Xx-H-T1 -20 / + 80;C 0 / 100 % R.F. 4-20 Ma Amp; Pt100 Direkt 15-30 V Dc	
Wm52 Wm52-2+xx+h+t5+f16	Relative humidity and temperature transmitter, suitable for outdoor wall mounting Measuring range rel. Humidity: 0-100% Temperature range: -20 ° to + 80 ° C Accuracy: Relative humidity: <± 2% RH (10-90% RH) at 23 ° C Accuracy: Temperature: ± 0.2 ° C at 23 ° C Output: 4-20mA, 0-1V, 0-5V or 0-10V Supply voltage: 14 - 30 V DC 5-30 VDC (0-1V & 4-20 mA output) Dimensions: 44x50x95 mm Weight: 82 g Further details according to attached data sheet Product Configuration: Basic model: WM52-2 base unit with (4-20mA output signal) Display: + XX without display Humidity signal output: + H Relative humidity Temperature output: + T5 Pt1000: -50 to + 200 ° C Class A Filter + F16 Filter made of PVDF, with protective cap white
Ht-923-I-06 Obsolete! Replaced By Wm52	
Hx-923-I-06 Rh- Obsolete, Replaced By Wm-52-2-Xx-H-X-F01	
A000014 Pvdf Filtereinsatz	
Ht-734-M-06 Obsolete	
Wm52-2- Xx-H-T1 -20 / + 80°c 0 / 100 % R.F. 4-20 Ma & Pt100 Direkt 15-30 V Dc	
Hx-923-I-06 Rh- Obsolete, Replaced By Wm-52-2-Xx-H-X-F01 Mini Wall Mounted Humidity Sensor / Transm	
Wm52-2-Xx-H-To	Feuchtigkeitssensor

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.