

Resato

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Resato Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Resato Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
123-331-16	Test chart paper Chart diameter 223 mm Pressure range 0-15 PSI x 1000 1 hour clock work
Portable Powerpack, DPS-400-1-W-1	Pump P160-400-1/U/V Key features: ☐ Low noise level ☐ Easy and low cost maintenance ☐ Proven reliability under severe conditions Performance: ☐ Max. outlet pressure 2800 bar (40,000 psi) at 7 bar (100 psi) air drive pressure. ☐ Pump is limited to 2500 bar ☐ Max. flow 0.7 litres / min. at 0 bar/psi outlet pressure. ☐ Ratio: 400 High pressure gauge type PBX-160-LH-Spec2500 ☐ Case diameter: 160 mm, provided with blow out ☐ Double dial (2 measuring elements) ☐ Liquid filled: filled with liquid, class 1.0 ☐ Range: 0-2500 bar (divided per 10 bar) ☐ Finish: stainless steel. ☐ Dial marking: Wartsila logo. ☐ Provided with heavy extinction, provided with safety glass. ☐ Including: 2 certificates. ☐ Air pressure gauge, type PBX-160-LH 0-7 bar (0-2800 bar) ☐ Case diameter: 160 mm. ☐ Liquid filled: filled with liquid, class 1.0 ☐ Range: 0-7 bar (read-out 0-2800 bar) ☐ Finish: stainless steel. ☐ Dial marking: Wartsila logo. ☐ Including certificate. Medium: Castrol AWS-15 (5 l included) ☐ High pressure Outlet type CEIJN 10125-6202 (2x)
Hose package DPS-400-1-W-1	Consisting of: ☐ 1 hose length 3 meter

Ürün	Açıklama
	☐ 1 hose length 4 meter Both hose are provide with: ☐ Transparent hose guard ☐ One end provide with angled female quick connector ☐ One end provided with straight female quick connector
P160-400-1/U/V.	Resato air driven, single acting, high pressure pump, Key features: •Low noise level •Easy and low cost maintenance •Proven reliability under severe conditions Performance: • Max. outlet pressure 2800 bar (40,000 psi) at 7 bar (100 psi) air drive pressure. •Max. flow 0.7 litres / min. at 0 bar/psi outlet pressure •Ratio: 400
Rdhmu1-70	
Self Adjusting Compensating Packing Pump Type :Dps-400-1-W-1	
Wps-400-1/D/D/I	
V2-2-21-0160-2011 Replaced By 1060033	
Mini Pump P-80	
1004537	
Reservoir	
1004326	
1003260	
1004151	
Rdhmu2-42	
Rdhmu1-42	
Rdhm2-42	
1004541	
1054189	
Hand Operated Higly Press.Valves -3 Way For Pump Type :Dps-400-1-W-1	

Ürün	Açıklama
1004206	
Rdhm1-42	
Rdhm1-70	
S-30-A-W	
Fim3-42-20	
1004150	
1005322 Obsolete/Replacement 1054189	
Dps-520-1/D/D/I	
1004677	
Wide Internal Orifices For Hp Valves For Pump Type :Dps-400-1-W-1	
1004604	
Fim3-21-20	
Non Rotating Stem For H.P Valves For Pump Type :Dps-400-1-W-1	
1004148	
1003544	
Fim1-42-20	
Fim2-42-20	
O Ring For Wide Internal Orifice For Pump Type :Dps-400-1-W-1	