

Rion

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Rion Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rion Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
NL53EX	Sound level meter NL53EX Class 1 according to DIN EN 61672 and calibrated (PTB type examination according to DIN EN 61672-2) Ex: Extended Function Program: Level time history / Auto Logging and 512 MB SD card Included accessories: Windscreen, USB data cable, Wrist strap, IEC type R6 batteries (4x), Equipment bag Optional but highly recommended Certificate: 4TRAC106: Factory calibration certificate / Certificate of calibration (English) Optional certificates/reports available: 4TEST106: Test report (English) 4TRAC116: Traceability chart (English) NH-25 preamplifier UC-59 1/2" free field microphone (50mV/Pa)
565.00290 Windschutz Für 1/2" Mikrofone	
Vt-06	
Vt-Verlängerungsstab Für Vt-06 Vt-Verlängerungsstab Für Viskostester	
Vm-82a	
Vt-04f (Obsolete) Replaced By 565.03160 Vt-06	
565.02420	
Vt05	
Va-05j	

Ürün	Açıklama
565.02360	
Na-28	Sound analyzer with TFT color display, real-time third octave / Octave analysis (optional noise recording with optional program card NX-28WR) according to IEC 61672-1 class 1, PTB approval-approved, CE Simultaneous measurement and display of thirds and octaves in real time Easy to use and very fast - multi-spectra from 1 ms High-contrast, backlit TFT-LCD color display Time and frequency ratings can be separated for the main and secondary channels be set Measuring range: 25-140 dBA @ 1kHz; peak 143dB Frequency range: 10 (!) Hz-20,000 Hz Frequency weighting: A, C, Z: Time weighting: F, S, 10mss, Pulse, Measurement parameters: Lp, Leq, LE, Lmin, Lmax, LN (1-99%, 1% steps), Lpeak, Ltm5 Level, time and external trigger, Storage on SD card PC connection via USB interface as a virtual disk; Approximately 16 hours use with standard alkaline batteries AC / DC output; Dimensions: WxHxD 330 x 88 x 59 mm Weight: approx. 770g incl. Batteries; Supplied with: equipment case,
565.03160	
Vt05	
Vt06 Viskositätstester	
Va-04	
Ao283	
Vm-82a Hand-Schwingungsmessgerät	
Vm 83	
Vm-63a	
Ec-04b	
Rion-Stö;Nder-F3;R-Vt-06-Istanbul-Türkiye	

Ürün	Açıklama
Vm-82 Obsolete, Replaced By Vm-82a	
NI-52	
Ständer Für Vt-06 Ständer Für Viskotester	
Na-28 Sound Level Meter	
Vt-06 Viskositätstester	
NI-52s1 NI-52 Bu Urun Un Satislari Daha Baslamadi	
Rotors No.3	
565.00290	
Rion-Vt-Verlõ;Ngerungsstab-F3;R-Vt-06-Istanbul-Türkiye	
Dmi600	