

Ritz

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Ritz Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ritz Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Typ: Ven 40,5-17	single-pole isolated voltage converter Type: VEN 40.5-17 Dimension drawing: V 40-33-017 Standard: IEC 61869-3 Insulation level: 40.5 / 80/185 kV Frequency: 50 Hz Ratio: 34500: V3 // 100: V3 / 100: 3 volts Winding 1: 100 VA; Kl. 0.5 Winding 2: 30 VA; Kl.3P (da-dn) [th. Limit current 6A] Voltage factor: 1.9xUn - 8h [internal note: repetition A 10407418.030]
Typ: Ass 40,5-01	Support current transformer cast resin insulated, for interior Type: ASS 40.5-01 Dimension drawing: A 40-41-001 Standard: IEC 61869-2 Insulation level: 40.5 / 80/185 kV Frequency: 50 Hz Ratio: 500 // 5/5/1 A Core 1: 15 VA; Cl. 0.5 FS10 Core 2: 15 VA; Cl.5P 15 Core 3: 30 VA; Cl. 0.5 FS10 I _{th} = 31.5 kA / 1 sec. I _{dyn} = 2.5 x I _{th} I _{cth} = 1.0 x I _n [internal note: repetition A 103884.010]
Ritz	
Ritz	
Ritz	
Ritz	
Ritz	

Ürün	Açıklama
VES 17,5-02	Voltage converter - single pole Block design for indoor use cast resin insulated, insulation class E Standard: IEC 61869, with test report Dimension drawing: V 15-37-002 Insulation level: 16.6/38/95 kV Frequency: 50/60Hz Voltage factor: 1.9xUn - 8h Gear Ratio: 13,800/√3 // 100/√3 / 100/3 V Winding 1: 50 VA, terminal 3P; 6Ath Winding 2: 50 VA, terminal 3P (da-dn); 6Ath [Internal Note: Repeat A.10462417.020]
ASS 12-10	Support current transformer cast resin insulated, for interior Type: ASS 12-10 narrow design according to DIN VDE 42600 part 8 Dimension drawing: 11-xx-41-010/011 Standard: IEC 61869-2 Insulation level: 12/28/75 kV Frequency: 60Hz Gear ratio: 400 // 1 A Core 1: 20VA; Kl. 5P 10 I _{th} = 20kA/1s I _{dyn} = 2.5 x I _{th} I _{cth} = 1.0 x I _n
Type: GSWS12D size 3	Supports current transformers cast resin insulated, for indoor use Type: GSWS12D size 3 Dimensions: 4.4913 Standard: IEC 61869-2 Insulation level: 28.12.75 kV Frequency: 50Hz Gear ratio: 2000 // 1/1 A Core 1: 30VA; Class 0.2 FS5 Core 2: 20VA; Class 5P 30 I _{th} = 100kA/1s I _{dynes} = 100kA I _{cth} = 1.0 x I _n
Typ: GSES12D	single-pole isolated voltage converter cast resin insulated, for interior Type: GSES12D narrow design according to DIN VDE 42600 part 9 Dimensions: 482001 ref Standard: IEC 61869-3 Insulation level: 12/28/75 kV Frequency: 50Hz Ratio: 11,000:V3 // 100:V3 / 100:V3 / 100:3 volts

Ürün	Açıklama
	Winding 1: 30VA; Class 0.2 Winding 2: 10VA; Class 0.2 Winding 3: 30VA; Kl. 3P (da-dn); 6A(th) Voltage factor: 1.9xUn - 8h [internal note: same as serial no. 16/31039198]
GSEFB 25F Gr.0	
UGSSF 708 Gr.2	
1.1000592	
Ass12-10 100/1/1a	
Kso74	
Gis12d	
32-250.F/B+1,5/4	
49 150/8/S+132/4	
Ass12-10 250/1/1a	
Vzf24-15	
10002	
7aa-100I-4	
002	
Eass12/10 150/1/1a	
2081739	
49125/7/5	
Ven 17.5-0.2	
Gsz10 Kl.0,5(Drawing Nr.4,2061)	
10.1014396	
Es - Design 03 En 733	
Gsz10 Kl.0,5	
125-250.2b	
Ves 12-02	

Ürün	Açıklama
Gsefb 25 F	
2007060.03	
Ven 36-14	
Ass12-10 150/1/1a	
Aftrafo	
3925e	
Sd 100-260 F/A	
Ass-12-02	
Eass12-10 2000/1/21/1a	
Es 125-315.2/A(Ex.125-315.2f)	
8103	
50-250f/B+3/4	
Ass 12-10	
Kso 63 Size: 2	
Sksw300	
Kso73	
Aflm 3	
Ks79-05	
Iso 100x65-250	
125-250.2b+15/4	
7aa-160m-4	
Ass 12-14	
7aa-160l-4	
Eass12-10 2000/1/1a 31,5ka/1s	
49200/5/E2	
2076052.02	

Ürün	Açıklama
3.1000126	
10.1006346	
Gsz10 Kl.0,2(Drawing Nr.4,2061)	
Kso62 100/5a 5va Kl3	
100-400 1/E + 22/4	
Rb-50-200/B+15/2	
49200/5/E2+200/4	
Vdk-2-32-250-2fma	
Kso74 500/5a 15va Kl.3	
Ks79-05/600/5/5va	
3419704	
Typ 4504	
10.1004641	
Gsws12w-10	
Rku-2314	
Ks0 812	
10035	
Gis12e	
Gsz10 Kl.0,2	
Ass 36-01	
Kso 50 Gr. 1	
Es 150-250.4/A	
Tsw 215/1	