Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Rls

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Rls Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rls Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Rls	
RMK4 und RMK4KIT	Evaluationsplatinen mit AM4096 https://www.rls.si/eng/rmk4-evaluation-board
RM08ID009	Contactless rotary magnetic encoder; 8 mm diameter; incremental, 5 V, without line-driver; without magnetic actuator; 1024 counts per revolution; 0.20 m cable length; leads only; cylindrical body, radial cable exit; IP68; power supply = 3.30 V
RM08ID0010B02L2G33	RM08ID009 Contactless rotary magnetic encoder; 8 mm diameter; incremental, 5 V, without line-driver; without magnetic actuator; 1024 counts per revolution; 0.20 m cable length; leads only; cylindrical body, radial cable exit; IP68; power supply = 3.30 V
RM44IA 0012B60F2M49	
RMB28SC14BS12	RMB28SC14BS12 Rotary magnetic encoder board; 28 mm diameter; absolute binary synchro-serial (SSI), RS422; 16384 positions per revolution; square board; Molex connector
ACC028	Cable assembly Molex 15133-0603 for connection with Molex 501568-0607
5X2V14	
AS10A/I 092304	
Indikator H25 - 5 (500ml)	32-084205 For the determination of residual/total hardness Sycon 2501/2502/2602: Limit value 5 °dH, 8.9 °f, 0.18915 mmol/l Sycon 2702/2800/2802: Measuring range 1.5-15 °dH, 2.67-26.7 °f, 0.27-2.67 mmol/l
Value pack indicator H25 - 5 (container 4 x	32-484205

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
500 ml)	For the determination of residual/total hardness Sycon 2501/2502/2602: Limit value 5 °dH, 8.9 °f, 0.18915 mmol/l Sycon 2702/2800/2802: Measuring range 1.5-15 °dH, 2.67-26.7 °f, 0.27-2.67 mmol/l
SYCON 2702 sensor	
RM22IC291	RM22IC0012B20F1C00 Contactless rotary magnetic encoder; 22mm diameter; incremental with RS422 line driver, 5V power supply; without magnetic actuator; 4096 counts per revolution; 2.00 m cable length; flying lead (no connector); flanged body, radial cable exit; IP68 (-40 °C to 85 °C), high EMC grade; no special requirements (standard)
RM22IC0012B20F1C00	RM22 ROTARY MAGNETIC ENCODER
Rmb29ac01ss1	
RMM44A3A00	MAGNET D4 H4 SmCo GRADE 3 STD Magnet; Diameter 4 mm; Height 4 mm; Diametrically polarised, SmCo, Surface protection NiCuNi; Very good, Grade 3; individually packed in plastic bag; no special requirements (standard)
Re36ia062d010f2a00	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.