Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Rmg Regel Messtechnik

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Rmg Regel Messtechnik Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rmg Regel Messtechnik Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
D119A F2 FF1	R3/4 İNC 6Bar Range 0,003 0,016bar
33623	
200/WS-028	ET set 200/WS-028 + 3. 206/WN/010 GUIDE NUT 226Z/150 MC/MS PLTD Customer article number Pos. 1 4. 730OAVN018 O-RING BS 018 NITRILE Customer item number: POS 2 5. 206/WN/007 VALVE RESET MC/AL/150/226 Customer item number: POS 3 6. 730OAVN428 O-RING BS 428 NITRILE Customer item number: POS 4 7. 206/WN/008 VALVE PLUG Customer item number: POS 5 8. 730OAVN017624 O-RING BS 0176-24 NITRILE

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Customer item number: POS 6 9. 204/XH/056 DIAPHRAGM PLATE MC/COATED Customer item number: POS 7 10. 204/XH/057 DIAPHRAGM PLATE MC/COATED Customer item number: POS 9 11. 206/WL/023 SPINDLE MC/MS/PL/150/226ZSO Customer item number: POS18 12.SS1328 COMPRESSION SPRING Customer item number: POS27 13. 206/WL/018 LEAD SPINDLE MC/STAINLESS STEEL Customer item number: POS47
TME400VCDN08	0Turbine gas meter TME400VCDN080 Turbine gas meter TME400-VC DN80 These devices contain lithium batteries installed. The delivery is therefore a Dangerous goods shipment. configuration Standard version Material: spheroidal graphite cast iron Measuring range (m3/h) 13 -160 Turbine wheel aluminum turbine wheel Pressure level PN10 Language German Mounting the counter head on the meter, standing Ex protection variant ATEX / IECEx Gas flow direction from left to right Acceptance test certificate PED 3.1 Zeug.nach DIN EN 10204 Lubrication Manual oil pump Pressure range 2 -10 bar(a) Surface treatment measuring mechanism None RS485 Ex-barrier no Pulse output Ex barrier(s) None

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Alarm output Ex-barrier None Analog output current output + Ex barrier Temperature diving bags No Accuracy class Pt1000 Standard High pressure test (separate price) No
TME400VCDN080	turbine gas meter configuration Version standard Material nodular cast iron Measuring range (m /h) 25-400 Turbine wheel Delrin turbine wheel Pressure level PN10 Language: English Installing the meter head On the meter, upright Ex-protection variant non-EX Gas flow direction From right to left Inspection certificate PED 3.1 according to DIN EN 10204 Lubrication Permanent lubrication Pressure range 0.8 - 6 bar(a) Surface treatment of movement None RS485 Ex barrier none Pulse output Ex barrier(s) None Ex-barrier signaling output None Analog output current output (4-20mA) Temperature dive bags None Accuracy class Pt1000 standard High-pressure test (separate price) None - The necessary Non-Ex power supply for the Power output is on site through the provided to customers. Customs tariff number: 90281000
TEC24	
RMG 361	type DN50 size. The original gasket or the complete repair kit on the part number 2 on page 5 of the attached catalogue.
40018798 à COMPLE FILTER STAGE 89051000	TYPE : 650-100 00001 PRESS.MAX : 100 BAR CONTROLLED CONDITION : PA SET POINT SPRING RANGE WH : 1.0-5.0 BAR SET POINT WORKS ADJUSTMENT : POS.3.1. BAR FOR MAIN VALVE TYPE : RMG 5.T 2 B SERIAL NO : 8710 90296

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	STOCK NO : 100 1351 5 COMPLE FILTER STAGE 89051000
HON 370-80/K1a/60/2/9	- Medium: Natural gas - Connection: Flange DN 80 PN 16 - DIN EN 1092-1 - Control device: K1a - Control range: Wdo= 0.025 to 1.5 bar / Wdu= 0.01 to 0.30 bar - Control device: RE 2 with blocked SBV - Control range: Wds 290 mbar to 360 mbar (rapeseed yellow) - Kg value: 2500 (m^3/h)/bar - Valve seat diameter 60 mm - Temperature range: -20°C to +60°C - Color: RAL 6011 Reseda green - Certificate language: German - Nameplate: German - Factory acceptance certificate according to EN 10204, 3.1, on strength, tightness and function - Weight approx.: 63 kg
HON 372-80-K1a/0-60/610N	Number of configured model: HON372-AA-BAA-AEAAAAA-GG-CD-QAA0-QE00-ABBDBABB0AA-00-KB000- NMEPA0000-00-AAAEA000-A0A00000A-A Special features: No Gas pressure regulator RMG 372: HON372
PRESSURE REGULATOR	RMG 460 20056
PN16 DN25	
D119A F2 F F1	
720K1A	Who: 0,05-1,5Bar Whu:0,01-0,12Bar Pzul:16Bar DN:25 VENTİL-0:25mm Range:Who 0,08-0,25Bar Whu:0,014-0,04Bar,
RMG300	Fab. Nr: 2006 060871711 DIN-DVGW-Reg. Nr: NG-4301AR0760 Pzul: 16 Bar PN::25 Ventil-0:11mm Wh:20-2000 mBar/Pmax: 16Bar/Pemin: Pas 80mBar Shut Off Valve Specification; Type: 720K1A Who: 0,05-1,5Bar Whu:0,01-0,12Bar Pzul:16Bar DN:25 VENTİL-0:25mm Range:Who 0,08-0,25Bar Whu:0,014-0,04Bar Setpoint:Pso:0,2Bar Psu:0,02Bar
Tme400-Vm Dn100	turbine - Standard version Material nodular cast iron Measuring range (m / h) 40-650

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Turbine wheel Delrin turbine wheel Pressure rating PN10 - Language: German Mounting counter head At the counter Ex-protection variant ATEX Gas flow direction From left to right Inspection certificate 3.1 Certificate according to DIN EN 10204 Lubrication permanent lubrication Temperature Diving Bags None Pressure connection none Surface treatment measuring mechanism None RS485 Ex-barrier None Pulse output Ex-barrier (s) None Signal output Ex-barrier None Analog Output Current Output + Ex-barrier

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.