

Roland Electronic

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Roland Electronic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Roland Electronic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
1000006517	
1000006736	
1000012719	
6701409010	
6701409200	
A100	
E20-PN-S	
KISE-G	
KISS-G	
NS11	
P42AGS	
SCPWS-GG	
SHS42GS	
SKOISE-GG	
SKOISS-GG	
SL-CL	
SND40-EC-MF-IO	
UDK20-B-R-S	
T08	

Ürün	Açıklama
E20-4P-B-O	P.N.S0047902 Double sheet detector 24 VDC for FE materials, microcontroller-supported - Connection for a maximum of 4 identical P-type sensors that can be controlled sequentially (no sensor switch box required) - Measuring programs for 255 different sheets can be programmed via keyboard and called up via keyboard or PLC - Password protected - Setting without sheet pattern - Alphanumeric display of sheet thickness and operating parameters - LED displays for the actual value as well as the lower and upper limit and Enable (ready for operation) - Signal output for undersize, actual value within the limit values, oversize and Enable (ready for operation) via potential-free 4-bit parallel interface with optocoupler (+24V) - External control via potential-free 9-bit parallel interface with optocoupler (+24V) - Device system test via external input - Cable connection via PG screw connection - Wall housing with protection class IP 65
P42AGS	P.N.S0002800 Sensor Ø 42mm -for FE sheets up to 4.0 mm single sheet thickness -for evaluation device E20 -without cable, with M12 device plug for sensor cable connection -Sensor with threaded sleeve M 42 x 1.5 and 2 flat nuts
CPM12S-G	P.N.S0004511 Sensor cable, 20 meters - Oilflex drag chain compatible - between device and sensor - one cable end for terminal connection - the other with axial cable socket for connecting the sensors, P30GS, P42AGS - or for connecting EM-SH-EC15 or EM-SH-EC30
SCPWS-GG P.N.S0002084	PNS0002084 cable, 5 meters -Superflex - suitable for drag chains -between device UDK10/UDK20 and sensor PW42(A)GS or between Sensor switch box SSB-UDK10 and sensor PW42(A)GS -both cable ends pluggable

Ürün	Açıklama
	Delivery length: 30 m -with axial cable plug for connecting the device and axial cable socket for connection of the sensor
P42ag-2-S1m	
Ms42ags	
Skoise-Gg	
Kise-G	
I20-4-Pr-S-Fp	
2395109	
I20-2-Pn-S	
E20-4p-Bo-Z	
E20-4p-Pn-S	
Ie42-30gs	
Snd8s-Ns11 Sensor	
R1000-I10-Pr-S-Fp	
Snd8s-Ns11 Induktiver Sensor	
Sm12cpm12s-Gg	
2276007	
E20-B-O	
R100 A100 Detektor Des Doppeltes Blattes (Mit Sensor To8 ,2 Meter)	
Shx42	
E20-4p-Pr-S	
Shs42g-Fb	
Udk20-Dnt-S	
Pw42ags Sensor	

Ürün	Açıklama
E10-4p-B0-Z	
Me42ags	
S54s	
P42ags Sensor	
E20-4p-B-O	
Shs42g-Fb-01	
E20-Pr-S	
120-2-Pr-S	
P30gs	
E20-Pn-S Double Workpiece Inspection Unit	
E54s	
Shs42gs Vakuum-Dual-Sensor-Kopf	
2276116	
Udk20-2pw-Et-S-Fp	
Udk20-B-R-S Modul	
I20-4-Dnt-S	
Shs42gfb	
E20-C-O	
Scbi10-42a	
E20-4p-Dn-S-Fp	
I20-2-Pn-S-Fp	
2395110	
Pw42ags	
2277704	
I20-2-Dnt-S	

Ürün	Açıklama
Snd8s_Ns11	
Is42-30gs	
Ns 11	
Ssbe10	
P75vgs	
Kiss-G	
Shx-Az2-25	
Snd40-Ec-Mf-Pn	
Udk20-B-O-S	