



Ropex

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ropex Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Ropex Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Res-420-L/230vac	742012 RESISTRON temperature controller for heating conductors Front panel installation, 230VAC, fault diagnosis, LC display (green), alarm relay, 300 ° C / 500 ° C Weight: 0.65kg Customs tariff number: 90328900
RES-402/230VAC	740202 RESISTRON temperature controller for heating conductors DIN rail mounting, 230VAC, Alarm output, isolated analog inputs / outputs, 300 ° C Weight: 0.6kg 90328900
RES-5006	RESISTRON temperature controller for heating conductors CE and RoHS compliant DIN rail mounting (DIN rail TS35) Voltage range: 110-415 VAC Frequency range: 47-63 Hz PROFIBUS interface with error diagnosis USB interface for ROPEX Visual Weight: 0.4kg *** Compatible successor model to the expired and no longer available RES-406 ***
RES-407	
RES-5007	RESISTRON temperature controller for heating conductors CE, UL and RoHS Compliant DIN rail mounting (DIN rail TS35) Voltage range: 110-480 VAC Frequency range: 47-63 Hz Analog interface with error diagnosis USB interface for ROPEX Visual Weight: 0.4kg temperature controller
RES-408/400VAC	RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, error diagnosis, 300 ° C / 500 ° C, Alarm relay, connection for Terminal T-408 Weight: 0.6kg *** Discontinued Model Only available until December 31, 2021! successor Item no .: 7500800

Designation: RES-5008 *** Only available as long as stocks last! ***	
740843	
885441	T-408-1 terminal Terminal for RES-408 (# 74084x) Weight: 0.15kg ROHS compliant
LF-06480	Line filter for RES and UPT controllers, 6A, 480VAC Weight: 0.42 kg
06480v	
100030	
100031	
100032	
100037	
100695	
100971	
101809	
101810	
101916	
101935	
102849	
105604	
120084	
24020144	
30683930	
35480	
603000	
603500	
610201	
610222	
610223	
610229	
610332	
651015	
651045	
651071	
664023	
740833	
740842	
742022	

[744012](#)

[744022](#)

[744023](#)

[744513](#)

[744521](#)

[7500600](#)

[7500700](#)

[7500800](#)

[7501000](#)

[7501001](#)

[7601000](#)

[800044](#)

[883172](#)

[883201](#)

[883361](#)

[883463](#)

[883514](#)

[883582](#)

[883599](#)

[883627](#)

[883647](#)

[883702](#)

[883955](#)

[884205](#)

[884210](#)

[884252](#)

[885104](#)

[885106](#)

[885212](#)

[885301](#)

[888487](#)

[991000](#)

[999903](#)

[B-075400](#)

[CI-USB-1](#)

RES-5010_7501000	RESISTRON temperature controller for heating conductors CE and UL compliant DIN rail mounting (DIN rail TS35) Voltage range: 110VAC - 480VAC Frequency range: 47Hz - 63Hz PROFINET interface USB interface Weight: 0.4kg
PEX-W5	885107 Current transformer for RES and UPT temperature controllers RoHS and REACH compliant CE and UL compliant DIN rail mounting (DIN rail TS35) Weight: 0.18kg *** Successor model for the current transformers PEX-W2, PEXW3, PEX-W4 ***
LF-06480	885500 Mains filter for RES and UPT controllers, 6A, 480VAC Weight: 0.42kg
PEX-W5	Current transformer for RES and UPT temperature controllers RoHS and REACH compliant CE and UL compliant DIN rail mounting (DIN rail TS35) Weight: 0.18kg *** Successor model for the current transformers PEX-W2, PEXW3, PEX-W4 ***
885105	TRANSFORMER,CURRENT:VOLTAGE RATING 408/400 V AC,CONNECTION TYPE FLAT CONNECTOR,60X68X45 MM,MODEL NUMBER:PEX-W2
550162N	TRANSFORMER,POTENTIAL:VOLTAGE RATING 400/12-18 V,APPARENT POWER 2.5 KVA ,FREQUENCY 50-60 HZ
LF-06480	FILTER,ELECTRONIC:TYPE LINE,VOLTAGE RATING 480 V AC,CURRENT RATING 6 A ,POWER RATING 6 W,FREQUENCY 50/60 HZ,STANDARD EN 133200,EN 60950,W58 X L103 X H46MM
ROP-PEX-W3	TRANSFORMER,CURRENT:CONNECTION TYPE PLUG IN CONNECTOR,ENCLOSURE RATING IP20,24X89X60 MM,
RES-415-L/230VAC	RESISTRON temperature controller for heating conductors Front panel installation, 230VAC, error diagnosis, LC display (green), alarm relay, 300°C Weight: 0.65kg
RES-415-L/400VAC	RESISTRON temperature controller for heating conductors Front panel installation, 400VAC, error diagnosis, LC display (green), alarm relay, 300°C Weight: 0.65kg
RES-415-V/230VAC	RESISTRON temperature controller for heating conductors Front panel installation, 230VAC, error diagnosis, VF display (blue), alarm relay, 300°C. Weight: 0.65kg
RES-420-L/230VAC	RESISTRON temperature controller for heating conductors Front panel installation, 230VAC, error diagnosis, LC display (green), alarm relay, 300°C/500°C Weight: 0.65kg
RES-420-V/230VAC	RESISTRON temperature controller for heating conductors Front panel installation, 230 VAC, error diagnosis, VF display (blue), alarm relay, 300°C/500°C Weight: 0.65kg
RES-403/230VAC	Art Nr. 740302 RESISTRON temperature controller for heating conductors DIN rail mounting, 230VAC, error diagnosis, Alarm relay, 300°C/500°C
740203	RES-402/400VAC RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, Alarm output, isolated analog inputs/outputs, 300°C
107311	SHGP 6,0x1,50x750 type: SHGP (Silicone Hard Glass Profile) width: 6,0 mm thickness: 1,50 mm length: 750 mm adhesive: no surface: smooth min. order qty.: 10 pcs. weight: 0,01kg
107310	SHGP 6,0x1,50x550 type: SHGP (Silicone Hard Glass Profile) width: 6,0 mm thickness: 1,50 mm length: 550 mm adhesive: no surface: smooth min. order qty.: 10 pcs. weight: 0,009kg
107308	TB 5,0x0,25x430/650 asymmetric ends type: tapered band (Wulstband) width: 5,0 mm thickness: 0,25 mm overall length: 650 mm heated zone: 430 mm length of ends: 100/120 mm end-characteristic: edgeless end-coating: coppered+nicked heat-coating: none material: Alloy 20/L directed: no burned in: no annealed: no packaging: multiple min. order

	qty.: 10 pcs. weight: 0,007kg
106594	TB 5,0x0,25x320/465 asymmetric ends type: tapered band (Wulstband) width: 5,0 mm thickness: 0,25 mm overall length: 465 mm heated zone: 320 mm length of ends: 65/80 mm clamped length: 415 mm end-characteristic: edgeless end-coating: coppered+nicked heat-coating: none material: Alloy 20/L directed: no burned in: no annealed: no packaging: multiple min.order qty.: 10 pcs. weight: 0,006 kg
106595	TB 5,0x0,25x770/885 asymmetric ends type: tapered band (Wulstband) width: 5,0 mm thickness: 0,25 mm overall length: 885 mm heated zone: 770 mm length of ends: 50/65 mm clamped length: 805 mm end-characteristic: edgeless end-coating: coppered+nicked heat-coating: none material: Alloy 20/L directed: no burned in: no annealed: no packaging: multiple min.order qty.: 10 pcs. weight: 0,01 kg
106992	SHGP 6,0x2,00x790 type: SHGP (Silicone Hard Glass Profile) width: 6,0 mm thickness: 2,00 mm length: 790 mm adhesive: yes surface: smooth min. order qty.: 10 pcs. weight: 0,01 kg
106995	SHGP 4,0x1,00x550 type: SHGP (Silicone Hard Glass Profile) width: 4,0 mm thickness: 1,00 mm length: 550 mm adhesive: yes surface: smooth min. order qty.: 10 pcs. weight: 0,005 kg
7501200	RES-5012 RESISTRON temperature controller for heating conductors CE and UL compliant DIN rail mounting (DIN rail TS35) Voltage range: 110VAC - 480VAC Frequency range: 47Hz - 63Hz EtherCAT interface USB interface Weight: 0.4kg
885107	PEX-W5 Current transformer for RES and UPT temperature controllers RoHS and REACH compliant CE and UL compliant DIN rail mounting (DIN rail TS35) Weight: 0.18kg *** Successor model for the current transformers PEX-W2, PEXW3, PEX-W4 ***
885500	LF-06480 Mains filter for RES and UPT controllers, 6A, 480VAC Weight: 0.42kg
RES-5011	RESISTRON temperature controller for heating conductors CE and UL compliant DIN rail mounting (DIN rail TS35) Voltage range: 110VAC - 480VAC Frequency range: 47Hz - 63Hz EtherNet/IP interface USB interface Weight: 0.4kg
885107 PEX-W5	PEX-W5 Current transformer for RES and UPT temperature controllers RoHS and REACH compliant CE and UL compliant DIN rail mounting (DIN rail TS35) Weight: 0.18kg *** Successor model for the current transformers PEX-W2, PEXW3, PEX-W4 ***
RES-403/400VAC	740303 RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, error diagnosis, Alarm relay, 300°C/500°C
RES-402/400VAC	740203 RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, Alarm output, isolated analog inputs/outputs, 300°C
RES-440-L/400VAC	744013 RESISTRON temperature controller for heating conductors Front panel installation, 400VAC, fault diagnosis, alarm relay, LC display (green), timer, OK output, preheat, 300°C/500°C Weight: 0.65kg
102134	FB 6,0x0,30x430/670 type: Flatband (Flachband) width: 6,0 mm thickness: 0,30 mm overall length: 670 mm heated zone: 430 mm length of ends: 120 mm end-characteristics: edgeless end-coating: coppered heat-coating: none material: Alloy 20/L directed and annealed: no burned in: no
RES-403/230VAC	740302 RESISTRON temperature controller for heating conductors DIN rail mounting, 230VAC, error diagnosis, Alarm relay, 300°C/500°C Weight: 0.6kg
	RES-5011 RESISTRON temperature controller for heating conductors CE and UL compliant DIN rail mounting (DIN rail TS35) Voltage range:

7501100	110VAC - 480VAC Frequency range: 47Hz - 63Hz EtherNet/IP interface USB interface Weight: 0.4kg
RES-407/230VAC	RESISTRON-Temperaturregler fr Heizleiter Hutschienenmontage, 230 VAC, Fehlerdiagnose, Alarmrelais, Isolierte analoge Ein-/Ausgnge, 300°C/500°C Gewicht: 0,6kg, 740702
RES-407/400VAC	RESISTRON-Temperaturregler fr Heizleiter Hutschienenmontage, 400VAC, Fehlerdiagnose, Alarmrelais, Isolierte analoge Ein-/Ausgnge, 300°C/500°C Gewicht: 0,6kg 740703
LF-06480	Netzfilter fr RES-und UPT-Regler, 6A, 480VAC 885500
742012	RES-420-L/230VAC RESISTRON temperature controller for heating conductors Front panel installation, 230VAC, error diagnosis, LC display (green), alarm relay, 300°C/500°C Weight: 0.65kg
885107	PEX-W5 Current transformer for RES and UPT temperature controllers RoHS and REACH compliant CE and UL compliant DIN rail mounting (DIN rail TS35) Weight: 0.18kg
639497	
883779	TR-0,5/19 Impulse transformer power: 500 VA duty cycle: 40 % prim.voltage: 230 VAC +/- 10% sec.voltage: 1-5-7-9 VAC dimensions (WxDxH): 135x140x140 mm weight:7,3 kg
RES-402/400VAC	RESISTRON-Temperaturregler fr Heizleiter Hutschienenmontage, 400VAC, Alarmausgang, Isolierte analoge Ein-/Ausgnge, 300°C Gewicht: 0.6kg
RES-5010	TEMPERATURE CONTROL DEVICE 110...480 VAC MAX 500 °C
RES-402 400VAC	740203 RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, Alarm output, isolated analog inputs/outputs, 300°C Weight: 0.6kg
RES403/400 VAC	
RES-203	
885107-	PEX-W 5
885500-	LF-06480, 6A, 480VAC
RES-5400	7540040
Strom Transformator 885106 Code 85043129 Pex-W4	
Res-407/400vac	740703 RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, fault diagnosis, Alarm relays, isolated analog inputs / outputs, 300 ° C / 500 ° C Weight: 0.6kg
885302	
Res- 5011	RESISTRON temperature controller for heating conductors CE and UL compliant DIN rail mounting (DIN rail TS35) Voltage range: 110VAC - 415VAC Frequency range: 47Hz - 63Hz EtherNet / IP interface USB interface Weight: 0.4kg Tarif No .: 90328900
Ls201	
Res 403 Tempreture Controller	
885650	
Msw-2 Unit	
740202	

Res-403 Controller	
740302 Reglerres-403/230vac	
740703	TEMPERATURE CONTROLLER
740703 Temperaturreglerres-407/400vac 50/60hz	
101935 Oem!! Damper,Silicon	
Cr7501100 Res 5011/110-415v	CR7501100 RES 5011/110-415V
Sf-F01-04-470-80 651017	
740302 Res-403/230vac Thermostat	
Res-407/400 V. Ac Mod:26 Fw00-202	
120125 Heizelement	
Res-408/400vac	
Res-403/230vac Controller	
Res-407/230vac Nog-4;5;6;7;8	
Res-403/400 Vac Heizblock	
740302	
744512	
885106 Transformator Pex-W3pex- W4stromwandlerce Und Ul Konformhutschienenmontage (Din-Rail Ts35)	
Res-440-V/115vac	TEMP CONTROLLER
Res-407/230 Vac,Artikel-Nr 740702	
610222 Oem!! Bracket,Heating Element	
740602 (Res-406/230vac)	
740302 , Type Res-403/230vac	
Lf-06480	Line filter for RES and UPT controllers, 6A, 480VAC Weight: 0.42 kg
664023 Upt-640-V 400vac	
Res-407 Temperaturregler	
Temperaturregler Res-402/400vac	
740843 Res-408/400vac =gt; Neu	
890000	
Art. Nr. 740843 , Type Res-408/400vac	
Res 408/230vac	
Res-403/400vac 740303	RESISTRON temperature controller for heating conductors DIN rail mounting, 400VAC, fault diagnosis, Alarm relay, 300 ° C / 500 ° C Weight: 0.6kg Tariff No .: 90328900
742013	
885506	

740202 Res-402/230vac	
Res-403/230vac Temperatur Controler	
610229 Upt K 600 4 8 Gc L	
610229 Upt-K-600/4.8-Gc-L-15	
740302 Regler Res-403/230vac	
691001 Upk-0,8 (50hz, 230vac)	
Art. Nr. 740702 , Type Res-407/230vac	
100695 Sealbar Head 15 Mm	
Wa-85-2 Wegaufnehmer	
740203, Res-402/400vac	
740302 Res-403/230vac	
100733	
Res-207-0-3	TEMP CONTROLLER
Res-402 400 Vac	
Res5011	TEMPERATURE CONTROLLER 400VAC 5AMP
740902	
740203	
610332 - Oem!	
740703 Temperaturregler Res-407/400vac	
Ropex Res-407 Temperaturregler	
Res 445-L230vac Resistron	
885105 Current Transformer Pex-W3	
Res40803	CONTROLLER
Art Nr. 7501100	RESISTRON-Temperaturregler f¼r Heizleiter CE- und UL-konform Hutschienenmontage (DIN-Schiene TS35) Spannungsbereich: 110VAC - 415VAC Frequenzbereich: 47Hz - 63Hz EtherNet/IP-Schnittstelle USB- Schnittstelle Gewicht: 0,4kg
Res-402	INCOMPLETE-TEMPERATURE CONTROLLER 400VAC
Res40702	RESISTOR
651059 Sf-T06-06-630-80	
Res-408-0-3/400- , Res-408/400vac	
Res-402/230vac	
Res-203-3/400v-50/60hz	TEMPERATURE CONTROLLER 400VAC 50/60HZ 0-300C
Res-403/230vac	
Res440v	DISPLAY
740903 Res-409/400vac	
Res440I115vac	TEMP CONTROL

Atr-3	
101916 Oem!! Strip,Silicon	
740303 / Res-403/400vac	
7501001 - , By 7501000	
740206	
603000 Upt-300 / 2,8 Gw	
Res 407 230vac	
883844	
602500 , Type Upt-250/2.8gw	
Svp Upt-K-2x150-30 20-03-13 !!	
T-408-1	
Resistron-Temperaturregler F¼r Heizleiter	
Res-440	INCOMPLETE-TEMPERATURE CONTROLLER 115VAC 50/60HZ
Res-445	
7501100	
Pd-3 Unit	
5 X 0,25	Widerstandsdraht - f¼r REs440 siehe Bilder
Type : Res - 409/400vac S/N 668806	
(886200)	
664023 Upt-640-V/400vac Oem!!	
Res-406/230vac	
885500 Lf6480	
Mws - 2	
Artikel-Nr 740843 , Type Res-408 / 400vac	
Pex-W3 Transformator	
Res-407	CONTROLLER
Res 403 230vac 740302	
Res-403 Temperature Controller	
Res-406/230vac Controller	
Ci-Usb-1	
740302 / Res-403/230vac Resistron-Temperaturregler F¼r Heizleiter	
885105 Ropex Current Transformer Pex-W3 Spare Part For Ropex Controller And Bagline Machine	
651059	
Res4030c	CONTROLLER

Res-403 Unit	
- Power Transformer 2.5 Kw 380/36v	
Art. Nr. 885105 , Type Pex-W3	
602500 Upt-250 2.8gw	
602002	UPT-200 / 4.8 GW Heatseal bar length: 200 mm, width: 4.8 mm, surface glace, temperature profile without peak, weight: 0.45 kg NEW : M7 thread for cooling water NOT for use in wet or aggressive / corrosive environments Tariff No .: 84229090
Pex-W3 Current Transformer	
101534	
740842 Res-408/230vac	
Res - 5011 . 00/ 400vac	
740602	
Res402230	CONTROLLER
100708	
Pex-W3 Stromwandler	
Etr-4/115 V 993500	
691001	
Sabm02-0317a0	
Res-402/400vac	
Res-407-0-3	CONTROLLER
Sabm02-0316a0	
Pd-3	
Rex402	SUPPLY BOARD
100036	
885500	
740103	
Wm-10-0	
Res-203-0-3/400v-50/60hz	TEMPEATURE CONTROLLER 400VAC 50/60HZ 0-300C
602500	
Res-225	
Res740702	RESISTOR
Wa-85	
740702 , Type Res-407/230vac	
7501002	
885106 Pex-W4stromwandlerce Und UJ Konformhutschienenmontage (Din-Rail Ts35)gewicht: 0,12kg	

Res-440-L/400vac 744013	
Res-406/400vac	
740902 Res-409/230vac	
Upt-640-L/400vac 664013	
201.	
Msw-2 Monitoring Stromtransformator	
Res-403/400vac Temperaturregler	
884205 Sub-D Connecting Cable	
Lf6480 Filter	
101810 Sealbar Head 15 Mm	
602500 Upt-250/2.8gw	
740603	
Res-403/230	
Lf6480 6a 480vac	
Res 409 / 400 Vac	
102027	
101809 Sealbar Head 15 Mm	
Res-402 Temperaturregler	
Res207	DO NOT USE**
Res 203 0 3	
42330k405060w242	TRANSFORMER
102314	
740702	TEMPERATURE CONTROLLER 230VAC 0-300DEG CELSIUS
Wa-85-2	
(881105) Type:Pd-5 Potentiometer	
Res407230v	RESISTOR
882130	
Res-403	INCOMPLETE-PART NUMBER DO NOT USE
740703 , Type Res-407/400vac	
740102	
4-P-116	
885107	
Pex-W5	Current transformers for RES and UPT temperature controllers RoHS and REACH compliant CE and UL compliant DIN rail mounting (DIN rail TS35) Weight: 0.18kg *** Successor model for the current transformers PEX-W2, PEXW3, PEX W4 ***

883200 885105	
Res-242	INCOMPLETE-TEMPERATURE CONTROLLER 0-300DEG C
740903	
Res-406/400vac (740603)	
885104 Current Transformer Pex-W2	
740303 Resistron Res-403 400vac Temperature Controller	
500-1000w	
744021	HEAT SEAL CONTROLLER 440V 115VAC
740603, Res-406/400vac	
Res-401/400vac Controller	
885441	
740203 Thermocontroller Res-402 (Res-402/400vac)	
Art.Nr. 744512 Model: Res-445-L/230vac	
885650 Communication Interface Ci-Usb-1	
744013	
740203 , Type Res-402/400vac	
Tfa-1	
Upt-250/2,8 Gw (602500)	UPT-250/2,8 GW Heatseal bar length: 250 mm, width: 2,8 mm, surface glaze , temperature profile without peak weight: 0,55 kg NEW : M7 thread for cooling water NOT for use in wet or aggressive/corrosive environments Zolltarif-Nr.: 84229090
Pex-W3	
Res-5010.00/230vac - , By 7501000 , Type Res-5010	
Res-420-L/400vac	RESISTRON temperature controller for heating conductors Front panel mounting, 400VAC, fault diagnosis, LC display (green), alarm relay, 300 ° C / 500 ° C Weight: 0.65kg
Res-5011.00 7501102 230vac	
610229 Upt-K-600/4.8-Gc-L-15 Oem 610229 Upt-K-600/48-Gc-L-15	
(886200) Aktiver Vorwiderstand	
610223 Oem!! Bar,Welding	
888487 Impuls-Transformatortr-2.0/121 2000va 400vac	
740702 / Res-407/230vac	
740102 / Res-401/230vac Resistron-Temperaturregler Für Heizleiter	
885107 Current Transformer Pex-W5	

651071 - Obsolete, Replacment 651059	
72081	
742013 Res-420-L/400vac	
Res-130	RESISTRON
B-075415	
Res-407/230vac	RESISTRON temperature controller for heating conductors DIN rail mounting, 230 VAC, fault diagnosis, Alarm relays, isolated analog inputs / outputs, 300 ° C / 500 ° C Weight: 0.6kg
Res-220-0-3	
Res20303400v	CONTROL
610201 - Oem!	
Lf-35480	Netzfilter für RES-Regler, 35A, 480VAC Gewicht: 1,8kg
Pd3	
Res401230	RESISTOR
740843	
E6014431	
Resistron Res-401 Temperature Controller	
103016	
742012	
Msw-2 045623 Current Transformer	
881103	
Res420lcd	CONTROLLER
Ex-W2 , Pex-W3	
800026	
Res-445-V/230	TEMPERATURE CONTROL 230VAC
Res-203	INCOMPLETE-TEMPERATURE CONTROL 230VAC 50/60HZ
Pex-W3 Current Transformator	
Lf-06480 / 885500 Rectifier Filter	
Lf-06480 Mains Filter	
Res-420	
740206 Thermoregler Ropex Res-402\230vac-Ac (With Digital Autocal-System-Signal, Terminal 16)	
Res409	CONTROLLER
742012 Res-420-L/230vac	
740303	
Res24215	TEMP CONTROL
744513 / Res-445-L/400vac	

[Res-402 Temperaturregler 400vac](#)

[Resistron Res - 5011](#)

[885106 Pex-W4stromwandlerce Und UI
Konformhutschienenmontage \(Din-Rail Ts35\)](#)