



Rotech

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Rotech** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Rotech T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
TCR3MVSAZK	TCR module Crouzet 83.161.301W2 Makrolon lid, Vestamid base Display ON + OFF, Yellow/red visual indicator with solenoid valve connection M12x1.5 and blanking plug, with short wave, without console
DOP180L240AL	swivel angle 180° shaft spacing 240 mm 376 x 140 x 52 mm Doppler module for use a second limit switch box without consoles without reinforcement plate (to be defined in case of order) Anodized aluminum, RAL 3020 and RAL 7001 for both drive directions
TPFF25EMVAZA2	TCR module P+F NBN3-F25F-E8 Lid Makrolon, base Vestamid display "OPEN + CLOSE" black 144/64/70, number "OPEN + CLOSE", Kl.Plan KPS23S8SM, with stainless steel shaft, without bracket
PPFF25NPSVAZ	PB module 1x P+F NCN3-F25F-N4P II 2G Ex ia IIC T6 Gb TÜV 99 ATEX1479 X Feedback Open+Close PRB housing Ø80x50, Base Vestamid black with visual indicator red/yellow, System connection: 1x cable gland M20x1.5 Protection class IP65 without console
TPF3SVVAZ	TCR module 2x P+F SJ3.5-SN II 2G Ex ia IIC T6 Gb PTB 00 ATEX 2049X Feedback Open+Close Vestamid housing System connection: 1x cable gland. M20x1.5 without console End position setting: Cable gland color: ----- B = End position damped U = End position undamped BL = M20x1.5 blue SW = M20x1.5 black
Etlogsa1	
Hppf2v3emvaz15	
Tcr8mvaz2m12	

Rsep-4-Vn	
Rtc260f640s.N.31	
Tpf25emvaz	
Cpf3sastaz0	
Pf3nlvfaz0c	
TCR3MVAZ	TCR module 2x Crouzet 83.161.301W2 Feedback On+Off Protection class IP65 Makrolon lid, clear - Vestamid base, black Dimensions 144x64x74 mm System connection: Cable gland M20x1.5 Temperature: -25 ... +85°C Terminal diagram KPM23S8SM without console
Ppf25esvvazwa	
Emv5232bi24dcttoa	
Pf3nfvaz0	
R1a+u1	
Tcr3mvsazk	
Tpf3emvaz	
Tl3	
Cr3maz	
Ppf25epmvaz	
Tcr3mvsaz	
Ppf25esmvaz	
Et4ogsa4	
Pcr3mvazwa	
Acr1areaz10m	
Ccr3astaz0	
Bamv003	
Emv52323124dcttoa	
Tpf3nvvaz	
Pcr3mvaz	
Tcr1vvazk	
T2a2	
85365080	
Pcr8svaz	
Bamv002	
Rsep-4-Va	
Et3ogsa3	
Hppf2v3emvaz30	
Tcr1vvaz	

Pcr3svaz
Tpf2v3emvsaz
Pff25eaz1
Et2ogsa2
Tcr8mvazm12
Pcr3sva - 61301 W2 ; Pb Crouzet 83
Tcr1vvazk 85365080
Tcr3mvazulcsa
Tcr1vvazm12
Tcr3mvazk