

Rueger

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Rueger Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rueger Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
0-60°C, TGL=400mm, TWL=250mm,	Swivelling Cap Connection U TI113-611 THI130U/0-60°C/TGL=400mm/TWL=250mm
Modell S80-TC	S80=S=T=K=N=1=2=3=7=O=R=C3=15000=350=_=5P=T S80 thermocouple sensor with mineral insulated cable S Version TC standard T Diameter measuring insert 1/4" or 6.35 mm K Type K thermocouple - measuring range: -200 ... +1100°C N Accuracy class according to ANSI MC 96.1: Standard class 1 sensor element isolated 2 measuring circuit double 3 Sheath material Inconel 600/ 2.4816 7 Cable connection not stripped O Extension cable PTFE (Teflon) R Extension cable: armored outer sheath, without anti-kink spring C3 process connection compression fitting 1/2 NPT, AISI 316 15,000 cable length Lc= 15,000 mm 350 sensor length L= 350 mm _ Without certificate 5P calibration certificate 5 points T marking with stainless steel tag without transmitter
ASHCROFT® Bimetal Thermometer Model A	100=AM=074=E=255=0_160C=_=EAYW=EN Class 1 according to EN 13190 Case, connection and stem stainless steel Bayonet style case, protection IP66 100 Dial size 100 mm AM Thermometer model A, stem diameter 6 mm 074 Adjustable union connection 1/2 NPT female E Every angle connection 255 Stem length 255 mm Standard instrument glass window EA External zero adjustment YW Case and ring material stainless steel 316L EN Product documentation in English Range: 0/160 °C

Ürün	Açıklama
THERMOMETER,RUEGER,THI100A+AMU, 380 MM	Thermometers, Dial, Bi metal Diameter, dial 100 mm Type, dial connection 1/2 inch NPT Material specification, case AISI 303/1.4305 Diameter, stem 6 mm Length, stem 380 mm Calibration units, scale Degrees Celsius Temperature range from 0 to 160 Manufacturer RUEGER Manufacturer's catalog No. THI100A+AMU
S20	Input: 1 x Pt100 cl.B IEC751
Pbx100xa	
Pmd150xk General Purpose Gauge	
Pbx100xa Rohrfedermanometer	
Tmi100a Amx+ Tw10412	
Tmi100a+amx	
Tmi100a + Amu	
Ppc 96x192mm	
Pbx150xa Rohrfedermanometer	
Tco075	
Pmd100xk Differential Pressure Indicator	
Typ Tmi100a + Amx, L1 = 350 Mm	
Pmd150xk	
Pbx150xa	
Pmx150xa,lp55	
S01.1.81baba.B--X-.-.-.-.-	

Ürün	Açıklama
Thi130a+amx	
Pmd100xk	
R1/2quot;Npt,4quot;,8x470mm	
Tmi100u	
Tta070/770	
Tmi100a + Amx, L1 = 250 Mm	
Rppy -1 - +3.5 Barg 2? Npt Female 150 Rf	
Pbx150xa,(Dial 150mm),lp67	