

## Sab Cable

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Sab Cable** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Sab Cable T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">L0784-0502</a>	SD 200 C 5 x 0.25 mm <sup>2</sup> CU surcharge: CU: 25.9 kg / 1000m Outer diameter approx.: 4.7 mm Wire identification: based on DIN 47100 Color: pebble gray Operating temperature: moving: -40°C/+90°C; fixed: -50°C/+90°C Operating voltage: max. 350 V
<a href="#">L0433-9249</a>	CABLE AGL NC 4X0.5MM2
<a href="#">L0784-1203</a>	SD 200 C 12 x 0.34 mm <sup>2</sup> Type: SD 200 C Construction: 12 x 0.34 mm <sup>2</sup> Outer diameter approx.: 6.7 mm Wire identification: in accordance with DIN 47100 Color: pebble grey Operating temperature: moving: -40°C/+90°C not moving: -50°C/+90°C Operating voltage: max. 350 V
<a href="#">T545-031-310</a>	Insert resistance thermometer N545-000015* 066-2001 Construction: Measuring resistor: 1 x Pt100 according to DIN EN 60751 Class B (film resistance -50°C/+500°C) Circuit: 4-wire Measuring point: Measuring tip: Ø 8 mm / 118° Material 1.4305 Nominal length [NL]: 18 mm Locking lug: Inner diameter = 12.2 mm / 1 x bayonet / B1F8 Spring length: 200 mm Connection cable: L0470-0418 (TGV 4x0.18mm <sup>2</sup> Ø3.8mm max.+285°C) Connection cable length: 3000 mm Connection

end: M4 fork cable lug Additional information: Temperature measuring range: 0 °C/+285 °C Labeling: self-laminating label: article number, order number, SAB Note: Connection end: M4 cable lug

[07710725 = Sd 90 C Tp 7x2x0.25mm](#)  
[Gt; Require Moq \(500m.\) /Alternative](#)  
[Gt; 0789-0725](#)

[Mt 400,Cable 24x2,5](#)

[Pb 632 2 X 0,34 Mmã178;](#)

[L0315-9...](#)

[Mt 200,Cable 4x1.5](#)

[0789-0725](#)

[Mt 2100,Cable 24x2,5](#)

[Art.-Nr. :3185-0725 S180 C Ht](#)  
[7x2,5mm2](#)