Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Satam

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Satam Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Satam Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
517564-20	
518028	
600149	
600151	
601237	
601607	
601714	
603802	
EC29	
XAD 36	
ZC17.250	PD Meter with mechanical register VR7887 (unit Liter) 6'' horizontal positive displacement flow meter for refueling trucks / facilities: Max flow rate up to 250 m^3/h (4 200 l/mn), Accuracy class : 0,5 (OIML R117-1),accuracy with linearization <0.1% (In association with a calculator only) on a flow rate range 1 to 10, typical repeatability 0.02%, linearity better than 0.1% Maximum working pressure 10 Bar, test pressure 15 Bar. Medium: Diesel/ Gasoline/ to be confirmed MA21 250 triple capsule design flow meter, iron body cast, carbon vanes, aluminum rotor, cast Iron inner and outer covers and high Nitrile seals. Flow direction: left to right or right to left / to be confirmed6'' ductile iron standard manifold, inlet and outlet flanged 6 inch ANSI DIN ASA150 150lbs RF flat face. AB 21 mechanical stepless adjustment mechanism VR Gear plate + VR7887 mechanical indication meter register – decaliters, designed for delivery operations with resettable

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	register and non resettable totalizer. The register totalizes and displays high-speed deliveries and transactions in large, easy-to-read figures.ATEX Marking : II 2 G c T4 (Mechanical version) / Ex IIA T4 Gb (Including electrical parts) Ambient temp. range (°C) : [-20°C?Tamb?+55°C]
ZC 17-24/24 H R/VR7887 LR	SATAM vane meter, DN50 step by step Adjusting gear AB35 VR roller counter R/VR7887 Display: LITER Measuring range: 40-400 l/min (MID) 40-400 l/min (EEC Approval) 40-400 l/min (domestic) (calibrated measuring range 1:10) Cyclic volume: 0.4 liters Smallest delivery quantity: 100 liters (MID) 100 liters (EEC Approval) 20/50/100 liters (Domestic) Temp. range: -20 /+90°C (calibrated range -10 /+50°C) Flow direction: from left to right Connection: both. Square welding flanges, steel Installation length: 180 mm Nominal pressure 8 bar Lid: Steel, Kanigen Rotor: aluminum Slider: carbon Ball bearing: stainless steel Seals: FKM
SATAM ZC17 330 MECA	8'' horizontal positive displacement flow meterMax flow rate up to 330 m^3/h (5 500 l/mn), Accuracy class : 0,5 (OIML R117-1),on a flow rate range 1 to 10, typical repeatability 0.02%, linearity better than 0.1% Maximum working pressure 10 Bar, test pressure 15 Bar. Medium: diesel/ to be confirmed MA21 330 - 4 capsules design positive displacement flow meter, iron body cast, carbon vanes, aluminum rotor, cast Iron inner and outer covers and high Nitrile seals. Flow direction: left to right or right to left / to be confirmed 8'' ductile iron standard manifold, inlet and outlet flanged 8 inch DIN ASA150 150lbs RF AB 21 mechanical stepless adjustment mechanism with VR Gear plate VR Gear plate + VR7887 mechanical indication meter register – decaliters, designed for delivery operations with resettable register and non resettable totalizer. The register totalizes and displays high-speed deliveries and transactions in large, easy-to-read figures. ATEX Marking : II 2 G c T4 (Mechanical version) / Ex IIA T4 Gb (Including electrical parts)Ambient temp. range (°C) : [-20°C?Tamb?+55°C]

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
ZC17 330 MECA	SATAM 8" horizontal positive displacement flow meterMax flow rate up to 330 m³/h (5,500 l/mn), Accuracy class : 0.5 (OIML R117-1),on a flow rate range 1 to 10, typical repeatability 0.02%, linearity better than 0.1% maximum working pressure 10 bar, test pressure 15 bar. Medium: diesel/to be confirmed MA21 330 - 4 capsules design positive displacement flow meter, iron body cast, carbon vanes, aluminum rotor, cast Iron inner and outer covers and high Nitrile seals. Flow direction: left to right or right to left / to be confirmed 8" ductile iron standard manifold, inlet and outlet flanged 8 inch DIN ASA150 150lbs RF AB 21 mechanical stepless adjustment mechanism with VR Gear plate VR Gear plate + VR7887 mechanical indication meter register – decaliters, designed for delivery operations with resettable register and non-resettable totalizer. The register totalizes and displays high-speed deliveries and transactions in large, easy-to-read figures. ATEX Marking: II 2 G c T4 (Mechanical version) / Ex IIA T4 Gb (Including electrical parts)Ambient temp. range (°C): [-20°C?Tamb?+55°C]
ZC 17-80/150 H DIN ST R/VR7887 AV RL	SATAM drive valve counter, DN100 stepless adjustment gearbox AB21 VR Roller counter R/VR7887 Display: LITER Flow rate: 250-2500 L/min (MID) Flow direction: from right to left Flange connection: both sides DIN, DN100, PN16, steel (AMERON) coated) Medium: Aviation fuels Jet A1
ZC 17-80/150 H DIN ST R/VR7887 AV LR	SATAM drive valve counter, DN100 stepless adjustment gearbox AB21 VR Roller counter R/VR7887 Display: LITER Flow rate: 250-2500 L/min (MID) Flow direction: from left to right Flange connection: both sides DIN, DN100, PN16, steel (AMERON) coated) Medium: Aviation fuels Jet A1
Ems48 G / (Zce11-48)	
601469 / 0324633-007 (997110)	
602846 Ab21 Lr	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Zc 17-24/24 H R/Vr7887 Lr	
507007	
435169	
Ec.30	
Zc 17-80/150 H Ansi R/Vr7887 Av Lr	
601543	
Zc 17-80 140823 (992771)	
Zc.17-12	
Zc 17-24	
140824	
Zc17 330(H)	
F95 Zc17 24/24	
601880 / 516209	
Zc.17.80/150	
140823	
Ec30-20	
514737	
Fzc 17-80/150 H Ansi Emr Lr	
Zc 17-80/80 H Tw1 R/Vr7887 Lr	
Zc17-250	
Zce5 Equalis	
Fzc 17-80/250 H Ansi Rst Kurz Epox Emr4 Av Lr	SATAM driving slide meter, DN150 stepless adjustment gearbox AB21 Display head EMR4 elec. Counter, quantity display, presetting, currency, TMU, ATEX Display: Dekaliter, LITER, GALLONS z. B. Measuring range: 416-4160 l / min (MID) (calibrated measuring range 1:10) Cyclic volume: 6.82 liters

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	smallest delivery quantity:1000 liters (MID)1000lt Temp. Range: -20 / + 90 ° C (calibration range -10 / + 50 ° C) Flow direction: from left to right Connection: both. 6 "ANSI 150lbs flange, steel Installation length: 400 mm (short pipe connection piece) Nominal pressure: 10 bar Housing: nodular cast iron Lid: steel, kanigen--Rotor: aluminum Driving slide: coal--Ball bearing: stainless steel Seals: FKM--Medium: mineral oils, solids-free incl. IB supply unit !!! Before ordering please check the flow direction!
Repair Kit For Zc17 80/250	
Zc 17-24/24	
354391 (991732)	
601722 / Zc 17-150 Lr	
Zce 17 150 (H)	
435414 (992119)	
Zc 17-80/250 H Ansi Rst Kurz R/Vr7887 Rl (603357)	
Zc 17 80/250	
356660 (989126)	
600773, Zc 17-24/48	
Zc.17.80	
Zc 17-24/48 H R/Vr7887 Lr	
435413 (992100)	
Satam-Pin-F3;R-Zc-17-12-Istanbul-Turkiye	
601195 / Zc 17-150 Rl	
500961-10	
Zc 17-80 140824 (992780)	
Zc 17-12/12 H R/Vr7887 Lr	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
364858	
Zc 17-24/48	
Zc 17-80/250 H Ansi Rst Kurz R/Vr7887 Rl	SATAM Rotary Vane Bulkmeter, 6" stepless Adjuster Unit AB21 VR Register R/VR7887 - reverse gearing Indication: DECALITRES Flow direction: from right to left Flange connection: both sides 6"ANSI 150lbs, short Manifold, 400mm Zolltarifnummer: 90282000
364499 (991694)	
Zc17 250(H) Meca	
Zc17 [80/150]n [15069 Ce]	
Zc 17-24/24 H Lr	
Zc17-24/24. (600300)	
324613-001 Td-42284 , 601469 / 0324633-007 (997110)!!!	
Zc 17-80/150 H Din St Lr	
Vr1871	
Zc.17-150	
Zce5-80	
603696 / 364477-20	
Zc 17-80/150 H Tw3 R/Vr7887 Lr	
Ac30 / 516038-50	
Zce 17 80 (H)	
Zc17 48	
600002 R/Vr 7887	
600431 Zc 17-24/24 H R/Vr7887 Rl	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.