Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Schischek

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Schischek Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Schischek Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Inmax 100-Y	
Inmax 100-S	
Exmax 100-Y	
Exmax 100-S	
057.1910	
090.3160	
1.6-Bin-FR6/057.9002	
5.10-Y	
5.10-YF	
BETAFLAM 145	
CTF-50	
DBK-2G	
ExBin-FR6 / 055.3005	
ExBin-P-100	
ExBin-P-500	
ExBin-P-500	differential pressure switch, 0-500Pa, 24VAC/DC, output 1x contact, display, IP66, ATEX 1,2,21,22 Electrical, explosion-proof differential pressure switch, binary. Certified according to ATEX, IEC, EAC. Highest protection class for all gases, mists, vapors, dusts in zones 1, 2, 21 and 22. Nominal voltage: 24VAC/DC

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Connection: Ex-e terminal box, incl. screw terminals 0.14-2.5mm² Measuring range: 0-100/500/5000 Pa, model dependent Overload protection: See datasheet Output: Potential-free contact Display: LCD actual value display, switching point indication via LEDs Protection rating: IP66 Ambient temperature: -20°C...+50°C Optionally available: ExBin-P-...-2 Additional switching point and potential-free contact Kit 2 pressure hose (2m), inner diameter 6mm, 2x plastic connection nipples MKR mounting bracket for installation on round air ducts up to 600mm in diameter
EXBOX-3P / 090.5000	
ExBox-Y/S	
ExBox-Y/S Ex terminal box for ExMax-..-Y or -S	
ExCos-D	ExCos-D transmitter for ExPro-C.. temperature & humidity sensors, 24VAC/DC, display, IP66, ATEX 1,2,21,22
ExCos-D / 056.3040	
EXCOS-D Ex	
ExCos-P	
ExCos-P-100-OCT	
ExCos-P-1250	
EXCOS-P-500 / 056.3010	
ExCos-P-500-OCT	
EXL-IMU-1	
EXL-IRU-1 / 050.2000	
EXM?650	
ExMax-15-BF	
ExMax-15-BF-VAS	
ExMax-15-F1	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
ExMax-15-SF1	
ExMax-15-YF	
ExMax-30-SF-CTM	
ExMax-30-YF-CTM	
EXMAX-5.10 / 090.1000	
ExBox-Y/S Ex terminal box for ExMax-..-Y or -S	
ExMax-5.10-YF	
ExMax-50-SF3	
ExMax-50-SF-CTM	
ExMax-8-SF1	
ExPro-BTF-50 / 057.8040	
EXPRO-CF-200	ExPro-CF-200 humidity sensor pluggable, suitable for ExReg/Cos-D or RedReg/Cos-D, 0 to 100 %RH, 200 mm, duct application, zone 1,2,21,22 ATEX
ExPro-CT-100	
ExPro-CT-100 Ex	
ExPro-CT-200	ExPro-CT-200 Temperature sensor pluggable, suitable for ExReg/Cos-D or RedReg/Cos-D, -40 to +125°C, 200 mm, duct application, zone 1,2,21,22 ATEX
ExPro-CTF-100	
ExPro-CTF-100 / 057.6045	
ExPro-CTF-50	
ExPro-TT-72	
EXRUN-25.50 / 090.4003	
ExRun-5.10-Y	
GH-6 Gegenhalter fur EXM-650	
InBin-P-5000	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
InBox-3P Klemmkasten passen zu InMax	
InBox-BF	
InBox-BF-CT / 090.5630	
InBox-Y/S Klemmkasten fur Max-..-Y or -S	
InMax-15.30-Y	
InMax-30-BF-CTM / 090.2855	
InMax-5.10-SF, 90°, 5/10 Nm, 24...240VAC	
InPro-CT-100	
INPRO-TT-72 / 057.2220	
KB-S	
Kit-2-Cos/Bin-P	
Kupplung fur InRun 25.50-Y	
MKK-S	
MKK-S / 090.3030	
MKK-S Montagebugel fur Klemmenkasten fur InMax-15.30-Y	
MKK-S Montagekonsole	
NOP-1024Y	
REDBIN-P5000-2	
RedBin-P-500	
RedBox-Y/S / 090.5110	
RedCos-D	
RedMax-15-F	
RedMax-15-SF / 090.1136	
RedMax-45.90-F-A 4kg	
RedMax-5.10-BF / 090.1155	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
RedMax-5.10-YF	
SCLA11REZ001	
TFR-2G	
TFR-2G3D Pt1000 DIN	Ex-rated room temperature sensor, IP65, -40 to +60°C
WFBK-2G	
InMax-8-SF1	Rotary actuator with 1 second spring return and 2 integrated limit switches (5°/85°) for the safe area
ExMax-8-SF1	Rotary actuator with 1 second spring return and 2 integrated limit switches (5°/85°) for zones 1, 2, 21, 22
TFR-2G3D Pt100 - 057.1700	
ExCos-D	Electrical, explosion-proof transmitter. Certified according to ATEX, IEC, EAC. Highest protection class for all gases, mist, vapours, dust in zones 1, 2, 21 and 22. Rated voltage: 24VAC/DC Connection: Ex-e terminal box, incl. screw terminals 0.14-2.5mm² screw connection for ExPro-C... sensors Output: 0-10V or 4-20mA Display: LCD actual value display Degree of protection: IP66 Ambient temperature: -20°...+50°C Optionally available: ExCos-D-...-A Two additional, intrinsically safe analog outputs for e.g. external digital displays VL3 sensor extension cable, 3m MKR mounting bracket for attachment to round air ducts with a diameter of up to 600mm
ExPro-CT-50	Temperature sensor suitable for ExCos-D/RedCos-D, -40..+80°C, sensor length: 50mm
MKR-VA/AL /	Mounting bracket for attachment to round air ducts with a diameter of up to 600mm
WS-CBR	Weather protection made of stainless steel, suitable for all ..Cos,Bin,Reg
RedMax-15-SF	Drive SCHISCHEK RedMax-15-SF Explosion-proof electric drive SCHISCHEK RedMax-15-SF
RedBox-Y/S	RedBox-Y/S Ex Terminal box for RedMax-..-Y or -S
KB-S Clamp for round shaft incl. bracket for Max s	
KB-S	KB-S Clamp for round shaft incl. bracket for Max size S

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
MKK-S	MKK-S Mounting bracket Box to Max actuators size S
WS-S	WS-S Weather shield stainless steel for Max size S
ExMax 5.10 – BF ve ExBox – BF	Spring Return Damper Motor and Ex Box
Ex Max-15-SF	090.1036 ExMax-15-SF Ex-proof rotary actuator 95°, 24-40VAC/DC, 15 Nm, IP66, 3-120 sec, spring. 10 or 3 sec, HS 5° and 85°, Zone 1,2,21,22 ATEX
ExBox-Y/S	090.5010 ExBox-Y/S Ex terminal box for ExMax-..-Y or -S
KB-S	090.3010 KB-S clamp for round flap axles 10-20mm and square axles 10-16mm for Ex Red-InMax size S
MKK-S mounting bracket for ...Box terminal boxes	for Ex-Red-InMax size S
KB-S clamp for round flap axles 10-20mm	and square axles 10-16mm for Ex Red-InMax Size S
WS-S weather protection roof ..Max-S	stainless steel V4A / AISI316
ExMax-5.10-SF	Ex-proof rotary drive 95°, 24-240VAC/DC, 5 or 10 Nm, IP66, 3-120 sec, spring. 10 or 3 sec., HS 5° and 85°, Zone 1,2,21,22 ATEX
ExRun-25.50-Y Ex-protected valve actuator	24-240VAC/DC, 2500 or 5000 N, 0..10V, 4..20mA, IP66, 2-12 sec/mm, Zone 1,2,21,22, ATEX
ExRun-5.10-Y Explosion-proof valve actuator	24-240VAC/DC, 500 or 1000 N, 0..10V, 4..20mA, IP66, 2-12 sec/mm, Zone 1,2,21,22, ATEX
InMax-5.10-BF fire protection drive 95°,	24-240VAC/DC, 5 or 10 Nm, open-close, 3-point, IP66, 3-120sec., 2xEPU, Spring.10 o.3 sec
InPro-TT-72 temperature trigger for InMax-..-BF at	72 °C, cable length 1m
ExMax-15-SF Explosion-proof rotary actuator 95°,	24-40VAC/DC, 15 Nm, IP66, 3-120 sec, spring. 10 or 3 seconds, HS 5° and 85°, Zone 1,2,21,22 ATEX
InMax-15-SF rotary actuator 95°,	24-240VAC/DC, 15 Nm, open-close, 3-point, IP66, 3-120 sec, spring.10 or 3 sec.,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	2integrated Auxiliary
InMax-30-SF	
InMax-50-YF	Electric rotary actuator 95°, 24-240VAC/DC, 50 Nm, 0...10 V, 4...20 mA, IP67, 40-150 sec, spring 20 sec InMax-...-YF size M with spring return Electric rotary drive with constant control, emergency function and robust aluminum die-cast housing. Rated voltage: 24-240VAC/DC Control: 0-10V, 4-20mA, 3-point Feedback: 0-10V, 4-20mA Torque: 30 to 50Nm, depending on the model Running time: 40/60/90/120/150s, adjustable Spring return: 20s Ambient temperature: -40...+50°C Rotation angle: 95° including 5° preload Protection class: IP 66 Axle mount: 16x16mm square More functions: Integrated, regulated heating Constant, load-independent running time Position indicator Connection cable 1m, not replaceable
InMax – 30 - SF	
EXBIN-FR-6	El.ex protected frost protection thermostat, 6m capillary, 24VAC/DC, IP66, -5 to +15°C, output 1 contact, Zone 1, 2, 21, 22, ATEX ExBin-FR Electric, explosion-proof frost protection thermostat. Certified according to ATEX, IEC, EAC. Highest protection class for all gases, mists, vapors and dusts in zones 1, 2, 21 and 22. Rated voltage: 24VAC/DC Connection: Ex-e terminal box, including screw terminals 0.14-2.5mm² Capillary: 3m or 6m Output: Potential-free contact Switching point: Mechanically adjustable Display: switching point display via LEDs Protection class: IP66 Temp. range: switching point -10°...+15°C Optionally available: Kit 1.3 capillary feedthrough, mounting brackets and 4 mounting brackets for frost protection thermostat ..Bin-FR3 Kit 1.6 capillary feedthrough, mounting brackets and 8 mounting

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	brackets for frost protection thermostat ..Bin-FR6 MKR mounting bracket for attachment to round air ducts up to a diameter of 600mm
98837006	INMAX-15.30-Y
ExMax-5.10-BF Rotary Actuator	
EXMAX-8-F1	ExMax-8-F1 90° rotary actuator, 24-240VAC/DC, 6Nm, open-close, 3-120sec, spring ~1sec, ATEX 1,2,21,22 ExBox-3P Ex-terminal box for ExMax-.. 3-pos., ATEX 1,2,21,22 MKK-S mounting bracket for ...box terminal boxes for Ex-Red-InMax size S
EXBIN-P500	ExBin-P-500 El.ex-protected differential pressure monitor, 0-500Pa, 24VAC/DC, IP66, display, 1-stage, output 1 contact zone 1,2,21,22, ATEX Installation Kit-2 Cos-P/Bin-P/Reg-V - 2 pieces plastic connection nipples, 2 m PVC hose MKR mounting bracket for mounting on round air ducts up to 600 mm in diameter
TR.EX-IY.EX-RT	
exmax-15-fs8	
ExPro-TT-72 safety temperature trigger 72°C for Ex/RedMax-..-BF	sensor length 65mm, cable length 1m
InBin-P500	
VL3 sensor extension cable 3 meter for Cos/Bin/Reg, shielded	
ExPro-TT-72	Ex-protected temperature release for Ex/RedMax-..-BF at 72°C, cable length 1m
Installation-Kit-2-Cos	Bin-P/Reg-V 2m pressure hose and 2x plastic fittings
TR.EX.IY.EX-RT	
ExBin-P500	Differential pressure switch
ExPro-CTF-200	ExPro-CTF-200 combi sensor connectable to ExCos-D or RedCos-D, -40 to +125°C, 0 to 100 %rH, 200mm,
Tfr-2g Sensor,Room Temperature,Tfr-2g	
Exmax50sf,50n.M	Type, operating Temperature rating: ELECTRICAL -40 TO +70 °C (STORAGE) Type: ROTARY, 1/4 TURN

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Series, Type, motor Mat, housing: ExMax BRUSHLESS DC ALUMINIUM DIE CAST, PAINTED Torque, spring: 50 N.m Torque, motor: 50 N.m (MINIMUM) Power supply: 24 TO 240 Vac/dc Power consumption: 5 W (HOLDING) Please see attached photo
Scla11rez001 Schischek Frostschutzthermostatexbin-Fr-6exbin-Fr-6	
Inmax-5.10-Bf	ACTUATOR,RTRY,SCHISCHK,INMAX51+,24TO240V Valve actuators Type, operating SPRING RETURN Size, valve M S Voltage 24 TO 240 Vdc/ac Torque 30 Nm Zone SAFE AREA With 2 contacts + circuit CODE:G04 Certification: TYPE 2.1 AS PER EN 10204:2004
Redbin-P500	
Exmax-15-F1 Elektroantrieb	
Exmax 15-Sf	
Redmax-15-Sf	
Inmax-8-Sf1	
Exl-Im-9182	
Exmax 5.10-Sf	
Redmax 15sf-S3	
Exmax-5.10-S	
Installation Kit 2-Cos/Bin-P	
Excos-P100	DIFFERENTIAL PRESSURE SENSOR
Inmax-50-Sf	
Exl-Ir-9170	
Kit-2-Cos/Bin-P Installation-Kit-2-Cos/Bin-P (2m Druckschlauch Und 2	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
Kunststoffanschlussnippel)	
MFK-ExPro	12 mm mounting flange for duct installation for Cos/Bin/Reg
ExBin-D	
ExPro-BT-50	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.