



Schischek

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Schischek Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Schischek T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Inmax 100-Y	
Inmax 100-S	
Exmax 100-Y	
Exmax 100-S	
057.1910	
090.3160	
1.6-Bin-FR6/057.9002	
5.10-Y	
5.10-YF	
BETAFLAM 145	
CTF-50	
DBK-2G	
ExBin-FR6 / 055.3005	
ExBin-P-100	

ExBin-P-500	
ExBin-P-500	differential pressure switch, 0-500Pa, 24VAC/DC, output 1x contact, display, IP66, ATEX 1,2,21,22 Electrical, explosion-proof differential pressure switch, binary. Certified according to ATEX, IEC, EAC. Highest protection class for all gases, mists, vapors, dusts in zones 1, 2, 21 and 22. Nominal voltage: 24VAC/DC Connection: Ex-e terminal box, incl. screw terminals 0.14-2.5mm ² Measuring range: 0-100/500/5000 Pa, model dependent Overload protection: See datasheet Output: Potential-free contact Display: LCD actual value display, switching point indication via LEDs Protection rating: IP66 Ambient temperature: -20°C...+50°C Optionally available: ExBin-P-...-2 Additional switching point and potential-free contact Kit 2 pressure hose (2m), inner diameter 6mm, 2x plastic connection nipples MKR mounting bracket for installation on round air ducts up to 600mm in diameter
EXBOX-3P / 090.5000	
ExBox-Y/S	
ExBox-Y/S Ex terminal box for ExMax-...-Y or -S	
ExCos-D	ExCos-D transmitter for ExPro-C.. temperature & humidity sensors, 24VAC/DC, display, IP66, ATEX 1,2,21,22
ExCos-D / 056.3040	
EXCOS-D Ex	
ExCos-P	
ExCos-P-100-OCT	
ExCos-P-1250	
EXCOS-P-500 / 056.3010	
ExCos-P-500-OCT	
EXL-IMU-1	
EXL-IRU-1 / 050.2000	
EXM?650	
ExMax-15-BF	
ExMax-15-BF-VAS	
ExMax-15-F1	
ExMax-15-SF1	
ExMax-15-YF	
ExMax-30-SF-CTM	

ExMax-30-YF-CTM	
EXMAX-5.10 / 090.1000	
ExBox-Y/S Ex terminal box for ExMax-... Y or -S	
ExMax-5.10-YF	
ExMax-50-SF3	
ExMax-50-SF-CTM	
ExMax-8-SF1	
ExPro-BTF-50 / 057.8040	
EXPRO-CF-200	ExPro-CF-200 humidity sensor pluggable, suitable for ExReg/Cos-D or RedReg/Cos-D, 0 to 100 %RH, 200 mm, duct application, zone 1,2,21,22 ATEX
ExPro-CT-100	
ExPro-CT-100 Ex	
ExPro-CT-200	ExPro-CT-200 Temperature sensor pluggable, suitable for ExReg/Cos-D or RedReg/Cos-D, -40 to +125°C, 200 mm, duct application, zone 1,2,21,22 ATEX
ExPro-CTF-100	
ExPro-CTF-100 / 057.6045	
ExPro-CTF-50	
ExPro-TT-72	
EXRUN-25.50 / 090.4003	
ExRun-5.10-Y	
GH-6 Gegenhalter fur EXM-650	
InBin-P-5000	
InBox-3P Klemmkasten passen zu InMax	
InBox-BF	
InBox-BF-CT / 090.5630	
InBox-Y/S Klemmkasten fur Max-...-Y or -S	
InMax-15.30-Y	
InMax-30-BF-CTM / 090.2855	
InMax-5.10-SF, 90°, 5/10 Nm, 24...240VAC	

InPro-CT-100	
INPRO-TT-72 / 057.2220	
KB-S	
Kit-2-Cos/Bin-P	
Kupplung fur InRun 25.50-Y	
MKK-S	
MKK-S / 090.3030	
MKK-S Montagebugel fur Klemmenkasten fur InMax-15.30-Y	
MKK-S Montagekonsole	
NOP-1024Y	
REDBIN-P5000-2	
RedBin-P-500	
RedBox-Y/S / 090.5110	
RedCos-D	
RedMax-15-F	
RedMax-15-SF / 090.1136	
RedMax-45.90-F-A 4kg	
RedMax-5.10-BF / 090.1155	
RedMax-5.10-YF	
SCLA11REZ001	
TFR-2G	
TFR-2G3D	
WFBK-2G	
InMax-8-SF1	Rotary actuator with 1 second spring return and 2 integrated limit switches (5°/85°) for the safe area
ExMax-8-SF1	Rotary actuator with 1 second spring return and 2 integrated limit switches (5°/85°) for zones 1, 2, 21, 22
TFR-2G3D Pt100 - 057.1700	
	Electrical, explosion-proof transmitter. Certified according to ATEX, IEC, EAC. Highest protection class for all gases, mist, vapours, dust in zones 1, 2, 21 and 22. Rated voltage: 24VAC/DC Connection: Ex-e terminal box, incl. screw terminals 0.14-2.5mm ² screw connection for ExPro-C...

ExCos-D	sensors Output: 0-10V or 4-20mA Display: LCD actual value display Degree of protection: IP66 Ambient temperature: -20°...+50°C Optionally available: ExCos-D-...-A Two additional, intrinsically safe analog outputs for e.g. external digital displays VL3 sensor extension cable, 3m MKR mounting bracket for attachment to round air ducts with a diameter of up to 600mm
ExPro-CT-50	Temperature sensor suitable for ExCos-D/RedCos-D, -40..+80°C, sensor length: 50mm
MKR-VA/AL /	Mounting bracket for attachment to round air ducts with a diameter of up to 600mm
WS-CBR	Weather protection made of stainless steel, suitable for all ..Cos,Bin,Reg
RedMax-15-SF	Drive SCHISCHEK RedMax-15-SF Explosion-proof electric drive SCHISCHEK RedMax-15-SF
RedBox-Y/S	RedBox-Y/S Ex Terminal box for RedMax-...-Y or -S
KB-S Clamp for round shaft incl. bracket for Max s	
KB-S	KB-S Clamp for round shaft incl. bracket for Max size S
MKK-S	MKK-S Mounting bracket Box to Max actuators size S
WS-S	WS-S Weather shield stainless steel for Max size S
ExMax 5.10 – BF ve ExBox – BF	Spring Return Damper Motor and Ex Box
Ex Max-15-SF	090.1036 ExMax-15-SF Ex-proof rotary actuator 95°, 24-40VAC/DC, 15 Nm, IP66, 3-120 sec, spring. 10 or 3 sec, HS 5° and 85°, Zone 1,2,21,22 ATEX
ExBox-Y/S	090.5010 ExBox-Y/S Ex terminal box for ExMax-...-Y or -S
KB-S	090.3010 KB-S clamp for round flap axles 10-20mm and square axles 10-16mm for Ex Red-InMax size S
MKK-S mounting bracket for ...Box terminal boxes	for Ex-Red-InMax size S
KB-S clamp for round flap axles 10-20mm	and square axles 10-16mm for Ex Red-InMax Size S
WS-S weather protection roof ..Max-S	stainless steel V4A / AISI316
ExMax-5.10-SF	Ex-proof rotary drive 95°, 24-240VAC/DC, 5 or 10 Nm, IP66, 3-120 sec, spring. 10 or 3 sec., HS 5° and 85°, Zone 1,2,21,22 ATEX
ExRun-25.50-Y Ex-protected valve actuator	24-240VAC/DC, 2500 or 5000 N, 0..10V, 4..20mA, IP66, 2-12 sec/mm, Zone 1,2,21,22, ATEX
ExRun-5.10-Y Explosion-proof valve actuator	24-240VAC/DC, 500 or 1000 N, 0..10V, 4..20mA, IP66, 2-12 sec/mm, Zone 1,2,21,22, ATEX

InMax-5.10-BF fire protection drive 95°	24-240VAC/DC, 5 or 10 Nm, open-close, 3-point, IP66, 3-120sec., 2xEPU, Spring.10 o.3 sec
InPro-TT-72 temperature trigger for InMax-..-BF at	72 °C, cable length 1m
ExMax-15-SF Explosion-proof rotary actuator 95°	24-40VAC/DC, 15 Nm, IP66, 3-120 sec, spring. 10 or 3 seconds, HS 5° and 85°, Zone 1,2,21,22 ATEX
InMax-15-SF rotary actuator 95°	24-240VAC/DC, 15 Nm, open-close, 3-point, IP66, 3-120 sec, spring.10 or 3 sec., 2integrated Auxiliary
InMax-30-SF	
InMax-50-YF	Electric rotary actuator 95°, 24-240VAC/DC, 50 Nm, 0...10 V, 4...20 mA, IP67, 40-150 sec, spring 20 sec InMax-...-YF size M with spring return Electric rotary drive with constant control, emergency function and robust aluminum die-cast housing. Rated voltage: 24-240VAC/DC Control: 0-10V, 4-20mA, 3-point Feedback: 0-10V, 4-20mA Torque: 30 to 50Nm, depending on the model Running time: 40/60/90/120/150s, adjustable Spring return: 20s Ambient temperature: -40...+50°C Rotation angle: 95° including 5° preload Protection class: IP 66 Axle mount: 16x16mm square More functions: Integrated, regulated heating Constant, load-independent running time Position indicator Connection cable 1m, not replaceable
InMax - 30 - SF	
EXBIN-FR-6	El.ex protected frost protection thermostat, 6m capillary, 24VAC/DC, IP66, -5 to +15°C, output 1 contact, Zone 1, 2, 21, 22, ATEX ExBin-FR Electric, explosion-proof frost protection thermostat. Certified according to ATEX, IEC, EAC. Highest protection class for all gases, mists, vapors and dusts in zones 1, 2, 21 and 22. Rated voltage: 24VAC/DC Connection: Ex-e terminal box, including screw terminals 0.14-2.5mm² Capillary: 3m or 6m Output: Potential-free contact Switching point: Mechanically adjustable Display: switching point display via LEDs Protection class: IP66 Temp. range: switching point -10°...+15°C Optionally available: Kit 1.3 capillary feedthrough, mounting brackets and 4 mounting brackets for frost protection thermostat ..Bin-FR3 Kit 1.6 capillary feedthrough, mounting brackets and 8 mounting brackets for frost protection thermostat ..Bin-FR6 MKR mounting bracket for attachment to round air ducts up to a diameter of 600mm
98837006	INMAX-15.30-Y
ExMax-5.10-BF Rotary Actuator	
EXMAX-8-F1	ExMax-8-F1 90° rotary actuator, 24-240VAC/DC, 6Nm, open-close, 3-120sec, spring ~1sec, ATEX 1,2,21,22 ExBox-3P Ex-terminal box for ExMax-.. 3-pos., ATEX 1,2,21,22 MKK-S mounting bracket for ...box terminal boxes for Ex-Red-InMax size S
	ExBin-P-500 El.ex-protected differential pressure monitor, 0-

EXBIN-P500	500Pa, 24VAC/DC, IP66, display, 1-stage, output 1 contact zone 1,2,21,22, ATEX Installation Kit-2 Cos-P/Bin-P/Reg-V - 2 pieces plastic connection nipples, 2 m PVC hose MKR mounting bracket for mounting on round air ducts up to 600 mm in diameter
TR.EX-IY.EX-RT	
exmax-15-fs8	
ExPro-TT-72 safety temperature trigger 72°C for Ex/RedMax-...-BF	sensor length 65mm, cable length 1m
InBin-P500	
VL3 sensor extension cable 3 meter for Cos/Bin/Reg, shielded	
ExPro-TT-72	Ex-protected temperature release for Ex/RedMax-...-BF at 72°C, cable length 1m
Installation-Kit-2-Cos	Bin-P/Reg-V 2m pressure hose and 2x plastic fittings
TR.EX.IY.EX-RT	
ExBin-P500	Differential pressure switch
ExPro-CTF-200	ExPro-CTF-200 combi sensor connectable to ExCos-D or RedCos-D, -40 to +125°C, 0 to 100 %rH, 200mm,
Tfr-2g Sensor,Room Temperature,Tfr-2g	
Exmax50sf,50n.M	Type, operating Temperature rating: ELECTRICAL -40 TO +70 °C (STORAGE) Type: ROTARY, 1/4 TURN Series, Type, motor Mat, housing: ExMax BRUSHLESS DC ALUMINIUM DIE CAST, PAINTED Torque, spring: 50 N.m Torque, motor: 50 N.m (MINIMUM) Power supply: 24 TO 240 Vac/dc Power consumption: 5 W (HOLDING) Please see attached photo
Scla11rez001 Schischek Frostschutzthermostatexbin-Fr-6exbin-Fr-6	
Inmax-5.10-Bf	ACTUATOR,RTRY,SCHISCHK,INMAX51+,24TO240V Valve actuators Type, operating SPRING RETURN Size, valve M S Voltage 24 TO 240 Vdc/ac Torque 30 Nm Zone SAFE AREA With 2 contacts + circuit CODE:G04 Certification: TYPE 2.1 AS PER EN 10204:2004
Redbin-P500	
Exmax-15-F1 Elektroantrieb	
Exmax 15-Sf	
Redmax-15-Sf	
Inmax-8-Sf1	
Exl-Im-9182	

Exmax 5.10-Sf	
Redmax 15sf-S3	
Exmax-5.10-S	
Installation Kit 2-Cos/Bin-P	
ExcOs-P100	DIFFERENTIAL PRESSURE SENSOR
Inmax-50-Sf	
Exl-Ir-9170	
Kit-2-Cos/Bin-P Installation-Kit-2-Cos/Bin-P (2m Druckschlauch Und 2 Kunststoffanschlussnippel)	