Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Schleuniger

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Schleuniger Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Schleuniger Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
24 V 120*120*25mm Fan 9480	
401.9008 V Set HSS Standart 16mm	
401.9570 Radius messer Set Ø 7.2mm 16 mm	
B240 Coaxial Stripping Machine	B240 programmable wire stripper for coax and Microcoaxial cable up to 9 mm - No blade change required for any of the cables that can be processed - No mechanical adjustments required when changing the cable - Machining parameters in mm² and AWG - Sequential processing of multi-conductor cables with Insulation stripping of sheath and inner conductor in programmable sequence - Optional kit for multi-conductor cables with short sheaths - Barcode scanner function - 5" color touchscreen Conductor cross-section: 0.013 - 13 mm² (36 – 6 AWG) Conductor cross-section (twisted): 0.14 - 2.5 mm² Cable diameter: 0.8 mm - 9 mm Stripping length: max. 39 mm Trigger length: max. 40 mm Stripping stages: 9 Interfaces: USB, Ethernet Scope of delivery: - HM wire stripper - Standard clamping jaws - Licensed Article Library

Schleuniger	
Schleuniger	
strimcrimp 200	crimpcenter 36s
EcoCut 3300	automatic cutting of various materials including wire, cable, flat cable, optical fiber (FO) and Round material such as hoses. - Precise and repeatable results - Menu-guided simple programming and operation - Versatile - Fast and quiet transport system Max. conductor cross-section stranded wire: 16mm2 / 8 AWG Max. transport speed: 1.6 m/s Max. passage height: 12mm Max. passage width: 100mm Scope of delivery: machine Standard knife Power cable tool set Operator's and Maintenance Manual Installation and safety instructions CE certificate Power cable Equipment: - Transport roller rubber EC3300_FR_GU - HSS knife EC3300_M_HSS - Rear panel EC3300_RB - Cable routing standard (not up to knife) EC3300_KF_ST
B300 programmable stripping machine	B300 programmable stripping machine - No article library - No blow-out unit Production is carried out exclusively via the QuickRun menu. The basic machine does not allow saving articles. Articles can only be saved using an optional article library.
B240 coaxial stripping machine	
100004017535	V-blade set HSS
B240 Coaxial Stripping Machine with Blow-Out Unit	B240 programmable wire stripper for coax and Microcoaxial cable up to 9 mm - No blade change required for any of the cables that can be processed - No mechanical adjustments required when changing the cable - Machining parameters in mm² and AWG - Sequential processing of multi-conductor cables with Insulation stripping of sheath and inner conductor in programmable sequence - Optional kit for multi-conductor cables with short sheaths - Barcode scanner function - 5" color touchscreen Conductor cross-section: 0.013 - 13 mm² (36 – 6 AWG) Conductor cross-section (twisted): 0.14 - 2.5 mm² Cable diameter: 0.8 mm - 9 mm Stripping length: max. 39 mm Trigger length: max. 40 mm Stripping stages: 9 Interfaces: USB, Ethernet Scope of delivery: - HM wire stripper - Standard clamping jaws - Licensed Article Library - Blow-off unit B240_LS
B240 Coaxial Stripping Machine with Waste Disposal	B240 programmable wire stripper for coax and Microcoaxial cable up to 9 mm - No blade change required for any of the cables that can be processed - No mechanical adjustments required when changing the cable - Machining parameters in mm² and AWG - Sequential processing of multi-conductor cables with Insulation stripping of sheath and inner conductor in programmable sequence - Optional kit for multi-conductor cables with short sheaths - Barcode scanner function - 5" color touchscreen Conductor cross-section: 0.013 - 13 mm² (36 – 6 AWG) Conductor cross-section (twisted): 0.14 - 2.5 mm² Cable diameter: 0.8 mm - 9 mm Stripping length: max. 39 mm Trigger length: max. 40 mm Stripping stages: 9 Interfaces: USB, Ethernet Scope of

	delivery: - HM wire stripper - Standard clamping jaws - Licensed Article Library - Suction unit incl. blow-out unit B240_LS_AS
B440	Coaxial End Stripping Machine
2450	
Rolls For Power Strip 9500	
50000133201	
405103143	
Cxp8015052c	POWER SUPPLY
401.9903	
401.8011	
17065	
Sts1100	
Prefeeder 2200 (403434)	
Unistrip-2500	WIRE STRIPPING MACHINE
Coaxstrip 5400	
401.7535	cutting knife
401.8012	
Ec3300	CUTTING MACHINE
Cxm-Pt20-25	
Coaxstrip 5500	
404128	
Acc436919	MOTOR
Cxm-Pt28 Pulltester 28 (2-5kn)	
300.145.510	
403865	
401.9908	
Coaxstrip 5300	
416006	
300.192.515	
421540	

Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

~~406035~~ 414738	
401.7535 - V-Blade Set Hss - 1 Set	
406036	
401.9008	
Cxm-Pt25-25	
The Main Display Screen For Model:Es9300 Seri No: 2603-2004	
Unistrip-2015	WIRE STRIPPING MACHINE PNEUMATIC
A4-0360	
Es-9300	WIRE CUT AND STRIP MACHINE
Js40010	MOTOR
Us2600ri	
401.9913	
Cxm-Pt28-10 Pulltester 28 (5-10kn)	
15150553	
300.213.501	