Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Schubert&Salzer

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Schubert&Salzer Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Schubert&Salzer Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
4040/050v31c3t1	Type 4040: ball sector valve Nominal size: DN 50 (Kvs 94; Cv 109) Item: valve Design: KS2 intermediate flange design for flanges DIN EN 1092-1 (DN25-DN50: PN40, DN65 - DN100: PN25, DN125-DN250: PN16, DN300: PN16 in flange design) Housing material: stainless steel 1.4408 or 1.4404 Seat combination: Seat ring: stellite; Ball sector: stainless steel, hard chrome-plated and lapped, hard chrome-plated retaining ring Sealing combination: sealing the bearing journal with packing PTFE; O-ring (part 15) made of VITON, media temperature: -15 ° C to + 200 ° C Drive: Pneumatic swivel drive (Air Torque) with mounting kit according to DIN / ISO 5211 Safety position: single-acting, spring closes
7010/015v1527203--B-S----0	Ident-Number 4057163 Type 7010: angle seat valve Nominal size: DN 15 Design: inclined seat Connection: NPT thread Housing material: stainless steel Seat seal: PEEK Control function: spring closes (closes against media flow) Drive: piston Ø50mm Piston springs: three springs Temperature version: high temperature version HT220 Special assembly: cone nut or control cone and piston rod secure additionally.
7031/025v292021---H	Ident-Number 4050789 Type 7031: angle seat flange valve

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal size: DN 25 Design: flange valve Connection: angle seat flange valve according to DIN EN 1092-1 PN40, Installation length according to DIN 3202 F3 Housing material: stainless steel Seat seal: PTFE Control function: spring closes (closes against media flow) Drive: piston Ø80mm Piston springs: standard spring assembly Temperature version: high temperature version
8231/080-Ss-O2-Nc	
8231/050-Cs-Ng-Nc	
8049/4p5-1s000-11-00	4058343 Digital positioner type 8049-4, 24VDC, IP65 Standard housing, standard air performance El. Connection 2x M16x1.5; pneu. Connection G1 / 8 " Standard feeler rod, indicator disc PA Customs fee number. 9032 8900
Pd225m 220	
Ident-Nummer 4082456	7010/080V10202CYK--7 Type 7010: angle seat valve Nominal size: DN 80 Design: angled seat Connection: Whitworth pipe thread Housing material: stainless steel Seat seal: PTFE Control function: spring closes (closes against media flow) Drive: membrane drive 250 cm^2 stainless steel Piston springs: 12 springs (for D250) Head piece material: head piece stainless steel and piston rod in reinforced version (16mm piston rod) Accessories: 3/2-way solenoid valve cpl. DN2, 24V DC, with plug
8040/050VB0001M--S	Ident number 4078185 Customs fee number. 8481 8079 Type 8040: GS shut-off valve (long design) Nominal size: DN 50 (Kvs 45; Cv 52) Function: GS shut-off valve, long design (type 8040) Design: GS1 wafer type PN10-PN40 (for flanges according to DIN EN 1092-1, form B) Housing: carbon steel 1.0570 or 1.0619 Safety position: spring closes Drive: piston ø80mm Springs: Standard springs Sliding washer, movable: stainless steel, SFC

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Schubert Salzer	
7010/015V101100---H	4086384 Angle seat valve Nominal size (015): DN 15, design (1): angled seat, connection (0): Whitworth pipe thread, housing material (1): gunmetal, seat seal (1): FKM (Viton), control function (0): spring closes (closes with media flow), Drive (0): piston Ø50mm, piston springs (-): standard spring equipment, Temperature version (H): high temperature version Customs fee number. 8481 8079
172*150*51 220V AC FAN	
4106824	MOVABLE SEALING WASHER DN50 -STANDARD COAL Zolltarif-Nr. 8481 9000
4094038	7080/015V401000----6 Customs fee number. 8481 8079 Type 7080: 3/2-way valve made of red brass Nominal size: DN 15 Design: 3/2 way valve mixing function Connection: Whitworth pipe thread according to DIN EN 10226-1 Housing material: gunmetal Seat seal: PTFE Control function: spring closes Drive: piston Ø50mm Piston springs: Standard spring equipment Accessories: pilot valve cpl. DN2, 230V, 50 / 60Hz, with plug
M220-00602	
4040/150V11A1T3	Ident number 2802702 Customs fee number. 8481 8099 Type 4040: spherical sector valve Nominal size: DN 150 (Kvs 810; Cv 948) Item: valve Design: KS1 wafer type construction for flanges DIN EN 1092-1 (DN25-DN50: PN40, DN80 and DN100: PN25, DN150-DN250: PN16, DN300: PN16 in flange design) Housing material: stainless steel 1.4408 or 1.4404 Seat combination: seat ring: PTFE; Ball sector: stainless steel, hard chrome-plated (max. media temperature: 170 ° C)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Sealing combination: all seals (part 13-16) made of VITON, Media temperature: -15 ° C to + 200 ° C Drive: Pneumatic swivel drive (Air Torque) with mounting kit according to DIN / ISO 5211 Fail-safe position: single-acting, spring opens
4040/150R--A1	Ident-Nummer 2801676 Nennweite(150): DN 150 (Kvs 810; Cv 948), Artikel(R): Reparatursatz komplett (mit Sitzring), Bauform(-): keine Angaben (nur bei Antrieben), Gehäuse Werkstoff(-): keine Angaben (nur bei Antrieben), Sitzkombination(A): Sitzring: PTFE; Kugelsektor: Edelstahl, hartverchromt (max. Medientemperatur: 170°C), Dichtungskombination(1): alle Dichtungen (Teil 13-16) aus VITON, Medientemperatur: -15°C bis +200°C Zolltarif-Nr. 8484 9000
8049/4P5-1S020-11-00	4059059 Digital positioner type 8049-4, 24VDC, IP65 Standard housing, standard air capacity El. Connection M12x1, 5-pin; pneu. Connection G1 / 8 Standard probe rod, indicator disc PA Customs fee number. 9032 8900
8049/EP3-1S000-11-00	Ident number 4090926 Digital positioner type 8049-ExPro-1 II 2G Ex ia T3 / T4, IP65 Standard housing, standard air flow rate, El. Connection 2x M16x1.5; pneu. Connection G1 / 8 " Standard probe rod, indicator disc PA Customs fee number. 9032 8900 Type 8049: Digital positioner type 8049 Base model: Model 8049-ExPro, II 2G Ex ia IIC T4 Gb IP65 OEM version: standard Drive type: single-acting Air output: standard air output (standard) Housing: aluminum / plastic Electrical connection: cable glands 2 x M16x1.5 Pneumatic connection: G1 / 8 " Position detection: linear potentiometer with standard probe rod (L = 99.6) Optical display: display disc for probe rod made of PA Additional modules: without additional modules Accessories: without
8049/4P6-1S000-11-00	Digital positioner Type 8049-4, 24VDC, IP65 standard housing, standard air performanceEl. Connection 2x M16x1.5; pneu. Connection G1/8" standard feeler rod, indicator disc PA

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
4023714	
8021/100VG0103M	ZWYS-2V-339 GS control valve with integrated positioner ID number 4023714 Nominal size (100): DN 100 (Kvs 154; Cv 179), function (G): control valve with pneumatic actuator type 8021, design (0): GS1 wafer type PN10-PN40 (for flanges according to DIN EN1092-1, form B), housing material (1): stainless steel 1.4408, safety position (0): spring closes, actuator (3): diaphragm actuator 125 cm², springs (-): standard spring equipment, sliding washer, movable (-): carbon material, sliding washer, fixed (-): Standard coating, stainless steel 1.4571, Kvs- / Cv-values (-): 100% (stand.), Characteristic (-): linear, positioner (W): digital positioner type 8049 ExPro, II 2G Ex ia IICT4 Gb, IP 65, signal devices (Y): feedback module RM4 for positioner type 8049 with 2 integrated limit switches according to NAMUR (EN60947-5-6)., Accessories (2): position indicator ring and stainless steel nameplate, special versions (V): with earth connection , DVGW test mark (covered with protective film), Additional special designs (339): Actuator rotated by 180 ° (supply air connection on valve outlet side, 1st Limit switch inductive Ex protected Namur M12x1 with 15m cable (P + F NJ4-12GK-SN-15M), [Ex] III 1G Ex ia IIC T6 ... T1 Ga, mounted in the safety position
4040/050V11C0T1	
7010/025V1D20203--H-S---B-93	Ident number 4081628 Type 7010: Angle seat valveNominal diameter: DN 25Design: Angle seatConnection: with butt weld ends according to DIN 11850 series 2 -Zchn.-Nr.R0112Housing material: stainless steelSeat seal: PTFE Control function: spring closes (closes against media flow) Drive: piston Ø50mmPiston design: three springs, high temperature Indicator pin, miscellaneous: hood, circlip and piston springs made of stainless steel Seals: head piece seal from Klinger Top-chem-2000 Attachments: Splash water protection M16x1 (for drive D50) Customs tariff no. 8481 8079
8021	
7010/050V1D20212----S-----92B	Type 7010: Angle seat valve Nominal width: DN 50 Design: Angle seat Connection: with butt weld ends according to DIN 11850 series 2 -Zchn.-Nr.R0112 Housing material: Stainless steel Seat seal: PTFE Control function: Spring closes (closes against media flow) Drive: Piston Ø80mmPiston springs: two springsSeals: Head piece seal from Klinger Top-chem-2000 attachments: Splash water protection D80 and D125 = G1 / 4 "or 1/4" NPT Special treatments: for low temperature applications (standard head piece

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	down to -40 ° C, long head piece -70 ° C)
IFL 4-250-10P	
Id Nr. 4098955	7010/050R102001-----S-----9-B Nominal size (050): DN 50, article (R): repair kit, design (1): angled seat, connection (0): Whitworth pipe thread, housing material (2): stainless steel, seat seal (0): PTFE, control function (0): Spring closes (with media flow closing), drive (1): piston Ø80mm, seals (9): head piece seal from Klinger Top-chem-2000, special treatments (B): for 2 Low temperature applications (standard head piece down to -40 ° C, long head piece -70 ° C) Customs tariff no. 8484 9000
7081/015V302000--H--S-------H125	4089265 Customs tariff no. 8481 8079Type 7081: 3/2-way valve made of stainless steel Nominal diameter: DN 15Item: valve design: 3/2-way valve - splitting function (spring closes) connection: Whitworth pipe thread housing material: stainless steel seat seal: PTFE control function: drive spring closes drive: piston Ø50mm piston springs: Standard spring assembly (1 spring) Head piece material: Standard stainless steel 1.4571 Packing installation: Packing installation, dead space-free (packing is below), PTFE guide rings Temperature design: Standard Accessories: without housing, screw-in seat: Standard head piece: Standard piston rod, cone, cone nut: Standard drive, indicator pin, other: Standard, special assembly: none Seals: standard attachments: none
8044/050VE0101M----A-ZC	ID number 4046530 Customs fee number. 8481 8079 Type 8044: GS control valve with piston drive (short design) Nominal size: DN 50 (Kvs 28; Cv 32) Function: GS piston control valve, short Construction (Type 8044) Construction: GS1 wafer design PN10-PN40 (for flanges according to DIN EN 1092-1, form B) Housing: stainless steel 1.4408 Safety position: spring closes Drive: Piston ø80mmSprings: Standard spring assembly Sliding disc (movable): carbon material Sliding washer (fixed): standard coating, stainless steel 1.4571 Kvs/Cv values: red. to 63% Characteristic: linear Positioner: digital positioner type 8049, 4-wire version, IP65
valve 830/032vm01-4 kvs-16	cv19 GS1 flangless design PN40 flanges acc. DIN EN 1092-1 STAINLESS STEEL BODY CF8M, POSITION WITHOUT POWER. NO CHANGE , MOTOR ACTUATOR 0.9 kN , IP65
8040/050VB0001M--S	Art. Nr. 4078185 Type 8040: GS shut-off valve (long design) Nominal width: DN 50

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	(Kvs 45; Cv 52) Function: GS shut-off valve, long design (Type 8040) Design: GS1 wafer design PN10-PN40 (for flanges according to DIN EN 1092 -1, Form B)Housing: carbon steel 1.0619 Safety position: spring closesDrive: piston ø80mmSprings: standard spring assemblySliding disc, moveable: stainless steel, SFC
8044/080VE0002M--91A1ZC	GS control valve with piston drive (short design) ID number 4064428 Nominal size (080): DN 80 (Kvs 35; Cv 41), function (E): GS piston control valve, short design (type 8044), design (0): GS1 wafer design PN10-PN40 (for flanges according to DIN EN 1092-1, form B), housing (0): carbon steel 1.0619, safety position (0): spring closes, drive (2): piston ø125mm, springs (-): standard spring assembly, sliding disc (movable)(9):STN2/STN3, sliding disc (fixed)(1): STN2, Kvs/Cv values(A): red. to 63%, characteristic (1): equal to %, positioner (C): digital positioner type 8049, 4-wire version, IP65, customs tariff no. 8481 8079
Type 7032 –	für DN65-DN80-und DN100
8049/4P6-1S000-11-00	4099713 Basic type (4P6): version 8049-4, 24VDC, IP65, OEM version (-): standard, Type of drive(1): single-acting, Air performance(S): standard air performance (standard), housing(0): aluminum / plastic, Electrical connection(0): Cable glands 2 x M16x1.5, Pneumatic connection(0): G1/8", (-): , Position detection(1): Linear potentiometer with standard feeler rod (L=99.6), Optical display(1): display disc for feeler rod made of PA, (-): , additional modules(0): without additional modules, accessories(0):
4300506	USB CONNECTOR V3.1 COMPLETE FOR PARAMETERIZATION OF SCHUBERT & SALZER DEVICES SUITABLE FOR TYPE 8049, 2030, 2032, 2040,
7010/015V101100---H	angle seat valve ID number 4086384 Nominal width (015): DN 15, design (1): angle seat, connection (0): Whitworth pipe thread, body material(1): gunmetal, seat seal(1): FKM (Viton), control function(0): spring closes (closes with media flow), Drive(0): piston Ø50mm, temperature version(H): high temperature version Customs fee number. 8481 8079
8021/100VGG003M--S---ZCPS-6F	Ident-Number 4025509,
8001/020FG1A-S	ident-no 4070067

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8021/020RGY--3	ident-no 4060208
8001/050FG1A-S-MA	ident-no 4072417
8021/050RGY--3	ident-no 4060212
(8021/015VGG003M--S-3-ZCNS-6F)	8001/015FG1A-S-M3 ident-no 4072485
(8021/015VGG003M--S-3-ZCNS-6F)	8021/015RGY--3 ident-no 4060207
8001/100FG1A-S	ident-no 4070083
8021/100RGY--3	ident-no 4060215
8001/015FG1A-S	ident-no 4072401
8021/015RGY--3	ident-no 4060207
8001/040FG1A-S	ident-no 4072427
8021/040RGY--3	ident-no 4060211
8001/150FG1A-S-MA1	ident-no 4072451
8021/150RGY--4	ident-no 4060229
8001/015FG1A-S-MB	ident-no 4070086
8021/015RGY--3	ident-no 4060207
7030/100R213052---H	ident-no 4050405
7030/080R213002---H	ident-no 4005076
7032/040R912002---H-S--K	ident-no 4083843
7032/050R912002-----S--K	ident-no 4088903
7020/025R1-20-1	ident-no 4058157
8001/100FG1A-S	ident-no 4070083
8021/100RGY--3	ident-no 4060215
8021/100AGY--3M4	Type(8021)
4105113pressure spring	
4080282	8049/4P5-1S000-11-20S--2Digitaler Stellungsregler Typ 8049-4,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	24VDC
Actuator, positioner, 8021/100AGY--3M------ZCNS-6F	
A complete set of spare parts and seals for valve	Sn: 2300620001/1 and for actuator D125 .
Springs, 8021/100AGY--3M------ZCNS-6F	
4099713	8049/4P6-1S000-11-00Basic type(4P6): version 8049-4, 24VDC, IP65, OEM version(-): standard, drive type(1): single-acting, air capacity(S): standard air capacity (standard), housing(0): aluminum / plastic, electrical connection(0): cable glands 2 x M16x1.5, pneumatic connection(0): G1/8", (-): , position detection(1): linear potentiometer with standard feeler rod (L=99.6) , Optical display(1): display disc for feeler rod made of PA, (-): , additional modules(0): without additional modules, accessories(0):
Valve	
Actuator	
7010/040V1D20212 angle seat valve	Number 4057684 nominal size (040): DN 40, design (1): angle seat, connection (D): with welding ends according to DIN 11850 series 2 - drawing no. R0112, housing material (2): stainless steel, seat seal (0): PTFE, control function(2): spring closes (closing against media flow), drive(1): piston Ø80mm, piston springs(2): two springs
Pneumatic Actuated Control Valve PN16 + Positioner	Steam pressure 6-7 Barg at the inlet; DP: for 0.5 barg Maximum capacity: 1.300 kg/h Nominal Capacity: 805 kg/h Min capacity: 300 kg/h with pneumatic positioner It will be used for temperature control. Steam line diameter : DN65 Valve diameter may be different.
Tip 8021 GS3 DN50	
4099713	8049/4P6-1S000-11-00 Basic type (4P6): version 8049-4, 24VDC, IP65, OEM version (-): standard, drive type (1): single-acting, air performance (S): standard air performance (standard), housing (0): aluminum / plastic, electrical connection (0): Cable glands 2 x M16x1.5, Pneumatic connection(0): G1/8", (-): , Position detection(1): Linear potentiometer with standard feeler rod (L=99.6), Optical display(1): Indicator disc for feeler rod made of PA, (-): , additional modules(0): without additional modules, accessories(0):without

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
8049/2P7-1S000-11-00	00Grundtyp(2P7): Ausführung 8049-2, IP65 (ab Version V7),OEM-Ausführung(-): Standard, Antriebsart(1): einfachwirkend, Luftleistung(S):Standard Luftleistung (Standard), Gehäuse(0): Aluminium / Kunststoff,Elektrischer Anschluss(0): Kabelverschraubungen 2 x M16x1,5,Pneumatischer Anschluss(0): G1/8", (-): , Wegerfassung(1):Linearpotentiometer mit Standard-Taststange (L=99,6), Optische Anzeige(1):Anzeigescheibe für Taststange aus PA, (-): , Zusatzmodule(0): ohneZusatzmodule, Zubehör(0): ohneZolltarif-
17010/032V1H2021---H angle seat valve	ID number 4052394 Nominal size (032): DN 32, design (1): Y-seat, connection (H): with welding ends according to ISO drawing no. R0089, body material (2): stainless steel, seat seal (0): PTFE, control function (2): spring closes (closing against media flow), drive (1): piston Ø80mm, temperature version (H): high temperature version
PSL204AMS11/230VAC	50-60Hz/19W/4,5kN/0,90 adaptation Schubert & Salzer Model 4 V2, for sliding gate valve type GS
7010/015V102220--0--S---B	Nummer 4053613 Nominal size (015): DN 15, design (1): angle seat, connection (0): Whitworth pipe thread, body material (2): stainless steel, seat seal (2): EPDM, control function (2): spring closes (against media flow closing), drive (0): piston Ø50mm, packing installation (0): PTFE-free version 140°C according to Z.-Nr. R 0116 (free of dead space), drive, indicator pin, other (B): hood, circlip and piston springs made of stainless steel Customs tariff-
PD225M-220 225x225x80mm 220VAC	
PD225M-220	
PD120B/220-240 V 220/240VAC 50/60 0.08A	
4040/100V31C310	4040/100V31C310 Actuator: Quarter Turn Double Acting Pneumatic Rotork Actuator, with mounting kit Connection Size: DN100 PN16 Body Material: 1.4408 Stainless Steel Connection type: Sandwich type Process Connection: Compatible with EN 1092-1 B1 Control ability: 300:1 Kvs value: KVS values of valves minimum 390 Sector Characteristic: Equal Percentage Plug Design: Coaxial Sealing Class: Class IV-S1 Retaining Gasket: Hard Chrome Plated Stainless Steel – 70 HRC Shaft Material: Stainless Steel (1.4404) Shaft Sealing: KALREZ + PTFE Sit Ring Material: Solid (Complete) Stellite (Not Welded) Sector Material: Hard Chrome Plated Stainless Steel (1.4404) Sector Surfaces: 70 Rockwell C Bearings: Iglidur Z Distance between two surfaces: 112 mm Complete length above the Valve and Actuator: Max. 450mm
8021/040VGG103M--91--Z--S----108	Type 8021: Slide gate valve 8021

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal diameter: DN 40 (Kvs 26; Cv 30) Function: Slide valve 8021 Design: GS3 intermediate flange design according to DIN, PN10-PN40, (at DN200 PN16; for DN250 PN10-PN16) Housing material: stainless steel 1.4408 Safety position: Spring closes Drive: membrane drive 125 cm^2 Springs: Standard spring equipment Sliding disc, movable: STN2/STN3 Sliding disc, fixed: STN2 Kvs/Cv values: 100% (as of date) Characteristic curve: linear Additional special versions: Drive rotated by 180° (Supply air connection on the valve outlet side).
7081/015V302000--H--S-------H125	3/2-way valve made of stainless steel Ident number 4089265 Nominal diameter (015): DN 15, article (V): valve, design (3): 3/2-way valve -Dividing function (spring closes), connection (0): Whitworth pipe thread, Housing material(2): Stainless steel, seat seal(0): PTFE, control function(0): Drive spring closes, drive(0): piston Ø50mm, piston springs(-): standard Spring assembly (1 spring), head piece material (-): standard stainless steel 1.4571, packing installation (H): packing installation, free of dead space (packing lies bottom), guide rings made of PTFE, temperature version (-): standard, Accessories(-): without, housing, screw-in seat(-): standard, head piece(-): Standard, piston rod, cone, cone nut(-): standard, drive, Indicator pin, other(-): standard, special assembly(-): without, seals(-): Standard, attachments (-): without, special treatments (H): version for Food applications, materials in contact with media in accordance with EC regulations 1935/2004, special additional versions (125): feedback unit for Proximity switch M12
4090926	8049/EP3-1S000-11-00 Basic type (EP3): Version 8049-ExPro, II 2G Ex ia IIC T4 Gb, IP65, OEM version(-): standard, drive type(1): single-acting, air capacity(S): Standard air performance (standard), housing (0): aluminum / plastic, Electrical connection(0): Cable glands 2 x M16x1.5,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Pneumatic connection(0): G1/8", (-): , position detection(1): Linear potentiometer with standard probe rod (L=99.6), optical display(1): Display disc for push rod made of PA, (-): , additional modules (0): without Additional modules, accessories (0): without
GS CONTROL VALVE DN50 TYPE 8044	+ THERMOELEMENTE CABLE 2,5M
7031/032V292020 Angle seat flange valve	Ident number 4050500 Nominal diameter (032): DN 32, design (2): flange valve, connection (9): Angle seat flange valve according to DIN EN 1092-1 PN40, installation length according to DIN 3202 F3, housing material(2): stainless steel, seat seal(0): PTFE, Control function(2): Spring closes (closing against media flow), drive(0): Piston Ø50mm
7010/032A102020	Alternative only as a drive (without housing) Ident number 4006401 Nominal diameter (032): DN 32, article (A): drive, design (1): inclined seat, Connection(0): Whitworth pipe thread, housing material(2): stainless steel, Seat seal(0): PTFE, control function(2): Spring closes (against media flow closing), drive (0): piston Ø50mm Customs fee number. 8481 8079 Type 7010: Angle seat valve Nominal diameter: DN 32 Item: drive Design: inclined seat Connection: Whitworth pipe thread Housing material: stainless steel Seat seal: PTFE Control function: Spring closes (closing against media flow) Drive: piston Ø50mm
4099713	8049/4P6-1S000-11-00 Basic type(4P6): Version 8049-4, 24VDC, IP65, OEM version(-): Standard, drive type (1): single-acting, air output (S): standard Air performance (standard), housing (0): aluminum / plastic, electric Connection (0): Cable glands 2 x M16x1.5, pneumatic Connection (0): G1/8", (-): , position detection (1): linear potentiometer with Standard touch rod (L=99.6), optical display (1): display disc for Sensor rod made of PA, (-): , additional modules(0): without

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	additional modules, accessories(0): without
7010/032A102811--B-S----09--30	ANGLE SEAT VALVE DN32-NO ACTUATOR
8044/100VE0002M--S---ZC	Identification number 4072206 Customs tariff number. 8481 8079 Type 8044: Sliding gate valve 8044 Nominal diameter: DN 100 (Kvs 154; Cv 179) Function: Sliding gate valve 8044 Design: GS1 intermediate flange design PN10-PN40 (for flanges according to DIN EN 1092-1, form B) Housing: C-steel 1.0619 Safety position: spring closes Actuator: piston ø125mm Springs: standard spring fitting Sliding disc (movable): stainless steel, SFC Sliding disc (fixed): standard coating, stainless steel 1.4571 Kvs/Cv values: 100% (standard) Characteristic curve: linear Position controller: digital position controller type 8049, 4-wire version, IP65
8049/4P6-1S000-11-00	4099713 Basic type (4P6): Version 8049-4, 24VDC, IP65, OEM version (-): Standard, Drive type (1): single-acting, Air output (S): Standard Air output (standard), Housing (0): Aluminum / plastic, Electrical Connection (0): Cable glands 2 x M16x1.5, Pneumatic Connection (0): G1/8", (-): , Position detection (1): Linear potentiometer with Standard probe rod (L=99.6), Optical display (1): Display disc for probe rod made of PA, (-): , Additional modules (0): without additional modules, Accessories (0): without Customs tariff number 9032 8900
8041/125VA0101	Type 8041: Sliding gate valve 8041 Nominal diameter: DN 125 (Kvs 237; Cv 275) Function: Sliding gate valve 8041 Design: GS1-intermediate flange design PN10-PN40 (for flanges according to DIN EN 1092-1, form B) Housing: Stainless steel 1.4408 Safety position: Spring closes Actuator: Piston ø80mm
4105765	UNIVERSAL FLANGE SEAL DN125 PN10-PN16 DIMENSIONS 192 X 141 X 2MM, ACCORDING TO DIN2690, S-FLEX GRAPHITE SEAL WITH A STAINLESS STEEL PLATE INSERT

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
4105768	UNIVERSAL FLANGE SEAL DN125 PN25-PN40 195 X 141 X 2MM, ACCORDING TO DIN2690, SIGRAFLEX UNIVERSAL V20010C2I S-FLEX GRAPHITE SEAL WITH A STAINLESS STEEL PLATE INSERT
Type 7078 – Pinch Valve	DN 15 up to DN 50
7015	7015/020A6-2020--LH-S-------2 Identification number 4014669 Nominal diameter (020): DN 20 Article(A): Drive Design(6): Angled seat Connection(-): - Housing material(2): Stainless steel 1.4408 in hygienic design - wetted parts Ra< 0.8 µm Seat seal(0): PTFE (FDA, EC Regulation 1935/2004) Control function (2): Spring closes (closes against media flow) Drive(0): Piston Ø50mm Piston springs(-): Default spring configuration Headpiece material(-): Stainless steel - media contact Ra< 0.8 µm 1.4408 Spindle seal (L): Spindle seal with V-ring packing, dead space-free (packing is at the bottom), max. operating pressure 12 bar, guide rings made of PTFE. -30°C to 200°C media temperature, (FDA, EC Regulation 1935/2004) Temperature version (H): High-temperature version with outer lip seal made of FKM for piston drives, media temperature -30°C to 200°C (temperature limits the spindle seal), ambient temperature -15°C to 100°C with H1 Permit Accessories(-): without Special versions (S): see following positions Housing(-): Standard Headpiece(-): Standard headpiece seal made of Klingersil Top-chem-2000 (FDA, EC Regulation 1935/2004 KTW, BAM DVGW) Piston rod, cone, cone nut(-): Standard Drive, indicator pin, other(-): Default Special assembly(-): without Other(-): without Attachments(-): without Special treatments(2): all parts cleaned and greased with hygienic grease with H1 Certification
7010/015A1-2010---H-S-----F--30	Identification number 4084814 Nominal diameter (015): DN 15 Article(A): Drive Design(1): Angled seat

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Connection(-): - Case material(2): stainless steel Seat seal(0): PTFE Control function(1): Spring opens (closes against media flow) Drive(0): Piston Ø50mm Piston springs(-): Standard spring configuration Headpiece material(-): Standard Packing installation(-): Standard Temperature version (H): High temperature version Accessories(-): without Special versions (S): see following positions Housing(-): Standard Headpiece(-): Standard Piston rod, cone(-): Standard Drive, indicator pin, other(-): Standard Special assembly(-): without Seals (F): with O-ring and inner lip seal for NO; head piece seal made of Klingersil Top-chem-2000 Attachments(-): without Special treatments(-): without Special additional versions(30): Indicator pin made of stainless steel for NO and double-acting
8049	7020/025V1020C111--AS--7 Identification number 4080699 Customs tariff number 8481 8079 Type 7020: Angle seat control valve Nominal diameter (025): DN 25 (Kvs 10; Cv 11.6) Article(V): Valve Design(1): Angled seat Connection(0): Whitworth pipe thread Housing material(2): Stainless steel W.-No.1.4408 or 1.4571 Seat seal(0): PTFE Positioner (C): digital positioner type 8049, 4-wire version, IP 65 Drive(1): Piston ø80mm Springs, Function(1): Spring opens (only with digital positioner) Characteristic curve(1): equal percentage Packing(-): Standard Kvs/Cv values(-): full Kvs value (100%) Accessory(A): Pilot valve 24V DC between positioner and actuator further special versions (S): see following items Seals(-): Standard Position indicator, attachments(-): Standard Positioner setting (7): 0 -10V
S-Control Valve DN40 TYP 8044	
7078/015V802100	dent-Nummer 4088398

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Zolltarif-Nr. 8481 8079 Type 7078: Pinch Valve Nominal size(015): DN 15 - 1/2" Item(V): Valve Design(8): pinch valve Connections(0): BSP thread Connecting parts material(2): stainless steel 1.4435(317L) Sleeve material(1): FKM, fluid temperature from -10°C to +130°C, for chemically aggressive fluids Control function(0): Spring closes Actuator(0): 50mm actuator
7078/020V802100	Type 7078: Pinch Valve Nominal size(020): DN 20 - 3/4" Item(V): Valve Design(8): pinch valve Connections(0): BSP thread Connecting parts material(2): stainless steel 1.4435(317L) Sleeve material(1): FKM, fluid temperature from -10°C to +130°C, for chemically aggressive fluids Control function(0): Spring closes Actuator(0): 50mm actuator
7078/025V802101	Ident-Nummer 4088386 Zolltarif-Nr. 8481 8079 Type 7078: Pinch Valve Nominal size(025): DN 25 - 1" Item(V): Valve Design(8): pinch valve Connections(0): BSP thread Connecting parts material(2): stainless steel 1.4435(317L) Sleeve material(1): FKM, fluid temperature from -10°C to +130°C, for chemically aggressive fluids Control function(0): Spring closes Actuator(1): 80mm actuator
7078/032V802101	Type 7078: Pinch Valve Nominal size(032): DN 32 - 1 1/4" Item(V): Valve Design(8): pinch valve Connections(0): BSP thread Connecting parts material(2): stainless steel 1.4435(317L) Sleeve material(1): FKM, fluid temperature from -10°C to +130°C, for chemically aggressive fluids Control function(0): Spring closes Actuator(1): 80mm actuator

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
7078/040V802101	Ident-Nummer 4098719 Zolltarif-Nr. 8481 8079 Type 7078: Pinch Valve Nominal size(040): DN 40 - 1 1/2" Item(V): Valve Design(8): pinch valve Connections(0): BSP thread Connecting parts material(2): stainless steel 1.4435(317L) Sleeve material(1): FKM, fluid temperature from -10°C to +130°C, for chemically aggressive fluids Control function(0): Spring closes Actuator(1): 80mm actuator
7078/050V802101	Type 7078: Pinch Valve Nominal size(050): DN 50 - 2" Item(V): Valve Design(8): pinch valve Connections(0): BSP thread Connecting parts material(2): stainless steel 1.4435(317L) Sleeve material(1): FKM, fluid temperature from -10°C to +130°C, for chemically aggressive fluids Control function(0): Spring closes Actuator(1): 80mm actuator
4090926	8049/EP3-1S000-11-00 Basic type (EP3): Version 8049-ExPro, II 2G Ex ia IIC T4 Gb, IP65 OEM version(-): Standard Drive type(1): single-acting Air performance (S): Standard air performance (standard) Housing(0): Aluminum / Plastic Electrical connection(0): Cable glands 2 x M16x1.5 Pneumatic connection(0): G1/8" (-): Position detection(1): Linear potentiometer with standard probe rod (L=99.6) Optical indicator(1): Indicator disc for touch rod made of PA (-): Additional modules(0): without additional modules Accessories(0): without
8049/4P6-1S000-11-00-	4099713 Basic type (4P6): Version 8049-4, 24VDC, IP65, IO-Link capable OEM version(-): Standard Actuation type (1): single-acting Airflow (S): Standard airflow (standard) Housing(0): Aluminum / Plastic Electrical connection(0): Cable glands 2 x M16x1.5 Pneumatic connection(0): G1/8" (-):

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Position sensing(1): Linear potentiometer with standard stylus (L=99.6) Optical display(1): Display disc for pushrod made of PA (-): Additional modules (0): without additional modules Accessories (0): none
8049_ExPro-1	
BK MIKRO 4	
8044/015VE0101M--911-ZC Sliding gate valve 8044	Identification number 4062772 Nominal diameter (015): DN 15 (Kvs 1.7; Cv 2) Article(V): Valve Function(s): Slide valve 8044 Design (0): GS1 wafer design PN10-PN40 (for flanges according to DIN EN 1092-1, Form B) Housing(1): Stainless steel 1.4408 Safety position (0): Spring closes Drive(1): Piston ø80mm Special versions (M): see subsequent items Springs (-): Standard spring configuration Spindle seal(-): Standard Sliding disc (movable)(9): STN2/STN3 Sliding disc (stationary)(1): STN2 Kvs/Cv values(1): reduced to 40% Characteristic curve(-): linear Accessories (Z): see subsequent items Position controller (C): digital position controller type 8049, 4-wire version, IP65 Customs tariff number 8481 8079 Unit weight approx. 4.5 kg
4063494	8021/025VGG103M--9111ZC Sliding gate valve 8021 Nominal diameter (025): DN 25 (Kvs 2.4; Cv 2.8) Article(V): Valve Function(G): Slide valve 8021 Design (G): GS3 wafer design according to DIN, PN10-PN40, (for DN200 PN16; for DN250 PN10-PN16) Housing material(1): Stainless steel 1.4408 Safety position (0): Spring closes Drive(3): Diaphragm drive 125 cm^2 Special versions (M): see subsequent items Springs (-): Standard spring configuration Spindle seal(-): Standard Movable sliding disc (9): STN2/STN3 Sliding disc, fixed(1): STN2 Kvs/Cv values(1): reduced to 40% Characteristic curve (1): equal%

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Accessories (Z): see subsequent items Position controller (C): digital position controller type 8049, 4-wire version, IP 65
4024354	8028/020VDG101M--9111ZC Sliding gate valve 8028 Nominal diameter (020): DN 20 (Kvs 1.5; Cv 1.7) Article(V): Valve Version (D): Slide valve 8028, long version Design (G): GS3 wafer design according to DIN, PN10-PN40, (for DN200 PN16; for DN250 PN10-PN16) Housing material(1): Stainless steel 1.4408 Safety position (0): Spring closes Drive(1): Diaphragm drive 60 cm² (D80) (ambient temperature -30 to +100°C) Special versions (M): see subsequent items Springs (-): Standard spring configuration Spindle seal(-): Standard Movable sliding disc (9): STN2/STN3 Sliding disc, fixed(1): STN2 Kvs/Cv values(1): reduced to 40% Characteristic curve (1): equal% Accessories (Z): see subsequent items Position controller (C): digital position controller type 8049, 4-wire version, IP 65
4027825	8028/015VDG101M--9112ZC Sliding gate valve 8028 Nominal diameter (015): DN 15 (Kvs 0.7; Cv 0.81) Article(V): Valve Version (D): Slide valve 8028, long version Design (G): GS3 wafer design according to DIN, PN10-PN40, (for DN200 PN16; for DN250 PN10-PN16) Housing material(1): Stainless steel 1.4408 Safety position (0): Spring closes Drive(1): Diaphragm drive 60 cm² (D80) (ambient temperature -30 to +100°C) Special versions (M): see subsequent items Springs (-): Standard spring configuration Spindle seal(-): Standard Movable sliding disc (9): STN2/STN3 Sliding disc, fixed(1): STN2 Kvs/Cv values(1): reduced to 40% Characteristic curve(2): equal% (with theoretical ratio 1:150) Accessories (Z): see subsequent items Position controller (C): digital position controller type 8049, 4-wire version, IP 65
8044/065VE0001M--91-1ZC	Identification number 4071458 Type 8044: Slide valve 8044 Nominal diameter (065): DN 65 (Kvs 30; Cv 35)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Article(V): Valve Function(s): Slide valve 8044 Design (0): GS1 wafer design PN10-PN40 (for flanges according to DIN EN 1092-1, Form B) Housing(0): Carbon steel 1.0619 Safety position (0): Spring closes Drive(1): Piston ø80mm Special versions (M): see subsequent items Springs (-): Standard spring configuration Spindle seal(-): Standard Sliding disc (movable)(9): STN2/STN3 Sliding disc (stationary)(1): STN2 Kvs/Cv values(-): 100% (Standard) Characteristic curve (1): equal% Accessories (Z): see subsequent items Positioner (C): digital positioner type 8049, 4-wire version, IP65
8044/050VE0001M--91-1ZC	Identification number 4064127 Type 8044: Slide valve 8044 Nominal diameter (050): DN 50 (Kvs 19; Cv 22) Article(V): Valve Function(s): Slide valve 8044 Design (0): GS1 wafer design PN10-PN40 (for flanges according to DIN EN 1092-1, Form B) Housing(0): Carbon steel 1.0619 Safety position (0): Spring closes Drive(1): Piston ø80mm Special versions (M): see subsequent items Springs (-): Standard spring configuration Spindle seal(-): Standard Sliding disc (movable)(9): STN2/STN3 Sliding disc (stationary)(1): STN2 Kvs/Cv values(-): 100% (Standard) Characteristic curve (1): equal% Accessories (Z): see subsequent items Positioner (C): digital positioner type 8049, 4-wire version, IP65
8049-2	CONTROL VALVE STEAM DN100 8044 8044/100VE0001M S ZR; KVS 154; CV 179; DIGITAL POSITIONER
7020/025V1020C111--AS--7 Angle seat control valve	Identification number 4080699 Nominal diameter (025): DN 25 (Kvs 10; Cv 11.6) Article(V): Valve Design (1): Angle seat Connection (0): Whitworth pipe thread Housing material (2): Stainless steel W.-Nr.1.4408 or 1.4571 Seat seal (0): PTFE Position controller (C): digital position controller type 8049, 4-wire version, IP 65

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Drive(1): Piston ø80mm Springs, Function(1): Spring opens (only with digital positioner) Characteristic curve(1): equal percentage Package(-): Standard Kvs/Cv values(-): full Kvs value (100%) Accessories (A): 24V DC pilot valve between positioner and actuator Further special versions (S): see subsequent items Seals (-): Standard Position indicator, attachments(-): Standard Position control setting (7): 0-10V
7010/040v151027-2-S-140	
Gs8030	
4051273	USB-CONNECTOR V3.0 M. SOFTWARE DEVICECONFIG KPL. FOR THE PARAMETERIZATION OF SCHUBERT & SALZER DEVICES SUITABLE FOR TYPE 8049, Customs fee number. 9032 9000
7010-032v1h2811---B-S----09-D30-Ï80	
4051273	Current successor to item number 4051273 4300506 USB CONNECTOR V3.1 COMPLETE FOR PARAMETERIZATION OF SCHUBERT & SALZER DEVICE SUITABLE FOR TYPE 8049, 2030, 2032, 2040,
7010/040v151017-2-S-140	
7010-015v1h20202--H-S-1--09-D294	
7020/015v102071-1ex. (7020/015v102071-1---S-0)	
7010/025v101221	Type 7010: Angle seat valve Nominal diameter: DN 25 Type: inclined seat Connection: Whitworth pipe thread Housing material: gunmetal Seat seal: EPDM Control function: Spring closes (closing against media flow) Drive: piston Ø80mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Gs-Dn6	
7010-025v1h28212--B-S----09-D	
8044/080ve0002m--91-1zc	Ident number 4065118 Customs fee number. 8481 8079 Type 8044: GS control valve with piston drive (short design) Nominal diameter: DN 80 (Kvs 48; Cv 56) Function: GS piston control valve, short design (Type 8044) Design: GS1 intermediate flange design PN10-PN40 (for flanges according to DIN EN 1092-1, form B) Housing: C-steel 1.0570 or 1.0619 Safety position: Spring closes Drive: Piston ø125mm Springs: Standard spring mounting Sliding disc (movable): STN2 / STN3 Sliding disc (fixed): STN2 Kvs / Cv values: 100% (state) Characteristic: equal to% Positioner: digital positioner type 8049, 4-wire version, IP65
4040/050v11c0t1	
7010/025v151017-2-S-140	
4040/050v11c1t3	Ident number 2803800 Customs fee number. 8481 8099 Type 4040: ball sector valve Nominal diameter: DN 50 (Kvs 94; Cv 109) Article: Valve Design: Intermediate flange design for flanges DIN EN 1092-1 (DN25-DN50: PN40, DN80 and DN100: PN25, DN150-DN250: PN16, DN300: PN16 in flange design) Housing Material: Stainless steel 1.4408 or 1.4404 Seat combination: seat ring: stellite; Ball sector: Stainless steel, hard chrome plated and lapped, hard chrome plated retaining ring Sealing combination: all seals (part 13-16) made of VITON, Media temperature: -15 ° C to + 200 ° C Drive: Pneumatic rotary actuator (Air Torque) with mounting kit according to DIN / ISO 5211 Safety position: single-acting, spring opens
7010-015v1h28202--B-S----09-D	
4056017 (Ex.14559335)	
4056056	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
7010-025v1h2020---H-S----09-D294	
8036/100vt/Rm/4/Z/S/6	
4056017 (Ex. 14559335)	
8043/025vf0001m-1--A-Z8	
4008175	
4040/050v11c1t1	Ident number 2801373 Customs fee number. 8481 8099 Type 4040: ball sector valve Nominal diameter: DN 50 (Kvs 94; Cv 109) Article: Valve Design: Intermediate flange design for flanges DIN EN 1092-1 (DN25-DN50: PN40, DN80 and DN100: PN25, DN150-DN250: PN16, DN300: PN16 in flange design) Housing Material: Stainless steel 1.4408 or 1.4404 Seat combination: seat ring: stellite; Ball sector: Stainless steel, hard chrome plated and lapped, hard chrome plated retaining ring Sealing combination: all seals (part 13-16) made of VITON, Media temperature: -15 ° C to + 200 ° C Drive: Pneumatic rotary actuator (Air Torque) with mounting kit according to DIN / ISO 5211 Safety position: single acting, spring closes
2700091	
8049-4p5-1s000-11-00	
7010-032v1h20002—h-S-1--09-D	
8043-015vfg101m--911-Zc3	
7010-025v1h28212--B-S----09-D294	
7010/025v151027-2-S-140	
8021/080vgg103m	
8043-025vfg101m--911-Zc3	
015vmh1-1m3-932-Z-	
8021/025vgg103m--91--Zcns-2	GS control valve with integrated positioner Ident number 4068679 Nominal diameter (025): DN 25 (Kvs 11, Cv 13), Function (G): Control valve with

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	pneumatic actuator type 8021, type (G): GS3 intermediate flange construction according to DIN, PN10-PN40, (with DN200 PN16; DN250 PN10-PN16), Housing material (1): Stainless steel 1.4581 / 1.4571 or 1.4408 / 1.4404, safety position (0): spring closes, drive (3): Diaphragm drive 125 cm², springs (-): standard spring mounting, Slide washer, movable (9): STN2 / STN3, sliding washer, fixed (1): STN2, Kvs / Cv values (-): 100% (state), characteristic (-): linear, positioner (C): digital positioner type 8049, 4-wire version, IP 65, Signal devices (N): Feedback module RM2 for positioner type 8049 with 2 integrated limit switches., Accessories (2): Position indicator ring and Stainless steel nameplate Customs fee number. 8481 8079
7081/015v302000--H--S-------H125	Ident number 4089265 Customs fee number. 8481 8079 Type 7081: 3/2-way valve made of stainless steel Nominal diameter: DN 15 Article: Valve Type: 3/2 way valve-parting function (spring closes) Connection: Whitworth pipe thread Housing material: stainless steel Seat seal: PTFE Control function: Drive spring closes Drive: piston Ø50mm Piston springs: standard spring assembly (1 spring) Header material: standard stainless steel 1.4571 Packing: Packing installation, dead space free (pack is below), Guide rings made of PTFE Temperature version: standard Accessories: without Housing, screw-in seat: standard Headpiece: standard Piston rod, plug, conical nut: standard Drive, indicator pin, miscellaneous: standard Special assembly: without Seals: standard Attachments: without
S212 1632359	
8020/050upg00	
8044/020ve0101m--91-1zc	Ident number 4064396 Customs fee number. 8481 8079 Type 8044: GS control valve with piston drive (short design) Nominal diameter: DN 20 (Kvs 3, Cv 3.5)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Function: GS piston control valve, short design (Type 8044) Design: GS1 intermediate flange design PN10-PN40 (for flanges according to DIN EN 1092-1, form B) Housing: Stainless steel 1.4581 / 1.4571 or 1.4408 / 1.4404 Safety position: Spring closes Drive: Piston ø80mm Springs: Standard spring mounting Sliding disc (movable): STN2 / STN3 Sliding disc (fixed): STN2 Kvs / Cv values: 100% (state) Characteristic: equal to% Positioner: digital positioner type 8049, 4-wire version, IP65

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.