



Schuhmann Messtechnik

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Schuhmann Messtechnik** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Schuhmann Messtechnik T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
WU39.04GW	Resistance transducer with special entrance Input: switchable 2-wire: 0 ... 100K / 20K / 10K / 2K Output: 0 (4) ... 20 mA 0 (2) ... 10 V Auxiliary power: 24 ... 250 V DC 90 ... 253 V AC 22.5 mm housing for top hat rail Weight: 140 gr. The WU3.04GW is sold out and is no longer being built.
SE30.00GW	Setpoint adjuster - parameterizable Input potential-free contacts, output U,I Output: 0(4)...20 mA active or loop powered 0(2)...10 V DC external control inputs: potential-free contacts UP/DOWN Adjustable from the front 0...100% or Parameterization with KALIB SOFTWARE Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN rail Weight: 116g Setting upon delivery: Output: 4...20mA
SE30.00GW	Setpoint adjuster - parameterizable Input potential-free contacts, output U,I Output: 0(4)...20 mA active or loop powered 0(2)...10Vdc external control inputs: potential-free contacts UP DOWN Adjustable from the front 0...100% or Parameterization with KALIB SOFTWARE Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN rail Weight: 116g Setting upon delivery: Output: 4...20mA
TT2.00GW	Isolation amplifier active, 2-channel permanently calibrated or adjustable via trimmer Input: 2 x 0(4)...20 mA or 0(2)...10 V Output simultaneous: 2 x 0(4)...20 mA and 0(2)...10 V linearization error <0.1% pluggable screw terminals Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN

	rail 2-channel Weight: 150 gr. ****The TR2.00UC is sold out and will no longer be built.
UT19.04GW	Isolating amplifier active Special input, universal outputs Input: 0... Output simultaneously: 0(4)...20 mA 0(2)...10 V Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN rail 1-channel Weight: 160 gr. In the case of an order, please specify the input value you require. For example: E: 0...60mV or E: 0...100 mV DC or E: 0...200 V DC or E: 10...20 mA DC or E: 0...250 mA DC The device will be built according to your specifications.
UT19.00GW	isolation amplifier active Universal inputs and outputs Input: Current 0(4)...20 mA, ± 10 mA or Voltage 0(2)...10 V, ± 10 V switchable Output simultaneous: 0(4)...20 mA 0(2)...10 V Auxiliary power: 24...250 V DC 90...253 V AC 22.5 mm housing for DIN rail 1-channel Weight: 160 gr.
DGS2.01GW	Digital limit switch 1-channel, temperature sensors, SW parameterizable Input: 1 x PT100, PT 1000, NI, KTY, thermocouple, resistance Output: 2 x relays with changeover contacts Hysteresis, pick-up and drop-out delay, sensor break, alarm limits per relay Parameterization with KALIB-SOFTWARE/ push button switch, LCD display, LEDs for relay states Auxiliary power: 24...250 V DC 90...253 V AC 22.5 mm housing for DIN rail pluggable and coded screw terminals 1-channel Weight: 160 gr. The DGW2.01G is sold out and is no longer being built. We offer you the replacement type to.
UTS 19.00 GW	Active power amplifier Universal inputs and outputs Entrance: Current 0(4)...20 mA, +/- 10 mA or Voltage 0(2)...10 V, +/- 10 V Output simultaneous: 0(4)...20 mA 0(2)...10 V Integrated transmitter power supply Auxiliary power: 24...250 V DC 90...253 V AC 22.5 mm housing for DIN rail 1-channel
Trv2.00uc	
St1.00sdc	
Ut 1.00g Relais	
Pt4.00gac	
Dgw 1.00g	
Usb2	
Trsv 2.00uc Obsolete Replacement Ttsv2.00gw	
Ut1.00gdc	Isolation Amplifier active 2019/04 2 units 94.00 188.00 Universal inputs and outputs Input: switchable Output simultaneous: 0 (4) ... 20 mA 0 (2) ... 10 V Power supply: 20 ... 30 V DC 22.5 mm housing for DIN rail 1-channel Weight: 118 gr.
Sti.00sdc	
Wandler 60-69-200-0005 Dt 1.13 Gw	

Dfa8.00gw Digitaler Frequenz-Analog-Umformemit Digitalanzeige
Ut1.04gdc
Ut 1.04 Gw
UT1.00G 230VAC
Controller Dt1.13gw, 100975, 0-20ma,24v
Stp1.00sdc
Wandler Wu3.00gw;
Trsv2.00uc
Tr2.00uc U5 Module Input: 20-30v Dv
Er2.00mw
Wu3.00gw
Daf9.00tw
Konverter Tu2.09gw
Gs2.00gdc
Ng 15.00g-315
Gw2.00gac
Tt1.00mw
Tr.00uc
Dt1.13gw
Gw2.00g
Mu 1.01 S
Dgw4.00g
Dgw.2.00.Tuc
Ttsv2.00gw
Er26.00gdc
Dgw1.00tw
Dgw2.08g
Wu3.04gw
Dgw1.00tuc

Tr .00uc By Tt1.00mw
Trs.00 Uc
Wandler Wu3.00gw
Dgw4.00guc
Av2.00sdc
As3.00mw
Gw2.04gw
Dt 1.13gw Wandler
Dgw1.00gdc