Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Schuhmann Messtechnik

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Schuhmann Messtechnik Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Schuhmann Messtechnik Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
WU39.04GW	Resistance transducer with special entrance Input: switchable 2-wire: 0 ... 100K / 20K / 10K / 2K Output: 0 (4) ... 20 mA 0 (2) ... 10 V Auxiliary power: 24 ... 250 V DC 90 ... 253 V AC 22.5 mm housing for top hat rail Weight: 140 gr. The WU3.04GW is sold out and is no longer being built.
SE30.00GW	Setpoint adjuster - parameterizable Input potential-free contacts, output U,I Output: 0(4)...20 mA active or loop powered 0(2)...10 V DC external control inputs: potential-free contacts UP/DOWN Adjustable from the front 0...100% or Parameterization with KALIB SOFTWARE Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN rail Weight: 116g Setting upon delivery: Output: 4...20mA
SE30.00GW	Setpoint adjuster - parameterizable Input potential-free contacts, output U,I Output: 0(4)...20 mA active or loop powered 0(2)...10Vdc external control inputs: potential-free contacts UP DOWN Adjustable from the front 0...100% or Parameterization with KALIB SOFTWARE Auxiliary power: 24...250 V DC

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	90...253VAC 22.5 mm housing for DIN rail Weight: 116g Setting upon delivery: Output: 4...20mA
TT2.00GW	Isolation amplifier active, 2-channel permanently calibrated or adjustable via trimmer Input: 2 x 0(4)...20 mA or 0(2)...10 V Output simultaneous: 2 x 0(4)...20 mA and 0(2)...10 V linearization error <0.1% pluggable screw terminals Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN rail 2-channel Weight: 150 gr. ****The TR2.00UC is sold out and will no longer be built.
UT19.04GW	Isolating amplifier active Special input, universal outputs Input: 0... Output simultaneously: 0(4)...20 mA 0(2)...10 V Auxiliary power: 24...250 V DC 90...253VAC 22.5 mm housing for DIN rail 1-channel Weight: 160 gr. In the case of an order, please specify the input value you require. For example: E: 0...60mV or E: 0...100 mV DC or E: 0...200 V DC or E: 10...20 mA DC or E: 0...250 mA DC The device will be built according to your specifications.
UT19.00GW	isolation amplifier active Universal inputs and outputs Input: Current 0(4)...20 mA, ± 10 mA or Voltage 0(2)...10 V, ± 10 V switchable Output simultaneous: 0(4)...20 mA 0(2)...10 V Auxiliary power: 24...250 V DC 90...253 V AC 22.5 mm housing for DIN rail 1-channel Weight: 160 gr.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
DGS2.01GW	Digital limit switch 1-channel, temperature sensors, SW parameterizable Input: 1 x PT100, PT 1000, NI, KTY, thermocouple, resistance Output: 2 x relays with changeover contacts Hysteresis, pick-up and drop-out delay, sensor break, alarm limits per relay Parameterization with KALIB-SOFTWARE/ push button switch, LCD display, LEDs for relay states Auxiliary power: 24...250 V DC 90...253 V AC 22.5 mm housing for DIN rail pluggable and coded screw terminals 1-channel Weight: 160 gr. The DGW2.01G is sold out and is no longer being built. We offer you the replacement type to.
UTS 19.00 GW	Active power amplifier Universal inputs and outputs Entrance: Current 0(4)...20 mA, +/- 10 mA or Voltage 0(2)...10 V, +/- 10 V Output simultaneous: 0(4)...20 mA 0(2)...10 V Integrated transmitter power supply Auxiliary power: 24...250 V DC 90...253 V AC 22.5 mm housing for DIN rail 1-channel
Trv2.00uc	
St1.00sdc	
Ut 1.00g Relais	
Pt4.00gac	
Dgw 1.00g	
Usb2	
Trsv 2.00uc Obsolete Replacement Ttsv2.00gw	
Ut1.00gdc	Isolation Amplifier active 2019/04 2 units 94.00 188.00 Universal inputs and outputs Input: switchable Output simultaneous: 0 (4) ... 20 mA 0 (2) ... 10 V

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Power supply: 20 ... 30 V DC 22.5 mm housing for DIN rail 1-channel Weight: 118 gr.
Sti.00sdc	
Wandler 60-69-200-0005 Dt 1.13 Gw	
Dfa8.00gw Digitaler Frequenz-Analog-Umformermit Digitalanzeige	
Ut1.04gdc	
Ut 1.04 Gw	
UT1.00G 230VAC	
Controller Dt1.13gw, 100975, 0-20ma,24v	
Stp1.00sdc	
Wandler Wu3.00gw;	
Trsv2.00uc	
Tr2.00uc U5 Module Input: 20-30v Dv	
Er2.00mw	
Wu3.00gw	
Daf9.00tw	
Konverter Tu2.09gw	
Gs2.00gdc	
Ng 15.00g-315	
Gw2.00gac	
Tt1.00mw	
Tr.00uc	
Dt1.13gw	
Gw2.00g	
Mu 1.01 S	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Dgw4.00g	
Dgw.2.00.Tuc	
Ttsv2.00gw	
Er26.00gdc	
Dgw1.00tw	
Dgw2.08g	
Wu3.04gw	
Dgw1.00tuc	
Tr .00uc By Tt1.00mw	
Trs.00 Uc	
Wandler Wu3.00gw	
Dgw4.00guc	
Av2.00sdc	
As3.00mw	
Gw2.04gw	
Dt 1.13gw Wandler	
Dgw1.00gdc	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.