

## Schwer Fittings



Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Schwer Fittings** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Schwer Fittings Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Gf-125r38x10-7</a>	Locking screw 1.4571 with hexagon socket R3 / 8 "Si8x10
<a href="#">Sr-594g18</a>	Locking screw 1.4571 Viton ring G1 / 8 "D14x12
<a href="#">Sr-594g14</a>	Locking screw 1.4571 Viton ring G1 / 4 "D19x17
<a href="#">Gf-125r12x14-7</a>	Locking screw 1.4571 Special length R1 / 2 "S10x14
<a href="#">Sr-594g34</a>	Locking screw 1.4571 Viton ring G3 / 4 "D32x21
<a href="#">Gf-105g1238-7</a>	Hexagon reducing double nipple 1.4571 G1 / 2 "> G3 / 8" S24x32.5
<a href="#">Mi-Gs25din-4l</a>	1.4404
<a href="#">u2-BV1m12HLD-4LiP</a>	2-way low pressure ball valve (up to 1000 PSI) AISI316L 1.4404 / PTFE -30 ° C <180 ° C Functional reliability 1.5 times D12 / S22 S22 / Hex27x99.3 b12.5
<a href="#">u2-CVFN14ps1-4LV</a>	Check valve (NPT) 1.4404 / Viton 1psi Functional reliability 1.5 times 1/4 "NPT IT
<a href="#">NPT 1/4" Fittings</a>	leider keine Artikel nr. vorhanden
<a href="#">Union Tee</a>	leider keine Artikel nr. vorhanden
<a href="#">NPT 1/2" Fitting</a>	leider keine Artikel nr. vorhanden
<a href="#">1/2 "-12.7mm Hydraulic Green Pipe Clamp (Single)</a>	leider keine Artikel nr. vorhanden

<a href="#">SK-9070S1420</a>	T-piece for orbital welding 1.4571 D14x2.0 S19x31 / 31
<a href="#">IC-HLN-N18x50-4i-8</a>	Long hexagonal double nipple 1.4401 AG1 / 8 "NPTx50.8 S7 / 16 (11.11) x50.8
<a href="#">SR-594M12</a>	Screw plug 1.4571 / FKM M12x1.5 D17x17
<a href="#">GF-151G14-7</a>	Welding socket 1.4571 D11x1.5 <G1 / 4 "D18x20
<a href="#">A-BV2F50PN40F-8i</a>	
<a href="#">A-BV2F80PN40F-8i</a>	
<a href="#">A-BV2G12-8i</a>	
<a href="#">A-BV2G14-8i</a>	
<a href="#">A-BV2GR12-8i</a>	
<a href="#">A-BVHB12S77POV</a>	
<a href="#">A-BVHB30S77POV</a>	
<a href="#">AS-BS13-4L</a>	
<a href="#">AS-BS41-4Li</a>	
<a href="#">AS-N13-4Li</a>	
<a href="#">AS-N41-4Li</a>	
<a href="#">AS-OR13-V</a>	
<a href="#">AS-OR41-V</a>	
<a href="#">CL-CL1D155-2i</a>	
<a href="#">CL-CL1D34-2i</a>	
<a href="#">CL-CL1D505-2i</a>	
<a href="#">CL-CL1D64-2i</a>	
<a href="#">CL-CL1D775-2i</a>	
<a href="#">CL-CL1D91-2i</a>	
<a href="#">CL-CL2D505-2i</a>	
<a href="#">CL-CR1-34Z505-25-H4-5</a>	
<a href="#">CL-CR1-34Z505-34-H4-5</a>	
<a href="#">CL-CR2-112Z64-505-4L</a>	
<a href="#">CL-CR2-112Z64-505-H4-5</a>	
<a href="#">CL-CR34-12Z34-25-H4-5</a>	
<a href="#">CL-CS40DIN505-B</a>	

<a href="#">CL-EC34-4Li</a>
<a href="#">CL-EC505-4Li</a>
<a href="#">CL-EC64-4Li</a>
<a href="#">CL-EC775-4Li</a>
<a href="#">CL-EC91-4Li</a>
<a href="#">CL-FA10ISO34G38-4L</a>
<a href="#">CL-FA15DIN34G12-4L</a>
<a href="#">CL-HA25DIN505-4L</a>
<a href="#">CL-MA10DIN34G14-4L</a>
<a href="#">CL-MA15DIN34G12-4L</a>
<a href="#">CL-MA1Z505G14-4L</a>
<a href="#">CL-WF50DIN64-4Li</a>
<a href="#">GF-10712-4i</a>
<a href="#">GF-110G14-5i</a>
<a href="#">GF-11516R12-7</a>
<a href="#">GF-1399G12-7</a>
<a href="#">GF-141FR1-7</a>
<a href="#">GF-143FR34-7</a>
<a href="#">MO-RBV0622</a>
<a href="#">MO-RE10-54E</a>
<a href="#">Pace1Press, c futlyarom PAC-P1pressSE</a>
<a href="#">PAC-P1VO12L</a>
<a href="#">PAC-P1VO12S</a>
<a href="#">PAC-P1VO16S</a>
<a href="#">PAC-P1VO20S</a>
<a href="#">PAC-P1VO30S</a>
<a href="#">PAC-P1VO38S</a>
<a href="#">SA-DKR16G12</a>
<a href="#">SR-500Z12LSi</a>
<a href="#">SR-500Z16Si</a>

[SR-500Z20Si](#)

[SR-500Z30Si](#)

[SR-500Z38Si](#)

[SR-50112S](#)

[SR-50112S-7i](#)

[SR-50116S](#)

[SR-50120S](#)

[SR-50130S](#)

[SR-50138S](#)

[SR-50512S](#)

[SR-50516S](#)

[SR-50530S](#)

[SR-50538S](#)

[SR-50612S](#)

[SR-50616S](#)

[SR-50630S](#)

[SR-50638S](#)

[SR-50712S](#)

[SR-50716S](#)

[SR-50720S](#)

[SR-50730S](#)

[SR-50738S](#)

[SR-50812S](#)

[SR-50816S](#)

[SR-50830S](#)

[SR-50838S](#)

[SR-51220S12](#)

[SR-51220S34](#)

[SR-51230S1](#)

[SR-537121612S](#)

[SR-537161216S](#)

<a href="#">SR-5391612S</a>	
<a href="#">SR-5393830S</a>	
<a href="#">SR-5401612S</a>	
<a href="#">SR-5403012S</a>	
<a href="#">SR-5403016S</a>	
<a href="#">SR-5403812S</a>	
<a href="#">SR-5403816S</a>	
<a href="#">SR-5403830S</a>	
<a href="#">SR-58912LS</a>	
<a href="#">SR-58916S</a>	
<a href="#">SR-58930S</a>	
<a href="#">SR-58938S</a>	
<a href="#">SR-592S12S-7227</a>	
<a href="#">SR-592S16S-7227</a>	
<a href="#">SR-592S20S-7227</a>	
<a href="#">SR-592S30S-7227</a>	
<a href="#">SR-592S38S-7227</a>	
<a href="#">u2-MS-G12-4i</a>	
<a href="#">u2-Tm12-4L</a>	
<a href="#">V-NVG12-7</a>	
<a href="#">V-NVG14-7</a>	
<a href="#">V-NVZ12S-7</a>	
<a href="#">CL-EC64-4Li</a>	
<a href="#">SR-51216S12</a>	Straight screw connection 1.4571 viton ring 16S<G1/2" S27x51
<a href="#">SR-51216S38</a>	Straight screw connection 1.4571 incl. FKM (Viton ®) soft sealing ring DIN EN ISO 8434-1 16S>G3/8" S30x52.2
<a href="#">SR-50616S</a>	Store Verschraubung 1.4571 DIN EN ISO 8434-1 16S B24/S30x46,5
<a href="#">SR-50716S</a>	T-screw connection 1.4571 EN ISO 8434-1 16S S30x46.2
<a href="#">SR-5391612S</a>	Straight reducing fitting 1.4571 16/12S

<a href="#">SR-51212S14</a>	Straight screw connection 1.4571 viton ring 12S<G1/4" S22x45
<a href="#">RS-IS16PA</a>	Pipe clamp, heavy series, Complete version V4A/PA DIN3015 Part2 16.00 73x30x48
<a href="#">CL-CL2D505-2i</a>	Two-jointed clamp 1.4308 with clamping nut DIN32676 D50.5
<a href="#">A-BV1F15PN16F-8i</a>	Short flanged ball valve 1.4408/PTFE15% glass fiber/FKM 15 Drive preparation according to ISO5211 Flanges according to DIN 2501 DN15 PN16 D95xL42
<a href="#">A-BV1F25PN16F-8i</a>	Short flanged ball valve 1.4408/PTFE15% glass fiber/FKM 25 Drive preparation according to ISO5211 Flanges according to DIN 2501 DN25 PN16 D115xL50
<a href="#">A-BV1F40PN16F-8i</a>	Short flanged ball valve 1.4408/PTFE15% glass fiber/FKM 25 Drive preparation according to ISO5211 Flanges according to DIN 2501 DN25 PN16 D115xL50
<a href="#">V-CVZG25S</a>	Check valve 1.4571/FKM 25S Po 1 bar G1"<25S S46/50x78.5
<a href="#">V-CVZG42L</a>	Check valve 1.4571/FKM 42 poe 1 bar G1-1/2"<42L S80/90x105.5
<a href="#">A-MSVG12SM-7</a>	Pressure gauge shut-off valve 1.4571 15 Form A G1/2"
<a href="#">A-STMG12-7</a>	Pressure gauge accessories 1.4571 with set screw G1/2" 4kt27x63
<a href="#">F-GF15-16-40-7i</a>	Threaded flange turned bright 1.4571 DN15 PN16-40, Form B1 EN 1092-1 Rp 1/2" A95xH22>b16xf2xk65
<a href="#">F-GF25-16-40-7i</a>	Threaded flange turned bright 1.4571 DN25 PN16-40, Form B1 EN 1092-1 Rp 1" A115xH28>b18xf2xk85
<a href="#">F-GF32-16-40-7i</a>	Threaded flange turned bright 1.4571 DN32 PN16-40, form B1 EN 1092-1 Rp 1-1/4" A140xH30>b18xf2xk100
<a href="#">F-GF40-16-40-7i</a>	Threaded flange turned bright 1.4571 DN40 PN16-40, Form B1 EN 1092-1 Rp 1-1/2" A150xH32>b18xf3xk110
<a href="#">F-VF65-10-16-7i</a>	Welding flange 1.4571 DN65 PN10-16, form B1 turned bright EN 1092-1 type 11 D76.1x2.9 A185xH45>b18xf3xk145
<a href="#">SR-50625S</a>	Elbow screw connection 1.4571 EN ISO 8434-1 25S B36/S46x59
<a href="#">SR-50642L</a>	Elbow screw connection 1.4571 42L S60/B50x63
<a href="#">WF-B761x29-7Ni</a>	Elbow, ISO 1.4571 seamless DIN2605 D76.1x2.9 D76.1xR95
<a href="#">SR-57125SG</a>	Adjustable L fitting with Screw socket 1.4571 25S<G1" S46/B36x54/91
<a href="#">SR-57142LG</a>	Adjustable L fitting with Screw socket 1.4571 42L<G1-1/2" S60/B50x63/104
<a href="#">SR-50725S</a>	T-screw connection 1.4571 25S S46/B36x54

<a href="#">SR-50742L</a>	T-screw connection 1.4571 42L S60/B50x63
<a href="#">SR-56825SG</a>	Adjustable T-barrel fitting with Screw socket 1.4571 25S<G1" S46/B36x54/91
<a href="#">SR-56842LG</a>	Adjustable T-barrel fitting with Screw socket 1.4571 42L G11/2"8 50x63
<a href="#">SR-51025S1</a>	Straight screw connection 1.4571 25S<G1" S41x47
<a href="#">SR-51025S112</a>	Straight screw connection 1.4571 25S<G1-1/2" S55x50
<a href="#">SR-51042L112</a>	Straight screw connection 1.4571 42L<G1-1/2" S55x42
<a href="#">SR-53025S</a>	Straight screw connection 1.4571 25S inside G1"DIN/ISO228 SW46x62
<a href="#">SR-5431234</a>	Reducing socket 1.4571 viton ring AG1/2"<IG3/4" S36x46
<a href="#">SR-543121</a>	Reducing socket 1.4571 viton ring AG1/2"<IG1" S41x49
<a href="#">SR-54334112</a>	Reducing socket 1.4571 viton ring AG3/4"<IG1-1/2" S60x57
<a href="#">SR-5431112</a>	Reducing socket 1.4571 viton ring AG1"<IG1-1/2" S60x59
<a href="#">GF-105134-7</a>	Hexagon reducing double nipple 1.4571 R1">R3/4" S36x45.5
<a href="#">GF-105112114-4i</a>	Hexagon reducing double nipple 1.4408 R1-1/2">R1-1/4" S50x54, R1-1/2">R1-1/4"
<a href="#">GF-149CR1-7</a>	Screw connection, external thread on both sides 1.4571/1.4408 conical sealing R1" S55x90
<a href="#">SA-BE9025S25*</a>	Hose connector with shaft 90° 1.4571 25S>DN25
<a href="#">HOS-PT125</a>	PTFE hose, smooth PTFE DN 25 DN 25 A notice: Please check length!
<a href="#">SA-DKRF25G1</a>	Hose connector DKR FG 1.4571 G1">DN25 SW41x68
<a href="#">SA-DKRF25G1</a>	Hose connector DKR FG 1.4571 G1">DN25 SW41x68
<a href="#">HOS-PT125</a>	PTFE hose, smooth PTFE DN 25 DN 25 A notice: Please check length!
<a href="#">SA-DKR25G1</a>	Hose connector DKR 1.4571 G1">DN25 SW41x73.5
<a href="#">SA-AGR16R12</a>	Hose connector AGR conical 1.4571 R1/2" SW22x66.5
<a href="#">QC-FCG112IB-4LPV</a>	High-pressure coupling, shutting off on both sides: Coupling 1.4404/FKM/PTFE DN40 DIN ISO 7241-1B G1-1/2" S65x126
<a href="#">QC-MCG112IB-4LV</a>	High-pressure coupling, shutting off on both sides: Plug 1.4404/FKM DN40 DIN ISO 7241-1B G1-1/2" S65x126
<a href="#">SA-AGR40G112</a>	Hose connector EGR cylindrical 1.4571 G 1 1/2">DN40
<a href="#">GF-130G12-4i</a>	Angle 90° 1.4408 G1/2" L28
<a href="#">Stainless Steel - 1"-14 UNS Vented Cap, 3/8" NPT</a>	Grease Fitting

<a href="#">A-BV3DN50-8i</a>	3-part ball valve 1.4408 DN50 with welding ends on both sides
<a href="#">A-BVHBG1477POV</a>	High-pressure block ball valve 1.4571/POM/FKM G1/4" S22/26x69
<a href="#">GF-115645R212-5i</a>	Screw-in hose nipple 1.4408 di64.5<R2-1/2" S78x99
<a href="#">HOSE HEAD 2"1/2 CODE:GF-11560R212-7 SCHWER</a>	STAINLESS 2"1/2x60 MM
<a href="#">MANOMETER HOSE 1500MM M16X2 AISI 316Ti PN 630BAR</a>	755 DN2 1500
<a href="#">Liste am anhang</a>	
<a href="#">SR-5146L18</a>	Straight screw connection 1.4571 6L<1/8NPT S14/B12x31.5
<a href="#">HyF-LCW M880µm</a>	Screw-in filter V4A/V4 M8x1.25 4x5
<a href="#">KF-SF40x70-4L</a>	Small flange 1.4404 DN 40 DIN 28403/ISO 2861 D55 D55x70
<a href="#">HyF-LCW M880µm</a>	Screw-in filter V4A/V4 M8x1.25 4x5
<a href="#">GF-100R11440-7</a>	Weld nipple 1.4571 DIN EN 10226 D42.4x3.25>R1-1/4" D42.4x40
<a href="#">MANOMETER HOSE 1000MM M16X2</a>	AISI 316Ti PN 630BAR 755 DN2 1000
<a href="#">MANOMETER HOSE 1500MM M16X2</a>	AISI 316Ti PN 630BAR 755 DN2 1500
<a href="#">MANOMETER HOSE 2000MM M16X2</a>	AISI 316Ti PN 630BAR 755 DN2 2000
<a href="#">MANOMETER HOSE 2500MM M16X2</a>	AISI 316Ti PN 630 BAR 755 DN2 2500
<a href="#">THROTTLEFREE 3/4" BANJO - SCHWER SR-580-20S</a>	
<a href="#">THROTTLEFREE 1/2" BANJO - SCHWER SR-580-20S</a>	
<a href="#">SR-58020S</a>	Throttle-free angle swivel fitting 1.4571 20S<G3/4" S36/B46x549/74
<a href="#">THROTTLEFREE 1/2" BANJO -</a>	SCHWER SR-580-20S 316Ti
<a href="#">A-BVHBG12B1377POV</a>	High pressure block ball valve 1.4571/POM/FKM G1/2" S30/35x83
<a href="#">Ref.Sr-594g14 S.S.</a>	PLUG G1/4"
<a href="#">T-Rm35x25-7000mm</a>	PIPE STAINLESS STEEL T-Rm35x25-7000mm SCHWER
<a href="#">Gf-147cr112i40-7</a>	screw Externally threaded hose connection 1.4571 / 1.4408 conical sealing R1-1 / 2 "> di40 S75x146
<a href="#">A-Bveg12-8i</a>	One-piece ball valve 1.4408 / PTFE G1 / 2 "S25x60
<a href="#">Gf-11613g38-7</a>	HOSE ADAPTER STAINLESS STEEL G3/8" - di 13 mm (HOSE

	DN12) SCHWER GF-11613G38-7 (OR EQUIVALENT PART)
<a href="#">A-Dag112-8i</a>	Dirt catcher 1.4408 40 G1-1 / 2 "H79,5xL = 120
<a href="#">Gf-107112-4i</a>	Hexagon double nipple 1.4408 R1-1 / 2 "S50x54
<a href="#">A-Ftg112-5i</a>	Check valve 1.4408 Straight seat design DIN / ISO 228 G11 / 2 "S58x120
<a href="#">Wf-T213x29-7e</a>	TEE, IMPERIAL 1.4571 21,3x2,9 SCHWER WF-T213x29-7E
<a href="#">Sr-594g12</a>	1.4571 G 1/2" DIN 228 SCHWER SR-594G12 (OR EQUIVALENT PART)
<a href="#">A-Eah20-240vj3</a>	Electric Actuator Model J3S20 Standard SCS000109 SW 14
<a href="#">Gf-143cr12-7</a>	UNION, OUTSIDE THREAD 1.4571 G 1/2" SCHWER GF-143CR12-7
<a href="#">Rs-179a4060-2</a>	Screw thread hose clamp 1.4301 W4 version DIN3017-A B9, d40-60
<a href="#">Gf-113g112-7</a>	Hexagon bolt 1.4571 G1-1 / 2 "D55x33
<a href="#">Wf-B35x2-7n</a>	ELBOWS STAINLESS STEEL WF-B35x2-7N SCHWER (OR EQUIVALENT PART)
<a href="#">A-Dtg12-4l</a>	Hose tap 1.4404 08 G1 / 2 "D28x99
<a href="#">Mr-Rsmg100 0-10</a>	Bourdon tube safety gauge 1.4301 / 1.4571 / glycerine filling NG100 display range 0-10 bar, G1 / 2 "below,
<a href="#">134 G 38-4 I</a>	
<a href="#">Gf-10712-7</a>	HEXAGONAL COUPLING 1.4571 G 1/2" SCHWER GF-10712-7
<a href="#">Gf-113g12-7</a>	Hexagon bolt 1.4571 G1 / 2 "D26x26
<a href="#">Cvd25s (Ex 550-25s)</a>	
<a href="#">Wf-B213x2</a>	ELBOW STAINLESS STEEL Ø48,3x3,2 SCHWER WF-B213x2 (OR EQUIVALENT PART)
<a href="#">Gf-110g34-4i</a>	PROJE 2328 POZ- 10 FEMALE HEXAGONAL CAP STAINLESS STEEL G 3/4" SCHWER GF-110G34-4i
<a href="#">T-Rz483x32</a>	PIPE STAINLESS STEEL Ø48,3x3,2-5000mm SCHWER T-Rz483x32 (OR EQUIVALENT PART)
<a href="#">Wf-B483x32</a>	ELBOW STAINLESS STEEL Ø48,3x3,2 SCHWER WF-B483x32 (OR EQUIVALENT PART)
<a href="#">Gf-134g12-7</a>	Tee 1.4571 15 G1 / 2 "D30xL32
<a href="#">H0s-1sn40</a>	di=38.1mm; D=50.1mm; l=3m H0S-1SN40 HOSE
<a href="#">134 G 12-4 I</a>	
<a href="#">Gf-141cr114-7</a>	Screw connection, internal external thread 1.4571 / 1.4408 DN32 conical sealing R / G1-1 / 4 "S70x83

<a href="#">Gf-134g112-4i</a>	Tee 1.4408 DN40 G1-1 / 2 "D57x50
<a href="#">Gf-131g112-4i</a>	Store 90 ° 1.4408 R / G1-1 / 2 "L68 / 48
<a href="#">A-Bv3g112-8i</a>	3-piece ball valve 1.4408 G1-1 / 2 "S..x123
<a href="#">Gf-149cr112-7</a>	Screw connection, male thread on both sides 1.4571 / 1.4408 conical sealing R1-1 / 2 "S75x112
<a href="#">Gf-131g114-4i</a>	Store 90 ° 1.4408 R / G1-1 / 4 "L62 / 46
<a href="#">Ref.Sr-594g12 S.S.</a>	PLUG G1/2"
<a href="#">Gf-145cr12-7</a>	UNION, OUTSIDE THREAD - WELDING END 1.4571 G 1/2" SCHWER GF-145CR12-7
<a href="#">Gf-106g11212-7</a>	Hexagon Reducer 1.4571 AG / IG G1-1 / 2 "> G1 / 2" S50x30
<a href="#">Ref.Sr-594g114 S.S</a>	PLUG G1 1/4"