

Senotec



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Senotec Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Senotec T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
130 54	Level probe R3T-5/7 L10W PTFE, SI = 65mm, d = 18mm, cable cross exit with metal angled connector Manufacturer: Binder series 682 Package: 18x24x11cm net weight: 0.5 kg gross weight: 0.8 kg
Sensor R2t-3/5I20	Art nr. 130 61 Your model description: 50058351
110 95	
11015	
130 118	
130 18	
130 19	
130 58	
130 77	
20 022 05 / CLC 22-L05	
20 028 99	
30 033 20	
30 045 60	
30 080 05	
4-008-40-0247	

4-008-40-259	
C3W 4-4/4	
CLC40-L05	
CLS45-LO5H	
CLS-60	
CLS80-LO5H	
R3E-816L12	
R3T-5/7 L10W	
SVK44-L50M0	
R2T-3/5L20	130 61 Capazitive level sensor Capazitive level sensor Sensor length: 50 mm Cable cross exit Cable length: approx.1990 mm Active zone: 25 mm Weight: 0,170 kg Country of origin: Germany Customs tariff no.: 90268020
CLS-33	
30 080 60	CLS 80-L60 Switching amplifier Supply voltage: 18...30 V/DC Connection: Cable 4x0,25mm ² length: 6,0m Output: 2 x PNP-NO
CLS 90-M12 Homag	30 090 00H Switching amplifier Supply voltage: 18...30 V/DC Connection: 4 pin connector M12x1 Output: 2 x PNP-NO Low Level / High Level Weight: 0,245 kg Homag Teilenummer: 4-008-40-0256
D1Q-2x3/13L12	130 141 Capazitive level sensor for two levels Sensor length: 130 mm Cable cross exit Cable length: approx.1200 mm Active zone: 2 x 30mm Lowlevel / Highlevel Weight: 0,190 kg Country of origin: Germany Customs tariff no.: 90268020 (Use with switching amplifier 4-008-40-0256)
30 090 00H	CLS 90-M12 Homag Switching amplifier Supply voltage: 18...30 V/DC Connection: 4 pin connector M12x1 Output: 2 x PNP-NO Low Level / High Level Weight: 0,245 kg Country of origin: Germany Customs tariff number: 85365080 Homag Teilenummer: 4-008-40-0256
20 022 05 CLC 22-L05	
20 040 08 CLC 40-SM8	
130 99	Description: Level sensor
130 61	Description: Level probe
130 11 Type R3e-5/12	
130 61 Teflonsonde R2t-3/5I20 SI=50mm Mit Kabelquerausgang, KI=2m	

130 18 Sensorteflonsonde R2q L20 5/10sl 100mm, Kabelquerausgang, 2m	
130 61	Level probe
R4t-1/6	
ClS80-L05h	
30 033 05	
130 104p R3e 8 16l12	
130 54 R3t 5 7 L10w	
Clc 40 Sm8	
Clc 28-L15	
Clc40-Sm8	
20 040 05 Clc40-L05	
130 58 Teflonsonde R6g-5/17sl 170mm, Mb Mit Gew. D M18, Mb L=60mm	
130 11 Teflonsonde R3e-5/12 Sl=120mm, Montagebereich V2a Mit Knickschutzfeder	
R3e-8/16l12	Art nr. 130 104 Level probe R3E-8 / 16L12 Sl = 160mm, mounting area V2A Material: PTFE; Cable length 1100mm with anti-kink spring Package: 18x24x11cm net weight: 0.2 kg gross weight: 0.3 kg Customs number: 85365080 Country of Origin: Germany
13011 Teflonsonde R3e-5/12sl=120mm, Montagebereich V2amit Knickschutzfeder	
30 045 05 Schaltverstã196;Rker Cls 45- L05 18-30 V/Dc	
130 20	
Fullstandssonde R3e-8/16l12	
Svk 44 , By 30 045 05 Type Cls 45-L05	
10 055 00	
20 028 99 Schaltverstã196;Rker Clc 28- Ima	
Clc 28-L50	
130 54 R3t-5/7 L10w	
130 54 Teflonsonde R3t-5/7 L10w	

10_055_100
Csv41 Csv41-Gt;Cls 33-L05 18-30 V/Dc (Nachfolgemodell Fur Csv41)
130_104
130_61 R2t-3/5I20
130_19 Teflonsonde R2q-5/8 SI 86,5mm, Mb Mit Gew. D=m18,Kabelqueraus
Csv55 (10_055_00) Adhesive Level Sensor Signal Booster
Cls 33-L05 18-30 V/Dc
130_11 Teflonsonde R3e- 5/12sl=120mm, Montagebereich V2amit Knickschutzfeder
130_99
20_040_08
30_045_05 Type Cls 45-L05
130_61 Sensor
Cls45-L05h
130_58 Teflonsonde R6g-5/17 SI 170mm, Mb Mit Gew. D M18, Mb L=60mm
130_11 Teflonsonde R3e-5/12 SI=120mm, Montagebereich V2a
Svk44 Adhesive Level Control Module
Cls 33-L05
130_94
130_61 Teflon-Sonde R2t- 3/5I20sl=50mm Kabel Mit Einem Ausgang, Kl=2m
Clc 28-Ima (20_028_99)
Csv41ce
R3e-5/12 Artikel-Nr 130_11
Cls 45-L05 18-30 V/Dc
130_11 (R3e-5/12)
20_022_05
130_20 Teflonsonde R3ew-3/8

130 104 Type R3e-8/16l12	
10 055 00 Schalterverstaerker Csv 55110-240 V/Ac, 50-60 Hzzzeitverzoeigerung, Kl=1,5m	
R2q-5/10l20 Sensor	
30 045 05	Successor of SVK 44! Switching amplifier CLS 45-L05 18-30 V / DC Connecting cable LIYCY 4x0,25mm ² Length = 0.5m
30 033 05 (ClS 33-L05)	
130 19 Teflonsonde R2q-5/8sl 86,5mm, Mb Mit Gew. D=m18,Kabelqueraus	
Clc22 Adhesive Level Sensor Signal Booster	
ClS 45-L50 30 045 50	
Rpk-3/6l6	
Clc 22-L05 (Art.-Nr. 20 022 05)	
Clc40-L05 18-30 V/Dc	
R2t-3/5l20 130 61teflonsonde R2t- 3/5l20sl=50mm Mit Kabelquerausgang, Kl=2m	
130 99 Sl 60mm, Kabellö;Nge 530mm Material: Ptfе	
130 61	
Clc 40-Sm8	
R2q 5/10 L20	
11015 M161028-1 Type C3g-6/10	
130 11	
130 104p R3e-8/16l12	
Svk 44 M0h3	
ClS 33 L05	
30 060 05	
130 61 Teflonsonde R2t-3/5l20sl=50mm Mit Kabelquerausgang, Kl=2m	
30 033 225	
Rpk-3/6l6 Level Sensorseries R 130 99	

[R3e-5/12](#)

[R2q-5/10 Sensoren](#)

[Clc 28 Ima](#)

[130 72](#)

[Clc28-Ima](#)