Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Sensotec

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Sensotec Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sensotec Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Al312cn	SENSOR MODEL 34 250LBS 60-160 DEGREE
060-F491-01	TRANSDUCER MODEL FP2000 0.10% ACCURACY 2.5PSID
Bp217	
Tq3662	TORQUE WATCH GAUGE, ACCURACY:+/-10%, TORQUE MAX: 0.1IN-OZ, TORQUE MIN:0.01IN-OZ ROHS COMPLIANT: NA
Lkw50kz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:50LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:50LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CELL
Al131ep	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 50000LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.5%, L
V-Bp513ug-2j-3d-5f-9e-14a	PRESSURE TRANSDUCER 30INCH HGV 4-20MA 1/4IN G FM
Al111bn	(PRICE/EA) LOAD CELL, LOAD CAPACITY:50LB, SUPPLY VOLTAGE:10VDC, OPERATING TEMPERATURE MIN:-5 C, OPERATING TEMPERATURE MAX:105 C, CELL OUTPUT MV / V: 3
Lkw25kz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:25LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:25LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CELL
Rf/7673-03	
73171101	CEMENT
060-H417-01	PRESSURE TRANSDUCER
90002141	
41/571-01	LOAD CELL 100LBS

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
060957504	PRESSURE TRANS
Al111dr	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 5000LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.1%, LO
Ap121br	PRESSURE SENSOR, SENSING ACCURACY:0.1%, OPERATING PRESSURE MAX:100PSI, SENSOR OUTPUT:VOLTAGE, PORT SIZE:1/4, PORT STYLE:NPT, PRESSURE MEASURE TYPE:GA
41057205	LOAD CELL
Lkw10kz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:10LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:10LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CELL
Lkw500kz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:500LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:500LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CE
060-J500-01	TRANSDUCER SINGLE CHANNEL 1AMP 30VDC PROGRAMMABLE
Sns-R3100-Za	
A-105a	
Nicr-Ni(K) ,Type-K	
060-0571-01	LOAD CELL 100LB
Al311ar	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 1000G, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.15%, LO
Tq651c3	GAUGE, TORQUE WATCH 15N-MM TO 285N-MM 2%, TORQUE RANGE N-M:15N-MM TO 265N-MM, TORQUE RANGE FT-LB: 0.01LB-FT TO 0.208LB-FT, ACCURACY %:2%, ACCURACY:+/-2
Termocupla Tipo S Doble Termopozo	
Al322ar	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY: 1000G, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0
Al111br	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 100LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.1%, LOA

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Tq651c2	TORQUE WATCH GAUGE, ACCURACY:+/-2%, TORQUE MAX: 20IN-OZ, TORQUE MIN:1IN-OZ ROHS COMPLIANT: NA
060-E286-02	
Tq9402	TORQUE WATCH GAUGE, ACCURACY:+/-2%, TORQUE MAX: 100IN-OZ, TORQUE MIN:15IN-OZ ROHS COMPLIANT: NA
Al322bn	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY: 50LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.
Ap142bn,1b,2t,5b,6i	MODEL A-5, ABSOLUTE PRESSURE, 50PSI, 30 TO 130 DEG F.(0 TO 55 DEG.C) TEMPERATURE COMPENSATION, VEHICLE VOLTAGE AMPLIFIER (0 TO 10 VDC) WITH 15 TO 28 V
060-9613-01-02	
81205-20 Miniatur-Drucksensor Messbereich 20 Bar	
Al322bl	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY: 25LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.
Al111ej	LOAD CELL 32VDC 20MA 60-160F 15000LB
Al111dv	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 10000LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.1%, L
Al111cr	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 500LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.1%, LOA
Tje/6321-01	TRANSDUCER 0-2PSI
Ae213qa,52j,58em	
809901	LOAD CELL
060-H032-01-01	
Lkw250kz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:250LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:250LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CE
811fmg108309	TRANSDUCER

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
34	
Fpg1bj25b6m	PRESSURE SENSOR, SENSING ACCURACY:0.1%, OPERATING PRESSURE MAX:15PSI, SENSOR OUTPUT:CURRENT, PORT SIZE: 1/4, PORT STYLE:NPT, PRESSURE MEASURE TYPE:GAG
651-X-4mcald	651-X-4M CALIBRATED
Al311an4a	(PRICE/EA) LOAD CELL, LOAD CAPACITY:250G, SUPPLY VOLTAGE:5VDC, OPERATING TEMPERATURE MIN:-5 C, OPERATING TEMPERATURE MAX:105 C, CELL OUTPUT MV / V: 20
060-F642-01	PRESSURE TRANSMITTER WING UNION 424
Lkw5kkz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:5000LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:5000LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD
060-0574-03-01	PANCAKE LOAD CELL MODEL 41 RANGE 10000LBS 10VDC
Al311bl	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 25LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.15%, LOA
060-F441-04	PNEUMATIC PRESSURE TRANSDUCER 1500PSI G9-32VDC
9940c-Kcn2x05-Fv	
Al311cn	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY: 250LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY: 0.15%, LO
Fdw1as-1aj-2d-5c-6q	TRANSDUCER MODEL FP2000 0.10% ACCURACY 2.5PSID
Ap121cv	PRESSURE SENSOR, SENSING ACCURACY:0.1%, OPERATING PRESSURE MAX:1000PSI, SENSOR OUTPUT:VOLTAGE, PORT SIZE:1/4, PORT STYLE:NPT, PRESSURE MEASURE TYPE:G
Al322br	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY: 100LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0
Wp9000	
Aa123	
Lkw10kkz	DIGITAL FORCE INDICATOR, LOAD CAPACITY:10000LB, LOAD CELL OUTPUT:FORCE, LINE CELL LINEARITY:0.2%, LOAD CELL

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	FORCE MAX:10000LBF, SUPPLY VOLTAGE MAX:9VD
By136hu	TRANSDUCER LVDT MODEL MDLC
Al111el	(PRICE/EA) LOAD CELL, LOAD CAPACITY:20000LB, SUPPLY VOLTAGE:10VDC, OPERATING TEMPERATURE MIN:-5 C, OPERATING TEMPERATURE MAX:105 C, CELL OUTPUT MV / V
060-9189-02tjg	PRESSURE TRANSDUCER HIGH PSI
32	
060-F203-01-01	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.