

Shb

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Shb Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Shb Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
COSID 466	831317 BRAKE SHOE SHN 3101.16 - 315 COSID 466 $\mu = 0.4$ Customs tariff number: 84314980 Form A1C according to DIN 15435, cast aluminum with steel bushes with brake lining COSID 466, asbestos-free, $\mu = 0.4$, glued Value of goods
HYDRAULIC BUMPER 2.FD THREE FEET SHB KP160	2. RAW MILL ROLLER THREE FEET TORQUE SUPPORT HYDRAULIC BUMPER - SHB HYDRAULIC BUFFER SHB TYPE: KP160X100 EF-E-HT Piston rod diameter: 150MM Hydraulic piston: 160 mm, Stroke: 87 mm, Impact mass: 13900 kg, Impact speed: 0.3 m/s, Preload force: 51000 N, Proportional impact force: 97900 N Maximum impact force: 152000 N, X distance: 281 mm, Y distance: 136 MM Z distance: 43mm Oil amount: 2.72 lt., Gas amount: 1.62 liters. (Nitrogen), Gas pressure: 29 bar, manufactured to withstand +70 oC. THERE ARE 3 PIECES IN THE SYSTEM.
	Drum brake DIN 15435-EB 200-23/5 AVN-EB-466-E-HHT-WA for drum diameter 200mmx75mm width according to DIN 15431 Braking torque 100-300Nm adjustable Brake pad glued asbestos-free 0.4 Brake 2x left and 2x right With automatic wear adjustment AVN with measuring cap with hand release lever HHT for manually opening the brake, Bolts made of

05494-5	stainless steel, bright parts galvanized Bozen AVN and bolts can be relubricated via spring tube with grease nipples M10x1 Bearings with brass, bronze bushing. Stainless steel scale without Macrolon cover All steel components without Macrolon cover **Including Motor 221425 ELHY EB 220-50/2 II W7 230/400V,50HZ Connection dimensions according to DIN 15430, operating temperature 0-+70 Celsius. with Viton seals for high-temperature design restricted operating mode, S1 operation not permitted, S3 operation with max. 240c/h 25% ED, Can only be used in a stationary bearing (piston rod upwards), Coating 2K polyacrylic RAL3003
221425	ELHY EB 220-50/2 II W7 230/400V,50HZ Connection dimensions according to DIN 15430, operating temperature 0-+70 Celsius. with Viton seals for high-temperature design restricted operating mode, S1 operation not permitted, S3 operation with max. 240c/h 25% ED, Can only be used in a stationary bearing (piston rod upwards), Coating 2K polyacrylic RAL3003
05494-09	Trommelbremse DIN 15435 EB 400-80/6 AVN-EB-466-E-HHT-WA for the installation of an Eldro ED 80/6 or Elhy EB800-60II according to DIN 15430 for drum diameter 400mmx150mm width according to DIN 15431 Braking torque 300-1610 Nm adjustable, Brake 1x left and 1x right with automatic wear adjustment AVN with brass cap with hand release lever HHT for manually opening the brake Bolt AVN and bolts via spring tube can be relubricated with grease nipples M10x1 **Including Motor 221428 ELHY EB 800-60 II W7 230/400V 50HZ
221428	ELHY EB 800-60 II W7 230/400V 50HZ
HYDRAULIC BUMPER KP 200X100 ER -E	
HYDRAULIC BUMPER KP 200X100 LEAKING	
KP160X100 EF-E-HT	
221948	
Disc Brake Shn 3108-Dbf 145.2	80KN-5010-E-L consisting of two halves, emergency stop and holder brakes on the flanged pulley of the cable drum, braking with spring force, hydraulic release, with four mechanical position switches for monitoring the release position "brake open" and "brake closed"
06303-01	
Kp125x1000 Ef-Sk	
S350101 11438	
S311100 1048	