Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Sierra

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Sierra Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sierra Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
241 VTP	
241i-VT-1-LS-E4( )-DD-P2-V6-ST-MP0-CM	
241s-V-LS-E4(50)-DD-PV1L-V4LH-ST-MPO-ST	
241-VTP-LC-E2-DD-PV1-V4H-ST-MP3-CM	
241-VTP-LC-E4-NR-PS-V4H-HT-MP2-CM	
620S - L06-M1-EN2-V4-DD-0	
640S-ATEX-L06(M5)-E3(15')-P2-V4-DD-13-HART-CC	
640S-FM-L06-M1-M2(4")-E2-P2-V4-DD-0-PULSE	
640S-NAA-L18-M8(4")-E4(50?)-P2-V4-DD-0-HART	
780S-FM-D6-E2-P2-V4-PULSE-DD-8	
780S-FM-FD7-E2-P2-V4-DD-11	
780S-O2C1	
822-13-OV1-PV1-V1-MP	
C100M-15-OV1-SV1-PV2-V1-S0-C0-DP	
C100-M-NR-10-OV1-SV1-PV2-V1-SO-CO-DP	
CAL-TRAK ,MODELL SL-800-B , BASISEINHEIT	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
fxt009	
Innova mass 240	
Model: 780S-ATEX-D6-E2-P2-V4-MODBUS-DD-SCR	
Side-Trak 830/840	
SL 800-24	
SL 800-75	
Typ: C22B-02400E1-18.6NA	
WP7603-G-1104248	
Thermal Mass Flow Meter for Gases	TAG Informations (pls. complete): Gas: Pipe size/diameter: mm Exact inner pipe diam: mm Operating pressure: bar a Operating temperature: °C Flow range: Nl/h Orders with incomplete tag informations cannot be processed! Sierra-Model 620S - "Fast-Flo" Type code: 620S-L06-M1-EN2-V4-DD-10 Fast Flow™ Insertion Flow probe, to measuere various gas flow rates in different pipe sizes Probe shaft: made of stainless steel 304 SS (1.4301), Sensor materials: glas coated, Epoxy resin. Probe diameter: 3/8“(9,525 mm), Electronics: including "Smart" type electronics with high/low alarm output. SMART-Interface for Mod. 620S, incl. connection cabel and configuration /Software Max. operating temp.: -40 to 80°C Max. operating press.: 8 bar Ü Power supply: 15 - 18 VDC regulated, 625 mA L06 Probe length: 150 mm M1 Mounting access.: Compression fitting for 3/8"-probe shaft with 1/2" NPTM thread EN2 Electron. enclos.: NEMA 4X (IP 65) rated enclo sure directly mounted on the probe V4 Output signal: 4 - 20 mA, linear DD Display: Digital display, 2 x 2 digit, backlit, LCD display indicates

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	flow rate and totalized mass in engineering units. For simplified configuration settings, provides system status information. 10 Calibration: Calibrated with nitrogen, max. cal. pressure 8 bar g, max. cal. temp. 80°C. Consult product datasheets for flowrate, pressure and temperature limits
Quadtherm 780 i DN80	
Quadtherm 780 i DN20	
5100-28-It	
Wp7603-G	
C100l-Dd-2-Ov1-Sv1-Pv2-V1-S0	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.